

# Package ‘DALEX’

July 21, 2025

**Title** moDel Agnostic Language for Exploration and eXplanation

**Version** 2.4.3

**Description** Any unverified black box model is the path to failure. Opaqueness leads to distrust. Distrust leads to ignorance. Ignorance leads to rejection. DALEX package xrays any model and helps to explore and explain its behaviour. Machine Learning (ML) models are widely used and have various applications in classification or regression. Models created with boosting, bagging, stacking or similar techniques are often used due to their high performance. But such black-box models usually lack direct interpretability. DALEX package contains various methods that help to understand the link between input variables and model output. Implemented methods help to explore the model on the level of a single instance as well as a level of the whole dataset. All model explainers are model agnostic and can be compared across different models. DALEX package is the cornerstone for 'DrWhy.AI' universe of packages for visual model exploration. Find more details in (Biecek 2018) <[doi:10.48550/arXiv.1806.08915](https://doi.org/10.48550/arXiv.1806.08915)>.

**License** GPL

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.2.3

**Depends** R (>= 3.5)

**Imports** ggplot2, iBreakDown (>= 1.3.1), ingredients (>= 2.0)

**Suggests** gower, ranger, testthat, methods

**URL** <https://modeloriented.github.io/DALEX/>, <https://dalex.drwhy.ai>

**BugReports** <https://github.com/ModelOriented/DALEX/issues>

**NeedsCompilation** no

**Author** Przemyslaw Biecek [aut, cre] (ORCID: <<https://orcid.org/0000-0001-8423-1823>>),  
Szymon Maksymiuk [aut] (ORCID: <<https://orcid.org/0000-0002-3120-1601>>),  
Hubert Baniecki [aut] (ORCID: <<https://orcid.org/0000-0001-6661-5364>>)

**Maintainer** Przemyslaw Biecek <[przemyslaw.biecek@gmail.com](mailto:przemyslaw.biecek@gmail.com)>

**Repository** CRAN

**Date/Publication** 2023-01-15 23:10:02 UTC

## Contents

apartments . . . . .	3
colors_discrete_drwhy . . . . .	3
covid . . . . .	4
dragons . . . . .	5
explain.default . . . . .	5
fifa . . . . .	9
happiness . . . . .	11
HR . . . . .	11
install_dependencies . . . . .	12
loss_cross_entropy . . . . .	12
loss_yardstick . . . . .	13
model_diagnostics . . . . .	14
model_info . . . . .	15
model_parts . . . . .	17
model_performance . . . . .	19
model_profile . . . . .	21
plot.list . . . . .	23
plot.model_diagnostics . . . . .	24
plot.model_parts . . . . .	25
plot.model_performance . . . . .	25
plot.model_profile . . . . .	27
plot.predict_diagnostics . . . . .	28
plot.predict_parts . . . . .	29
plot.predict_profile . . . . .	31
plot.shap_aggregated . . . . .	32
predict.explainer . . . . .	33
predict_diagnostics . . . . .	34
predict_parts . . . . .	35
predict_profile . . . . .	38
print.description . . . . .	40
print.explainer . . . . .	40
print.model_diagnostics . . . . .	41
print.model_info . . . . .	41
print.model_performance . . . . .	42
print.model_profile . . . . .	43
print.predict_diagnostics . . . . .	43
set_theme_dalex . . . . .	44
shap_aggregated . . . . .	45
theme_drwhy . . . . .	46
titanic . . . . .	46
update_data . . . . .	48
update_label . . . . .	48

<i>apartments</i>	3
variable_effect . . . . .	49
yhat . . . . .	50
<b>Index</b>	<b>53</b>

---

<i>apartments</i>	<i>Apartments Data</i>
-------------------	------------------------

---

### Description

Datasets *apartments* and *apartments\_test* are artificial, generated from the same model. Structure of the dataset is copied from real dataset from *PBI* package, but they were generated in a way to mimic effect of Anscombe quartet for complex black box models.

### Usage

```
data(apartments)
```

### Format

a data frame with 1000 rows and 6 columns

### Details

- *m2.price* - price per square meter
- *surface* - apartment area in square meters
- *n.rooms* - number of rooms (correlated with *surface*)
- *district* - district in which apartment is located, factor with 10 levels
- *floor* - floor
- *construction.date* - construction year

---

<i>colors_discrete_drwhy</i>	<i>DrWhy color palettes for ggplot objects</i>
------------------------------	--

---

### Description

*DrWhy* color palettes for ggplot objects

### Usage

```
colors_discrete_drwhy(n = 2)
```

```
colors_diverging_drwhy()
```

```
colors_breakdown_drwhy()
```

**Arguments**

n                    number of colors for color palette

**Value**

color palette as vector of charactes

---

covid	<i>Data for early COVID mortality</i>
-------	---------------------------------------

---

**Description**

Two datasets of characteristics of patients infected with COVID. It is important to note that these are not real patient data. This is simulated data, generated to have relationships consistent with real data (obtained from NIH), but the data itself is not real. Fortunately, they are sufficient for the purposes of our exercise.

**Usage**

```
data(covid_summer)
data(covid_spring)
```

**Format**

a data frame with 10 000 rows each and 12 columns

**Details**

The data is divided into two sets covid\_spring and covid\_summer. The first is acquired in spring 2020 and will be used as training data while the second dataset is acquired in summer and will be used for validation. In machine learning, model validation is performed on a separate data set. This controls the risk of overfitting an elastic model to the data. If we do not have a separate set then it is generated using cross-validation, out of sample or out of time techniques.

It contains 20 000 rows related fo COVID mortality. it contains 11 variables such as: Gender, Age, Cardiovascular.Diseases, Diabetes, Neurological.Diseases, Kidney.Diseases.

Source: <https://github.com/BetaAndBit/RML>

**Source**

<https://github.com/BetaAndBit/RML>

---

`dragons`*Dragon Data*

---

**Description**

Datasets `dragons` and `dragons_test` are artificial, generated from the same ground truth model, but with sometimes different data distribution.

**Usage**

```
data(dragons)
```

**Format**

a data frame with 2000 rows and 8 columns

**Details**

Values are generated in a way to: - have nonlinearity in `year_of_birth` and `height` - have concept drift in the test set

- `year_of_birth` - year in which the dragon was born. Negative year means year BC, eg: -1200 = 1201 BC
- `year_of_discovery` - year in which the dragon was found.
- `height` - height of the dragon in yards.
- `weight` - weight of the dragon in tons.
- `scars` - number of scars.
- `colour` - colour of the dragon.
- `number_of_lost_teeth` - number of teeth that the dragon lost.
- `life_length` - life length of the dragon.

---

`explain.default`*Create Model Explainer*

---

**Description**

Black-box models may have very different structures. This function creates a unified representation of a model, which can be further processed by functions for explanations.

**Usage**

```

explain.default(
  model,
  data = NULL,
  y = NULL,
  predict_function = NULL,
  predict_function_target_column = NULL,
  residual_function = NULL,
  weights = NULL,
  ...,
  label = NULL,
  verbose = TRUE,
  precalculate = TRUE,
  colorize = !isTRUE(getOption("knitr.in.progress")),
  model_info = NULL,
  type = NULL
)

explain(
  model,
  data = NULL,
  y = NULL,
  predict_function = NULL,
  predict_function_target_column = NULL,
  residual_function = NULL,
  weights = NULL,
  ...,
  label = NULL,
  verbose = TRUE,
  precalculate = TRUE,
  colorize = !isTRUE(getOption("knitr.in.progress")),
  model_info = NULL,
  type = NULL
)

```

**Arguments**

model	object - a model to be explained
data	data.frame or matrix - data which will be used to calculate the explanations. If not provided, then it will be extracted from the model. Data should be passed without a target column (this shall be provided as the y argument). NOTE: If the target variable is present in the data, some of the functionalities may not work properly.
y	numeric vector with outputs/scores. If provided, then it shall have the same size as data
predict_function	function that takes two arguments: model and new data and returns a numeric vector with predictions. By default it is yhat.

predict_function_target_column	Character or numeric containing either column name or column number in the model prediction object of the class that should be considered as positive (i.e. the class that is associated with probability 1). If NULL, the second column of the output will be taken for binary classification. For a multiclass classification setting, that parameter cause switch to binary classification mode with one vs others probabilities.
residual_function	function that takes four arguments: model, data, target vector y and predict function (optionally). It should return a numeric vector with model residuals for given data. If not provided, response residuals ( $y - \hat{y}$ ) are calculated. By default it is residual_function_default.
weights	numeric vector with sampling weights. By default it's NULL. If provided, then it shall have the same length as data
...	other parameters
label	character - the name of the model. By default it's extracted from the 'class' attribute of the model
verbose	logical. If TRUE (default) then diagnostic messages will be printed
precalculate	logical. If TRUE (default) then predicted_values and residual are calculated when explainer is created. This will happen also if verbose is TRUE. Set both verbose and precalculate to FALSE to omit calculations.
colorize	logical. If TRUE (default) then WARNINGS, ERRORS and NOTES are colored. Will work only in the R console. Now by default it is FALSE while knitting and TRUE otherwise.
model_info	a named list (package, version, type) containing information about model. If NULL, DALEX will seek for information on it's own.
type	type of a model, either classification or regression. If not specified then type will be extracted from model_info.

### Details

Please NOTE that the model is the only required argument. But some explanations may expect that other arguments will be provided too.

### Value

An object of the class explainer.

It's a list with the following fields:

- model the explained model.
- data the dataset used for training.
- y response for observations from data.
- weights sample weights for data. NULL if weights are not specified.
- y\_hat calculated predictions.
- residuals calculated residuals.





```

# binary classification
titanic_ranger <- ranger::ranger(as.factor(survived)~., data = titanic_imputed, num.trees = 50,
                                probability = TRUE)
# keep in mind that for binary classification y parameter has to be numeric with 0 and 1 values
titanic_ranger_exp <- explain(titanic_ranger, data = titanic_imputed, y = titanic_imputed$survived)

# multiclass task
hr_ranger <- ranger::ranger(status~., data = HR, num.trees = 50, probability = TRUE)
# keep in mind that for multiclass y parameter has to be a factor,
# with same levels as in training data
hr_ranger_exp <- explain(hr_ranger, data = HR, y = HR$status)

# set model_info
model_info <- list(package = "stats", ver = "3.6.2", type = "regression")
aps_lm_model4 <- lm(m2.price ~., data = apartments)
aps_lm_explainer4 <- explain(aps_lm_model4, data = apartments, label = "model_4v",
                             model_info = model_info)

# simple function
aps_fun <- function(x) 58*x$surface
aps_fun_explainer <- explain(aps_fun, data = apartments, y = apartments$m2.price, label="sfun")
model_performance(aps_fun_explainer)

# set model_info
model_info <- list(package = "stats", ver = "3.6.2", type = "regression")
aps_lm_model4 <- lm(m2.price ~., data = apartments)
aps_lm_explainer4 <- explain(aps_lm_model4, data = apartments, label = "model_4v",
                             model_info = model_info)

aps_lm_explainer4 <- explain(aps_lm_model4, data = apartments, label = "model_4v",
                             weights = as.numeric(apartments$construction.year > 2000))

# more complex model
library("ranger")
aps_ranger_model4 <- ranger(m2.price ~., data = apartments, num.trees = 50)
aps_ranger_explainer4 <- explain(aps_ranger_model4, data = apartments, label = "model_ranger")
aps_ranger_explainer4

```

---

fifa

*FIFA 20 preprocessed data*


---

### Description

The fifa dataset is a preprocessed players\_20.csv dataset which comes as a part of "FIFA 20 complete player dataset" at Kaggle.

**Usage**

```
data(fifa)
```

**Format**

a data frame with 5000 rows, 42 columns and rownames

**Details**

It contains 5000 'overall' best players and 43 variables. These are:

- short\_name (rownames)
- nationality of the player (not used in modeling)
- overall, potential, value\_eur, wage\_eur (4 potential target variables)
- age, height, weight, attacking skills, defending skills, goalkeeping skills (37 variables)

It is advised to leave only one target variable for modeling.

Source: <https://www.kaggle.com/stefanoleone992/fifa-20-complete-player-dataset>

All transformations:

1. take 43 columns: [3, 5, 7:9, 11:14, 45:78] (R indexing)
2. take rows with value\_eur > 0
3. convert short\_name to ASCII
4. remove rows with duplicated short\_name (keep first)
5. sort rows on overall and take top 5000
6. set short\_name column as rownames
7. transform nationality to factor
8. reorder columns

**Source**

The players\_20.csv dataset was downloaded from the Kaggle site and went through few transformations. The complete dataset was obtained from [https://www.kaggle.com/stefanoleone992/fifa-20-complete-player-dataset#players\\_20.csv](https://www.kaggle.com/stefanoleone992/fifa-20-complete-player-dataset#players_20.csv) on January 1, 2020.

---

happiness	<i>World Happiness Report data</i>
-----------	------------------------------------

---

**Description**

The happiness\_train and happiness\_test datasets are generated based on the "World Happiness Report" at Kaggle <https://www.kaggle.com/datasets/unsdsn/world-happiness>.

**Usage**

```
data(happiness_train)
data(happiness_test)
```

**Format**

two data frames with total 781 rows, 7 columns each and rownames

**Details**

It contains data for 781 countries and 7 variables. These are:

- score - Happiness score
- gdp\_per\_capita - GDP per capita
- social\_support - Social support
- healthy\_life\_expectancy - Healthy life expectancy
- freedom\_life\_choices - Freedom to make life choices
- generosity - Generosity
- perceptions\_of\_corruption - Perceptions of corruption

**Source**

World Happiness Report data <https://worldhappiness.report/>

---

HR	<i>Human Resources Data</i>
----	-----------------------------

---

**Description**

Datasets HR and HR\_test are artificial, generated from the same model. Structure of the dataset is based on a real data, from Human Resources department with information which employees were promoted, which were fired.

**Usage**

```
data(HR)
```

**Format**

a data frame with 10000 rows and 6 columns

**Details**

Values are generated in a way to: - have interaction between age and gender for the 'fired' variable  
- have non monotonic relation for the salary variable - have linear effects for hours and evaluation.

- gender - gender of an employee.
- age - age of an employee in the moment of evaluation.
- hours - average number of working hours per week.
- evaluation - evaluation in the scale 2 (bad) - 5 (very good).
- salary - level of salary in the scale 0 (lowest) - 5 (highest).
- status - target variable, either 'fired' or 'promoted' or 'ok'.

---

`install_dependencies` *Install all dependencies for the DALEX package*

---

**Description**

By default 'heavy' dependencies are not installed along DALEX. This function silently install all required packages.

**Usage**

```
install_dependencies/packages = c("ingredients", "iBreakDown", "ggpubr"))
```

**Arguments**

`packages` which packages shall be installed?

---

`loss_cross_entropy` *Calculate Loss Functions*

---

**Description**

Calculate Loss Functions

**Usage**

```
loss_cross_entropy(observed, predicted, p_min = 1e-04, na.rm = TRUE)
```

```
loss_sum_of_squares(observed, predicted, na.rm = TRUE)
```

```
loss_root_mean_square(observed, predicted, na.rm = TRUE)
```

```
loss_accuracy(observed, predicted, na.rm = TRUE)
```

```
loss_one_minus_auc(observed, predicted)
```

```
loss_default(x)
```

**Arguments**

observed	observed scores or labels, these are supplied as explainer specific y
predicted	predicted scores, either vector of matrix, these are returned from the model specific predict_function()
p_min	for cross entropy, minimal value for probability to make sure that log will not explode
na.rm	logical, should missing values be removed?
x	either an explainer or type of the model. One of "regression", "classification", "multiclass".

**Value**

numeric - value of the loss function

**Examples**

```
library("ranger")
titanic_ranger_model <- ranger(survived~., data = titanic_imputed, num.trees = 50,
                             probability = TRUE)
loss_one_minus_auc(titanic_imputed$survived, yhat(titanic_ranger_model, titanic_imputed))

HR_ranger_model_multi <- ranger(status~., data = HR, num.trees = 50, probability = TRUE)
loss_cross_entropy(as.numeric(HR$status), yhat(HR_ranger_model_multi, HR))
```

**Description**

The yardstick package provides many auxiliary functions for calculating the predictive performance of the model. However, they have an interface that is consistent with the tidyverse philosophy. The `loss_yardstick` function adapts loss functions from the yardstick package to functions understood by DALEX. Type compatibility for y-values and for predictions must be guaranteed by the user.

**Usage**

```
loss_yardstick(loss, reverse = FALSE, reference = 1)
```

**Arguments**

<code>loss</code>	loss function from the yardstick package
<code>reverse</code>	shall the metric be reversed? for loss metrics lower values are better. <code>reverse = TRUE</code> is useful for accuracy-like metrics
<code>reference</code>	if the metric is reverse then it is calculated as <code>reference - loss</code> . The default value is 1.

**Value**

loss function that can be used in the `model_parts` function

**Examples**

```
titanic_glm_model <- glm(survived~., data = titanic_imputed, family = "binomial")
explainer_glm <- DALEX::explain(titanic_glm_model,
                               data = titanic_imputed[,-8],
                               y = factor(titanic_imputed$survived))
# See the 'How to use DALEX with the yardstick package' vignette
# which explains this model with measures implemented in the 'yardstick' package
```

---

model\_diagnostics      *Dataset Level Model Diagnostics*

---

**Description**

This function performs model diagnostic of residuals. Residuals are calculated and plotted against predictions, true y values or selected variables. Find information how to use this function here: <https://ema.drwhy.ai/residualDiagnostic.html>.

**Usage**

```
model_diagnostics(explainer, variables = NULL, ...)
```

**Arguments**

explainer	a model to be explained, preprocessed by the explain function
variables	character - name of variables to be explained. Default NULL stands for all variables
...	other parameters

**Value**

An object of the class `model_diagnostics`. It's a data frame with residuals and selected variables.

**References**

Explanatory Model Analysis. Explore, Explain and Examine Predictive Models. <https://ema.drwhy.ai/>

**Examples**

```
library(DALEX)
apartments_lm_model <- lm(m2.price ~ ., data = apartments)
explainer_lm <- explain(apartments_lm_model,
                       data = apartments,
                       y = apartments$m2.price)
diag_lm <- model_diagnostics(explainer_lm)
diag_lm
plot(diag_lm)

library("ranger")
apartments_ranger_model <- ranger(m2.price ~ ., data = apartments)
explainer_ranger <- explain(apartments_ranger_model,
                           data = apartments,
                           y = apartments$m2.price)
diag_ranger <- model_diagnostics(explainer_ranger)
diag_ranger
plot(diag_ranger)
plot(diag_ranger, diag_lm)
plot(diag_ranger, diag_lm, variable = "y")
plot(diag_ranger, diag_lm, variable = "construction.year")
plot(diag_ranger, variable = "y", yvariable = "y_hat")
plot(diag_ranger, variable = "y", yvariable = "abs_residuals")
plot(diag_ranger, variable = "ids")
```

---

model\_info

*Extract info from model*

---

**Description**

This generic function let user extract base information about model. The function returns a named list of class `model_info` that contain about package of model, version and task type. For wrappers like `mlr` or `caret` both, package and wrapper information are stored

**Usage**

```
model_info(model, is_multiclass = FALSE, ...)

## S3 method for class 'lm'
model_info(model, is_multiclass = FALSE, ...)

## S3 method for class 'randomForest'
model_info(model, is_multiclass = FALSE, ...)

## S3 method for class 'svm'
model_info(model, is_multiclass = FALSE, ...)

## S3 method for class 'glm'
model_info(model, is_multiclass = FALSE, ...)

## S3 method for class 'lrm'
model_info(model, is_multiclass = FALSE, ...)

## S3 method for class 'glmnet'
model_info(model, is_multiclass = FALSE, ...)

## S3 method for class 'cv.glmnet'
model_info(model, is_multiclass = FALSE, ...)

## S3 method for class 'ranger'
model_info(model, is_multiclass = FALSE, ...)

## S3 method for class 'gbm'
model_info(model, is_multiclass = FALSE, ...)

## S3 method for class 'model_fit'
model_info(model, is_multiclass = FALSE, ...)

## S3 method for class 'train'
model_info(model, is_multiclass = FALSE, ...)

## S3 method for class 'rpart'
model_info(model, is_multiclass = FALSE, ...)

## Default S3 method:
model_info(model, is_multiclass = FALSE, ...)
```

**Arguments**

model	- model object
is_multiclass	- if TRUE and task is classification, then multitask classification is set. Else is omitted. If model_info was executed withing explain function. DALEX will recognize subtype on it's own.



... - another arguments

## Details

Currently supported packages are:

- class `cv.glmnet` and `glmnet` - models created with **glmnet** package
- class `glm` - generalized linear models
- class `lrm` - models created with **rms** package,
- class `model_fit` - models created with **parsnip** package
- class `lm` - linear models created with `stats::lm`
- class `ranger` - models created with **ranger** package
- class `randomForest` - random forest models created with **randomForest** package
- class `svm` - support vector machines models created with the **e1071** package
- class `train` - models created with **caret** package
- class `gbm` - models created with **gbm** package

## Value

A named list of class `model_info`

## Examples

```
aps_lm_model4 <- lm(m2.price ~., data = apartments)
model_info(aps_lm_model4)
```

```
library("ranger")
model_regr_rf <- ranger::ranger(status~., data = HR, num.trees = 50, probability = TRUE)
model_info(model_regr_rf, is_multiclass = TRUE)
```

---

model_parts	<i>Dataset Level Variable Importance as Change in Loss Function after Variable Permutations</i>
-------------	---

---

## Description

From DALEX version 1.0 this function calls the [feature\\_importance](#) Find information how to use this function here: <https://ema.drwhy.ai/featureImportance.html>.

**Usage**

```
model_parts(
  explainer,
  loss_function = loss_default(explainer$model_info$type),
  ...,
  type = "variable_importance",
  N = n_sample,
  n_sample = 1000
)
```

**Arguments**

explainer	a model to be explained, preprocessed by the explain function
loss_function	a function that will be used to assess variable importance. By default it is 1-AUC for classification, cross entropy for multilabel classification and RMSE for regression. Custom, user-made loss function should accept two obligatory parameters (observed, predicted), where observed states for actual values of the target, while predicted for predicted values. If attribute "loss_accuracy" is associated with function object, then it will be plotted as name of the loss function.
...	other parameters
type	character, type of transformation that should be applied for dropout loss. variable_importance and raw results raw drop losses, ratio returns drop_loss/drop_loss_full_model while difference returns drop_loss - drop_loss_full_model
N	number of observations that should be sampled for calculation of variable importance. If NULL then variable importance will be calculated on whole dataset (no sampling).
n_sample	alias for N held for backwards compatibility. number of observations that should be sampled for calculation of variable importance.

**Value**

An object of the class `feature_importance`. It's a data frame with calculated average response.

**References**

Explanatory Model Analysis. Explore, Explain and Examine Predictive Models. <https://ema.drwhy.ai/>

**Examples**

```
# regression

library("ranger")
apartments_ranger_model <- ranger(m2.price~., data = apartments, num.trees = 50)
explainer_ranger <- explain(apartments_ranger_model, data = apartments[,-1],
  y = apartments$m2.price, label = "Ranger Apartments")
model_parts_ranger_aps <- model_parts(explainer_ranger, type = "raw")
```

```

head(model_parts_ranger_aps, 8)
plot(model_parts_ranger_aps)

# binary classification

titanic_glm_model <- glm(survived~., data = titanic_imputed, family = "binomial")
explainer_glm_titanic <- explain(titanic_glm_model, data = titanic_imputed[, -8],
                                y = titanic_imputed$survived)
logit <- function(x) exp(x)/(1+exp(x))
custom_loss <- function(observed, predicted){
  sum((observed - logit(predicted))^2)
}
attr(custom_loss, "loss_name") <- "Logit residuals"
model_parts_glm_titanic <- model_parts(explainer_glm_titanic, type = "raw",
                                      loss_function = custom_loss)

head(model_parts_glm_titanic, 8)
plot(model_parts_glm_titanic)

# multilabel classification

HR_ranger_model_HR <- ranger(status~., data = HR, num.trees = 50,
                             probability = TRUE)
explainer_ranger_HR <- explain(HR_ranger_model_HR, data = HR[, -6],
                              y = HR$status, label = "Ranger HR")
model_parts_ranger_HR <- model_parts(explainer_ranger_HR, type = "raw")
head(model_parts_ranger_HR, 8)
plot(model_parts_ranger_HR)

```

---

model\_performance

*Dataset Level Model Performance Measures*


---

## Description

Function `model_performance()` calculates various performance measures for classification and regression models. For classification models following measures are calculated: F1, accuracy, recall, precision and AUC. For regression models following measures are calculated: mean squared error, R squared, median absolute deviation.

## Usage

```
model_performance(explainer, ..., cutoff = 0.5)
```

## Arguments

<code>explainer</code>	a model to be explained, preprocessed by the <a href="#">explain</a> function
<code>...</code>	other parameters
<code>cutoff</code>	a cutoff for classification models, needed for measures like recall, precision, ACC, F1. By default 0.5.

**Value**

An object of the class `model_performance`.

It's a list with following fields:

- `residuals` - data frame that contains residuals for each observation
- `measures` - list with calculated measures that are dedicated for the task, whether it is regression, binary classification or multiclass classification.
- `type` - character that specifies type of the task.

**References**

Explanatory Model Analysis. Explore, Explain, and Examine Predictive Models. <https://ema.drwhy.ai/>

**Examples**

```
# regression

library("ranger")
apartments_ranger_model <- ranger(m2.price~., data = apartments, num.trees = 50)
explainer_ranger_apartments <- explain(apartments_ranger_model, data = apartments[,-1],
  y = apartments$m2.price, label = "Ranger Apartments")
model_performance_ranger_aps <- model_performance(explainer_ranger_apartments )
model_performance_ranger_aps
plot(model_performance_ranger_aps)
plot(model_performance_ranger_aps, geom = "boxplot")
plot(model_performance_ranger_aps, geom = "histogram")

# binary classification

titanic_glm_model <- glm(survived~., data = titanic_imputed, family = "binomial")
explainer_glm_titanic <- explain(titanic_glm_model, data = titanic_imputed[,-8],
  y = titanic_imputed$survived)
model_performance_glm_titanic <- model_performance(explainer_glm_titanic)
model_performance_glm_titanic
plot(model_performance_glm_titanic)
plot(model_performance_glm_titanic, geom = "boxplot")
plot(model_performance_glm_titanic, geom = "histogram")

# multilabel classification

HR_ranger_model <- ranger(status~., data = HR, num.trees = 50,
  probability = TRUE)
explainer_ranger_HR <- explain(HR_ranger_model, data = HR[,-6],
  y = HR$status, label = "Ranger HR")
model_performance_ranger_HR <- model_performance(explainer_ranger_HR)
model_performance_ranger_HR
plot(model_performance_ranger_HR)
plot(model_performance_ranger_HR, geom = "boxplot")
plot(model_performance_ranger_HR, geom = "histogram")
```

---

model_profile	<i>Dataset Level Variable Profile as Partial Dependence or Accumulated Local Dependence Explanations</i>
---------------	--

---

### Description

This function calculates explanations on a dataset level set that explore model response as a function of selected variables. The explanations can be calculated as Partial Dependence Profile or Accumulated Local Dependence Profile. Find information how to use this function here: <https://ema.drwhy.ai/partialDependenceProfiles.html>. The variable\_profile function is a copy of model\_profile.

### Usage

```
model_profile(
  explainer,
  variables = NULL,
  N = 100,
  ...,
  groups = NULL,
  k = NULL,
  center = TRUE,
  type = "partial"
)
```

```
variable_profile(
  explainer,
  variables = NULL,
  N = 100,
  ...,
  groups = NULL,
  k = NULL,
  center = TRUE,
  type = "partial"
)
```

```
single_variable(explainer, variable, type = "pdp", ...)
```

### Arguments

explainer	a model to be explained, preprocessed by the explain function
variables	character - names of variables to be explained
N	number of observations used for calculation of aggregated profiles. By default 100. Use NULL to use all observations.

...	other parameters that will be passed to <code>ingredients::aggregate_profiles</code>
groups	a variable name that will be used for grouping. By default NULL which means that no groups shall be calculated
k	number of clusters for the <code>hclust</code> function (for clustered profiles)
center	shall profiles be centered before clustering
type	the type of variable profile. Either <code>partial</code> , <code>conditional</code> or <code>accumulated</code> .
variable	deprecated, use <code>variables</code> instead

### Details

Underneath this function calls the [partial\\_dependence](#) or [accumulated\\_dependence](#) functions from the `ingredients` package.

### Value

An object of the class `model_profile`. It's a data frame with calculated average model responses.

### References

Explanatory Model Analysis. Explore, Explain, and Examine Predictive Models. <https://ema.drwhy.ai/>

### Examples

```
titanic_glm_model <- glm(survived~., data = titanic_imputed, family = "binomial")
explainer_glm <- explain(titanic_glm_model, data = titanic_imputed)
model_profile_glm_fare <- model_profile(explainer_glm, "fare")
plot(model_profile_glm_fare)

library("ranger")
titanic_ranger_model <- ranger(survived~., data = titanic_imputed, num.trees = 50,
                             probability = TRUE)
explainer_ranger <- explain(titanic_ranger_model, data = titanic_imputed)
model_profile_ranger <- model_profile(explainer_ranger)
plot(model_profile_ranger, geom = "profiles")

model_profile_ranger_1 <- model_profile(explainer_ranger, type = "partial",
                                       variables = c("age", "fare"))
plot(model_profile_ranger_1, variables = c("age", "fare"), geom = "points")

model_profile_ranger_2 <- model_profile(explainer_ranger, type = "partial", k = 3)
plot(model_profile_ranger_2, geom = "profiles")

model_profile_ranger_3 <- model_profile(explainer_ranger, type = "partial", groups = "gender")
plot(model_profile_ranger_3, geom = "profiles")

model_profile_ranger_4 <- model_profile(explainer_ranger, type = "accumulated")
plot(model_profile_ranger_4, geom = "profiles")
```

```
# Multiple profiles
model_profile_ranger_fare <- model_profile(explainer_ranger, "fare")
plot(model_profile_ranger_fare, model_profile_glm_fare)
```

---

plot.list

*Plot List of Explanations*


---

## Description

Plot List of Explanations

## Usage

```
## S3 method for class 'list'
plot(x, ...)
```

## Arguments

x	a list of explanations of the same class
...	other parameters

## Value

An object of the class ggplot.

## Examples

```
library("ranger")
titanic_ranger_model <- ranger(survived~., data = titanic_imputed, num.trees = 50,
                             probability = TRUE)
explainer_ranger <- explain(titanic_ranger_model, data = titanic_imputed[,-8],
                           y = titanic_imputed$survived)
mp_ranger <- model_performance(explainer_ranger)

titanic_ranger_model2 <- ranger(survived~gender + fare, data = titanic_imputed,
                              num.trees = 50, probability = TRUE)
explainer_ranger2 <- explain(titanic_ranger_model2, data = titanic_imputed[,-8],
                            y = titanic_imputed$survived,
                            label = "ranger2")
mp_ranger2 <- model_performance(explainer_ranger2)

plot(list(mp_ranger, mp_ranger2), geom = "prc")
plot(list(mp_ranger, mp_ranger2), geom = "roc")
tmp <- list(mp_ranger, mp_ranger2)
names(tmp) <- c("ranger", "ranger2")
plot(tmp)
```

---

plot.model\_diagnostics

*Plot Dataset Level Model Diagnostics*

---

## Description

Plot Dataset Level Model Diagnostics

## Usage

```
## S3 method for class 'model_diagnostics'
plot(x, ..., variable = "y_hat", yvariable = "residuals", smooth = TRUE)
```

## Arguments

x	a data.frame to be explained, preprocessed by the <code>model_diagnostics</code> function
...	other object to be included to the plot
variable	character - name of the variable on OX axis to be explained, by default <code>y_hat</code>
yvariable	character - name of the variable on OY axis, by default <code>residuals</code>
smooth	logical shall the smooth line be added

## Value

an object of the class `model_diagnostics_explainer`.

## Examples

```
apartments_lm_model <- lm(m2.price ~ ., data = apartments)
explainer_lm <- explain(apartments_lm_model,
  data = apartments,
  y = apartments$m2.price)
diag_lm <- model_diagnostics(explainer_lm)
diag_lm
plot(diag_lm)

library("ranger")
apartments_ranger_model <- ranger(m2.price ~ ., data = apartments)
explainer_ranger <- explain(apartments_ranger_model,
  data = apartments,
  y = apartments$m2.price)
diag_ranger <- model_diagnostics(explainer_ranger)
diag_ranger
plot(diag_ranger)
plot(diag_ranger, diag_lm)
plot(diag_ranger, diag_lm, variable = "y")
plot(diag_ranger, diag_lm, variable = "construction.year")
plot(diag_ranger, variable = "y", yvariable = "y_hat")
```



---

plot.model\_parts      *Plot Variable Importance Explanations*

---

### Description

Plot Variable Importance Explanations

### Usage

```
## S3 method for class 'model_parts'  
plot(x, ...)
```

### Arguments

x                    an object of the class model\_parts  
...                  other parameters described below

### Value

An object of the class ggplot.

### Plot options

#### **variable\_importance:**

- max\_vars maximal number of features to be included in the plot. default value is 10
- show\_boxplots logical if TRUE (default) boxplot will be plotted to show permutation data.
- bar\_width width of bars. By default 10
- desc\_sorting logical. Should the bars be sorted descending? By default TRUE
- title the plot's title, by default 'Feature Importance'
- subtitle a character. Plot subtitle. By default NULL - then subtitle is set to "created for the XXX, YYY model", where XXX, YYY are labels of given explainers.

---

plot.model\_performance      *Plot Dataset Level Model Performance Explanations*

---

### Description

Plot Dataset Level Model Performance Explanations

**Usage**

```
## S3 method for class 'model_performance'
plot(
  x,
  ...,
  geom = "ecdf",
  show_outliers = 0,
  ptlabel = "name",
  lossFunction = loss_function,
  loss_function = function(x) sqrt(mean(x^2))
)
```

**Arguments**

x	a model to be explained, preprocessed by the <a href="#">explain</a> function
...	other parameters
geom	either "prc", "roc", "ecdf", "boxplot", "gain", "lift" or "histogram" determines how residuals shall be summarized
show_outliers	number of largest residuals to be presented (only when geom = boxplot).
ptlabel	either "name" or "index" determines the naming convention of the outliers
lossFunction	alias for loss_function held for backwards compatibility.
loss_function	function that calculates the loss for a model based on model residuals. By default it's the root mean square. NOTE that this argument was called lossFunction.

**Value**

An object of the class model\_performance.

**Examples**

```
library("ranger")
titanic_ranger_model <- ranger(survived~., data = titanic_imputed, num.trees = 50,
                             probability = TRUE)
explainer_ranger <- explain(titanic_ranger_model, data = titanic_imputed[, -8],
                           y = titanic_imputed$survived)
mp_ranger <- model_performance(explainer_ranger)
plot(mp_ranger)
plot(mp_ranger, geom = "boxplot", show_outliers = 1)

titanic_ranger_model2 <- ranger(survived~gender + fare, data = titanic_imputed,
                              num.trees = 50, probability = TRUE)
explainer_ranger2 <- explain(titanic_ranger_model2, data = titanic_imputed[, -8],
                           y = titanic_imputed$survived,
                           label = "ranger2")
mp_ranger2 <- model_performance(explainer_ranger2)
plot(mp_ranger, mp_ranger2, geom = "prc")
plot(mp_ranger, mp_ranger2, geom = "roc")
plot(mp_ranger, mp_ranger2, geom = "lift")
```

```

plot(mp_ranger, mp_ranger2, geom = "gain")
plot(mp_ranger, mp_ranger2, geom = "boxplot")
plot(mp_ranger, mp_ranger2, geom = "histogram")
plot(mp_ranger, mp_ranger2, geom = "ecdf")

titanic_glm_model <- glm(survived~., data = titanic_imputed, family = "binomial")
explainer_glm <- explain(titanic_glm_model, data = titanic_imputed[,-8],
                        y = titanic_imputed$survived, label = "glm",
                        predict_function = function(m,x) predict.glm(m,x,type = "response"))
mp_glm <- model_performance(explainer_glm)
plot(mp_glm)

titanic_lm_model <- lm(survived~., data = titanic_imputed)
explainer_lm <- explain(titanic_lm_model, data = titanic_imputed[,-8],
                      y = titanic_imputed$survived, label = "lm")
mp_lm <- model_performance(explainer_lm)
plot(mp_lm)

plot(mp_ranger, mp_glm, mp_lm)
plot(mp_ranger, mp_glm, mp_lm, geom = "boxplot")
plot(mp_ranger, mp_glm, mp_lm, geom = "boxplot", show_outliers = 1)

```

---

plot.model\_profile      *Plot Dataset Level Model Profile Explanations*

---

## Description

Plot Dataset Level Model Profile Explanations

## Usage

```

## S3 method for class 'model_profile'
plot(x, ..., geom = "aggregates")

```

## Arguments

x	a variable profile explanation, created with the <a href="#">model_profile</a> function
...	other parameters
geom	either "aggregates", "profiles", "points" determines which will be plotted

## Value

An object of the class ggplot.

### aggregates:

- color a character. Either name of a color, or hex code for a color, or `_label_` if models shall be colored, or `_ids_` if instances shall be colored

- size a numeric. Size of lines to be plotted
- alpha a numeric between 0 and 1. Opacity of lines
- facet\_ncol number of columns for the `facet_wrap`
- variables if not NULL then only variables will be presented
- title a character. Partial and accumulated dependence explainers have default value.
- subtitle a character. If NULL value will be dependent on model usage.

## Examples

```
titanic_glm_model <- glm(survived~., data = titanic_imputed, family = "binomial")
explainer_glm <- explain(titanic_glm_model, data = titanic_imputed)
expl_glm <- model_profile(explainer_glm, "fare")
plot(expl_glm)

library("ranger")
titanic_ranger_model <- ranger(survived~., data = titanic_imputed, num.trees = 50,
                             probability = TRUE)
explainer_ranger <- explain(titanic_ranger_model, data = titanic_imputed)
expl_ranger <- model_profile(explainer_ranger)
plot(expl_ranger)
plot(expl_ranger, geom = "aggregates")

vp_ra <- model_profile(explainer_ranger, type = "partial", variables = c("age", "fare"))
plot(vp_ra, variables = c("age", "fare"), geom = "points")

vp_ra <- model_profile(explainer_ranger, type = "partial", k = 3)
plot(vp_ra)
plot(vp_ra, geom = "profiles")
plot(vp_ra, geom = "points")

vp_ra <- model_profile(explainer_ranger, type = "partial", groups = "gender")
plot(vp_ra)
plot(vp_ra, geom = "profiles")
plot(vp_ra, geom = "points")

vp_ra <- model_profile(explainer_ranger, type = "accumulated")
plot(vp_ra)
plot(vp_ra, geom = "profiles")
plot(vp_ra, geom = "points")
```

---

plot.predict\_diagnostics

*Plot Instance Level Residual Diagnostics*

---

## Description

Plot Instance Level Residual Diagnostics

**Usage**

```
## S3 method for class 'predict_diagnostics'  
plot(x, ...)
```

**Arguments**

**x** an object with instance level residual diagnostics created with `predict_diagnostics` function

**...** other parameters that will be passed to `plot.ceteris_paribus_explaine`.

**Value**

an `ggplot2` object of the class `gg`.

**Examples**

```
library("ranger")  
titanic_glm_model <- ranger(survived ~ gender + age + class + fare + sibsp + parch,  
                           data = titanic_imputed)  
explainer_glm <- explain(titanic_glm_model,  
                        data = titanic_imputed,  
                        y = titanic_imputed$survived)  
johnny_d <- titanic_imputed[24, c("gender", "age", "class", "fare", "sibsp", "parch")]  
  
p1 <- predict_diagnostics(explainer_glm, johnny_d, variables = NULL)  
plot(p1)  
  
p1 <- predict_diagnostics(explainer_glm, johnny_d,  
                        neighbors = 10,  
                        variables = c("age", "fare"))  
plot(p1)  
  
p1 <- predict_diagnostics(explainer_glm,  
                        johnny_d,  
                        neighbors = 10,  
                        variables = c("class", "gender"))  
plot(p1)
```

---

plot.predict\_parts      *Plot Variable Attribution Explanations*

---

**Description**

Plot Variable Attribution Explanations

**Usage**

```
## S3 method for class 'predict_parts'
plot(x, ...)
```

**Arguments**

x                    an object of the class predict\_parts  
 ...                  other parameters described below

**Value**

An object of the class ggplot.

**Plot options****break\_down:**

- max\_features maximal number of features to be included in the plot. default value is 10
- min\_max a range of OX axis. By default NA, therefore it will be extracted from the contributions of x. But it can be set to some constants, useful if these plots are to be used for comparisons.
- add\_contributions if TRUE, variable contributions will be added to the plot.
- shift\_contributions number describing how much labels should be shifted to the right, as a fraction of range. By default equal to 0.05.
- vcolors If NA (default), DrWhy colors are used.
- vnames a character vector, if specified then will be used as labels on OY axis. By default NULL.
- digits number of decimal places ([round](#)) or significant digits ([signif](#)) to be used.
- rounding\_function a function to be used for rounding numbers.
- plot\_distributions if TRUE then distributions of conditional proportions will be plotted. This requires keep\_distributions=TRUE in the [break\\_down](#), [local\\_attributions](#), or [local\\_interactions](#).
- baseline if numeric then vertical line starts in baseline.
- title a character. Plot title. By default "Break Down profile".
- subtitle a character. Plot subtitle. By default NULL - then subtitle is set to "created for the XXX, YYY model", where XXX, YYY are labels of given explainers.
- max\_vars alias for the max\_features parameter.

**shap:**

- show\_boxplots logical if TRUE (default) boxplot will be plotted to show uncertainty of attributions.
- vcolors If NA (default), DrWhy colors are used.
- max\_features maximal number of features to be included in the plot. default value is 10
- max\_vars alias for the max\_features parameter.

**oscillations:**

- bar\_width width of bars. By default 10

---

plot.predict\_profile *Plot Variable Profile Explanations*

---

## Description

Plot Variable Profile Explanations

## Usage

```
## S3 method for class 'predict_profile'  
plot(x, ...)
```

## Arguments

x                    an object of the class predict\_profile  
...                   other parameters

## Value

An object of the class ggplot.

## Plot options

### **ceteris\_paribus:**

- color a character. Either name of a color or name of a variable that should be used for coloring
- size a numeric. Size of lines to be plotted
- alpha a numeric between 0 and 1. Opacity of lines
- facet\_ncol number of columns for the [facet\\_wrap](#)
- variables if not NULL then only variables will be presented
- variable\_type a character. If numerical then only numerical variables will be plotted. If categorical then only categorical variables will be plotted.
- title a character. Plot title. By default "Ceteris Paribus profile".
- subtitle a character. Plot subtitle. By default NULL - then subtitle is set to "created for the XXX, YYY model", where XXX, YYY are labels of given explainers.
- categorical\_type a character. How categorical variables shall be plotted? Either "lines" (default) or "bars".

---

plot.shap\_aggregated *Plot Generic for Break Down Objects*

---

## Description

Displays a waterfall aggregated shap plot for objects of shap\_aggregated class.

## Usage

```
## S3 method for class 'shap_aggregated'
plot(
  x,
  ...,
  shift_contributions = 0.05,
  add_contributions = TRUE,
  add_boxplots = TRUE,
  max_features = 10,
  title = "Aggregated SHAP"
)
```

## Arguments

**x** an explanation object created with function [explain](#).

**...** other parameters like vcolors, vnames, min\_max, digits, rounding\_function, baseline, subtitle, baseline, max\_vars.

**shift\_contributions** number describing how much labels should be shifted to the right, as a fraction of range. By default equal to 0.05.

**add\_contributions** if TRUE, variable contributions will be added to the plot

**add\_boxplots** if TRUE, boxplots of SHAP will be shown

**max\_features** maximal number of features to be included in the plot. default value is 10.

**title** a character. Plot title. By default "Break Down profile".

## Value

a ggplot2 object.

## Examples

```
library("DALEX")
set.seed(1313)
model_titanic_glm <- glm(survived ~ gender + age + fare,
  data = titanic_imputed, family = "binomial")
explain_titanic_glm <- explain(model_titanic_glm,
  data = titanic_imputed,
```



```

y = titanic_imputed$survived,
label = "glm")

bd_glm <- shap_aggregated(explain_titanic_glm, titanic_imputed[1:10, ])
bd_glm
plot(bd_glm)
plot(bd_glm, max_features = 3)
plot(bd_glm, max_features = 3,
      vnames = c("average", "+ male", "+ young", "+ cheap ticket", "+ other factors", "final"))

```

---

predict.explainer      *Predictions for the Explainer*

---

### Description

This is a generic predict() function works for explainer objects.

### Usage

```

## S3 method for class 'explainer'
predict(object, newdata, ...)

model_prediction(explainer, new_data, ...)

```

### Arguments

object	a model to be explained, object of the class explainer
newdata	data.frame or matrix - observations for prediction
...	other parameters that will be passed to the predict function
explainer	a model to be explained, object of the class explainer
new_data	data.frame or matrix - observations for prediction

### Value

An numeric matrix of predictions

### Examples

```

HR_glm_model <- glm(status == "fired"~., data = HR, family = "binomial")
explainer_glm <- explain(HR_glm_model, data = HR)
predict(explainer_glm, HR[1:3,])

library("ranger")
HR_ranger_model <- ranger(status~., data = HR, num.trees = 50, probability = TRUE)

```

```
explainer_ranger <- explain(HR_ranger_model, data = HR)
predict(explainer_ranger, HR[1:3,])

model_prediction(explainer_ranger, HR[1:3,])
```

---

predict\_diagnostics    *Instance Level Residual Diagnostics*

---

## Description

This function performs local diagnostic of residuals. For a single instance its neighbors are identified in the validation data. Residuals are calculated for neighbors and plotted against residuals for all data. Find information how to use this function here: <https://ema.drwhy.ai/localDiagnostics.html>.

## Usage

```
predict_diagnostics(
  explainer,
  new_observation,
  variables = NULL,
  ...,
  nbins = 20,
  neighbors = 50,
  distance = gower::gower_dist
)
```

```
individual_diagnostics(
  explainer,
  new_observation,
  variables = NULL,
  ...,
  nbins = 20,
  neighbors = 50,
  distance = gower::gower_dist
)
```

## Arguments

explainer	a model to be explained, preprocessed by the 'explain' function
new_observation	a new observation for which predictions need to be explained
variables	character - name of variables to be explained
...	other parameters
nbins	number of bins for the histogram. By default 20
neighbors	number of neighbors for histogram. By default 50.
distance	the distance function, by default the gower_dist() function.

**Value**

An object of the class 'predict\_diagnostics'. It's a data frame with calculated distribution of residuals.

**References**

Explanatory Model Analysis. Explore, Explain, and Examine Predictive Models. <https://ema.drwhy.ai/>

**Examples**

```
library("ranger")
titanic_glm_model <- ranger(survived ~ gender + age + class + fare + sibsp + parch,
                           data = titanic_imputed)
explainer_glm <- explain(titanic_glm_model,
                        data = titanic_imputed,
                        y = titanic_imputed$survived)
johnny_d <- titanic_imputed[24, c("gender", "age", "class", "fare", "sibsp", "parch")]

id_johnny <- predict_diagnostics(explainer_glm, johnny_d, variables = NULL)
id_johnny
plot(id_johnny)

id_johnny <- predict_diagnostics(explainer_glm, johnny_d,
                                neighbors = 10,
                                variables = c("age", "fare"))

id_johnny
plot(id_johnny)

id_johnny <- predict_diagnostics(explainer_glm,
                                johnny_d,
                                neighbors = 10,
                                variables = c("class", "gender"))

id_johnny
plot(id_johnny)
```

---

predict\_parts

*Instance Level Parts of the Model Predictions*

---

**Description**

Instance Level Variable Attributions as Break Down, SHAP, aggregated SHAP or Oscillations explanations. Model prediction is decomposed into parts that are attributed for particular variables. From DALEX version 1.0 this function calls the [break\\_down](#) or [shap](#) functions from the iBreakDown package or [ceteris\\_paribus](#) from the ingredients package. Find information how to use the break\_down method here: <https://ema.drwhy.ai/breakDown.html>. Find information how to use the shap method here: <https://ema.drwhy.ai/shapley.html>. Find information how

to use the oscillations method here: <https://ema.drwhy.ai/ceterisParibusOscillations.html>. aSHAP method provides explanations for a set of observations based on SHAP.

### Usage

```

predict_parts(
  explainer,
  new_observation,
  ...,
  N = if (substr(type, 1, 4) == "osci") 500 else NULL,
  type = "break_down"
)

predict_parts_oscillations(explainer, new_observation, ...)

predict_parts_oscillations_uni(
  explainer,
  new_observation,
  variable_splits_type = "uniform",
  ...
)

predict_parts_oscillations_emp(
  explainer,
  new_observation,
  variable_splits = NULL,
  variables = colnames(explainer$data),
  ...
)

predict_parts_break_down(explainer, new_observation, ...)

predict_parts_break_down_interactions(explainer, new_observation, ...)

predict_parts_shap(explainer, new_observation, ...)

predict_parts_shap_aggregated(explainer, new_observation, ...)

variable_attribution(
  explainer,
  new_observation,
  ...,
  N = if (substr(type, 1, 4) == "osci") 500 else NULL,
  type = "break_down"
)

```

### Arguments

`explainer` a model to be explained, preprocessed by the `explain` function

new_observation	a new observation for which predictions need to be explained
...	other parameters that will be passed to <code>iBreakDown::break_down</code>
N	the maximum number of observations used for calculation of attributions. By default NULL (use all) or 500 (for oscillations).
type	the type of variable attributions. Either <code>shap</code> , <code>aggregated_shap</code> , <code>oscillations</code> , <code>oscillations_uni</code> , <code>oscillations_emp</code> , <code>break_down</code> or <code>break_down_interactions</code> .
variable_splits_type	how variable grids shall be calculated? Will be passed to <code>ceteris_paribus</code> .
variable_splits	named list of splits for variables. It is used by oscillations based measures. Will be passed to <code>ceteris_paribus</code> .
variables	names of variables for which splits shall be calculated. Will be passed to <code>ceteris_paribus</code> .

### Value

Depending on the type there are different classes of the resulting object. It's a data frame with calculated average response.

### References

Explanatory Model Analysis. Explore, Explain, and Examine Predictive Models. <https://ema.drwhy.ai/>

### Examples

```
library(DALEX)

new_dragon <- data.frame(
  year_of_birth = 200,
  height = 80,
  weight = 12.5,
  scars = 0,
  number_of_lost_teeth = 5
)

model_lm <- lm(life_length ~ year_of_birth + height +
  weight + scars + number_of_lost_teeth,
  data = dragons)

explainer_lm <- explain(model_lm,
  data = dragons,
  y = dragons$year_of_birth,
  label = "model_lm")

bd_lm <- predict_parts_break_down(explainer_lm, new_observation = new_dragon)
head(bd_lm)
plot(bd_lm)
```

```
library("ranger")
model_ranger <- ranger(life_length ~ year_of_birth + height +
  weight + scars + number_of_lost_teeth,
  data = dragons, num.trees = 50)

explainer_ranger <- explain(model_ranger,
  data = dragons,
  y = dragons$year_of_birth,
  label = "model_ranger")

bd_ranger <- predict_parts_break_down(explainer_ranger, new_observation = new_dragon)
head(bd_ranger)
plot(bd_ranger)
```

---

predict\_profile

*Instance Level Profile as Ceteris Paribus*

---

### Description

This function calculated individual profiles aka Ceteris Paribus Profiles. From DALEX version 1.0 this function calls the `ceteris_paribus` from the `ingredients` package. Find information how to use this function here: <https://ema.drwhy.ai/ceterisParibus.html>.

### Usage

```
predict_profile(
  explainer,
  new_observation,
  variables = NULL,
  ...,
  type = "ceteris_paribus",
  variable_splits_type = "uniform"
)

individual_profile(
  explainer,
  new_observation,
  variables = NULL,
  ...,
  type = "ceteris_paribus",
  variable_splits_type = "uniform"
)
```

### Arguments

`explainer` a model to be explained, preprocessed by the `explain` function

new_observation	a new observation for which predictions need to be explained
variables	character - names of variables to be explained
...	other parameters
type	character, currently only the ceteris_paribus is implemented
variable_splits_type	how variable grids shall be calculated? Use "quantiles" (default) for percentiles or "uniform" to get uniform grid of points. Will be passed to 'ingredients'.

### Value

An object of the class `ceteris_paribus_explainer`. It's a data frame with calculated average response.

### References

Explanatory Model Analysis. Explore, Explain, and Examine Predictive Models. <https://ema.drwhy.ai/>

### Examples

```
new_dragon <- data.frame(year_of_birth = 200,
  height = 80,
  weight = 12.5,
  scars = 0,
  number_of_lost_teeth = 5)

dragon_lm_model4 <- lm(life_length ~ year_of_birth + height +
  weight + scars + number_of_lost_teeth,
  data = dragons)
dragon_lm_explainer4 <- explain(dragon_lm_model4, data = dragons, y = dragons$year_of_birth,
  label = "model_4v")
dragon_lm_predict4 <- predict_profile(dragon_lm_explainer4,
  new_observation = new_dragon,
  variables = c("year_of_birth", "height", "scars"))
head(dragon_lm_predict4)
plot(dragon_lm_predict4,
  variables = c("year_of_birth", "height", "scars"))

library("ranger")
dragon_ranger_model4 <- ranger(life_length ~ year_of_birth + height +
  weight + scars + number_of_lost_teeth,
  data = dragons, num.trees = 50)
dragon_ranger_explainer4 <- explain(dragon_ranger_model4, data = dragons, y = dragons$year_of_birth,
  label = "model_ranger")
dragon_ranger_predict4 <- predict_profile(dragon_ranger_explainer4,
  new_observation = new_dragon,
  variables = c("year_of_birth", "height", "scars"))

head(dragon_ranger_predict4)
plot(dragon_ranger_predict4,
```

```
variables = c("year_of_birth", "height", "scars"))
```

---

`print.description`      *Print Natural Language Descriptions*

---

### **Description**

Generic function

### **Usage**

```
## S3 method for class 'description'  
print(x, ...)
```

### **Arguments**

`x`                    an individual explainer produced with the ‘describe()’ function  
`...`                 other arguments

---

`print.explainer`      *Print Explainer Summary*

---

### **Description**

Print Explainer Summary

### **Usage**

```
## S3 method for class 'explainer'  
print(x, ...)
```

### **Arguments**

`x`                    a model explainer created with the ‘explain’ function  
`...`                 other parameters



**Examples**

```

aps_lm_model4 <- lm(m2.price~., data = apartments)
aps_lm_explainer4 <- explain(aps_lm_model4, data = apartments, y = apartments$m2.price,
                           label = "model_4v")

aps_lm_explainer4

library("ranger")
titanic_ranger_model <- ranger(survived~., data = titanic_imputed, num.trees = 50,
                             probability = TRUE)
explainer_ranger <- explain(titanic_ranger_model, data = titanic_imputed[, -8],
                          y = titanic_imputed$survived,
                          label = "model_ranger")

explainer_ranger

```

---

```
print.model_diagnostics
```

*Print Dataset Level Model Diagnostics*

---

**Description**

Generic function

**Usage**

```
## S3 method for class 'model_diagnostics'
print(x, ...)
```

**Arguments**

x	an object with dataset level residual diagnostics created with <a href="#">model_diagnostics</a> function
...	other parameters

---

```
print.model_info
```

*Print model\_info*

---

**Description**

Function prints object of class `model_info` created with [model\\_info](#)

**Usage**

```
## S3 method for class 'model_info'
print(x, ...)
```

**Arguments**

x                   - an object of class model\_info  
...                 - other parameters

---

print.model\_performance

*Print Dataset Level Model Performance Summary*

---

**Description**

Print Dataset Level Model Performance Summary

**Usage**

```
## S3 method for class 'model_performance'  
print(x, ...)
```

**Arguments**

x                   a model to be explained, object of the class 'model\_performance\_explainer'  
...                 other parameters

**Examples**

```
library("ranger")  
titanic_ranger_model <- ranger(survived~., data = titanic_imputed, num.trees = 100,  
                              probability = TRUE)  
# It's a good practice to pass data without target variable  
explainer_ranger <- explain(titanic_ranger_model, data = titanic_imputed[, -8],  
                            y = titanic_imputed$survived)  
# resulting dataframe has predicted values and residuals  
mp_ex_rn <- model_performance(explainer_ranger)  
mp_ex_rn  
plot(mp_ex_rn)
```

---

`print.model_profile`    *Print Dataset Level Model Profile*

---

**Description**

Generic function

**Usage**

```
## S3 method for class 'model_profile'  
print(x, ...)
```

**Arguments**

`x`                    an object with dataset level profile created with [model\\_profile](#) function  
`...`                other parameters

---

`print.predict_diagnostics`  
                          *Print Instance Level Residual Diagnostics*

---

**Description**

Generic function

**Usage**

```
## S3 method for class 'predict_diagnostics'  
print(x, ...)
```

**Arguments**

`x`                    an object with instance level residual diagnostics created with [predict\\_diagnostics](#) function  
`...`                other parameters

---

set\_theme\_dalex      *Default Theme for DALEX plots*

---

### Description

Default Theme for DALEX plots

### Usage

```
set_theme_dalex(
  default_theme = "drwhy",
  default_theme_vertical = default_theme
)

theme_default_dalex()

theme_vertical_default_dalex()
```

### Arguments

`default_theme`    object - string ("drwhy" or "ema") or an object of ggplot theme class. Will be applied by default by DALEX to all horizontal plots

`default_theme_vertical`    object - string ("drwhy" or "ema") or an object of ggplot theme class. Will be applied by default by DALEX to all vertical plots

### Value

list with current default themes

### Examples

```
old <- set_theme_dalex("ema")

library("ranger")
apartments_ranger_model <- ranger(m2.price~., data = apartments, num.trees = 50)
explainer_ranger <- explain(apartments_ranger_model, data = apartments[,-1],
  y = apartments$m2.price, label = "Ranger Apartments")
model_parts_ranger_aps <- model_parts(explainer_ranger, type = "raw")
head(model_parts_ranger_aps, 8)
plot(model_parts_ranger_aps)

old <- set_theme_dalex(ggplot2::theme_void(), ggplot2::theme_void())
plot(model_parts_ranger_aps)

old <- set_theme_dalex("drwhy")
plot(model_parts_ranger_aps)
old <- set_theme_dalex(ggplot2::theme_void(), ggplot2::theme_void())
plot(model_parts_ranger_aps)
```

---

shap_aggregated	<i>SHAP aggregated values</i>
-----------------	-------------------------------

---

### Description

This function works in a similar way to shap function from iBreakDown but it calculates explanations for a set of observation and then aggregates them.

### Usage

```
shap_aggregated(explainer, new_observations, order = NULL, B = 25, ...)
```

### Arguments

explainer	a model to be explained, preprocessed by the explain function
new_observations	a set of new observations with columns that correspond to variables used in the model.
order	if not NULL, then it will be a fixed order of variables. It can be a numeric vector or vector with names of variables.
B	number of random paths
...	other parameters like label, predict_function, data, x

### Value

an object of the shap\_aggregated class.

### References

Explanatory Model Analysis. Explore, Explain and Examine Predictive Models. <https://ema.drwhy.ai>

### Examples

```
library("DALEX")
set.seed(1313)
model_titanic_glm <- glm(survived ~ gender + age + fare,
                        data = titanic_imputed, family = "binomial")
explain_titanic_glm <- explain(model_titanic_glm,
                             data = titanic_imputed,
                             y = titanic_imputed$survived,
                             label = "glm")

bd_glm <- shap_aggregated(explain_titanic_glm, titanic_imputed[1:10, ])
```

```
bd_glm  
plot(bd_glm, max_features = 3)
```

---

theme_drwhy	<i>DrWhy Theme for ggplot objects</i>
-------------	---------------------------------------

---

**Description**

DrWhy Theme for ggplot objects

**Usage**

```
theme_drwhy()  
theme_ema()  
theme_drwhy_vertical()  
theme_ema_vertical()
```

**Value**

theme for ggplot2 objects

---

titanic	<i>Passengers and Crew on the RMS Titanic Data</i>
---------	--

---

**Description**

The `titanic` data is a complete list of passengers and crew members on the RMS Titanic. It includes a variable indicating whether a person did survive the sinking of the RMS Titanic on April 15, 1912.

**Usage**

```
data(titanic)  
data(titanic_imputed)
```

**Format**

a data frame with 2207 rows and 9 columns

## Details

This dataset was copied from the `stablelearner` package and went through few variable transformations. Levels in `embarked` was replaced with full names, `sibsp`, `parch` and `fare` were converted to numerical variables and values for crew were replaced with 0. If you use this dataset please cite the original package.

From `stablelearner`: The website <https://www.encyclopedia-titanica.org> offers detailed information about passengers and crew members on the RMS Titanic. According to the website 1317 passengers and 890 crew member were aboard. 8 musicians and 9 employees of the shipyard company are listed as passengers, but travelled with a free ticket, which is why they have NA values in `fare`. In addition to that, `fare` is truly missing for a few regular passengers.

- `gender` a factor with levels `male` and `female`.
- `age` a numeric value with the persons age on the day of the sinking.
- `class` a factor specifying the class for passengers or the type of service aboard for crew members.
- `embarked` a factor with the persons place of of embarkment (`Belfast/Cherbourg/Queenstown/Southampton`).
- `country` a factor with the persons home country.
- `fare` a numeric value with the ticket price (0 for crew members, musicians and employees of the shipyard company).
- `sibsp` an ordered factor specifying the number if siblings/spouses aboard; adopted from `Vanderbild` data set (see below).
- `parch` an ordered factor specifying the number of parents/children aboard; adopted from `Vanderbild` data set (see below).
- `survived` a factor with two levels (`no` and `yes`) specifying whether the person has survived the sinking.

NOTE: The `titanic_imputed` dataset use following imputation rules.

- Missing `'age'` is replaced with the mean of the observed ones, i.e., 30.
- For `sibsp` and `parch`, missing values are replaced by the most frequently observed value, i.e., 0.
- For `fare`, mean fare for a given class is used, i.e., 0 pounds for crew, 89 pounds for the 1st, 22 pounds for the 2nd, and 13 pounds for the 3rd class.

## Source

This dataset was copied from the `stablelearner` package and went through few variable transformations. The complete list of persons on the RMS titanic was downloaded from <https://www.encyclopedia-titanica.org> on April 5, 2016. The information given in `sibsp` and `parch` was adopted from a data set obtained from <https://biostat.app.vumc.org/wiki/Main/DataSets>.

## References

<https://www.encyclopedia-titanica.org> and <https://CRAN.R-project.org/package=stablelearner>

---

update_data	<i>Update data of an explainer object</i>
-------------	---

---

**Description**

Function allows users to update data and y of any explainer in a unified way. It doesn't require knowledge about structure of an explainer.

**Usage**

```
update_data(explainer, data, y = NULL, verbose = TRUE)
```

**Arguments**

explainer	- explainer object that is supposed to be updated.
data	- new data, is going to be passed to an explainer
y	- new y, is going to be passed to an explainer
verbose	- logical, indicates if information about update should be printed

**Value**

updated explainer object

**Examples**

```
aps_lm_model4 <- lm(m2.price ~., data = apartments)
aps_lm_explainer4 <- explain(aps_lm_model4, data = apartments, label = "model_4v")
explainer <- update_data(aps_lm_explainer4, data = apartmentsTest, y = apartmentsTest$m2.price)
```

---

update_label	<i>Update label of explainer object</i>
--------------	---

---

**Description**

Function allows users to update label of any explainer in a unified way. It doesn't require knowledge about structure of an explainer.

**Usage**

```
update_label(explainer, label, verbose = TRUE)
```



**Arguments**

- explainer - explainer object that is supposed to be updated.
- label - new label, is going to be passed to an explainer
- verbose - logical, indicates if information about update should be printed

**Value**

updated explainer object

**Examples**

```
aps_lm_model4 <- lm(m2.price ~., data = apartments)
aps_lm_explainer4 <- explain(aps_lm_model4, data = apartments, label = "model_4v")
explainer <- update_label(aps_lm_explainer4, label = "lm")
```

---

variable_effect	<i>Dataset Level Variable Effect as Partial Dependency Profile or Accumulated Local Effects</i>
-----------------	---

---

**Description**

From DALEX version 1.0 this function calls the [accumulated\\_dependence](#) or [partial\\_dependence](#) from the ingredients package. Find information how to use this function here: <https://ema.drwhy.ai/partialDependenceProfiles.html>.

**Usage**

```
variable_effect(explainer, variables, ..., type = "partial_dependency")
```

```
variable_effect_partial_dependency(explainer, variables, ...)
```

```
variable_effect_accumulated_dependency(explainer, variables, ...)
```

**Arguments**

- explainer a model to be explained, preprocessed by the 'explain' function
- variables character - names of variables to be explained
- ... other parameters
- type character - type of the response to be calculated. Currently following options are implemented: 'partial\_dependency' for Partial Dependency and 'accumulated\_dependency' for Accumulated Local Effects

**Value**

An object of the class 'aggregated\_profiles\_explainer'. It's a data frame with calculated average response.

## References

Explanatory Model Analysis. Explore, Explain, and Examine Predictive Models. <https://ema.drwhy.ai/>

## Examples

```
titanic_glm_model <- glm(survived~., data = titanic_imputed, family = "binomial")
explainer_glm <- explain(titanic_glm_model, data = titanic_imputed)
expl_glm <- variable_effect(explainer_glm, "fare", "partial_dependency")
plot(expl_glm)

library("ranger")
titanic_ranger_model <- ranger(survived~., data = titanic_imputed, num.trees = 50,
                              probability = TRUE)
explainer_ranger <- explain(titanic_ranger_model, data = titanic_imputed)
expl_ranger <- variable_effect(explainer_ranger, variables = "fare",
                              type = "partial_dependency")
plot(expl_ranger)
plot(expl_ranger, expl_glm)

# Example for factor variable (with factorMerger)
expl_ranger_factor <- variable_effect(explainer_ranger, variables = "class")
plot(expl_ranger_factor)
```

---

yhat

*Wrap Various Predict Functions*

---

## Description

This function is a wrapper over various predict functions for different models and different model structures. The wrapper returns a single numeric score for each new observation. To do this it uses different extraction techniques for models from different classes, like for classification random forest it forces the output to be probabilities not classes itself.

## Usage

```
yhat(X.model, newdata, ...)
```

## S3 method for class 'lm'

```
yhat(X.model, newdata, ...)
```

## S3 method for class 'randomForest'

```
yhat(X.model, newdata, ...)
```

## S3 method for class 'svm'

```
yhat(X.model, newdata, ...)  
  
## S3 method for class 'gbm'  
yhat(X.model, newdata, ...)  
  
## S3 method for class 'glm'  
yhat(X.model, newdata, ...)  
  
## S3 method for class 'cv.glmnet'  
yhat(X.model, newdata, ...)  
  
## S3 method for class 'glmnet'  
yhat(X.model, newdata, ...)  
  
## S3 method for class 'ranger'  
yhat(X.model, newdata, ...)  
  
## S3 method for class 'model_fit'  
yhat(X.model, newdata, ...)  
  
## S3 method for class 'train'  
yhat(X.model, newdata, ...)  
  
## S3 method for class 'lrm'  
yhat(X.model, newdata, ...)  
  
## S3 method for class 'rpart'  
yhat(X.model, newdata, ...)  
  
## S3 method for class '~function~'  
yhat(X.model, newdata, ...)  
  
## S3 method for class 'party'  
yhat(X.model, newdata, ...)  
  
## Default S3 method:  
yhat(X.model, newdata, ...)
```

### Arguments

X.model	object - a model to be explained
newdata	data.frame or matrix - observations for prediction
...	other parameters that will be passed to the predict function

### Details

Currently supported packages are:

- class `cv.glmnet` and `glmnet` - models created with **glmnet** package,

- class `glm` - generalized linear models created with `glm`,
- class `model_fit` - models created with `parsnip` package,
- class `lm` - linear models created with `lm`,
- class `ranger` - models created with `ranger` package,
- class `randomForest` - random forest models created with `randomForest` package,
- class `svm` - support vector machines models created with the `e1071` package,
- class `train` - models created with `caret` package,
- class `gbm` - models created with `gbm` package,
- class `lrm` - models created with `rms` package,
- class `rpart` - models created with `rpart` package.

**Value**

An numeric matrix of predictions

# Index

- \* **HR**
    - HR, [11](#)
  - \* **apartments**
    - apartments, [3](#)
  - \* **covid\_spring**
    - covid, [4](#)
  - \* **covid\_summer**
    - covid, [4](#)
  - \* **dragons**
    - dragons, [5](#)
  - \* **fifa**
    - fifa, [9](#)
  - \* **happiness\_test**
    - happiness, [11](#)
  - \* **happiness\_train**
    - happiness, [11](#)
  - \* **titanic**
    - titanic, [46](#)
- accumulated\_dependence, [22](#), [49](#)
- apartments, [3](#)
- apartments\_test (apartments), [3](#)
- apartmentsTest (apartments), [3](#)
- break\_down, [30](#), [35](#)
- ceteris\_paribus, [35](#), [37](#), [38](#)
- colors\_breakdown\_drwhy
  - (colors\_discrete\_drwhy), [3](#)
- colors\_discrete\_drwhy, [3](#)
- colors\_diverging\_drwhy
  - (colors\_discrete\_drwhy), [3](#)
- covid, [4](#)
- covid\_spring (covid), [4](#)
- covid\_summer (covid), [4](#)
- dragons, [5](#)
- dragons\_test (dragons), [5](#)
- explain, [19](#), [26](#), [32](#)
- explain (explain.default), [5](#)
- explain.default, [5](#)
- facet\_wrap, [28](#), [31](#)
- feature\_importance, [17](#)
- feature\_importance (model\_parts), [17](#)
- fifa, [9](#)
- glm, [52](#)
- happiness, [11](#)
- happiness\_test (happiness), [11](#)
- happiness\_train (happiness), [11](#)
- HR, [11](#)
- HR\_test (HR), [11](#)
- HRTTest (HR), [11](#)
- individual\_diagnostics
  - (predict\_diagnostics), [34](#)
- individual\_profile (predict\_profile), [38](#)
- install\_dependencies, [12](#)
- lm, [52](#)
- local\_attributions, [30](#)
- local\_interactions, [30](#)
- loss\_accuracy (loss\_cross\_entropy), [12](#)
- loss\_cross\_entropy, [12](#)
- loss\_default (loss\_cross\_entropy), [12](#)
- loss\_one\_minus\_auc
  - (loss\_cross\_entropy), [12](#)
- loss\_root\_mean\_square
  - (loss\_cross\_entropy), [12](#)
- loss\_sum\_of\_squares
  - (loss\_cross\_entropy), [12](#)
- loss\_yardstick, [13](#)
- model\_diagnostics, [14](#), [24](#), [41](#)
- model\_info, [15](#), [41](#)
- model\_parts, [17](#)
- model\_performance, [19](#)
- model\_prediction (predict.explainer), [33](#)
- model\_profile, [21](#), [27](#), [43](#)

partial\_dependence, 22, 49  
plot.list, 23  
plot.model\_diagnostics, 24  
plot.model\_parts, 25  
plot.model\_performance, 25  
plot.model\_profile, 27  
plot.predict\_diagnostics, 28  
plot.predict\_parts, 29  
plot.predict\_profile, 31  
plot.shap\_aggregated, 32  
predict.explainer, 33  
predict\_diagnostics, 29, 34, 43  
predict\_parts, 35  
predict\_parts\_break\_down  
    (predict\_parts), 35  
predict\_parts\_break\_down\_interactions  
    (predict\_parts), 35  
predict\_parts\_ibreak\_down  
    (predict\_parts), 35  
predict\_parts\_oscillations  
    (predict\_parts), 35  
predict\_parts\_oscillations\_emp  
    (predict\_parts), 35  
predict\_parts\_oscillations\_uni  
    (predict\_parts), 35  
predict\_parts\_shap(predict\_parts), 35  
predict\_parts\_shap\_aggregated  
    (predict\_parts), 35  
predict\_profile, 38  
print.description, 40  
print.explainer, 40  
print.model\_diagnostics, 41  
print.model\_info, 41  
print.model\_performance, 42  
print.model\_profile, 43  
print.predict\_diagnostics, 43  
  
round, 30  
  
set\_theme\_dalex, 44  
shap, 35  
shap\_aggregated, 45  
signif, 30  
single\_variable(model\_profile), 21  
  
theme\_default\_dalex(set\_theme\_dalex),  
    44  
theme\_drwhy, 46  
theme\_drwhy\_vertical(theme\_drwhy), 46  
  
theme\_ema(theme\_drwhy), 46  
theme\_ema\_vertical(theme\_drwhy), 46  
theme\_vertical\_default\_dalex  
    (set\_theme\_dalex), 44  
titanic, 46  
titanic\_imputed(titanic), 46  
  
update\_data, 48  
update\_label, 48  
  
variable\_attribution(predict\_parts), 35  
variable\_effect, 49  
variable\_effect\_accumulated\_dependency  
    (variable\_effect), 49  
variable\_effect\_partial\_dependency  
    (variable\_effect), 49  
variable\_importance(model\_parts), 17  
variable\_profile(model\_profile), 21  
  
yhat, 50