

Package ‘absorber’

July 22, 2025

Type Package

Title Variable Selection in Nonparametric Models using B-Splines

Version 1.0

Date 2024-02-22

Author Mary E. Savino [aut, cre],
Celine Levy-Leduc [ctb]

Maintainer Mary E. Savino <mary.savino@outlook.fr>

Description A variable selection method using B-Splines in multivariate nOnparametric Regres-
sion models Based on partial dErivatives Regularization (ABSORBER) implements a novel vari-
able selection method in a nonlinear multivariate model using B-splines. For further de-
tails we refer the reader to the paper Savino, M. E. and Lévy-
Leduc, C. (2024), <<https://hal.science/hal-04434820>>.

License GPL-2

Encoding UTF-8

LazyData true

Depends R (>= 3.5.0), Matrix, sparsegl, fda, parallel

Imports ggplot2, MASS, irlba

Suggests knitr, markdown

VignetteBuilder knitr

NeedsCompilation no

Repository CRAN

Date/Publication 2024-02-23 18:50:08 UTC

Contents

absorber-package	2
absorber	2
plot_selection	3
x_obs	4
y_obs	4

Index	5
--------------	----------

absorber-package

Variable Selection in Nonparametric Models using B-Splines

Description

absorber consists of two functions: "absorber.R" and "plot_selection.R". For further information on how to use these functions, we refer the reader to the vignette of the package.

Details

Two datasets are also provided within this package and used as examples of this manual and in the vignette.

Author(s)

Mary E. Savino

Maintainer: Mary E. Savino <mary.savino@outlook.fr>

References

Savino, M. E. and Lévy-Leduc, C. (2024) A novel variable selection method in nonlinear multivariate models using B-splines with an application to geoscience. <<https://hal.science/hal-04434820>>.

absorber

Variable selection in nonparametric models

Description

This function implements the method described in Savino, M. E. and Levy-Leduc, C (2024) for variable selection in nonlinear multivariate settings where observations are assumed to satisfy a nonparametric regression model. Each observation point should belong to $[0, 1]^p$.

Usage

```
absorber(x, y, M = 3, K = 1, all.variables = NULL, parallel = FALSE, nbCore = 1)
```

Arguments

x	matrix of p columns containing the input values of the observations, each observation belonging to $[0, 1]^p$.
y	vector containing the corresponding response variable associated to the input values x.
M	order of the B-spline basis used in the regression model. Default is 3 (quadratic B-splines).
K	number of evenly spaced knots to use in the B-spline basis. Default value is 1.

<code>all.variables</code>	list of characters or integers, labels of the variables. Default is NULL.
<code>parallel</code>	logical, if TRUE then a parallelized version of the code is used. Default is FALSE.
<code>nbCore</code>	numerical, number of cores used for parallelization, if parallel is set to TRUE.

Value

<code>selec.var</code>	list of vectors of the selected variables, one vector for each penalization parameter.
<code>aic.var</code>	vector of variables selected using AIC.

Examples

```
# --- Loading values of x --- #
data('x_obs')
# --- Loading values of the corresponding y --- #
data('y_obs')
x_trunc = x_obs[1:70,,drop=FALSE]
y_trunc = y_obs[1:70]

# --- Variable selection of f1 --- #
absorber(x=x_trunc, y=y_trunc, M = 3)

# --- Parallel computing --- #
absorber(x=x_trunc, y=y_trunc, M = 3, parallel = TRUE, nbCore = 2)
```

plot_selection	<i>Visualization of the selected variables</i>
----------------	--

Description

This function produces a histogram of the variable selection percentage for each variable on which f depends. It also displays the results obtained with the AIC.

Usage

```
plot_selection(object)
```

Arguments

object	output obtained with <code>absorber()</code> .
--------	--

Value

This function produces a `ggplot2::ggplot()` plot to visualize the variables selected with `absorber()`.

Examples

```
# --- Loading values of x --- #
data('x_obs')
# --- Loading values of the corresponding y --- #
data('y_obs')
x_trunc = x_obs[1:70,,drop=FALSE]
y_trunc = y_obs[1:70]

# --- Variable selection of f1 --- #
res = absorber(x=x_trunc, y=y_trunc, M = 3)
plot_selection(res)
```

x_obs	Observation matrix x of five variables
-------	--

Description

An example of 700 observations for the variable selection of function f_1 (see Savino and Lévy-Leduc (2024) for more details) with five input variables.

Usage

```
data("x_obs")
```

Format

Numeric matrix of 700 rows and 5 columns.

y_obs	Values of the response variable of the noisy observation set of five input variables
-------	--

Description

An example of noisy observations obtained by adding a Gaussian noise to $f_1(x_i)$ associated to the input values contained in x_obs.rda. See Savino and Lévy-Leduc (2024) for the expression of f_1 .

Usage

```
data("y_obs")
```

Format

Numeric vector of 700 values.

Index

* **package**

absorber-package, [2](#)

absorber, [2](#)

absorber(), [3](#)

absorber-package, [2](#)

ggplot2::ggplot(), [3](#)

plot_selection, [3](#)

x_obs, [4](#)

y_obs, [4](#)