

Package ‘botor’

July 22, 2025

Type Package

Title 'AWS Python SDK' ('boto3') for R

Description Fork-safe, raw access to the 'Amazon Web Services' ('AWS') 'SDK' via the 'boto3' 'Python' module, and convenient helper functions to query the 'Simple Storage Service' ('S3') and 'Key Management Service' ('KMS'), partial support for 'IAM', the 'Systems Manager Parameter Store' and 'Secrets Manager'.

SystemRequirements Python and boto3
(<https://aws.amazon.com/sdk-for-python>)

Version 0.4.1

Date 2025-01-23

URL <https://daroczig.github.io/botor/>

BugReports <https://github.com/daroczig/botor/issues>

RoxygenNote 7.3.2

License AGPL-3

Encoding UTF-8

Imports utils, reticulate, checkmate, logger, jsonlite

Suggests testthat, covr, digest

NeedsCompilation no

Author Gergely Daróczi [aut, cre] (ORCID:
<<https://orcid.org/0000-0003-3149-8537>>),
System1 [fnd]

Maintainer Gergely Daróczi <daroczig@rapporter.net>

Repository CRAN

Date/Publication 2025-01-24 13:20:02 UTC

Contents

boto3	2
boto3_version	3

boto	3
boto_client	4
check_s3_uri	5
iam	5
iam_get_user	6
iam_whoami	6
kinesis	7
kinesis_describe_stream	7
kinesis_get_records	8
kinesis_get_shard_iterator	8
kinesis_put_record	9
kms	10
kms_decrypt	11
kms_decrypt_file	11
kms_encrypt	12
kms_encrypt_file	12
kms_generate_data_key	13
mime_guess	13
s3	14
s3_copy	14
s3_delete	15
s3_download_file	15
s3_exists	16
s3_list_buckets	17
s3_ls	17
s3_object	18
s3_put_object_tagging	18
s3_read	19
s3_upload_file	20
s3_write	21
sm	22
sm_get_secret	22
ssm	23
ssm_get_parameter	23
sts_whoami	24

Index 25

boto3

Raw access to the boto3 module imported at package load time

Description

Raw access to the boto3 module imported at package load time

Usage

boto3

Format

An object of class `python.builtins.module` (inherits from `python.builtins.object`) of length 0.

Note

You may rather want to use `botor` instead, that provides a fork-safe boto3 session.

boto3_version	<i>boto3 version</i>
---------------	----------------------

Description

boto3 version

Usage

`boto3_version()`

Value

string

botor	<i>The default, fork-safe Boto3 session</i>
-------	---

Description

The default, fork-safe Boto3 session

Usage

```
botor(  
    aws_access_key_id,  
    aws_secret_access_key,  
    aws_session_token,  
    region_name,  
    botocore_session,  
    profile_name  
)
```

Arguments

aws_access_key_id	AWS access key ID
aws_secret_access_key	AWS secret access key
aws_session_token	AWS temporary session token
region_name	Default region when creating new connections
botocore_session	Use this Botocore session instead of creating a new default one
profile_name	The name of a profile to use. If not given, then the default profile is used

Value

boto3 Session

botor_client	<i>Creates an initial or reinitialize an already existing AWS client or resource cached in the package's namespace</i>
--------------	--

Description

Creates an initial or reinitialize an already existing AWS client or resource cached in the package's namespace

Usage

```
botor_client(service, type = c("client", "resource"), cache = TRUE, ...)
```

Arguments

service	string, eg S3 or IAM
type	AWS service client or resource to be created, eg s3
cache	boolean flag for caching the client or resource in the package namespace. For (internal) package functions, it's best to set to TRUE to avoid reinitializing the client/resource, but for custom use and when you need to use multiple clients for the same service in parallel (eg working with different regions etc), you might want to set this to FALSE
...	further parameters passed to the client or resource, eg endpoint_url

Value

cached AWS client

References

<https://boto3.amazonaws.com/v1/documentation/api/latest/reference/core/session.html>

`check_s3_uri`*Check if an argument looks like an S3 bucket*

Description

Check if an argument looks like an S3 bucket

Usage

```
check_s3_uri(x)
```

Arguments

<code>x</code>	string, URI of an S3 object, should start with <code>s3://</code> , then bucket name and object key
----------------	---

Examples

```
check_s3_uri('s3://foo/bar')
check_s3_uri('https://foo/bar')
## Not run:
assert_s3_uri('https://foo/bar')

## End(Not run)
```

`iam`*The default, fork-safe IAM client on the top of boto*

Description

The default, fork-safe IAM client on the top of boto

Usage

```
iam()
```

Value

```
botocore.client.IAM
```

References

<https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/iam.html>

iam_get_user	<i>Retrieves information about the specified IAM user, including the user's creation date, path, unique ID, and ARN</i>
--------------	---

Description

Retrieves information about the specified IAM user, including the user's creation date, path, unique ID, and ARN

Usage

```
iam_get_user(...)
```

Arguments

... optional extra arguments passed

Value

list

References

https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/iam.html#IAM.Client.get_user

iam_whoami	<i>Get the current AWS username</i>
------------	-------------------------------------

Description

Get the current AWS username

Usage

```
iam_whoami()
```

Value

string

See Also

[sts_whoami](#)

kinesis	<i>The default, fork-safe Kinesis client on the top of boto</i>
---------	---

Description

The default, fork-safe Kinesis client on the top of boto

Usage

kinesis()

Value

botocore.client.Kinesis

References

<https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/kinesis.html>

kinesis_describe_stream	<i>Describes the specified Kinesis data stream</i>
-------------------------	--

Description

Describes the specified Kinesis data stream

Usage

kinesis_describe_stream(stream)

Arguments

stream	the name of the stream to describe
--------	------------------------------------

Value

list

References

https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/kinesis.html#Kinesis.Client.describe_stream

kinesis_get_records	<i>Gets data records from a Kinesis data stream's shard</i>
---------------------	---

Description

Gets data records from a Kinesis data stream's shard

Usage

```
kinesis_get_records(shard_iterator, limit = 25L)
```

Arguments

shard_iterator	the position in the shard from which you want to start sequentially reading data records, usually provided by kinesis_get_shard_iterator
limit	maximum number of records to return

Value

list of Records, NextShardIterator and MillisBehindLatest

References

https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/kinesis.html#Kinesis.Client.get_records

Examples

```
## Not run:
botor(profile_name = 'botor-tester')
iterator <- kinesis_get_shard_iterator(stream = 'botor-tester', shard = '0')
kinesis_get_records(iterator$ShardIterator)

## End(Not run)
```

kinesis_get_shard_iterator	<i>Gets an Amazon Kinesis shard iterator</i>
----------------------------	--

Description

Gets an Amazon Kinesis shard iterator

Usage

```
kinesis_get_shard_iterator(
    stream,
    shard,
    shard_iterator_type = c("TRIM_HORIZON", "LATEST", "AT_SEQUENCE_NUMBER",
        "AFTER_SEQUENCE_NUMBER", "AT_TIMESTAMP"),
    ...
)
```

Arguments

stream	the name of the stream to describe
shard	the shard ID of the Kinesis Data Streams shard to get the iterator for
shard_iterator_type	determines how the shard iterator is used to start reading data records from the shard
...	optional further parameters, such as StartingSequenceNumber or Timestamp

Value

list of ShardIterator

References

https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/kinesis.html#Kinesis.Client.get_shard_iterator

See Also

[kinesis_get_records](#)

kinesis_put_record	<i>Writes a single data record into an Amazon Kinesis data stream</i>
--------------------	---

Description

Writes a single data record into an Amazon Kinesis data stream

Usage

```
kinesis_put_record(stream, data, partition_key, ...)
```

Arguments

<code>stream</code>	the name of the stream to describe
<code>data</code>	the data blob (<1 MB) to put into the record, which is base64-encoded when the blob is serialized
<code>partition_key</code>	Unicode string with a maximum length limit of 256 characters determining which shard in the stream the data record is assigned to
<code>...</code>	optional further parameters, such as <code>ExplicitHashKey</code> or <code>SequenceNumberForOrdering</code>

Value

list of `ShardId`, `SequenceNumber` and `EncryptionType`

References

https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/kinesis.html#Kinesis.Client.put_record

kms

The default, fork-safe KMS client on the top of boto

Description

The default, fork-safe KMS client on the top of boto

Usage

`kms()`

Value

`botocore.client.KMS`

References

<https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/kms.html>

kms_decrypt	<i>Decrypt cipher into plain text via KMS</i>
-------------	---

Description

Decrypt cipher into plain text via KMS

Usage

```
kms_decrypt(cipher, simplify = TRUE)
```

Arguments

cipher	Base64-encoded ciphertext
simplify	returns decrypted plain-text instead of raw list

Value

decrypted text as string or list

See Also

[kms_encrypt](#)

kms_decrypt_file	<i>Decrypt file via KMS</i>
------------------	-----------------------------

Description

Decrypt file via KMS

Usage

```
kms_decrypt_file(file, return = file)
```

Arguments

file	base file path (without the enc or key suffix)
return	where to place the encrypted file (defaults to file)

Value

decrypted file path

See Also

[kms_encrypt](#) [kms_encrypt_file](#)

kms_encrypt	<i>Encrypt plain text via KMS</i>
-------------	-----------------------------------

Description

Encrypt plain text via KMS

Usage

```
kms_encrypt(key, text, simplify = TRUE)
```

Arguments

key	the KMS customer master key identifier as a fully specified Amazon Resource Name (eg <code>arn:aws:kms:us-east-1:123456789012:key/12345678-1234-1234-1234-123456789012</code>) or an alias with the alias/ prefix (eg <code>alias/foobar</code>)
text	max 4096 bytes long string, eg an RSA key, a database password, or other sensitive customer information
simplify	returns Base64-encoded text instead of raw list

Value

string or list

See Also

[kms_decrypt](#)

kms_encrypt_file	<i>Encrypt file via KMS</i>
------------------	-----------------------------

Description

Encrypt file via KMS

Usage

```
kms_encrypt_file(key, file)
```

Arguments

key	the KMS customer master key identifier as a fully specified Amazon Resource Name (eg <code>arn:aws:kms:us-east-1:123456789012:key/12345678-1234-1234-1234-123456789012</code>) or an alias with the alias/ prefix (eg <code>alias/foobar</code>)
file	file path

Value

two files created with enc (encrypted data) and key (encrypted key) extensions

See Also

[kms_encrypt](#) [kms_decrypt_file](#)

kms_generate_data_key	<i>Generate a data encryption key for envelope encryption via KMS</i>
-----------------------	---

Description

Generate a data encryption key for envelope encryption via KMS

Usage

kms_generate_data_key(key, bytes = 64L)

Arguments

- | | |
|-------|---|
| key | the KMS customer master key identifier as a fully specified Amazon Resource Name (eg <code>arn:aws:kms:us-east-1:123456789012:key/12345678-1234-1234-1234-123456789012</code>) or an alias with the <code>alias/</code> prefix (eg <code>alias/foobar</code>) |
| bytes | the required length of the data encryption key in bytes (so provide eg 64L for a 512-bit key) |

Value

list of the Base64-encoded encrypted version of the data encryption key (to be stored on disk), the raw object of the encryption key and the KMS customer master key used to generate this object

mime_guess	<i>Guess the type of a file based on the filename using mimetypes Python module</i>
------------	---

Description

Guess the type of a file based on the filename using mimetypes Python module

Usage

mime_guess(file)

Arguments

- | | |
|------|------|
| file | path |
|------|------|

Value

string

s3	<i>The default, fork-safe Amazon Simple Storage Service (S3) client on the top of botor</i>
----	---

Description

The default, fork-safe Amazon Simple Storage Service (S3) client on the top of botor

Usage

```
s3(disable_signing = getOption("botor-s3-disable-signing"))
```

Arguments

disable_signing

boolean if requests should be signed. Set to FALSE when interacting with public S3 buckets requiring unauthenticated access.

Value

s3.ServiceResource

References

<https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/s3.html#service-resource>

s3_copy	<i>Copy an object from one S3 location to another</i>
---------	---

Description

Copy an object from one S3 location to another

Usage

```
s3_copy(uri_source, uri_target)
```

Arguments

uri_source	string, location of the source file
uri_target	string, location of the target file

Value

invisibly uri_target

References

<https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/s3.html#S3.Object.copy>

s3_delete	<i>Delete an object stored in S3</i>
-----------	--------------------------------------

Description

Delete an object stored in S3

Usage

```
s3_delete(uri)
```

Arguments

uri	string, URI of an S3 object, should start with s3://, then bucket name and object key
-----	---

s3_download_file	<i>Download a file from S3</i>
------------------	--------------------------------

Description

Download a file from S3

Usage

```
s3_download_file(uri, file, force = TRUE)
```

Arguments

uri	string, URI of an S3 object, should start with s3://, then bucket name and object key
file	string, location of local file
force	boolean, overwrite local file if exists

Value

invisibly file

References

https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/s3.html#S3.Client.download_file

Examples

```
## Not run:
s3_download_file('s3://botor/example-data/mtcars.csv', tempfile())

## End(Not run)
```

s3_exists	<i>Checks if an object exists in S3</i>
-----------	---

Description

Checks if an object exists in S3

Usage

```
s3_exists(uri)
```

Arguments

uri	string, URI of an S3 object, should start with s3://, then bucket name and object key
-----	---

Value

boolean

Examples

```
## Not run:
s3_exists('s3://botor/example-data/mtcars.csv')
s3_exists('s3://botor/example-data/UNDEFINED.CSVLX')

## End(Not run)
```

s3_list_buckets	<i>List all S3 buckets</i>
-----------------	----------------------------

Description

List all S3 buckets

Usage

```
s3_list_buckets(simplify = TRUE)
```

Arguments

simplify return bucket names as a character vector

Value

list of `boto3.resources.factory.s3.Bucket` or a character vector

s3_ls	<i>List objects at an S3 path</i>
-------	-----------------------------------

Description

List objects at an S3 path

Usage

```
s3_ls(uri)
```

Arguments

uri string, should start with `s3://`, then bucket name and optional object key prefix

Value

data.frame with `bucket_name`, object key, `uri` (that can be directly passed to eg [s3_read](#)), size in bytes, owner and `last_modified` timestamp

s3_object

Create an S3 Object reference from an URI

Description

Create an S3 Object reference from an URI

Usage

```
s3_object(uri)
```

Arguments

uri	string, URI of an S3 object, should start with s3://, then bucket name and object key
-----	---

Value

```
s3$Object
```

s3_put_object_tagging *Sets tags on s3 object overwriting all existing tags. Note: tags and metadata tags are not the same*

Description

Sets tags on s3 object overwriting all existing tags. Note: tags and metadata tags are not the same

Usage

```
s3_put_object_tagging(uri, tags)
```

Arguments

uri	string, URI of an S3 object, should start with s3://, then bucket name and object key
tags	named character vector, e.g. c(my_first_name = 'my_first_value', my_second_name = 'my_second_value') where names are the tag names and values are the tag values.

References

https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/s3.html#S3.Client.put_object_tagging

s3_read

*Download and read a file from S3, then clean up***Description**

Download and read a file from S3, then clean up

Usage

```
s3_read(uri, fun, ..., extract = c("none", "gzip", "bzip2", "xz"))
```

Arguments

uri	string, URI of an S3 object, should start with s3://, then bucket name and object key
fun	R function to read the file, eg fromJSON, stream_in, fread or readRDS
...	optional params passed to fun
extract	optionally extract/decompress the file after downloading from S3 but before passing to fun

Value

R object

Examples

```
## Not run:
s3_read('s3://botor/example-data/mtcars.csv', read.csv)
s3_read('s3://botor/example-data/mtcars.csv', data.table::fread)
s3_read('s3://botor/example-data/mtcars.csv2', read.csv2)
s3_read('s3://botor/example-data/mtcars.RDS', readRDS)
s3_read('s3://botor/example-data/mtcars.json', jsonlite::fromJSON)
s3_read('s3://botor/example-data/mtcars.jsonl', jsonlite::stream_in)

## read compressed data
s3_read('s3://botor/example-data/mtcars.csv.gz', read.csv, extract = 'gzip')
s3_read('s3://botor/example-data/mtcars.csv.gz', data.table::fread, extract = 'gzip')
s3_read('s3://botor/example-data/mtcars.csv.bz2', read.csv, extract = 'bzip2')
s3_read('s3://botor/example-data/mtcars.csv.xz', read.csv, extract = 'xz')

## End(Not run)
```

s3_upload_file	<i>Upload a file to S3</i>
----------------	----------------------------

Description

Upload a file to S3

Usage

```
s3_upload_file(file, uri, content_type = mime_guess(file))
```

Arguments

file	string, location of local file
uri	string, URI of an S3 object, should start with s3://, then bucket name and object key
content_type	content type of a file that is auto-guess if omitted

Value

invisibly uri

References

https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/s3.html#S3.Client.upload_file

See Also

[s3_download_file](#)

Examples

```
## Not run:
t <- tempfile()
write.csv(mtcars, t, row.names = FALSE)
s3_upload_file(t, 's3://botor/example-data/mtcars.csv')
unlink(t)
## note that s3_write would have been a much nicer solution for the above

## End(Not run)
```

s3_write

*Write an R object into S3***Description**

Write an R object into S3

Usage

```
s3_write(x, fun, uri, compress = c("none", "gzip", "bzip2", "xz"), ...)
```

Arguments

x	R object
fun	R function with file argument to serialize x to disk before uploading, eg write.csv, write_json, stream_out or saveRDS
uri	string, URI of an S3 object, should start with s3://, then bucket name and object key
compress	optionally compress the file before uploading to S3. If compression is used, it's better to include the related file extension in uri as well (that is not done automatically).
...	optional further arguments passed to fun

Note

The temp file used for this operation is automatically removed.

Examples

```
## Not run:
s3_write(mtcars, write.csv, 's3://botor/example-data/mtcars.csv', row.names = FALSE)
s3_write(mtcars, write.csv2, 's3://botor/example-data/mtcars.csv2', row.names = FALSE)
s3_write(mtcars, jsonlite::write_json, 's3://botor/example-data/mtcars.json', row.names = FALSE)
s3_write(mtcars, jsonlite::stream_out, 's3://botor/example-data/mtcars.jsonl', row.names = FALSE)
s3_write(mtcars, saveRDS, 's3://botor/example-data/mtcars.RDS')

## compress file after writing to disk but before uploading to S3
s3_write(mtcars, write.csv, 's3://botor/example-data/mtcars.csv.gz',
  compress = 'gzip', row.names = FALSE)
s3_write(mtcars, write.csv, 's3://botor/example-data/mtcars.csv.bz2',
  compress = 'bzip2', row.names = FALSE)
s3_write(mtcars, write.csv, 's3://botor/example-data/mtcars.csv.xz',
  compress = 'xz', row.names = FALSE)

## End(Not run)
```

sm	<i>The default, fork-safe AWS Systems Manager (SecretManager) client on the top of boto</i>
----	---

Description

The default, fork-safe AWS Systems Manager (SecretManager) client on the top of boto

Usage

sm()

Value

botocore.client.secretsmanager

References

<https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/secretsmanager.html>

sm_get_secret	<i>Read AWS System Manager's Secrets Manager via Secret Manager</i>
---------------	---

Description

Read AWS System Manager's Secrets Manager via Secret Manager

Usage

sm_get_secret(path, key = NULL, parse_json = TRUE)

Arguments

path	name/path of the key to be read
key	single key or a vector of keys.
parse_json	logical. Default TRUE

Value

(optionally decrypted) value

ssm	<i>The default, fork-safe AWS Systems Manager (SSM) client on the top of boto</i>
-----	---

Description

The default, fork-safe AWS Systems Manager (SSM) client on the top of boto

Usage

ssm()

Value

botocore.client.SSM

References

<https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/ssm.html>

ssm_get_parameter	<i>Read AWS System Manager's Parameter Store</i>
-------------------	--

Description

Read AWS System Manager's Parameter Store

Usage

ssm_get_parameter(path, decrypt = TRUE)

Arguments

path	name/path of the key to be read
decrypt	decrypt the value or return the raw ciphertext

Value

(optionally decrypted) value

sts_whoami	<i>Returns details about the IAM user or role whose credentials are used to call the operation</i>
------------	--

Description

Returns details about the IAM user or role whose credentials are used to call the operation

Usage

```
sts_whoami()
```

Value

list with UserId, Account and Arn

References

https://boto3.amazonaws.com/v1/documentation/api/latest/reference/services/sts.html#STS.Client.get_caller_identity

See Also

[iam_whoami](#)

Index

- * **datasets**
 - boto3, [2](#)
- assert_s3_uri (check_s3_uri), [5](#)
- boto3, [2](#)
- boto3_version, [3](#)
- botor, [3](#), [3](#)
- botor_client, [4](#)
- check_s3_uri, [5](#)
- expect_s3_uri (check_s3_uri), [5](#)
- iam, [5](#)
- iam_get_user, [6](#)
- iam_whoami, [6](#), [24](#)
- kinesis, [7](#)
- kinesis_describe_stream, [7](#)
- kinesis_get_records, [8](#), [9](#)
- kinesis_get_shard_iterator, [8](#), [8](#)
- kinesis_put_record, [9](#)
- kms, [10](#)
- kms_decrypt, [11](#), [12](#)
- kms_decrypt_file, [11](#), [13](#)
- kms_encrypt, [11](#), [12](#), [13](#)
- kms_encrypt_file, [11](#), [12](#)
- kms_generate_data_key, [13](#)
- mime_guess, [13](#)
- s3, [14](#)
- s3_copy, [14](#)
- s3_delete, [15](#)
- s3_download_file, [15](#), [20](#)
- s3_exists, [16](#)
- s3_list_buckets, [17](#)
- s3_ls, [17](#)
- s3_object, [18](#)
- s3_put_object_tagging, [18](#)
- s3_read, [17](#), [19](#)
- s3_upload_file, [20](#)
- s3_write, [21](#)
- sm, [22](#)
- sm_get_secret, [22](#)
- ssm, [23](#)
- ssm_get_parameter, [23](#)
- sts_whoami, [6](#), [24](#)
- test_s3_uri (check_s3_uri), [5](#)