

Package ‘censorncopula’

July 22, 2025

Type Package

Title Estimate Parameter of Bivariate Copula

Version 2.0

Date 2016-03-07

Author Yan Li, Yang Li, Yichen Qin, and Jun yan

Maintainer Yan Li <YanLi_stats@hotmail.com>

Description Implement an interval censor method
to break ties when using data with ties to fitting a
bivariate copula.

License GPL (>= 2)

Depends copula

NeedsCompilation no

Repository CRAN

Date/Publication 2016-03-25 14:48:05

Contents

censorncopula	1
intervalFitb	2
Newloglik2	4
Index	6

censorncopula	<i>Censor method to break ties</i>
---------------	------------------------------------

Description

Implement an interval censor method to break ties when using data with ties to fitting a bivariate copula.

Details

nothing

Author(s)

Yan Li, Yang Li, Yichen Qin, and Jun Yan

References

Yan Li, Yang Li, Yichen Qin, and Jun Yan. Statistical Inference for Copula Modeling(working paper)

Examples

```
library(copula)

## Generate sample and introduce ties
data <- rCopula(50, claytonCopula(2))
data[, 1] <- round(data[, 1], digit=1)

## Estimate parameter of clayton copula from the sample
intervalFitb(copula=claytonCopula(2), method="BFGS", data)
```

intervalFitb	<i>Using censor method to break ties</i>
--------------	--

Description

Estimate the parameter of copula with interval censor method to break ties in data.

Usage

```
intervalFitb(copula, method, x, start, lower, upper, optim.control,
             estimate.variance, hideWarnings, bound.eps)
```

Arguments

copula	Type of copula to fit the data
method	Method used in the 'optim' function
x	Data with ties

See Details for following inputs:

start	Initial value used in 'optim' function
lower, upper	Bounds on the variables for the "L-BFGS-B" method or method "Brent"
optim.control	A list of control parameters
estimate.variance	Estimate variance
hideWarnings	Hide warnings in procedure of estimation
bound.eps	Minimum finite distance

Details

Except the 'copula', 'x' and 'method', other inputs of the intervalFitb function has default value.

For method,

Method "BFGS" is a quasi-Newton method (also known as a variable metric algorithm), specifically that published simultaneously in 1970 by Broyden, Fletcher, Goldfarb and Shanno. This uses function values and gradients to build up a picture of the surface to be optimized.

Method "L-BFGS-B" is that of Byrd et. al. (1995) which allows box constraints, that is each variable can be given a lower and/or upper bound. The initial value must satisfy the constraints. This uses a limited-memory modification of the BFGS quasi-Newton method. If non-trivial bounds are supplied, this method will be selected, with a warning.

Method "Brent" is for one-dimensional problems only, using 'optimize' function. It can be useful in cases where optim() is used inside other functions where only method can be specified, such as in mle from package stats4.

Value

fit	Estimation of parameter
-----	-------------------------

Note

The intervalFitb function only works for bivariate copula function.

Author(s)

Yan Li

References

None

Examples

```
library(copula)

## Generate sample and introduce ties
data <- rCopula(50, claytonCopula(2))
data[, 1] <- round(data[, 1], digit=1)

## Estimate parameter of clayton copula from the sample
intervalFitb(copula=claytonCopula(2), method="BFGS", data)
```

Newloglik2	<i>likelihood function</i>
------------	----------------------------

Description

likelihood function used in intervalFitb()

Usage

```
Newloglik2(param, x, copula)
```

Arguments

param	Value of parameter in copula function
x	Inputted dataset
copula	Selected copula function

Details

none

Value

result	The result of log-likelihood function
--------	---------------------------------------

Note

It's a internal log-likelihood function used in optim function

Author(s)

Yan Li

References

none

See Also

none

Examples

```
library(copula)

## generate sample
data <- rCopula(50, claytonCopula(2))

## return the value of log-likelihood function for selected params
Newloglik2(param=2, data, claytonCopula(2))
```

Index

- * **sensor**
 - sensorcopula, [1](#)
- * **copula**
 - intervalFitb, [2](#)
 - Newloglik2, [4](#)
- * **likelihood**
 - Newloglik2, [4](#)

sensorcopula, [1](#)

intervalFitb, [2](#)

Newloglik2, [4](#)