

Package ‘connectapi’

July 22, 2025

Type Package

Title Utilities for Interacting with the 'Posit Connect' Server API

Version 0.7.0

Description Provides a helpful 'R6' class and methods for interacting with the 'Posit Connect' Server API along with some meaningful utility functions for regular tasks. API documentation varies by 'Posit Connect' installation and version, but the latest documentation is also hosted publicly at <https://docs.posit.co/connect/api/>.

License MIT + file LICENSE

URL <https://posit-dev.github.io/connectapi/>,
<https://github.com/posit-dev/connectapi>

BugReports <https://github.com/posit-dev/connectapi/issues>

Imports bit64, fs, glue, httr, mime, jsonlite, lifecycle, magrittr, purrr, R6, rlang (>= 0.4.2), tibble, uuid, vctrs (>= 0.3.0), base64enc

Suggests covr, dbplyr, dplyr, ggplot2, gridExtra, httptest, knitr, lubridate, progress, rmarkdown, rprojroot, rsconnect, spelling, testthat, webshot2, withr

VignetteBuilder knitr

Encoding UTF-8

Language en-US

RoxygenNote 7.3.2

Config/testthat/edition 3

NeedsCompilation no

Author Toph Allen [aut, cre],
Neal Richardson [aut],
Sean Lopp [aut],
Cole Arendt [aut],
Posit, PBC [cph, fnd]

Maintainer Toph Allen <toph@posit.co>

Repository CRAN

Date/Publication 2025-03-27 16:10:02 UTC

Contents

audit_access_open	4
audit_runas	4
audit_r_versions	5
browse_solo	5
Bundle	6
bundle_dir	7
bundle_path	7
bundle_static	8
connect	9
Content	10
ContentTask	16
content_delete	18
content_item	18
content_list_by_tag	19
content_list_with_permissions	20
content_render	21
content_restart	21
content_title	22
content_update	23
create_random_name	24
dashboard_url	24
dashboard_url_chr	25
delete_runtime_cache	26
delete_thumbnail	27
delete_vanity_url	28
deploy	28
deploy_repo	30
download_bundle	31
Environment	32
get_audit_logs	33
get_aws_content_credentials	35
get_aws_credentials	36
get_bundles	37
get_content	38
get_content_packages	41
get_environment	42
get_groups	43
get_group_content	44
get_group_members	45
get_image	46
get_job	47
get_jobs	48

get_log	50
get_oauth_content_credentials	51
get_oauth_credentials	52
get_packages	53
get_procs	54
get_runtimes	55
get_runtime_caches	56
get_tags	56
get_thumbnail	58
get_timezones	59
get_usage_shiny	59
get_usage_static	61
get_users	63
get_vanity_url	64
get_vanity_urls	65
get_variants	66
get_variant_renderings	66
get_variant_schedule	67
git	68
groups_create_remote	69
has_thumbnail	69
page_cursor	70
permissions	71
poll_task	72
PositConnect	73
promote	87
set_image_path	88
set_run_as	89
set_schedule	90
set_thumbnail	93
set_vanity_url	94
swap_vanity_url	95
swap_vanity_urls	95
Task	96
tbl_connect	98
terminate_jobs	98
users_create_remote	99
user_guid_from_username	100
Vanity	101
vanity_is_available	102
Variant	103
VariantSchedule	106
VariantTask	108
verify_content_name	110

audit_access_open	<i>Audit Access Controls</i>
-------------------	------------------------------

Description

[Experimental]

Usage

```
audit_access_open(content, type = "all")
```

Arguments

content	data.frame of content information, as from get_content()
type	One of "all" or "logged_in". If "all", return a list of apps whose access control is set to "Everyone". If "logged_in", return a list of apps whose access control is set to "All logged in users"

See Also

Other audit functions: [audit_r_versions\(\)](#), [audit_runas\(\)](#), [vanity_is_available\(\)](#)

audit_runas	<i>Audit Run As Settings</i>
-------------	------------------------------

Description

[Experimental]

Usage

```
audit_runas(content)
```

Arguments

content	data.frame of content information, as from get_content()
---------	--

Value

A data frame with the app name and the Run As user if the Run As user is not the default

See Also

Other audit functions: [audit_access_open\(\)](#), [audit_r_versions\(\)](#), [vanity_is_available\(\)](#)

audit_r_versions	<i>Audit R Versions</i>
------------------	-------------------------

Description

[Experimental]

Usage

audit_r_versions(content)

Arguments

content data.frame of content information, as from [get_content\(\)](#)

Value

A plot that shows the R version used by content over time and in aggregate.

See Also

Other audit functions: [audit_access_open\(\)](#), [audit_runas\(\)](#), [vanity_is_available\(\)](#)

browse_solo	<i>Browse</i>
-------------	---------------

Description

Browse to different locations on Connect via `utils::browseURL`

Usage

browse_solo(content)

browse_dashboard(content)

browse_api_docs(connect)

browse_connect(connect)

Arguments

content A R6 Content object
connect A R6 Connect object

Value

The url that is opened in the browser

Bundle

Bundle

Description

Bundle

Bundle

Details

An R6 class that represents a bundle

Public fields

path The bundle path on disk.

size The size of the bundle.

Methods**Public methods:**

- [Bundle\\$new\(\)](#)
- [Bundle\\$print\(\)](#)
- [Bundle\\$clone\(\)](#)

Method `new()`: Initialize this content bundle.

Usage:

`Bundle$new(path)`

Arguments:

path The bundle path on disk.

Method `print()`: Print this object.

Usage:

`Bundle$print(...)`

Arguments:

... Unused.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`Bundle$clone(deep = FALSE)`

Arguments:

deep Whether to make a deep clone.

See Also

Other R6 classes: [Content](#), [ContentTask](#), [Environment](#), [PositConnect](#), [Task](#), [Vanity](#), [Variant](#), [VariantSchedule](#), [VariantTask](#)

bundle_dir	<i>Define a bundle from a Directory</i>
------------	---

Description

Creates a bundle from a target directory.

Usage

```
bundle_dir(  
  path = ".",  
  filename = fs::file_temp(pattern = "bundle", ext = ".tar.gz")  
)
```

Arguments

path	The path to the directory to be bundled
filename	The output bundle path

Value

Bundle A bundle object

See Also

Other deployment functions: [bundle_path\(\)](#), [bundle_static\(\)](#), [deploy\(\)](#), [download_bundle\(\)](#), [poll_task\(\)](#)

Examples

```
bundle_dir(system.file("tests/testthat/examples/shiny/", package = "connectapi"))
```

bundle_path	<i>Define a bundle from a path (a path directly to a tar.gz file)</i>
-------------	---

Description

Define a bundle from a path (a path directly to a tar.gz file)

Usage

```
bundle_path(path)
```

Arguments

path The path to a .tar.gz file

Value

Bundle A bundle object

See Also

Other deployment functions: [bundle_dir\(\)](#), [bundle_static\(\)](#), [deploy\(\)](#), [download_bundle\(\)](#), [poll_task\(\)](#)

Examples

```
bundle_path(system.file("tests/testthat/examples/static.tar.gz", package = "connectapi"))
```

bundle_static	<i>Define a bundle from a static file (or files)</i>
---------------	--

Description

Defines a bundle from static files. It copies all files to a temporary directory, generates a basic manifest file (using the first file as the "primary"), and bundles the directory.

Usage

```
bundle_static(  
  path,  
  filename = fs::file_temp(pattern = "bundle", ext = ".tar.gz")  
)
```

Arguments

path The path to a file (or files) that will be used for the static bundle
filename The output bundle path

Details

NOTE: the `rsconnect` package is required for this function to work properly.

Value

Bundle A bundle object

See Also

Other deployment functions: [bundle_dir\(\)](#), [bundle_path\(\)](#), [deploy\(\)](#), [download_bundle\(\)](#), [poll_task\(\)](#)

Examples

```
bundle_static(system.file("logo.png", package = "connectapi"))
```

connect	<i>Create a connection to Posit Connect</i>
---------	---

Description

Creates a connection to Posit Connect using the server URL and an API key. Validates the connection and checks that the version of the server is compatible with the current version of the package.

Usage

```
connect(
  server = Sys.getenv(paste0(prefix, "_SERVER"), NA_character_),
  api_key = Sys.getenv(paste0(prefix, "_API_KEY"), NA_character_),
  token,
  token_local_testing_key = api_key,
  prefix = "CONNECT",
  ...,
  .check_is_fatal = TRUE
)
```

Arguments

server	The URL for accessing Posit Connect. Defaults to environment variable <code>CONNECT_SERVER</code>
api_key	The API Key to authenticate to Posit Connect with. Defaults to environment variable <code>CONNECT_API_KEY</code>
token	Optional. A user session token. When running on a Connect server, creates a client using the content visitor's account. Running locally, the created client uses the provided API key.
token_local_testing_key	Optional. Only used when not running on Connect and a token is provided. By default, the function returns a Connect object using the <code>api_key</code> . By providing a different key here you can test a visitor client with differently-scoped permissions.
prefix	The prefix used to determine environment variables
...	Additional arguments. Not used at present

`.check_is_fatal`

Whether to fail if "check" requests fail. Useful in rare cases where more http request customization is needed for requests to succeed.

Details

When running on Connect, the client's environment will contain default `CONNECT_SERVER` and `CONNECT_API_KEY` variables. The API key's permissions are scoped to the publishing user's account.

To create a client with permissions scoped to the content visitor's account, call `connect()` passing a user session token from content session headers to the `token` argument. To do this, you must first add a Connect API integration in your published content's Access sidebar.

Value

A Posit Connect R6 object that can be passed along to methods

Examples

```
## Not run:
client <- connect()

# Running in Connect, create a client using the content visitor's account.
# This example assumes code is being executed in a Shiny app's `server`
# function with a `session` object available.
token <- session$request$HTTP_POSIT_CONNECT_USER_SESSION_TOKEN
client <- connect(token = token)

# Test locally with an API key using a different role.
fallback_key <- Sys.getenv("VIEWER_ROLE_API_KEY")
client <- connect(token = token, token_local_testing_key = fallback_key)

## End(Not run)

# default is to read CONNECT_SERVER and CONNECT_API_KEY environment variables
# this example will read TEST_1_SERVER and TEST_1_API_KEY
connect(prefix = "TEST_1")
```

Content

Content

Description

Content

Content

Details

An R6 class that represents content

Public fields

connect An R6 Connect object

content The content details from Posit Connect

Active bindings

default_variant The default variant for this object.

is_rendered TRUE if this is a rendered content type, otherwise FALSE.

is_interactive TRUE if this is a rendered content type, otherwise FALSE.

Methods**Public methods:**

- `Content$new()`
- `Content$get_connect()`
- `Content$get_content()`
- `Content$get_content_remote()`
- `Content$get_bundles()`
- `Content$bundle_download()`
- `Content$bundle_delete()`
- `Content$internal_content()`
- `Content$update()`
- `Content$danger_delete()`
- `Content$get_url()`
- `Content$get_dashboard_url()`
- `Content$jobs()`
- `Content$job()`
- `Content$register_job_kill_order()`
- `Content$variants()`
- `Content$tag_set()`
- `Content$tag_delete()`
- `Content$tags()`
- `Content$permissions_add()`
- `Content$permissions_update()`
- `Content$permissions_delete()`
- `Content$permissions()`
- `Content$environment()`
- `Content$environment_set()`
- `Content$environment_all()`

- `Content$deploy()`
- `Content$repo_enable()`
- `Content$repo_set()`
- `Content$packages()`
- `Content$print()`
- `Content$clone()`

Method `new()`: Initialize this content.

Usage:

```
Content$new(connect, content)
```

Arguments:

`connect` The Connect instance.

`content` The content data.

Method `get_connect()`: Returns the Connect instance.

Usage:

```
Content$get_connect()
```

Method `get_content()`: Returns the underlying content data.

Usage:

```
Content$get_content()
```

Method `get_content_remote()`: Obtain the content data from the Connect server.

Usage:

```
Content$get_content_remote()
```

Method `get_bundles()`: Return the set of content bundles.

Usage:

```
Content$get_bundles()
```

Method `bundle_download()`: Download the source archive for a content bundle.

Usage:

```
Content$bundle_download(  
  bundle_id,  
  filename = tempfile(pattern = "bundle", fileext = ".tar.gz"),  
  overwrite = FALSE  
)
```

Arguments:

`bundle_id` The bundle identifier.

`filename` Where to write the result.

`overwrite` Overwrite an existing filename.

Method `bundle_delete()`: Delete a content bundle.

Usage:

`Content$bundle_delete(bundle_id)`

Arguments:

`bundle_id` The bundle identifier.

Method `internal_content()`: Get this (remote) content item.

Usage:

`Content$internal_content()`

Method `update()`: Update this content item.

Usage:

`Content$update(...)`

Arguments:

... Content fields.

Method `danger_delete()`: Delete this content item.

Usage:

`Content$danger_delete()`

Method `get_url()`: Return the URL for this content.

Usage:

`Content$get_url()`

Method `get_dashboard_url()`: Return the URL for this content in the Posit Connect dashboard.

Usage:

`Content$get_dashboard_url(pane = "")`

Arguments:

`pane` The pane in the dashboard to link to.

Method `jobs()`: Return the jobs for this content

Usage:

`Content$jobs()`

Method `job()`: Return a single job for this content.

Usage:

`Content$job(key)`

Arguments:

`key` The job key.

Method `register_job_kill_order()`: Terminate a single job for this content item.

Usage:

`Content$register_job_kill_order(key)`

Arguments:

key The job key.

Method variants(): Return the variants for this content.

Usage:

Content\$variants()

Method tag_set(): Set a tag for this content.

Usage:

Content\$tag_set(tag_id)

Arguments:

tag_id The tag identifier.

Method tag_delete(): Remove a tag for this content.

Usage:

Content\$tag_delete(tag_id)

Arguments:

tag_id The tag identifier.

Method tags(): The tags for this content.

Usage:

Content\$tags()

Method permissions_add(): Add a principal to the ACL for this content.

Usage:

Content\$permissions_add(principal_guid, principal_type, role)

Arguments:

principal_guid GUID for the target user or group.

principal_type Acting on user or group.

role The kind of content access.

Method permissions_update(): Alter a principal in the ACL for this content.

Usage:

Content\$permissions_update(id, principal_guid, principal_type, role)

Arguments:

id The target identifier.

principal_guid GUID for the target user or group.

principal_type Acting on user or group.

role The kind of content access.

Method permissions_delete(): Remove an entry from the ACL for this content.

Usage:

Content\$permissions_delete(id)

Arguments:

id The target identifier.

Method permissions(): Obtain some or all of the ACL for this content.

Usage:

```
Content$permissions(id = NULL, add_owner = FALSE)
```

Arguments:

id The target identifier.

add_owner Include the content owner in the result set.

Method environment(): Return the environment variables set for this content.

Usage:

```
Content$environment()
```

Method environment_set(): Adjust the environment variables set for this content.

Usage:

```
Content$environment_set(...)
```

Arguments:

... Environment variable names and values. Use NA as the value to unset variables.

Method environment_all(): Overwrite the environment variables set for this content.

Usage:

```
Content$environment_all(...)
```

Arguments:

... Environment variable names and values.

Method deploy(): Deploy this content

Usage:

```
Content$deploy(bundle_id = NULL)
```

Arguments:

bundle_id Target bundle identifier.

Method repo_enable(): Adjust Git polling.

Usage:

```
Content$repo_enable(enabled = TRUE)
```

Arguments:

enabled Polling enabled.

Method repo_set(): Adjust Git repository

Usage:

```
Content$repo_set(repository, branch, subdirectory)
```

Arguments:

repository Git repository URL

branch Git repository branch

subdirectory Git repository directory

Method packages(): Get package dependencies

Usage:
Content\$packages()

Method print(): Print this object.

Usage:
Content\$print(...)

Arguments:
... Unused.

Method clone(): The objects of this class are cloneable with this method.

Usage:
Content\$clone(deep = FALSE)
Arguments:
deep Whether to make a deep clone.

See Also

Other R6 classes: [Bundle](#), [ContentTask](#), [Environment](#), [PositConnect](#), [Task](#), [Vanity](#), [Variant](#), [VariantSchedule](#), [VariantTask](#)

ContentTask	<i>ContentTask</i>
-------------	--------------------

Description

ContentTask
ContentTask

Details

An R6 class that represents a Task for a piece of Content

Super class

[connectapi::Content](#) -> ContentTask

Public fields

task The task.
data The task data.

Methods

Public methods:

- [ContentTask\\$new\(\)](#)
- [ContentTask\\$get_task\(\)](#)
- [ContentTask\\$add_data\(\)](#)
- [ContentTask\\$get_data\(\)](#)
- [ContentTask\\$print\(\)](#)
- [ContentTask\\$clone\(\)](#)

Method `new()`: Initialize this task.

Usage:

```
ContentTask$new(connect, content, task)
```

Arguments:

`connect` The Connect instance.

`content` The Content instance.

`task` The task data.

Method `get_task()`: Return the underlying task.

Usage:

```
ContentTask$get_task()
```

Method `add_data()`: Set the data.

Usage:

```
ContentTask$add_data(data)
```

Arguments:

`data` The data.

Method `get_data()`: Get the data.

Usage:

```
ContentTask$get_data()
```

Method `print()`: Print this object.

Usage:

```
ContentTask$print(...)
```

Arguments:

`...` Unused.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
ContentTask$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other R6 classes: [Bundle](#), [Content](#), [Environment](#), [PositConnect](#), [Task](#), [Vanity](#), [Variant](#), [VariantSchedule](#), [VariantTask](#)

content_delete	<i>Delete Content</i>
----------------	-----------------------

Description

Delete a content item. WARNING: This action deletes all history, configuration, logs, and resources about a content item. It *cannot* be undone.

Usage

```
content_delete(content, force = FALSE)
```

Arguments

content	an R6 content item
force	Optional. A boolean that determines whether we should prompt in interactive sessions

Value

The R6 Content item. The item is deleted, but information about it is cached locally

See Also

Other content functions: [content_item\(\)](#), [content_title\(\)](#), [content_update\(\)](#), [create_random_name\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_thumbnail\(\)](#), [delete_vanity_url\(\)](#), [deploy_repo\(\)](#), [get_bundles\(\)](#), [get_environment\(\)](#), [get_image\(\)](#), [get_job\(\)](#), [get_jobs\(\)](#), [get_log\(\)](#), [get_thumbnail\(\)](#), [get_vanity_url\(\)](#), [git](#), [has_thumbnail\(\)](#), [permissions](#), [set_image_path\(\)](#), [set_run_as\(\)](#), [set_thumbnail\(\)](#), [set_vanity_url\(\)](#), [swap_vanity_url\(\)](#), [swap_vanity_urls\(\)](#), [terminate_jobs\(\)](#), [verify_content_name\(\)](#)

content_item	<i>Get Content Item</i>
--------------	-------------------------

Description

Returns a single content item based on guid

Usage

```
content_item(connect, guid)
```

Arguments

connect	A Connect object
guid	The GUID for the content item to be retrieved

Value

A Content object for use with other content endpoints

See Also

Other content functions: [content_delete\(\)](#), [content_title\(\)](#), [content_update\(\)](#), [create_random_name\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_thumbnail\(\)](#), [delete_vanity_url\(\)](#), [deploy_repo\(\)](#), [get_bundles\(\)](#), [get_environment\(\)](#), [get_image\(\)](#), [get_job\(\)](#), [get_jobs\(\)](#), [get_log\(\)](#), [get_thumbnail\(\)](#), [get_vanity_url\(\)](#), [git](#), [has_thumbnail\(\)](#), [permissions](#), [set_image_path\(\)](#), [set_run_as\(\)](#), [set_thumbnail\(\)](#), [set_vanity_url\(\)](#), [swap_vanity_url\(\)](#), [swap_vanity_urls\(\)](#), [terminate_jobs\(\)](#), [verify_content_name\(\)](#)

Examples

```
## Not run:
connect() %>%
  content_item("some-guid") %>%
  content_update_access_type("all")

## End(Not run)
```

content_list_by_tag	<i>Content List</i>
---------------------	---------------------

Description

[Experimental] Get a content list

Usage

```
content_list_by_tag(src, tag)
```

Arguments

- src An R6 Connect object
- tag A connect_tag_tree object or tag ID

Details

content_list_by_tag() retrieves a content list by tag

content_list_with_permissions

Get Content List with Permissions

Description

[Experimental] These functions are experimental placeholders until the API supports this behavior.

Usage

```
content_list_with_permissions(src, ..., .p = NULL)
```

```
content_list_guid_has_access(content_list, guid)
```

Arguments

src	A Connect R6 object
...	Extra arguments. Currently not used
.p	Optional. A predicate function, passed as-is to <code>purrr::keep()</code> . See <code>get_content()</code> for more details. Can greatly help performance by reducing how many items to get permissions for
content_list	A "content list with permissions" as returned by <code>content_list_with_permissions()</code>
guid	A user or group GUID to filter the content list by whether they have access

Details

`content_list_with_permissions` loops through content and retrieves permissions for each item (with a progress bar). This can take a long time for lots of content! Make sure to use the optional `.p` argument as a predicate function that filters the content list before it is transformed.

`content_list_guid_has_access` works with a `content_list_with_permissions` dataset by checking whether a given GUID (either user or group) has access to the content by:

- checking if the content has `access_type == "all"`
- checking if the content has `access_type == "logged_in"`
- checking if the provided guid is the content owner
- checking if the provided guid is in the list of content permissions (in the "permissions" column)

content_render	<i>Render a content item.</i>
----------------	-------------------------------

Description

Submit a request to render a content item. Once submitted, the server runs an asynchronous process to render the content. This might be useful if content needs to be updated after its source data has changed, especially if this doesn't happen on a regular schedule.

Only valid for rendered content (e.g., most Quarto documents, Jupyter notebooks, R Markdown reports).

Usage

```
content_render(content, variant_key = NULL)
```

Arguments

content	The content item you wish to render.
variant_key	If a variant key is provided, render that variant. Otherwise, render the default variant.

Value

A [VariantTask](#) object that can be used to track completion of the render.

Examples

```
## Not run:
client <- connect()
item <- content_item(client, "951bf3ad-82d0-4bca-bba8-9b27e35c49fa")
task <- content_render(item)
poll_task(task)

## End(Not run)
```

content_restart	<i>Restart a content item.</i>
-----------------	--------------------------------

Description

Submit a request to restart a content item. Once submitted, the server performs an asynchronous request to kill all processes associated with the content item, starting new processes as needed. This might be useful if the application relies on data that is loaded at startup, or if its memory usage has grown over time.

Note that users interacting with certain types of applications may have their workflows interrupted.

Only valid for interactive content (e.g., applications, APIs).

Usage

```
content_restart(content)
```

Arguments

content The content item you wish to restart.

Examples

```
## Not run:
client <- connect()
item <- content_item(client, "8f37d6e0-3395-4a2c-aa6a-d7f2fe1babb0")
content_restart(item)

## End(Not run)
```

content_title	<i>Get Content Title</i>
---------------	--------------------------

Description

Return content title for a piece of content. If the content is missing (deleted) or not visible, then returns the default

Usage

```
content_title(connect, guid, default = "Unknown Content")
```

Arguments

connect A Connect object
guid The GUID for the content item to be retrieved
default The default value returned for missing or not visible content

Value

character. The title of the requested content

See Also

Other content functions: [content_delete\(\)](#), [content_item\(\)](#), [content_update\(\)](#), [create_random_name\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_thumbnail\(\)](#), [delete_vanity_url\(\)](#), [deploy_repo\(\)](#), [get_bundles\(\)](#), [get_environment\(\)](#), [get_image\(\)](#), [get_job\(\)](#), [get_jobs\(\)](#), [get_log\(\)](#), [get_thumbnail\(\)](#), [get_vanity_url\(\)](#), [git](#), [has_thumbnail\(\)](#), [permissions](#), [set_image_path\(\)](#), [set_run_as\(\)](#), [set_thumbnail\(\)](#), [set_vanity_url\(\)](#), [swap_vanity_url\(\)](#), [swap_vanity_urls\(\)](#), [terminate_jobs\(\)](#), [verify_content_name\(\)](#)

content_update	<i>Update Content</i>
----------------	-----------------------

Description

Update settings for a content item. For a list of all settings, see the [latest documentation](#) or the documentation for your server via `connectapi::browse_api_docs()`.

Usage

```
content_update(content, ...)

content_update_access_type(content, access_type = c("all", "logged_in", "acl"))

content_update_owner(content, owner_guid)
```

Arguments

content	An R6 content item
...	Settings up update that are passed along to Posit Connect
access_type	One of "all", "logged_in", or "acl"
owner_guid	The GUID of a user who is a publisher, so that they can become the new owner of the content

Details

Popular selections are `content_update(access_type="all")`, `content_update(access_type="logged_in")` or `content_update(access_type="acl")`, process settings, title, description, etc.

- `content_update_access_type()` is a helper to make it easier to change `access_type`
- `content_update_owner()` is a helper to make it easier to change owner

Value

An R6 content item

See Also

Other content functions: `content_delete()`, `content_item()`, `content_title()`, `create_random_name()`, `dashboard_url()`, `dashboard_url_chr()`, `delete_thumbnail()`, `delete_vanity_url()`, `deploy_repo()`, `get_bundles()`, `get_environment()`, `get_image()`, `get_job()`, `get_jobs()`, `get_log()`, `get_thumbnail()`, `get_vanity_url()`, `git`, `has_thumbnail()`, `permissions`, `set_image_path()`, `set_run_as()`, `set_thumbnail()`, `set_vanity_url()`, `swap_vanity_url()`, `swap_vanity_urls()`, `terminate_jobs()`, `verify_content_name()`

create_random_name	Create Random Name
--------------------	--------------------

Description

Creates a random name from the LETTERS dataset

Usage

```
create_random_name(length = 25)
```

Arguments

length Optional. The length of the random name. Defaults to 25

Value

The randomly generated name

See Also

connectapi::verify_content_name

Other content functions: [content_delete\(\)](#), [content_item\(\)](#), [content_title\(\)](#), [content_update\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_thumbnail\(\)](#), [delete_vanity_url\(\)](#), [deploy_repo\(\)](#), [get_bundles\(\)](#), [get_environment\(\)](#), [get_image\(\)](#), [get_job\(\)](#), [get_jobs\(\)](#), [get_log\(\)](#), [get_thumbnail\(\)](#), [get_vanity_url\(\)](#), [git](#), [has_thumbnail\(\)](#), [permissions](#), [set_image_path\(\)](#), [set_run_as\(\)](#), [set_thumbnail\(\)](#), [set_vanity_url\(\)](#), [swap_vanity_url\(\)](#), [swap_vanity_urls\(\)](#), [terminate_jobs\(\)](#), [verify_content_name\(\)](#)

dashboard_url	Build a Dashboard URL from a Content Item
---------------	---

Description

Returns the URL for the content dashboard (opened to the selected pane).

Usage

```
dashboard_url(content, pane = "")
```

Arguments

content [Content](#) A Content object

pane character The pane in the dashboard to link to

Value

character The dashboard URL for the content provided

See Also

Other content functions: `content_delete()`, `content_item()`, `content_title()`, `content_update()`, `create_random_name()`, `dashboard_url_chr()`, `delete_thumbnail()`, `delete_vanity_url()`, `deploy_repo()`, `get_bundles()`, `get_environment()`, `get_image()`, `get_job()`, `get_jobs()`, `get_log()`, `get_thumbnail()`, `get_vanity_url()`, `git`, `has_thumbnail()`, `permissions`, `set_image_path()`, `set_run_as()`, `set_thumbnail()`, `set_vanity_url()`, `swap_vanity_url()`, `swap_vanity_urls()`, `terminate_jobs()`, `verify_content_name()`

 dashboard_url_chr

Build a Dashboard URL from Character Vectors

Description

Returns the URL for the content dashboard (opened to the selected pane). NOTE: this takes a character object for performance optimization.

Usage

```
dashboard_url_chr(connect_url, content_guid, pane = "")
```

Arguments

<code>connect_url</code>	character The base URL of the Connect server
<code>content_guid</code>	character The guid for the content item in question
<code>pane</code>	character The pane in the dashboard to link to

Value

character The dashboard URL for the content provided

See Also

Other content functions: `content_delete()`, `content_item()`, `content_title()`, `content_update()`, `create_random_name()`, `dashboard_url()`, `delete_thumbnail()`, `delete_vanity_url()`, `deploy_repo()`, `get_bundles()`, `get_environment()`, `get_image()`, `get_job()`, `get_jobs()`, `get_log()`, `get_thumbnail()`, `get_vanity_url()`, `git`, `has_thumbnail()`, `permissions`, `set_image_path()`, `set_run_as()`, `set_thumbnail()`, `set_vanity_url()`, `swap_vanity_url()`, `swap_vanity_urls()`, `terminate_jobs()`, `verify_content_name()`

delete_runtime_cache *Delete a runtime cache*

Description

Delete a runtime cache from a Connect server. Requires Administrator privileges.

Usage

```
delete_runtime_cache(
  client,
  language,
  version,
  image_name = "Local",
  dry_run = FALSE
)
```

Arguments

client	A Connect object.
language	The language of the cache, either "R" or "Python".
version	The version of the cache, e.g. "4.3.3".
image_name	Optional. The name of the off-host execution image for the cache, or "Local" (the default) for native execution caches.
dry_run	Optional, default FALSE. If true, perform a dry run of the deletion.

Value

A Task object representing the deletion task. If dry_run is TRUE, returns NULL or throws an error if the deletion would fail.

See Also

[get_runtime_caches\(\)](#)

Other server management functions: [get_runtime_caches\(\)](#)

Examples

```
## Not run:
client <- connect()
task <- delete_runtime_cache(client, "R", "4.3.3")
poll_task(task)

## End(Not run)
```

delete_thumbnail	<i>Delete content item thumbnail</i>
------------------	--------------------------------------

Description

Delete the thumbnail from a content item on Connect.

Usage

```
delete_thumbnail(content)
```

Arguments

content	A content item.
---------	-----------------

Value

The content item (invisibly).

See Also

Other thumbnail functions: [get_thumbnail\(\)](#), [has_thumbnail\(\)](#), [set_thumbnail\(\)](#)

Other content functions: [content_delete\(\)](#), [content_item\(\)](#), [content_title\(\)](#), [content_update\(\)](#), [create_random_name\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_vanity_url\(\)](#), [deploy_repo\(\)](#), [get_bundles\(\)](#), [get_environment\(\)](#), [get_image\(\)](#), [get_job\(\)](#), [get_jobs\(\)](#), [get_log\(\)](#), [get_thumbnail\(\)](#), [get_vanity_url\(\)](#), [git](#), [has_thumbnail\(\)](#), [permissions](#), [set_image_path\(\)](#), [set_run_as\(\)](#), [set_thumbnail\(\)](#), [set_vanity_url\(\)](#), [swap_vanity_url\(\)](#), [swap_vanity_urls\(\)](#), [terminate_jobs\(\)](#), [verify_content_name\(\)](#)

Examples

```
## Not run:  
client <- connect()  
item <- content_item(client, "8f37d6e0-3395-4a2c-aa6a-d7f2fe1babd0")  
thumbnail <- get_thumbnail(item)  
  
## End(Not run)
```

delete_vanity_url	<i>Delete the Vanity URL</i>
-------------------	------------------------------

Description

Delete the vanity URL for a piece of content.

Usage

```
delete_vanity_url(content)
```

Arguments

content	A Content object
---------	------------------

See Also

Other content functions: [content_delete\(\)](#), [content_item\(\)](#), [content_title\(\)](#), [content_update\(\)](#), [create_random_name\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_thumbnail\(\)](#), [deploy_repo\(\)](#), [get_bundles\(\)](#), [get_environment\(\)](#), [get_image\(\)](#), [get_job\(\)](#), [get_jobs\(\)](#), [get_log\(\)](#), [get_thumbnail\(\)](#), [get_vanity_url\(\)](#), [git](#), [has_thumbnail\(\)](#), [permissions](#), [set_image_path\(\)](#), [set_run_as\(\)](#), [set_thumbnail\(\)](#), [set_vanity_url\(\)](#), [swap_vanity_url\(\)](#), [swap_vanity_urls\(\)](#), [terminate_jobs\(\)](#), [verify_content_name\(\)](#)

deploy	<i>Deploy a bundle</i>
--------	------------------------

Description

Deploys a bundle (tarball) to an Posit Connect server. If not provided, name (a unique identifier) will be an auto-generated alphabetic string. If deploying to an existing endpoint, you can set name or guid to the desired content.

Usage

```
deploy(
  connect,
  bundle,
  name = create_random_name(),
  title = name,
  guid = NULL,
  ...,
  .pre_deploy = {
  }
)

deploy_current(content)
```

Arguments

connect	A Connect object
bundle	A Bundle object
name	The unique name for the content on the server
title	optional The title to be used for the content on the server
guid	optional The GUID if the content already exists on the server
...	Additional arguments passed along to the content creation
.pre_deploy	An expression to execute before deploying the new bundle. The variables content and bundle_id are supplied
content	A Content object

Details

This function accepts the same arguments as `connectapi::content_update()`.

`deploy_current()` is a helper to easily redeploy the currently active bundle for an existing content item.

Value

Task A task object

See Also

`connectapi::content_update`

Other deployment functions: [bundle_dir\(\)](#), [bundle_path\(\)](#), [bundle_static\(\)](#), [download_bundle\(\)](#), [poll_task\(\)](#)

Examples

```
## Not run:
client <- connect()

# beware bundling big directories, like `renv/`, `data/`, etc.
bnd <- bundle_dir(".")

deploy(client, bnd)

## End(Not run)

client <- connect(prefix = "TEST_1")
bnd <- bundle_path(system.file("tests/testthat/examples/static.tar.gz", package = "connectapi"))
deploy(client, bnd)
```

 deploy_repo

Deploy a Git Repository

Description

[Experimental] Deploy a git repository directly to Posit Connect, using Posit Connect's "pull-based" "git-polling" method of deployment.

Usage

```
deploy_repo(
  client,
  repository,
  branch,
  subdirectory,
  name = create_random_name(),
  title = name,
  ...
)

deploy_repo_enable(content, enabled = TRUE)

deploy_repo_update(content)
```

Arguments

client	A Connect R6 object
repository	The git repository to deploy
branch	The git branch to deploy
subdirectory	The subdirectory to deploy (must contain a manifest.json)
name	The "name" / unique identifier for the content. Defaults to a random character string
title	The "title" of the content
...	Additional options for defining / specifying content attributes
content	An R6 Content object (i.e. the result of <code>content_item()</code>)
enabled	Whether Connect will enable automatic polling for repository updates

Details

- `deploy_repo_enable()` enables (or disables) Posit Connect's git polling for a piece of content
- `deploy_repo_update()` triggers an update of the content from its git repository, if any are present

Value

A ContentTask object, for use with poll_task() (if you want to follow the logs)

See Also

connectapi::poll_task, connectapi::repo_check_branches, connectapi::repo_check_manifest_dirs

Other content functions: [content_delete\(\)](#), [content_item\(\)](#), [content_title\(\)](#), [content_update\(\)](#), [create_random_name\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_thumbnail\(\)](#), [delete_vanity_url\(\)](#), [get_bundles\(\)](#), [get_environment\(\)](#), [get_image\(\)](#), [get_job\(\)](#), [get_jobs\(\)](#), [get_log\(\)](#), [get_thumbnail\(\)](#), [get_vanity_url\(\)](#), [git](#), [has_thumbnail\(\)](#), [permissions](#), [set_image_path\(\)](#), [set_run_as\(\)](#), [set_thumbnail\(\)](#), [set_vanity_url\(\)](#), [swap_vanity_url\(\)](#), [swap_vanity_urls\(\)](#), [terminate_jobs\(\)](#), [verify_content_name\(\)](#)

download_bundle

Download a Bundle from Deployed Connect Content

Description

Downloads a Content item's active bundle, or (optionally) one of its other bundles.

Usage

```
download_bundle(
  content,
  filename = fs::file_temp(pattern = "bundle", ext = ".tar.gz"),
  bundle_id = NULL,
  overwrite = FALSE
)
```

Arguments

content	A Content object
filename	Optional. The output bundle path
bundle_id	Optional. A string representing the bundle_id to download. If NULL, will use the currently active bundle.
overwrite	Optional. Default FALSE. Whether to overwrite the target location if it already exists

Value

Bundle A bundle object

See Also

Other deployment functions: [bundle_dir\(\)](#), [bundle_path\(\)](#), [bundle_static\(\)](#), [deploy\(\)](#), [poll_task\(\)](#)

Environment

Environment

Description

Environment

Environment

Details

An R6 class that represents a Content's Environment Variables

Super class

`connectapi::Content` -> Environment

Public fields

`env_raw` The (raw) set of environment variables.

`env_vars` The set of environment variables.

Methods

Public methods:

- `Environment$new()`
- `Environment$environment()`
- `Environment$environment_set()`
- `Environment$environment_all()`
- `Environment$env_refresh()`
- `Environment$print()`
- `Environment$clone()`

Method `new()`: Initialize this set of environment variables.

Usage:

`Environment$new(connect, content)`

Arguments:

`connect` The Connect instance.

`content` The Content instance.

Method `environment()`: Fetch the set of environment variables.

Usage:

`Environment$environment()`

Method `environment_set()`: Update the set of environment variables.

Usage:

```
Environment$environment_set(...)
```

Arguments:

... Environment variable names and values.

Method environment_all(): Overwrite the set of environment variables.

Usage:

```
Environment$environment_all(...)
```

Arguments:

... Environment variable names and values.

Method env_refresh(): Fetch the set o environment variables.

Usage:

```
Environment$env_refresh()
```

Method print(): Print this object.

Usage:

```
Environment$print(...)
```

Arguments:

... Unused.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
Environment$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other R6 classes: [Bundle](#), [Content](#), [ContentTask](#), [PositConnect](#), [Task](#), [Vanity](#), [Variant](#), [VariantSchedule](#), [VariantTask](#)

get_audit_logs

Get Audit Logs from Posit Connect Server

Description

Get Audit Logs from Posit Connect Server

Usage

```
get_audit_logs(src, limit = 500, previous = NULL, nxt = NULL, asc_order = TRUE)
```

Arguments

src	The source object
limit	The number of records to return.
previous	Retrieve the previous page of Shiny application usage logs relative to the provided value. This value corresponds to an internal reference within the server and should be sourced from the appropriate attribute within the paging object of a previous response.
nxt	Retrieve the next page of Shiny application usage logs relative to the provided value. This value corresponds to an internal reference within the server and should be sourced from the appropriate attribute within the paging object of a previous response.
asc_order	Defaults to TRUE; Determines if the response records should be listed in ascending or descending order within the response. Ordering is by the started timestamp field.

Details

Please see https://docs.posit.co/connect/api/#get-/v1/audit_logs for more information.

Value

A tibble with the following columns:

- id: ID of the audit action
- time: Timestamp in RFC3339 format when action was taken
- user_id: User ID of the actor who made the audit action
- user_description: Description of the actor
- action: Audit action taken
- event_description: Description of action

Examples

```
## Not run:
library(connectapi)
client <- connect()

# get the last 20 audit logs
get_audit_logs(client, limit = 20, asc_order = FALSE)

## End(Not run)
```

```
get_aws_content_credentials
```

Obtain AWS credentials for your content.

Description

Obtain AWS credentials for your content.

Usage

```
get_aws_content_credentials(connect, content_session_token = NULL)
```

Arguments

connect	A Connect R6 object.
content_session_token	Optional. The content session token. This token can only be obtained when the content is running on a Connect server. The token identifies the service account integration previously configured by the publisher on the Connect server. Defaults to the value from the environment variable: CONNECT_CONTENT_SESSION_TOKEN

Details

Please see <https://docs.posit.co/connect/user/oauth-integrations/#obtaining-service-account-aws-credentials> for more information. See the example below of using this function with paws to access S3. Any library that allows you to pass AWS credentials will be able to utilize the credentials returned from this function call.

Value

The AWS credentials as a list with fields named access_key_id, secret_access_key, session_token, and expiration.

Examples

```
## Not run:
library(connectapi)
library(paws)

client <- connect()
# Pulls the content session token from the environment
# when deployed into Connect.
aws_credentials <- get_aws_content_credentials(client)

# Create S3 client with AWS credentials from Connect
svc <- paws::s3(
  credentials = list(
    creds = list(
```

```

        access_key_id = aws_credentials$access_key_id,
        secret_access_key = aws_credentials$secret_access_key,
        session_token = aws_credentials$session_token
    )
}

# Get object from S3
obj <- svc$get_object(
  Bucket = "my-bucket",
  Key = "my-data.csv"
)

## End(Not run)

```

get_aws_credentials *Obtain a visitor's AWS credentials*

Description

Obtain a visitor's AWS credentials

Usage

```
get_aws_credentials(connect, user_session_token)
```

Arguments

connect	A Connect R6 object.
user_session_token	The content visitor's session token. This token can only be obtained when the content is running on a Connect server. The token identifies the user who is viewing the content interactively on the Connect server. Read this value from the HTTP header: Posit-Connect-User-Session-Token

Details

Please see <https://docs.posit.co/connect/user/oauth-integrations/#obtaining-service-account-aws-credentials> for more information. See the example below of using this function in a Plumber API with paws to access S3. Any library that allows you to pass AWS credentials will be able to utilize the credentials returned from this function call.

Value

The AWS credentials as a list with fields named access_key_id, secret_access_key, session_token, and expiration.

Examples

```
## Not run:
library(connectapi)
library(plumber)
library(paws)
client <- connect()

## @get /do
function(req) {
  user_session_token <- req$HTTP_POSIT_CONNECT_USER_SESSION_TOKEN
  aws_credentials <- get_aws_credentials(client, user_session_token)

  # Create S3 client with AWS credentials from Connect
  svc <- paws::s3(
    credentials = list(
      creds = list(
        access_key_id = aws_credentials$access_key_id,
        secret_access_key = aws_credentials$secret_access_key,
        session_token = aws_credentials$session_token
      )
    )
  )

  # Get object from S3
  obj <- svc$get_object(
    Bucket = "my-bucket",
    Key = "my-data.csv"
  )

  "done"
}

## End(Not run)
```

get_bundles*Get Bundles*

Description

Lists bundles for a content item

Usage

```
get_bundles(content)
```

```
delete_bundle(content, bundle_id)
```

Arguments

content	A R6 Content item, as returned by content_item()
bundle_id	A specific bundle ID for a content item

See Also

Other content functions: [content_delete\(\)](#), [content_item\(\)](#), [content_title\(\)](#), [content_update\(\)](#), [create_random_name\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_thumbnail\(\)](#), [delete_vanity_url\(\)](#), [deploy_repo\(\)](#), [get_environment\(\)](#), [get_image\(\)](#), [get_job\(\)](#), [get_jobs\(\)](#), [get_log\(\)](#), [get_thumbnail\(\)](#), [get_vanity_url\(\)](#), [git](#), [has_thumbnail\(\)](#), [permissions](#), [set_image_path\(\)](#), [set_run_as\(\)](#), [set_thumbnail\(\)](#), [set_vanity_url\(\)](#), [swap_vanity_url\(\)](#), [swap_vanity_urls\(\)](#), [terminate_jobs\(\)](#), [verify_content_name\(\)](#)

Other content functions: [content_delete\(\)](#), [content_item\(\)](#), [content_title\(\)](#), [content_update\(\)](#), [create_random_name\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_thumbnail\(\)](#), [delete_vanity_url\(\)](#), [deploy_repo\(\)](#), [get_environment\(\)](#), [get_image\(\)](#), [get_job\(\)](#), [get_jobs\(\)](#), [get_log\(\)](#), [get_thumbnail\(\)](#), [get_vanity_url\(\)](#), [git](#), [has_thumbnail\(\)](#), [permissions](#), [set_image_path\(\)](#), [set_run_as\(\)](#), [set_thumbnail\(\)](#), [set_vanity_url\(\)](#), [swap_vanity_url\(\)](#), [swap_vanity_urls\(\)](#), [terminate_jobs\(\)](#), [verify_content_name\(\)](#)

get_content

*Get information about content on the Posit Connect server***Description**

Get information about content on the Posit Connect server

Usage

```
get_content(src, guid = NULL, owner_guid = NULL, name = NULL, ..., .p = NULL)
```

Arguments

src	A Connect object
guid	The guid for a particular content item
owner_guid	The unique identifier of the user who owns the content
name	The content name specified when the content was created
...	Extra arguments. Currently not used.
.p	Optional. A predicate function, passed as-is to <code>purrr::keep()</code> before turning the response into a tibble. Can be useful for performance.

Details

Please see <https://docs.posit.co/connect/api/#get-v1/content> for more information.

Value

A tibble with the following columns:

- `guid`: The unique identifier of this content item.
- `name`: A simple, URL-friendly identifier. Allows alpha-numeric characters, hyphens ("-"), and underscores ("_").
- `title`: The title of this content.
- `description`: A rich description of this content
- `access_type`: Access type describes how this content manages its viewers. It may have a value of `all`, `logged_in` or `acl`. The value `all` is the most permissive; any visitor to Posit Connect will be able to view this content. The value `logged_in` indicates that all Posit Connect accounts may view the content. The `acl` value lets specifically enumerated users and groups view the content. Users configured as collaborators may always view content.
- `connection_timeout`: Maximum number of seconds allowed without data sent or received across a client connection. A value of 0 means connections will never time-out (not recommended). When null, the default `Scheduler.ConnectionTimeout` is used. Applies only to content types that are executed on demand.
- `read_timeout`: Maximum number of seconds allowed without data received from a client connection. A value of 0 means a lack of client (browser) interaction never causes the connection to close. When null, the default `Scheduler.ReadTimeout` is used. Applies only to content types that are executed on demand.
- `init_timeout`: The maximum number of seconds allowed for an interactive application to start. Posit Connect must be able to connect to a newly launched Shiny application, for example, before this threshold has elapsed. When null, the default `Scheduler.InitTimeout` is used. Applies only to content types that are executed on demand.
- `idle_timeout`: The maximum number of seconds a worker process for an interactive application to remain alive after it goes idle (no active connections). When null, the default `Scheduler.IdleTimeout` is used. Applies only to content types that are executed on demand.
- `max_processes`: Specifies the total number of concurrent processes allowed for a single interactive application. When null, the default `Scheduler.MaxProcesses` setting is used. Applies only to content types that are executed on demand.
- `min_processes`: Specifies the minimum number of concurrent processes allowed for a single interactive application. When null, the default `Scheduler.MinProcesses` is used. Applies only to content types that are executed on demand.
- `max_conns_per_process`: Specifies the maximum number of client connections allowed to an individual process. Incoming connections which will exceed this limit are routed to a new process or rejected. When null, the default `Scheduler.MaxConnsPerProcess` is used. Applies only to content types that are executed on demand.
- `load_factor`: Controls how aggressively new processes are spawned. When null, the default `Scheduler.LoadFactor` is used. Applies only to content types that are executed on demand.
- `created_time`: The timestamp (RFC3339) indicating when this content was created.
- `last_deployed_time`: The timestamp (RFC3339) indicating when this content last had a successful bundle deployment performed.

- **bundle_id**: The identifier for the active deployment bundle. Automatically assigned upon the successful deployment of that bundle.
- **app_mode**: The runtime model for this content. Has a value of unknown before data is deployed to this item. Automatically assigned upon the first successful bundle deployment. Allowed: api, jupyter-static, python-api, python-bokeh, python-dash, python-streamlit, rmd-shiny, rmd-static, shiny, static, tensorflow-saved-model, unknown.
- **content_category**: Describes the specialization of the content runtime model. Automatically assigned upon the first successful bundle deployment.
- **parameterized**: True when R Markdown rendered content allows parameter configuration. Automatically assigned upon the first successful bundle deployment. Applies only to content with an app_mode of rmd-static.
- **r_version**: The version of the R interpreter associated with this content. The value null represents that an R interpreter is not used by this content or that the R package environment has not been successfully restored. Automatically assigned upon the successful deployment of a bundle.
- **py_version**: The version of the Python interpreter associated with this content. The value null represents that a Python interpreter is not used by this content or that the Python package environment has not been successfully restored. Automatically assigned upon the successful deployment of a bundle.
- **run_as**: The UNIX user that executes this content. When null, the default Applications.RunAs is used. Applies only to executable content types - not static.
- **run_as_current_user**: Indicates if this content is allowed to execute as the logged-in user when using PAM authentication. Applies only to executable content types - not static.
- **owner_guid**: The unique identifier for the owner
- **content_url**: The URL associated with this content. Computed from the associated vanity URL or GUID for this content.
- **dashboard_url**: The URL within the Connect dashboard where this content can be configured. Computed from the GUID for this content.
- **role**: The relationship of the accessing user to this content. A value of owner is returned for the content owner. editor indicates a collaborator. The viewer value is given to users who are permitted to view the content. A none role is returned for administrators who cannot view the content but are permitted to view its configuration. Computed at the time of the request.
- **id**: The internal numeric identifier of this content item

Examples

```
## Not run:
library(connectapi)
client <- connect()

get_content(client)

## End(Not run)
```

get_content_packages	<i>Package dependencies for a content item</i>
----------------------	--

Description

Get a data frame of package dependencies used by a content item.

Usage

```
get_content_packages(content)
```

Arguments

content	A content item
---------	----------------

Value

A data frame with the following columns:

- language : Language ecosystem the package belongs to (r or python)
- name: The package name
- version: The package version
- hash: For R packages, the package DESCRIPTION hash

See Also

Other packages functions: [get_packages\(\)](#)

Examples

```
## Not run:  
client <- connect()  
item <- content_item(client, "951bf3ad-82d0-4bca-bba8-9b27e35c49fa")  
packages <- get_content_packages(item)  
  
## End(Not run)
```

get_environment	<i>Manage Environment Variables</i>
-----------------	-------------------------------------

Description

Manage Environment Variables for a piece of content.

Usage

```
get_environment(content)

set_environment_new(env, ...)

set_environment_remove(env, ...)

set_environment_all(env, ...)
```

Arguments

content	An R6 Content object as returned by <code>content_item()</code>
env	An R6 Environment object as returned by <code>get_environment()</code>
...	name = value pairs of environment variable names and values

Details

`get_environment()` returns an Environment object for use with "setter" methods

`set_environment_new()` updates environment values (either creating new values or updating existing). Set NA as the value to remove a variable.

`set_environment_remove()` is a wrapper on `set_environment_new()` that allows removing named / listed variables quickly

`set_environment_all()` sets *all* environment variable values (will remove variables not specified)

See Also

Other content functions: [content_delete\(\)](#), [content_item\(\)](#), [content_title\(\)](#), [content_update\(\)](#), [create_random_name\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_thumbnail\(\)](#), [delete_vanity_url\(\)](#), [deploy_repo\(\)](#), [get_bundles\(\)](#), [get_image\(\)](#), [get_job\(\)](#), [get_jobs\(\)](#), [get_log\(\)](#), [get_thumbnail\(\)](#), [get_vanity_url\(\)](#), [git](#), [has_thumbnail\(\)](#), [permissions](#), [set_image_path\(\)](#), [set_run_as\(\)](#), [set_thumbnail\(\)](#), [set_vanity_url\(\)](#), [swap_vanity_url\(\)](#), [swap_vanity_urls\(\)](#), [terminate_jobs\(\)](#), [verify_content_name\(\)](#)

get_groups

Get group information from the Posit Connect server

Description

Get group information from the Posit Connect server

Usage

```
get_groups(src, page_size = 500, prefix = NULL, limit = Inf)
```

Arguments

src	The source object.
page_size	The number of records to return per page (max 500).
prefix	Filters groups by prefix (group name). The filter is case insensitive.
limit	The number of groups to retrieve before paging stops. limit will be ignored if prefix is not NULL. To limit results when prefix is not NULL, change page_size.

Details

Please see <https://docs.posit.co/connect/api/#get-v1/groups> for more information.

Value

A tibble with the following columns:

- guid: The unique identifier of the group
- name: The group name
- owner_guid: The group owner's unique identifier. When using LDAP or Proxied authentication with group provisioning enabled this property will always be null.

See Also

Other groups functions: [get_group_content\(\)](#), [get_group_members\(\)](#)

Examples

```
## Not run:
library(connectapi)
client <- connect()

# get all groups
get_groups(client, limit = Inf)

## End(Not run)
```

get_group_content	<i>Get content access permissions for a group or groups</i>
-------------------	---

Description

Get content access permissions for a group or groups

Usage

```
get_group_content(src, guides)
```

Arguments

src	A Connect client object
guids	A character vector of group guides

Value

A tibble with the following columns:

- group_guid: The group's GUID
- group_name: The group's name
- content_guid: The content item's GUID
- content_name: The content item's name
- content_title: The content item's title
- access_type: The access type of the content item ("all", "logged_in", or "acl")
- role: The access type that members of the group have to the content item, "publisher" or "viewer".

See Also

Other groups functions: [get_group_members\(\)](#), [get_groups\(\)](#)

Examples

```
## Not run:
library(connectapi)
client <- connect()

# Get a data frame of groups
groups <- get_groups(client)

# Get permissions for a single group by passing in the corresponding row.
get_group_content(client, groups[1, "guid"])
dplyr::filter(groups, name = "research_scientists") %>%
  dplyr::pull(guid) %>%
  get_group_content(client, .)
```

```
# Get permissions for all groups by passing in all group guids.
get_group_content(client, groups$guid)

## End(Not run)
```

get_group_members	<i>Get users within a specific group</i>
-------------------	--

Description

Get users within a specific group

Usage

```
get_group_members(src, guid)
```

Arguments

src	A Connect client object
guid	A group GUID identifier

Details

Please see https://docs.posit.co/connect/api/#get-/v1/groups/-group_guid-/members for more information.

Value

A tibble with the following columns:

- email: The user's email
- username: The user's username
- first_name: The user's first name
- last_name: The user's last name
- user_role: The user's role. It may have a value of administrator, publisher or viewer.
- created_time: The timestamp (in RFC3339 format) when the user was created in the Posit Connect server
- updated_time: The timestamp (in RFC3339 format) when the user was last updated in the Posit Connect server
- active_time: The timestamp (in RFC3339 format) when the user was last active on the Posit Connect server
- confirmed: When false, the created user must confirm their account through an email. This feature is unique to password authentication.
- locked: Whether or not the user is locked
- guid: The user's GUID, or unique identifier, in UUID RFC4122 format

See Also

Other groups functions: [get_group_content\(\)](#), [get_groups\(\)](#)

Examples

```
## Not run:
library(connectapi)
client <- connect()

# get the first 20 groups
groups <- get_groups(client)

group_guid <- groups$guid[1]

get_group_members(client, guid = group_guid)

## End(Not run)
```

get_image

Get the Content Image

Description

[Deprecated]

Please use [get_thumbnail](#), [delete_thumbnail](#), and [has_thumbnail](#) instead.

`get_image` saves the content image to the given path (default: temp file). `delete_image` removes the image (optionally saving to the given path) `has_image` returns whether the content has an image

Usage

```
get_image(content, path = NULL)
```

```
delete_image(content, path = NULL)
```

```
has_image(content)
```

Arguments

content	A content object
path	optional. The path to the image on disk

See Also

Other content functions: [content_delete\(\)](#), [content_item\(\)](#), [content_title\(\)](#), [content_update\(\)](#), [create_random_name\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_thumbnail\(\)](#), [delete_vanity_url\(\)](#), [deploy_repo\(\)](#), [get_bundles\(\)](#), [get_environment\(\)](#), [get_job\(\)](#), [get_jobs\(\)](#), [get_log\(\)](#), [get_thumbnail\(\)](#), [get_vanity_url\(\)](#), [git](#), [has_thumbnail\(\)](#), [permissions](#), [set_image_path\(\)](#), [set_run_as\(\)](#), [set_thumbnail\(\)](#), [set_vanity_url\(\)](#), [swap_vanity_url\(\)](#), [swap_vanity_urls\(\)](#), [terminate_jobs\(\)](#), [verify_content_name\(\)](#)

get_job	<i>Retrieve details about a server process associated with a content_item, such as a FastAPI app or a Quarto render.</i>
---------	--

Description

Retrieve details about a server process associated with a `content_item`, such as a FastAPI app or a Quarto render.

Usage

```
get_job(content, key)
```

Arguments

content	A Content object, as returned by <code>content_item()</code>
key	The key for a job

See Also

Other job functions: [get_jobs\(\)](#), [get_log\(\)](#), [terminate_jobs\(\)](#)

Other content functions: [content_delete\(\)](#), [content_item\(\)](#), [content_title\(\)](#), [content_update\(\)](#), [create_random_name\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_thumbnail\(\)](#), [delete_vanity_url\(\)](#), [deploy_repo\(\)](#), [get_bundles\(\)](#), [get_environment\(\)](#), [get_image\(\)](#), [get_jobs\(\)](#), [get_log\(\)](#), [get_thumbnail\(\)](#), [get_vanity_url\(\)](#), [git](#), [has_thumbnail\(\)](#), [permissions](#), [set_image_path\(\)](#), [set_run_as\(\)](#), [set_thumbnail\(\)](#), [set_vanity_url\(\)](#), [swap_vanity_url\(\)](#), [swap_vanity_urls\(\)](#), [terminate_jobs\(\)](#), [verify_content_name\(\)](#)

get_jobs

*Get Jobs***Description**

Retrieve details about server processes associated with a `content_item`, such as a FastAPI app or a Quarto render.

Usage

```
get_jobs(content)
```

```
get_job_list(content)
```

Arguments

`content` A Content object, as returned by `content_item()`

Details

Note that Connect versions below 2022.10.0 use a legacy endpoint, and will not return the complete set of information provided by newer versions.

`get_jobs()` returns job data as a data frame, whereas `get_jobs_list()` returns job data in a list.

You might get job data as a data frame if you want to perform some calculations about job data (e.g. counting server processes over time), or if you want to filter jobs to find a specific key.

The objects in list returned by `get_jobs_list()` are useful if you want to take an action on a job, such as getting its process log with `get_log()`.

Value

- `get_jobs()`: A data frame with a row representing each job.
- `get_job_list()`: A list with each element representing a job.

Jobs contain the following fields:

- `id`: The job identifier.
- `ppid`: The job's parent process identifier (see Note 1).
- `pid`: The job's process identifier.
- `key`: The job's unique key identifier.
- `remote_id`: The job's identifier for off-host execution configurations (see Note 1).
- `app_id`: The job's parent content identifier; deprecated in favor of `content_id`.
- `app_guid`: The job's parent content GUID; deprecated in favor of `content_guid`.
- `content_id`: The job's parent content identifier.
- `content_guid`: The job's parent content GUID.

- `variant_id`: The identifier of the variant owning this job.
- `bundle_id`: The identifier of a content bundle linked to this job.
- `start_time`: The timestamp (RFC3339) indicating when this job started.
- `end_time`: The timestamp (RFC3339) indicating when this job finished.
- `last_heartbeat_time`: The timestamp (RFC3339) indicating the last time this job was observed to be running (see Note 1).
- `queued_time`: The timestamp (RFC3339) indicating when this job was added to the queue to be processed. Only scheduled reports will present a value for this field (see Note 1).
- `queue_name`: The name of the queue which processes the job. Only scheduled reports will present a value for this field (see Note 1).
- `tag`: A tag to identify the nature of the job.
- `exit_code`: The job's exit code. Present only when job is finished.
- `status`: The current status of the job. On Connect 2022.10.0 and newer, one of Active: 0, Finished: 1, Finalized: 2; on earlier versions, Active: 0, otherwise NA.
- `hostname`: The name of the node which processes the job.
- `cluster`: The location where this content runs. Content running on the same server as Connect will have either a null value or the string Local. Gives the name of the cluster when run external to the Connect host (see Note 1).
- `image`: The location where this content runs. Content running on the same server as Connect will have either a null value or the string Local. References the name of the target image when content runs in a clustered environment such as Kubernetes (see Note 1).
- `run_as`: The UNIX user that executed this job.

Note

1. On Connect instances earlier than 2022.10.0, these fields will contain NA values.

See Also

Other job functions: [get_job\(\)](#), [get_log\(\)](#), [terminate_jobs\(\)](#)

Other content functions: [content_delete\(\)](#), [content_item\(\)](#), [content_title\(\)](#), [content_update\(\)](#), [create_random_name\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_thumbnail\(\)](#), [delete_vanity_url\(\)](#), [deploy_repo\(\)](#), [get_bundles\(\)](#), [get_environment\(\)](#), [get_image\(\)](#), [get_job\(\)](#), [get_log\(\)](#), [get_thumbnail\(\)](#), [get_vanity_url\(\)](#), [git_has_thumbnail\(\)](#), [permissions](#), [set_image_path\(\)](#), [set_run_as\(\)](#), [set_thumbnail\(\)](#), [set_vanity_url\(\)](#), [swap_vanity_url\(\)](#), [swap_vanity_urls\(\)](#), [terminate_jobs\(\)](#), [verify_content_name\(\)](#)

Examples

```
## Not run:
client <- connect()
item <- content_item(client, "951bf3ad-82d0-4bca-bba8-9b27e35c49fa")
jobs <- get_jobs(item)
job_list <- get_job_list(item)

## End(Not run)
```

get_log

*Get Job Log***Description**

Get the log output for a job. Requires Connect 2022.10.0 or newer.

Usage

```
get_log(job, max_log_lines = NULL)
```

Arguments

job	A job, represented by an element from the list returned by <code>get_job_list()</code> .
max_log_lines	Optional. An integer indicating the maximum number of log lines to return. If NULL (default), Connect returns a maximum of 5000 lines.

Details

Note: The output of `get_jobs()` cannot be used with `get_log()`. Please use an object from the list returned by `get_job_list()`.

Value

A data frame with the requested log. Each row represents an entry.

- source: stdout or stderr
- timestamp: The time of the entry.
- data: The logged text.

See Also

Other job functions: [get_job\(\)](#), [get_jobs\(\)](#), [terminate_jobs\(\)](#)

Other content functions: [content_delete\(\)](#), [content_item\(\)](#), [content_title\(\)](#), [content_update\(\)](#), [create_random_name\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_thumbnail\(\)](#), [delete_vanity_url\(\)](#), [deploy_repo\(\)](#), [get_bundles\(\)](#), [get_environment\(\)](#), [get_image\(\)](#), [get_job\(\)](#), [get_jobs\(\)](#), [get_thumbnail\(\)](#), [get_vanity_url\(\)](#), [git](#), [has_thumbnail\(\)](#), [permissions](#), [set_image_path\(\)](#), [set_run_as\(\)](#), [set_thumbnail\(\)](#), [set_vanity_url\(\)](#), [swap_vanity_url\(\)](#), [swap_vanity_urls\(\)](#), [terminate_jobs\(\)](#), [verify_content_name\(\)](#)

Examples

```
## Not run:
client <- connect()
item <- content_item(client, "951bf3ad-82d0-4bca-bba8-9b27e35c49fa")
jobs <- get_job_list(item)
log <- get_log(jobs[[1]])
```

```
## End(Not run)
```

```
get_oauth_content_credentials
```

Perform an OAuth credential exchange to obtain a content-specific OAuth access token.

Description

Perform an OAuth credential exchange to obtain a content-specific OAuth access token.

Usage

```
get_oauth_content_credentials(
  connect,
  content_session_token = NULL,
  requested_token_type = NULL
)
```

Arguments

`connect` A Connect R6 object.

`content_session_token`

Optional. The content session token. This token can only be obtained when the content is running on a Connect server. The token identifies the service account integration previously configured by the publisher on the Connect server. Defaults to the value from the environment variable: `CONNECT_CONTENT_SESSION_TOKEN`

`requested_token_type`

Optional. The requested token type. If unset, will default to `urn:ietf:params:oauth:token-type:access-token`. Otherwise, this can be set to `urn:ietf:params:aws:token-type:credentials` for AWS integrations or `urn:posit:connect:api-key` for Connect API Key integrations.

Details

Please see <https://docs.posit.co/connect/user/oauth-integrations/#obtaining-a-service-account-oauth-access-token> for more information.

Value

The OAuth credential exchange response.

Examples

```
## Not run:
library(connectapi)
library(plumber)
client <- connect()

## @get /do
function(req) {
  credentials <- get_oauth_content_credentials(client)

  # ... do something with `credentials$access_token` ...

  "done"
}

## End(Not run)
```

`get_oauth_credentials` *Perform an OAuth credential exchange to obtain a visitor's OAuth access token.*

Description

Perform an OAuth credential exchange to obtain a visitor's OAuth access token.

Usage

```
get_oauth_credentials(connect, user_session_token, requested_token_type = NULL)
```

Arguments

`connect` A Connect R6 object.

`user_session_token`

The content visitor's session token. This token can only be obtained when the content is running on a Connect server. The token identifies the user who is viewing the content interactively on the Connect server. Read this value from the HTTP header: Posit-Connect-User-Session-Token

`requested_token_type`

Optional. The requested token type. If unset, will default to `urn:ietf:params:oauth:token-type:access_token`. Otherwise, this can be set to `urn:ietf:params:aws:token-type:credentials` for AWS integrations or `urn:posit:connect:api-key` for Connect API Key integrations.

Details

Please see <https://docs.posit.co/connect/user/oauth-integrations/#obtaining-a-viewer-oauth-access-token> for more information.

Value

The OAuth credential exchange response.

Examples

```
## Not run:
library(connectapi)
library(plumber)
client <- connect()

## @get /do
function(req) {
  user_session_token <- req$HTTP_POSIT_CONNECT_USER_SESSION_TOKEN
  credentials <- get_oauth_credentials(client, user_session_token)

  # ... do something with `credentials$access_token` ...

  "done"
}

## End(Not run)
```

get_packages

All package dependencies on the server

Description

Get a data frame of package dependencies used by all content items on the server.

Usage

```
get_packages(src, name = NULL, page_size = 100000, limit = Inf)
```

Arguments

src	A Connect client object.
name	Optional package name to filter by. Python package are normalized during matching; R package names must match exactly.
page_size	Optional. Integer specifying page size for API paging.
limit	Optional. Specify the maximum number of records after which to cease paging.

Value

A data frame with the following columns:

- language: Language ecosystem the package belongs to (r or python)
- language_version: Version of R or Python used by the content
- name: Package name
- version: Package version
- hash: Package description hash for R packages
- bundle_id: Identifier for the bundle that depends on this package
- content_id: Numeric identifier for the content that depends on this package
- content_guid: The unique identifier of the content item that depends on this package

See Also

Other packages functions: [get_content_packages\(\)](#)

Examples

```
## Not run:  
client <- connect()  
packages <- get_packages(client)  
  
## End(Not run)
```

get_procs

Get Real-Time Process Data

Description

[Experimental] This returns real-time process data from the Posit Connect API. It requires administrator privileges to use. NOTE that this only returns data for the server that responds to the request (i.e. in a Highly Available cluster)

Usage

```
get_procs(src)
```

Arguments

src The source object

Value

A tibble with the following columns:

- pid: The PID of the current process
- appId: The application ID
- appId: The application GUID
- appName: The application name
- appUrl: The application URL
- appRunAs: The application RunAs user
- type: The type of process
- cpuCurrent: The current CPU usage
- cpuTotal: The total CPU usage
- ram: The current RAM usage

get_runtimes	<i>Get available runtimes on server</i>
--------------	---

Description

Get a table showing available versions of R, Python, Quarto, and Tensorflow on the Connect server.

Usage

```
get_runtimes(client, runtimes = NULL)
```

Arguments

client	A Connect object.
runtimes	Optional. A character vector of runtimes to include. Must be some combination of "r", "python", "quarto", and "tensorflow". Quarto is only supported on Connect >= 2021.08.0, and Tensorflow is only supported on Connect >= 2024.03.0.

Value

A tibble with columns for runtime, version, and cluster_name and image_name. Cluster name and image name are only meaningful on Connect instances running off-host execution.

Examples

```
## Not run:
library(connectapi)
client <- connect()
get_runtimes(client, runtimes = c("r", "python", "tensorflow"))

## End(Not run)
```

get_runtime_caches	<i>Get runtime caches</i>
--------------------	---------------------------

Description

View the runtime caches on a Connect server. Requires Administrator privileges.

Usage

```
get_runtime_caches(client)
```

Arguments

client	A Connect object.
--------	-------------------

Value

A tibble of runtime caches on the server, showing language, version and image_name. For Connect servers not using off-host execution, image_name is "Local".

See Also

[delete_runtime_cache\(\)](#)

Other server management functions: [delete_runtime_cache\(\)](#)

Examples

```
## Not run:  
client <- connect()  
get_runtime_caches(client)  
  
## End(Not run)
```

get_tags	<i>Get all Tags on the server</i>
----------	-----------------------------------

Description

Tag manipulation and assignment functions

Usage

```

get_tags(src)

get_tag_data(src)

create_tag(src, name, parent = NULL)

create_tag_tree(src, ...)

delete_tag(src, tag)

get_content_tags(content)

set_content_tag_tree(content, ...)

set_content_tags(content, ...)

filter_tag_tree_id(tags, ids)

filter_tag_tree_chr(tags, pattern)

```

Arguments

- | | |
|--------|---|
| src | The source object |
| name | The name of the tag to create |
| parent | optional. A connect_tag_tree object (as returned by get_tags()) pointed at the parent tag |
| ... | <p>Additional arguments</p> <p>Manage tags (requires Administrator role):</p> <ul style="list-style-type: none"> • get_tags() - returns a "tag tree" object that can be traversed with tag_tree\$tag1\$childtag • get_tag_data() - returns a tibble of tag data • create_tag() - create a tag by specifying the Parent directly • create_tag_tree() - create tag(s) by specifying the "desired" tag tree hierarchy • delete_tag() - delete a tag (and its children). WARNING: will disassociate any content automatically <p>Manage content tags:</p> <ul style="list-style-type: none"> • get_content_tags() - return a connect_tag_tree object corresponding to the tags for a piece of content. • set_content_tag_tree() - attach a tag to content by specifying the desired tag tree • set_content_tags() - Set multiple tags at once by providing connect_tag_tree objects <p>Search a tag tree:</p> <ul style="list-style-type: none"> • filter_tag_tree_chr() - filters a tag tree based on a regex |

	• <code>filter_tag_tree_id()</code> - filters a tag tree based on an id
tag	A <code>connect_tag_tree</code> object (as returned by <code>get_tags()</code>)
content	An R6 Content object, as returned by <code>content_item()</code>
tags	A <code>connect_tag_tree</code> object (as returned by <code>get_tags()</code>)
ids	A list of ids to filter the tag tree by
pattern	A regex to filter the tag tree by (it is passed to <code>grep1</code>)

get_thumbnail	<i>Get content item thumbnail</i>
---------------	-----------------------------------

Description

Download the thumbnail for a content item on Connect to a file on your computer.

Usage

```
get_thumbnail(content, path = NULL)
```

Arguments

content	A content item.
path	Optional. A path to a file used to write the thumbnail image. If no path is provided, a temporary file with the correct file extension is created.

Value

The path to the downloaded image file, if content has a thumbnail; otherwise NA.

See Also

Other thumbnail functions: [delete_thumbnail\(\)](#), [has_thumbnail\(\)](#), [set_thumbnail\(\)](#)

Other content functions: [content_delete\(\)](#), [content_item\(\)](#), [content_title\(\)](#), [content_update\(\)](#), [create_random_name\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_thumbnail\(\)](#), [delete_vanity_url\(\)](#), [deploy_repo\(\)](#), [get_bundles\(\)](#), [get_environment\(\)](#), [get_image\(\)](#), [get_job\(\)](#), [get_jobs\(\)](#), [get_log\(\)](#), [get_vanity_url\(\)](#), [git](#), [has_thumbnail\(\)](#), [permissions](#), [set_image_path\(\)](#), [set_run_as\(\)](#), [set_thumbnail\(\)](#), [set_vanity_url\(\)](#), [swap_vanity_url\(\)](#), [swap_vanity_urls\(\)](#), [terminate_jobs\(\)](#), [verify_content_name\(\)](#)

Examples

```
## Not run:
client <- connect()
item <- content_item(client, "8f37d6e0-3395-4a2c-aa6a-d7f2fe1babb0")
thumbnail <- get_thumbnail(item)

## End(Not run)
```

`get_timezones`*Get TimeZones*

Description

Get the available timezones from the server.

Usage

```
get_timezones(connect)
```

Arguments

`connect` An R6 Connect object

Value

A TimeZone vector to be used for setting time zones

See Also

Other schedule functions: [get_variant_schedule\(\)](#), [set_schedule\(\)](#)

`get_usage_shiny`*Get usage information for deployed shiny applications*

Description

Get usage information for deployed shiny applications

Usage

```
get_usage_shiny(  
  src,  
  content_guid = NULL,  
  min_data_version = NULL,  
  from = NULL,  
  to = NULL,  
  limit = 500,  
  previous = NULL,  
  nxt = NULL,  
  asc_order = TRUE  
)
```

Arguments

<code>src</code>	the source object
<code>content_guid</code>	Filter results by content GUID
<code>min_data_version</code>	Filter by data version. Records with a data version lower than the given value will be excluded from the set of results.
<code>from</code>	The timestamp that starts the time window of interest. Any usage information that ends prior to this timestamp will not be returned. Individual records may contain a starting time that is before this if they end after it or have not finished. Must be of class Date or POSIX
<code>to</code>	The timestamp that ends the time window of interest. Any usage information that starts after this timestamp will not be returned. Individual records may contain an ending time that is after this (or no ending time) if they start before it. Must be of class Date or POSIX
<code>limit</code>	The number of records to return.
<code>previous</code>	Retrieve the previous page of Shiny application usage logs relative to the provided value. This value corresponds to an internal reference within the server and should be sourced from the appropriate attribute within the paging object of a previous response.
<code>nxt</code>	Retrieve the next page of Shiny application usage logs relative to the provided value. This value corresponds to an internal reference within the server and should be sourced from the appropriate attribute within the paging object of a previous response.
<code>asc_order</code>	Defaults to TRUE; Determines if the response records should be listed in ascending or descending order within the response. Ordering is by the started timestamp field.

Details

Please see <https://docs.posit.co/connect/api/#get-v1/instrumentation/shiny/usage> for more information.

Value

A tibble with the following columns:

- `content_guid`: The GUID, in RFC4122 format, of the Shiny application this information pertains to.
- `user_guid`: The GUID, in RFC4122 format, of the user that visited the application.
- `started`: The timestamp, in RFC3339 format, when the user opened the application.
- `ended`: The timestamp, in RFC3339 format, when the user left the application.
- `data_version`: The data version the record was recorded with. The Shiny Application Events section of the Posit Connect Admin Guide explains how to interpret `data_version` values.

Examples

```
## Not run:
library(connectapi)
client <- connect()

from <- Sys.Date() - lubridate::days(5)
get_usage_shiny(client, limit = 20, from = from)

## End(Not run)
```

get_usage_static	<i>Get usage information from deployed static content</i>
------------------	---

Description

This function retrieves usage information from static content on the Posit Connect server (e.g. Rmarkdown, Jupyter Notebooks)

Usage

```
get_usage_static(
  src,
  content_guid = NULL,
  min_data_version = NULL,
  from = NULL,
  to = NULL,
  limit = 500,
  previous = NULL,
  next = NULL,
  asc_order = TRUE
)
```

Arguments

src	the source object
content_guid	Filter results by content GUID
min_data_version	Filter by data version. Records with a data version lower than the given value will be excluded from the set of results.
from	The timestamp that starts the time window of interest. Any usage information that ends prior to this timestamp will not be returned. Individual records may contain a starting time that is before this if they end after it or have not finished. Must be of class Date or POSIX

to	The timestamp that ends the time window of interest. Any usage information that starts after this timestamp will not be returned. Individual records may contain an ending time that is after this (or no ending time) if they start before it. Must be of class Date or POSIX
limit	The number of records to return.
previous	Retrieve the previous page of Shiny application usage logs relative to the provided value. This value corresponds to an internal reference within the server and should be sourced from the appropriate attribute within the paging object of a previous response.
nxt	Retrieve the next page of Shiny application usage logs relative to the provided value. This value corresponds to an internal reference within the server and should be sourced from the appropriate attribute within the paging object of a previous response.
asc_order	Defaults to TRUE; Determines if the response records should be listed in ascending or descending order within the response. Ordering is by the started timestamp field.

Details

Please see <https://docs.posit.co/connect/api/#get-/v1/instrumentation/content/visits> for more information.

Value

A tibble with the following columns:

- `content_guid`: The GUID, in RFC4122 format, of the Shiny application this information pertains to.
- `user_guid`: The GUID, in RFC4122 format, of the user that visited the application.
- `variant_key`: The key of the variant the user visited. This will be null for static content.
- `time`: The timestamp, in RFC3339 format, when the user visited the content.
- `rendering_id`: The ID of the rendering the user visited. This will be null for static content.
- `bundle_id`: The ID of the particular bundle used.
- `data_version`: The data version the record was recorded with. The Rendered and Static Content Visit Events section of the Posit Connect Admin Guide explains how to interpret `data_version` values.

Examples

```
## Not run:
library(connectapi)
client <- connect()

from <- Sys.Date() - lubridate::days(5)
get_usage_static(client, limit = 20, from = from)

## End(Not run)
```

`get_users`*Get user information from the Posit Connect server*

Description

Get user information from the Posit Connect server

Usage

```
get_users(  
  src,  
  page_size = 500,  
  prefix = NULL,  
  limit = Inf,  
  user_role = NULL,  
  account_status = NULL  
)
```

Arguments

<code>src</code>	The source object
<code>page_size</code>	the number of records to return per page (max 500)
<code>prefix</code>	Filters users by prefix (username, first name, or last name). The filter is case insensitive.
<code>limit</code>	The max number of records to return
<code>user_role</code>	Optionally filter by user role ("administrator", "publisher", "viewer"). Pass in a vector of multiple roles to match any value (boolean OR). When NULL (the default), results are not filtered.
<code>account_status</code>	Optionally filter by account status ("locked", "licensed", "inactive"). Pass a vector of multiple statuses to match any value (boolean OR). When NULL (the default), results are not filtered.

Details

Please see <https://docs.posit.co/connect/api/#get-/v1/users> for more information.

Value

A tibble with the following columns:

- `email`: The user's email
- `username`: The user's username
- `first_name`: The user's first name
- `last_name`: The user's last name
- `user_role`: The user's role. It may have a value of administrator, publisher or viewer.

- `created_time`: The timestamp (in RFC3339 format) when the user was created in the Posit Connect server
- `updated_time`: The timestamp (in RFC3339 format) when the user was last updated in the Posit Connect server
- `active_time`: The timestamp (in RFC3339 format) when the user was last active on the Posit Connect server
- `confirmed`: When false, the created user must confirm their account through an email. This feature is unique to password authentication.
- `locked`: Whether or not the user is locked
- `guid`: The user's GUID, or unique identifier, in UUID RFC4122 format

Examples

```
## Not run:
library(connectapi)
client <- connect()

# Get all users
get_users(client)

# Get all licensed users
get_users(client, account_status = "licensed")

# Get all users who are administrators or publishers
get_users(client, user_role = c("administrator", "publisher"))

## End(Not run)
```

get_vanity_url

Get the Vanity URL

Description

Get the vanity URL for a piece of content.

Usage

```
get_vanity_url(content)
```

Arguments

`content` A Content object

Value

A character string (or NULL if not defined)

See Also

Other content functions: `content_delete()`, `content_item()`, `content_title()`, `content_update()`, `create_random_name()`, `dashboard_url()`, `dashboard_url_chr()`, `delete_thumbnail()`, `delete_vanity_url()`, `deploy_repo()`, `get_bundles()`, `get_environment()`, `get_image()`, `get_job()`, `get_jobs()`, `get_log()`, `get_thumbnail()`, `git`, `has_thumbnail()`, `permissions`, `set_image_path()`, `set_run_as()`, `set_thumbnail()`, `set_vanity_url()`, `swap_vanity_url()`, `swap_vanity_urls()`, `terminate_jobs()`, `verify_content_name()`

get_vanity_urls	<i>Get all vanity URLs</i>
-----------------	----------------------------

Description

Get a table of all vanity URLs on the server. Requires administrator privileges.

Usage

```
get_vanity_urls(client)
```

Arguments

client	A Connect object.
--------	-------------------

Value

A tibble with columns for `content_guid`, `path`, and `created_time`.

Examples

```
## Not run:
library(connectapi)
client <- connect()
get_vanity_urls(client)

## End(Not run)
```

get_variants	<i>Get Variant</i>
--------------	--------------------

Description

[Experimental] Work with variants

Usage

```
get_variants(content)
```

```
get_variant(content, key)
```

```
get_variant_default(content)
```

Arguments

content	An R6 Content object. Returned from content_item()
key	The Variant key for a specific variant

Details

- get_variants() returns a tibble with variant data for a content_item
- get_variant_default() returns the default variant for a content_item
- get_variant() returns a specific variant for a content_item (specified by key)

See Also

Other variant functions: [get_variant_renderings\(\)](#)

Other variant functions: [get_variant_renderings\(\)](#)

Other variant functions: [get_variant_renderings\(\)](#)

get_variant_renderings	<i>Render a Variant</i>
------------------------	-------------------------

Description

[Experimental] Get details about renderings (i.e. render history) or execute a variant on demand

Usage

```
get_variant_renderings(variant)
```

```
variant_render(variant)
```

Arguments

variant An R6 Variant object. As returned by `get_variant()` or `get_variant_default()`

Details

- `get_variant_renderings()` returns all renderings / content for a particular variant. Returns a tibble
- `variant_render()` executes a variant on demand. Returns a VariantTask object

See Also

Other variant functions: [get_variants\(\)](#)

get_variant_schedule *Get a Variant Schedule*

Description

[Experimental] Gets the schedule associated with a Variant.

Usage

```
get_variant_schedule(variant)
```

Arguments

variant A Variant object, as returned by `get_variant()` or `get_variant_default()`

Value

A VariantSchedule object

See Also

Other schedule functions: [get_timezones\(\)](#), [set_schedule\(\)](#)

git

*Git Repository Helpers***Description**

[Experimental] These functions help use Posit Connect's configured authorization to query available branches and subdirectories for deployment using `deploy_repo()`

Usage

```
repo_check_account(client, host)

repo_check_branches(client, repository)

repo_check_branches_ref(client, repository)

repo_check_manifest_dirs(client, repository, branch)
```

Arguments

<code>client</code>	A Connect R6 object
<code>host</code>	The git repository host (with schema). For example, "https://github.com"
<code>repository</code>	The git repository to explore or consider deploying
<code>branch</code>	The git branch to explore for subdirectories

Details

- `repo_check_account()` messages whether an account is in use, and then returns that account
- `repo_check_branches()` retrieves which branches are available, returning in a named list
- `repo_check_manifest_dirs()` retrieves which directories contain a `manifest.json`, returning in a named list

See Also

`connectapi::deploy_repo`

Other content functions: `content_delete()`, `content_item()`, `content_title()`, `content_update()`, `create_random_name()`, `dashboard_url()`, `dashboard_url_chr()`, `delete_thumbnail()`, `delete_vanity_url()`, `deploy_repo()`, `get_bundles()`, `get_environment()`, `get_image()`, `get_job()`, `get_jobs()`, `get_log()`, `get_thumbnail()`, `get_vanity_url()`, `has_thumbnail()`, `permissions`, `set_image_path()`, `set_run_as()`, `set_thumbnail()`, `set_vanity_url()`, `swap_vanity_url()`, `swap_vanity_urls()`, `terminate_jobs()`, `verify_content_name()`

groups_create_remote	<i>Create a Remote Group</i>
----------------------	------------------------------

Description

Create a Remote Group

Usage

```
groups_create_remote(connect, prefix, expect = 1, check = TRUE, exact = FALSE)
```

Arguments

connect	An R6 Connect object.
prefix	character. The prefix of the user name to search for.
expect	number. Optional. The number of responses to expect for this search.
check	boolean. Optional. Whether to check for local existence first.
exact	boolean. Optional. Whether to only create groups whose name exactly matches the provided prefix.

Value

The results of creating the groups.

has_thumbnail	<i>Check content item thumbnail</i>
---------------	-------------------------------------

Description

Check whether a content item has a thumbnail.

Usage

```
has_thumbnail(content)
```

Arguments

content	A content item.
---------	-----------------

Value

TRUE if the content item has a thumbnail, otherwise FALSE. Throws an error if you do not have permission to view the thumbnail.

See Also

Other thumbnail functions: `delete_thumbnail()`, `get_thumbnail()`, `set_thumbnail()`

Other content functions: `content_delete()`, `content_item()`, `content_title()`, `content_update()`, `create_random_name()`, `dashboard_url()`, `dashboard_url_chr()`, `delete_thumbnail()`, `delete_vanity_url()`, `deploy_repo()`, `get_bundles()`, `get_environment()`, `get_image()`, `get_job()`, `get_jobs()`, `get_log()`, `get_thumbnail()`, `get_vanity_url()`, `git_permissions`, `set_image_path()`, `set_run_as()`, `set_thumbnail()`, `set_vanity_url()`, `swap_vanity_url()`, `swap_vanity_urls()`, `terminate_jobs()`, `verify_content_name()`

Examples

```
## Not run:
client <- connect()
item <- content_item(client, "8f37d6e0-3395-4a2c-aa6a-d7f2fe1babb0")
has_thumbnail(item)

## End(Not run)
```

page_cursor

Paging

Description

Helper functions that make paging easier in the Posit Connect Server API.

Helper functions that make paging easier in the Posit Connect Server API.

Usage

```
page_cursor(client, req, limit = Inf)
```

```
page_offset(client, req, limit = Inf)
```

Arguments

<code>client</code>	A Connect client object
<code>req</code>	The request that needs to be paged
<code>limit</code>	A row limit

Value

The aggregated results from all requests

The aggregated results from all requests

permissions	<i>Content permissions</i>
-------------	----------------------------

Description

Get or set content permissions for a content item

Usage

```
content_add_user(content, guid, role = c("viewer", "owner"))
content_add_group(content, guid, role = c("viewer", "owner"))
content_delete_user(content, guid)
content_delete_group(content, guid)
get_user_permission(content, guid, add_owner = TRUE)
get_my_permission(content, add_owner = TRUE)
get_group_permission(content, guid)
get_content_permissions(content, add_owner = TRUE)
```

Arguments

content	An R6 content object
guid	The guid associated with either a user (for content_add_user) or group (for content_add_group)
role	The role to assign to a user. Either "viewer" or "owner." Defaults to "viewer"
add_owner	Optional. Whether to include the owner in returned permission sets. Default is TRUE. The owner will have an NA_character_ permission "id"

Details

Permission modification:

- content_add_* adds a permission to the content
- content_delete_* removes a permission from the content

Permission retrieval:

- get_content_permissions() lists permissions
- get_my_permission() gets the permission associated with the caller.
- get_user_permission() gets the permissions associated with a given user. It does not evaluate group memberships

- `get_group_permission()` gets the permissions associated with a given group.

NOTE: by default, the owner is injected with an "NA_character_" permission id. This makes it easier to find / isolate this record.

See Also

Other content functions: `content_delete()`, `content_item()`, `content_title()`, `content_update()`, `create_random_name()`, `dashboard_url()`, `dashboard_url_chr()`, `delete_thumbnail()`, `delete_vanity_url()`, `deploy_repo()`, `get_bundles()`, `get_environment()`, `get_image()`, `get_job()`, `get_jobs()`, `get_log()`, `get_thumbnail()`, `get_vanity_url()`, `git_has_thumbnail()`, `set_image_path()`, `set_run_as()`, `set_thumbnail()`, `set_vanity_url()`, `swap_vanity_url()`, `swap_vanity_urls()`, `terminate_jobs()`, `verify_content_name()`

poll_task

Poll Task

Description

Polls a task, waiting for information about a deployment. If the task has results, the output will be a modified "Task" object with `task$get_data()` available to retrieve the results.

Usage

```
poll_task(task, wait = 1, callback = message)
```

Arguments

<code>task</code>	A Task object
<code>wait</code>	The interval to wait between polling
<code>callback</code>	A function to be called for each message received. Set to NULL for no callback

Details

For a simple way to silence messages, set `callback = NULL`

Value

Task The Task object that was input

See Also

Other deployment functions: `bundle_dir()`, `bundle_path()`, `bundle_static()`, `deploy()`, `download_bundle()`

PositConnect	<i>Class representing a Connect API client</i>
--------------	--

Description

Class representing a Connect API client

Class representing a Connect API client

Usage

```
client <- Connect$new(server = 'connect.example.com',  
  apiKey = 'mysecretkey')  
client$get_apps()  
client$get_tags()
```

Details

This class allows a user to interact with a Connect server via the Connect API. Authentication is done by providing an API key.

Public fields

`server` The base URL of your Posit Connect server.

`api_key` Your Posit Connect API key.

`tags` The initial set of tags.

`tag_map` The initial tag map.

`httr_additions` An initial set of httr configuration added to each HTTP call.

`using_auth` Indicates that the API key is added to each HTTP call.

Active bindings

`version` The server version.

Methods

Public methods:

- [Connect\\$get_connect\(\)](#)
- [Connect\\$new\(\)](#)
- [Connect\\$httr_config\(\)](#)
- [Connect\\$print\(\)](#)
- [Connect\\$raise_error\(\)](#)
- [Connect\\$add_auth\(\)](#)
- [Connect\\$api_url\(\)](#)
- [Connect\\$server_url\(\)](#)

- `Connect$request()`
- `Connect$GET()`
- `Connect$PUT()`
- `Connect$HEAD()`
- `Connect$DELETE()`
- `Connect$PATCH()`
- `Connect$POST()`
- `Connect$me()`
- `Connect$get_dashboard_url()`
- `Connect$get_tags()`
- `Connect$get_tag_id()`
- `Connect$get_tag_tree()`
- `Connect$tag_create_safe()`
- `Connect$tag_create()`
- `Connect$tag()`
- `Connect$tag_delete()`
- `Connect$get_apps()`
- `Connect$get_schedule()`
- `Connect$content_create()`
- `Connect$content_upload()`
- `Connect$content_deploy()`
- `Connect$content()`
- `Connect$task()`
- `Connect$set_content_tag()`
- `Connect$remove_content_tag()`
- `Connect$user()`
- `Connect$users()`
- `Connect$users_remote()`
- `Connect$users_create()`
- `Connect$users_create_remote()`
- `Connect$users_lock()`
- `Connect$users_unlock()`
- `Connect$users_update()`
- `Connect$groups()`
- `Connect$group_members()`
- `Connect$group_member_add()`
- `Connect$group_member_remove()`
- `Connect$groups_create()`
- `Connect$groups_create_remote()`
- `Connect$groups_remote()`
- `Connect$group_content()`
- `Connect$inst_content_visits()`

- `Connect$inst_shiny_usage()`
- `Connect$procs()`
- `Connect$repo_account()`
- `Connect$repo_branches()`
- `Connect$repo_manifest_dirs()`
- `Connect$schedules()`
- `Connect$packages()`
- `Connect$docs()`
- `Connect$audit_logs()`
- `Connect$vanities()`
- `Connect$server_settings_r()`
- `Connect$server_settings()`
- `Connect$clone()`

Method `get_connect()`: Return this connect.

Usage:

`Connect$get_connect()`

Method `new()`: Initialize a new connect.

Usage:

`Connect$new(server, api_key)`

Arguments:

`server` The base URL of your Posit Connect server.

`api_key` Your Posit Connect API key.

Method `httr_config()`: Set additional httr configuration that is added to each HTTP call.

Usage:

`Connect$httr_config(...)`

Arguments:

... Set of httr configurations.

Method `print()`: Print details about this instance.

Usage:

`Connect$print(...)`

Arguments:

... Ignored.

Method `raise_error()`: Raise an error when the HTTP result is an HTTP error.

Usage:

`Connect$raise_error(res)`

Arguments:

`res` HTTP result.

Method `add_auth()`: Returns HTTP authorization headers, or NULL when none are used.

Usage:

```
Connect$add_auth()
```

Method `api_url()`: Build a URL relative to the API root

Usage:

```
Connect$api_url(...)
```

Arguments:

... path segments

Method `server_url()`: Build a URL relative to the server root

Usage:

```
Connect$server_url(...)
```

Arguments:

... path segments

Method `request()`: General wrapper around `httr` verbs

Usage:

```
Connect$request(method, url, ..., parser = "parsed")
```

Arguments:

`method` HTTP request method

`url` URL to request

... Additional arguments passed to the request function

`parser` How the response is parsed. If NULL, the `httr_response` will be returned. Otherwise, the argument is forwarded to `httr::content(res, as = parser)`.

Method `GET()`: Perform an HTTP GET request of the named API path.

Usage:

```
Connect$GET(path, ..., url = self$api_url(path), parser = "parsed")
```

Arguments:

`path` API path relative to the server's `/__api__` root.

... Arguments to `httr::GET()`

`url` Target URL. Default uses `path`, but provide `url` to request a server resource that is not under `/__api__`

`parser` How the response is parsed. If NULL, the `httr_response` will be returned. Otherwise, the argument is forwarded to `httr::content(res, as = parser)`.

Method `PUT()`: Perform an HTTP PUT request of the named API path.

Usage:

```
Connect$PUT(
  path,
  body = "{}",
  ...,
  url = self$api_url(path),
  encode = "json",
  parser = "parsed"
)
```

Arguments:

path API path relative to the server's `/__api__` root.

body The HTTP payload.

... Arguments to `httr::PUT()`

url Target URL. Default uses path, but provide url to request a server resource that is not under `/__api__`

encode How the payload is encoded.

parser How the response is parsed. If NULL, the `httr_response` will be returned. Otherwise, the argument is forwarded to `httr::content(res, as = parser)`.

Method HEAD(): Perform an HTTP HEAD request of the named API path.

Usage:

```
Connect$HEAD(path, ..., url = self$api_url(path))
```

Arguments:

path API path relative to the server's `/__api__` root.

... Arguments to `httr::HEAD()`

url Target URL. Default uses path, but provide url to request a server resource that is not under `/__api__` `httr::content(res, as = parser)`.

Method DELETE(): Perform an HTTP DELETE request of the named API path. Returns the HTTP response object.

Usage:

```
Connect$DELETE(path, ..., url = self$api_url(path), parser = NULL)
```

Arguments:

path API path relative to the server's `/__api__` root.

... Arguments to `httr::DELETE()`

url Target URL. Default uses path, but provide url to request a server resource that is not under `/__api__`

parser How the response is parsed. If NULL, the `httr_response` will be returned. Otherwise, the argument is forwarded to `httr::content(res, as = parser)`.

Method PATCH(): Perform an HTTP PATCH request of the named API path.

Usage:

```
Connect$PATCH(
  path,
  body = "{}",
  ...,
  url = self$api_url(path),
  encode = "json",
  parser = "parsed"
)
```

Arguments:

path API path relative to the server's `/__api__` root.

body The HTTP payload.

... Arguments to `httr::PATCH()`
`url` Target URL. Default uses `path`, but provide `url` to request a server resource that is not under `/__api__`
`encode` How the payload is encoded.
`parser` How the response is parsed. If `NULL`, the `httr_response` will be returned. Otherwise, the argument is forwarded to `httr::content(res, as = parser)`.

Method `POST()`: Perform an HTTP POST request of the named API path.

Usage:

```
Connect$POST(  
  path,  
  body = "{}",  
  ...,  
  url = self$api_url(path),  
  encode = "json",  
  parser = "parsed"  
)
```

Arguments:

`path` API path relative to the server's `/__api__` root.
`body` The HTTP payload.
 ... Arguments to `httr::POST()`
`url` Target URL. Default uses `path`, but provide `url` to request a server resource that is not under `/__api__`
`encode` How the payload is encoded.
`parser` How the response is parsed. If `NULL`, the `httr_response` will be returned. Otherwise, the argument is forwarded to `httr::content(res, as = parser)`.

Method `me()`: Perform an HTTP GET request of the "me" server endpoint.

Usage:

```
Connect$me()
```

Method `get_dashboard_url()`: Return the base URL of the Connect server.

Usage:

```
Connect$get_dashboard_url()
```

Method `get_tags()`: Return all tags.

Usage:

```
Connect$get_tags(use_cache = FALSE)
```

Arguments:

`use_cache` Indicates that a cached set of tags is used.

Method `get_tag_id()`: Get the identifier for the named tag.

Usage:

```
Connect$get_tag_id(tagname)
```

Arguments:

tagname The name of the tag.

Method get_tag_tree(): Get the tag tree.

Usage:

```
Connect$get_tag_tree()
```

Method tag_create_safe(): Create a tag.

Usage:

```
Connect$tag_create_safe(name, parent_id = NULL)
```

Arguments:

name The tag name.

parent_id The parent identifier.

Method tag_create(): Create a tag.

Usage:

```
Connect$tag_create(name, parent_id = NULL)
```

Arguments:

name The tag name.

parent_id The parent identifier.

Method tag(): Get a tag.

Usage:

```
Connect$tag(id = NULL)
```

Arguments:

id The tag identifier.

Method tag_delete(): Delete a tag.

Usage:

```
Connect$tag_delete(id)
```

Arguments:

id The tag identifier.

Method get_apps(): Get content items.

Usage:

```
Connect$get_apps(filter = NULL, .collapse = "&", .limit = Inf, page_size = 25)
```

Arguments:

filter Named list containing filter conditions.

.collapse How multiple filters are combined.

.limit The limit.

page_size The page size.

Method get_schedule(): Get a schedule.

Usage:

```
Connect$get_schedule(schedule_id)
```

Arguments:

`schedule_id` The schedule identifier.

Method `content_create()`: Create content.

Usage:

```
Connect$content_create(name, title = name, ...)
```

Arguments:

`name` The content name.

`title` The content title.

`...` Other content fields.

Method `content_upload()`: Upload a content bundle.

Usage:

```
Connect$content_upload(bundle_path, guid)
```

Arguments:

`bundle_path` The path to the bundle archive.

`guid` The content GUID.

Method `content_deploy()`: Deploy a content bundle.

Usage:

```
Connect$content_deploy(guid, bundle_id)
```

Arguments:

`guid` The content GUID.

`bundle_id` The bundle identifier.

Method `content()`: Get a content item.

Usage:

```
Connect$content(  
  guid = NULL,  
  owner_guid = NULL,  
  name = NULL,  
  include = "tags,owner"  
)
```

Arguments:

`guid` The content GUID.

`owner_guid` The target content owner.

`name` The target name.

`include` Additional response fields.

Method `task()`: Get a task.

Usage:

```
Connect$task(task_id, first = 0, wait = 5)
```

Arguments:

`task_id` The task identifier.

`first` The initial status position.

`wait` Maximum time to wait for update.

Method `set_content_tag()`: Set a tag for a content item.

Usage:

```
Connect$set_content_tag(content_id, tag_id)
```

Arguments:

`content_id` The content identifier.

`tag_id` The tag identifier.

Method `remove_content_tag()`: Remove a tag from a content item.

Usage:

```
Connect$remove_content_tag(content_id, tag_id)
```

Arguments:

`content_id` The content identifier.

`tag_id` The tag identifier.

Method `user()`: Get user details.

Usage:

```
Connect$user(guid)
```

Arguments:

`guid` The user GUID.

Method `users()`: Get users.

Usage:

```
Connect$users(  
  page_number = 1,  
  prefix = NULL,  
  page_size = 500,  
  user_role = NULL,  
  account_status = NULL  
)
```

Arguments:

`page_number` The page number.

`prefix` The search term.

`page_size` The page size.

`user_role` Filter by user role.

`account_status` Filter by account status.

Method `users_remote()`: Get remote users.

Usage:

```
Connect$users_remote(prefix)
```

Arguments:

prefix The search term.

Method users_create(): Create a user.

Usage:

```
Connect$users_create(  
  username,  
  email,  
  first_name = NULL,  
  last_name = NULL,  
  password = NULL,  
  user_must_set_password = NULL,  
  user_role = NULL,  
  unique_id = NULL  
)
```

Arguments:

username The username.

email Email address.

first_name First name.

last_name Last name.

password The password.

user_must_set_password Indicates that user sets password on first login.

user_role Role for user.

unique_id Identifier for user.

Method users_create_remote(): Create a remote user.

Usage:

```
Connect$users_create_remote(temp_ticket)
```

Arguments:

temp_ticket Ticket identifying target remote user.

Method users_lock(): Lock a user.

Usage:

```
Connect$users_lock(user_guid)
```

Arguments:

user_guid User GUID.

Method users_unlock(): Unlock a user.

Usage:

```
Connect$users_unlock(user_guid)
```

Arguments:

user_guid User GUID.

Method users_update(): Update a user.

Usage:

Connect\$users_update(user_guid, ...)

Arguments:

user_guid User GUID.

... User fields.

Method groups(): Get groups.

Usage:

Connect\$groups(page_number = 1, prefix = NULL, page_size = 500)

Arguments:

page_number The page number.

prefix The search term.

page_size The page size.

Method group_members(): Get group members.

Usage:

Connect\$group_members(guid)

Arguments:

guid The group GUID.

Method group_member_add(): Add a group member.

Usage:

Connect\$group_member_add(group_guid, user_guid)

Arguments:

group_guid The group GUID.

user_guid The user GUID.

Method group_member_remove(): Remove a group member.

Usage:

Connect\$group_member_remove(group_guid, user_guid)

Arguments:

group_guid The group GUID.

user_guid The user GUID.

Method groups_create(): Create a group.

Usage:

Connect\$groups_create(name)

Arguments:

name The group name.

Method groups_create_remote(): Create a remote group.

Usage:

```
Connect$groups_create_remote(temp_ticket)
```

Arguments:

temp_ticket Ticket identifying target remote group.

Method groups_remote(): Get remote groups.

Usage:

```
Connect$groups_remote(prefix = NULL, limit = 500)
```

Arguments:

prefix The search term.

limit The maximal result set size.

Method group_content(): Get content to which a group has access

Usage:

```
Connect$group_content(guid)
```

Arguments:

guid The group GUID.

Method inst_content_visits(): Get (non-interactive) content visits.

Usage:

```
Connect$inst_content_visits(
  content_guid = NULL,
  min_data_version = NULL,
  from = NULL,
  to = NULL,
  limit = 500,
  previous = NULL,
  nxt = NULL,
  asc_order = TRUE
)
```

Arguments:

content_guid Content GUID.

min_data_version Data version for request.

from Start of range.

to End of range.

limit Result set size.

previous Previous item.

nxt Next item.

asc_order Indicates ascending result order.

Method inst_shiny_usage(): Get interactive content visits.

Get (non-interactive) content visits.

Usage:

```
Connect$inst_shiny_usage(  
  content_guid = NULL,  
  min_data_version = NULL,  
  from = NULL,  
  to = NULL,  
  limit = 500,  
  previous = NULL,  
  nxt = NULL,  
  asc_order = TRUE  
)
```

Arguments:

content_guid Content GUID.
min_data_version Data version for request.
from Start of range.
to End of range.
limit Result set size.
previous Previous item.
nxt Next item.
asc_order Indicates ascending result order.

Method procs(): Get running processes.

Usage:

```
Connect$procs()
```

Method repo_account(): Determine if Git repository is associated with authorization.

Usage:

```
Connect$repo_account(host)
```

Arguments:

host Repository URL.

Method repo_branches(): Get Git repository branches.

Usage:

```
Connect$repo_branches(repo)
```

Arguments:

repo Repository URL.

Method repo_manifest_dirs(): Get Git repository directories.

Usage:

```
Connect$repo_manifest_dirs(repo, branch)
```

Arguments:

repo Repository URL.

branch Repository branch.

Method `schedules()`: Get schedules.

Usage:

```
Connect$schedules(  
  start = Sys.time(),  
  end = Sys.time() + 60 * 60 * 24 * 7,  
  detailed = FALSE  
)
```

Arguments:

`start` Starting time.

`end` Ending time.

`detailed` Indicates detailed schedule information.

Method `packages()`: Get packages. This endpoint is paginated.

Usage:

```
Connect$packages(name = NULL, page_number = 1, page_size = 1e+05)
```

Arguments:

`name` The package name to filter by.

`page_number` Page number.

`page_size` Page size, default 100000.

Method `docs()`: Get documentation.

Usage:

```
Connect$docs(docs = "api", browse = TRUE)
```

Arguments:

`docs` Named document.

`browse` Open a browser.

Method `audit_logs()`: Get auditing.

Usage:

```
Connect$audit_logs(limit = 500, previous = NULL, nxt = NULL, asc_order = TRUE)
```

Arguments:

`limit` Result set size.

`previous` Previous item.

`nxt` Next item.

`asc_order` Indicates ascending result order.

Method `vanities()`: Get all vanity URLs

Usage:

```
Connect$vanities()
```

Method `server_settings_r()`: Get R installations.

Usage:

```
Connect$server_settings_r()
```

Method `server_settings()`: Get server settings.

Usage:

`Connect$server_settings()`

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`Connect$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

See Also

Other R6 classes: [Bundle](#), [Content](#), [ContentTask](#), [Environment](#), [Task](#), [Vanity](#), [Variant](#), [VariantSchedule](#), [VariantTask](#)

promote	<i>Promote content from one Connect server to another</i>
---------	---

Description

Promote content from one Connect server to another

Usage

`promote(from, to, to_key, from_key, name)`

Arguments

<code>from</code>	The url for the server containing the content (the originating server)
<code>to</code>	The url for the server where the content will be deployed (the destination server)
<code>to_key</code>	An API key on the destination "to" server. If the destination content is going to be updated, the API key must belong to a user with collaborator access on the content that will be updated. If the destination content is to be created new, the API key must belong to a user with publisher privileges.
<code>from_key</code>	An API key on the originating "from" server. The API key must belong to a user with collaborator access to the content to be promoted.
<code>name</code>	The name of the content on the originating "from" server. If content with the same name is found on the destination server, the content will be updated. If no content on the destination server has a matching name, a new endpoint will be created.

Value

The URL for the content on the destination "to" server

set_image_path	<i>Set the Content Image</i>
----------------	------------------------------

Description

[Deprecated]

Please use [set_thumbnail](#) instead.

Set the Content Image using a variety of methods.

Usage

```
set_image_path(content, path)

set_image_url(content, url)

set_image_webshot(content, ...)
```

Arguments

content	A content object
path	The path to an image on disk
url	The url for an image
...	Additional arguments passed on to webshot2::webshot()

Details

NOTE: `set_image_webshot()` requires [webshot2::webshot\(\)](#), but currently skips and warns for any content that requires authentication until the `webshot2` package supports authentication.

See Also

Other content functions: [content_delete\(\)](#), [content_item\(\)](#), [content_title\(\)](#), [content_update\(\)](#), [create_random_name\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_thumbnail\(\)](#), [delete_vanity_url\(\)](#), [deploy_repo\(\)](#), [get_bundles\(\)](#), [get_environment\(\)](#), [get_image\(\)](#), [get_job\(\)](#), [get_jobs\(\)](#), [get_log\(\)](#), [get_thumbnail\(\)](#), [get_vanity_url\(\)](#), [git](#), [has_thumbnail\(\)](#), [permissions](#), [set_run_as\(\)](#), [set_thumbnail\(\)](#), [set_vanity_url\(\)](#), [swap_vanity_url\(\)](#), [swap_vanity_urls\(\)](#), [terminate_jobs\(\)](#), [verify_content_name\(\)](#)

set_run_as

Set RunAs User

Description

Set the RunAs user for a piece of content. The run_as_current_user flag only does anything if:

Usage

```
set_run_as(content, run_as, run_as_current_user = FALSE)
```

Arguments

content	an R6 Content item
run_as	The RunAs user to use for this content
run_as_current_user	Whether to run this content as the viewer of the application

Details

- PAM is the authentication method
- Applications.RunAsCurrentUser is enabled on the server

Also worth noting that the run_as user must exist on the Posit Connect server (as a linux user) and have appropriate group memberships, or you will get a 400: Bad Request. Set to NULL to use the default RunAs user / unset any current configuration.

To "read" the current RunAs user, use the Content object or get_content() function.

Value

a Content object, updated with new details

See Also

connectapi::content_update

Other content functions: [content_delete\(\)](#), [content_item\(\)](#), [content_title\(\)](#), [content_update\(\)](#), [create_random_name\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_thumbnail\(\)](#), [delete_vanity_url\(\)](#), [deploy_repo\(\)](#), [get_bundles\(\)](#), [get_environment\(\)](#), [get_image\(\)](#), [get_job\(\)](#), [get_jobs\(\)](#), [get_log\(\)](#), [get_thumbnail\(\)](#), [get_vanity_url\(\)](#), [git_has_thumbnail\(\)](#), [permissions](#), [set_image_path\(\)](#), [set_thumbnail\(\)](#), [set_vanity_url\(\)](#), [swap_vanity_url\(\)](#), [swap_vanity_urls\(\)](#), [terminate_jobs\(\)](#), [verify_content_name\(\)](#)

set_schedule	<i>Set a Schedule</i>
--------------	-----------------------

Description

[Experimental] Sets the schedule for a given Variant. Requires a Schedule object (as returned by `get_variant_schedule()`)

Usage

```
set_schedule(.schedule, ...)
```

```
set_schedule_minute(  
  .schedule,  
  n = 30,  
  start_time = Sys.time(),  
  activate = TRUE,  
  email = FALSE,  
  timezone = Sys.timezone()  
)
```

```
set_schedule_hour(  
  .schedule,  
  n = 1,  
  start_time = Sys.time(),  
  activate = TRUE,  
  email = FALSE,  
  timezone = Sys.timezone()  
)
```

```
set_schedule_day(  
  .schedule,  
  n = 1,  
  start_time = Sys.time(),  
  activate = TRUE,  
  email = FALSE,  
  timezone = Sys.timezone()  
)
```

```
set_schedule_weekday(  
  .schedule,  
  start_time = Sys.time(),  
  activate = TRUE,  
  email = FALSE,  
  timezone = Sys.timezone()  
)
```

```
set_schedule_week(  
    .schedule,  
    n = 1,  
    start_time = Sys.time(),  
    activate = TRUE,  
    email = FALSE,  
    timezone = Sys.timezone()  
)
```

```
set_schedule_dayofweek(  
    .schedule,  
    days,  
    start_time = Sys.time(),  
    activate = TRUE,  
    email = FALSE,  
    timezone = Sys.timezone()  
)
```

```
set_schedule_semimonth(  
    .schedule,  
    first = TRUE,  
    start_time = Sys.time(),  
    activate = TRUE,  
    email = FALSE,  
    timezone = Sys.timezone()  
)
```

```
set_schedule_dayofmonth(  
    .schedule,  
    n = 1,  
    day = 1,  
    start_time = Sys.time(),  
    activate = TRUE,  
    email = FALSE,  
    timezone = Sys.timezone()  
)
```

```
set_schedule_dayweekofmonth(  
    .schedule,  
    n = 1,  
    day = 1,  
    week = 1,  
    start_time = Sys.time(),  
    activate = TRUE,  
    email = FALSE,  
    timezone = Sys.timezone()  
)
```

```

set_schedule_year(
  .schedule,
  n = 1,
  start_time = Sys.time(),
  activate = TRUE,
  email = FALSE,
  timezone = Sys.timezone()
)

set_schedule_remove(.schedule)

schedule_describe(.schedule)

```

Arguments

<code>.schedule</code>	A schedule object. As returned by <code>get_variant_schedule()</code>
<code>...</code>	Scheduling parameters
<code>n</code>	The "number of" iterations
<code>start_time</code>	The start time of the schedule
<code>activate</code>	Whether to publish the output of this schedule
<code>email</code>	Whether to send emails on this schedule
<code>timezone</code>	The timezone to use for setting the schedule. Defaults to <code>Sys.timezone()</code>
<code>days</code>	The days of the week (0-6)
<code>first</code>	logical Whether to execute on the 1st and 15th (TRUE) or 14th and last (FALSE)
<code>day</code>	The day of the week (0-6) or day of the month (0-31)
<code>week</code>	The week of the month (0-5)
<code>schedule</code>	A JSON blob (as a string) describing the schedule. See "More Details"

Details

- `set_schedule()` is a raw interface to Posit Connect's schedule API
- `set_schedule_*` functions provide handy wrappers around `set_schedule()`
- `set_schedule_remove()` removes a schedule / un-schedules a variant

Beware, using `set_schedule()` currently uses the Posit Connect schedule API directly, and so can be a little clunky. Using the `set_schedule_*` is generally recommended.

Value

An updated Schedule object

See Also

Other schedule functions: [get_timezones\(\)](#), [get_variant_schedule\(\)](#)

set_thumbnail	<i>Set content item thumbnail</i>
---------------	-----------------------------------

Description

Set the thumbnail for a content item.

Usage

```
set_thumbnail(content, path)
```

Arguments

content	A content item.
path	Either a path to a local file or a URL to an image available over HTTP/HTTPS. If path is an HTTP or HTTPS URL, the image will first be downloaded.

Value

The content item (invisibly).

See Also

Other thumbnail functions: [delete_thumbnail\(\)](#), [get_thumbnail\(\)](#), [has_thumbnail\(\)](#)

Other content functions: [content_delete\(\)](#), [content_item\(\)](#), [content_title\(\)](#), [content_update\(\)](#), [create_random_name\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_thumbnail\(\)](#), [delete_vanity_url\(\)](#), [deploy_repo\(\)](#), [get_bundles\(\)](#), [get_environment\(\)](#), [get_image\(\)](#), [get_job\(\)](#), [get_jobs\(\)](#), [get_log\(\)](#), [get_thumbnail\(\)](#), [get_vanity_url\(\)](#), [git](#), [has_thumbnail\(\)](#), [permissions](#), [set_image_path\(\)](#), [set_run_as\(\)](#), [set_vanity_url\(\)](#), [swap_vanity_url\(\)](#), [swap_vanity_urls\(\)](#), [terminate_jobs\(\)](#), [verify_content_name\(\)](#)

Examples

```
## Not run:
client <- connect()
item <- content_item(client, "8f37d6e0-3395-4a2c-aa6a-d7f2fe1babd0")
set_thumbnail(item, "resources/image.png")

## End(Not run)
```

set_vanity_url	<i>Set the Vanity URL</i>
----------------	---------------------------

Description

Set the vanity URL for a piece of content.

Usage

```
set_vanity_url(content, url, force = FALSE)
```

Arguments

content	A Content object
url	The path component of the URL
force	optional. Default FALSE. Whether to force-reassign a vanity URL that already exists

Value

An updated Content object

See Also

Other content functions: [content_delete\(\)](#), [content_item\(\)](#), [content_title\(\)](#), [content_update\(\)](#), [create_random_name\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_thumbnail\(\)](#), [delete_vanity_url\(\)](#), [deploy_repo\(\)](#), [get_bundles\(\)](#), [get_environment\(\)](#), [get_image\(\)](#), [get_job\(\)](#), [get_jobs\(\)](#), [get_log\(\)](#), [get_thumbnail\(\)](#), [get_vanity_url\(\)](#), [git](#), [has_thumbnail\(\)](#), [permissions](#), [set_image_path\(\)](#), [set_run_as\(\)](#), [set_thumbnail\(\)](#), [swap_vanity_url\(\)](#), [swap_vanity_urls\(\)](#), [terminate_jobs\(\)](#), [verify_content_name\(\)](#)

Examples

```
## Not run:
bnd <- bundle_dir("~/my/directory")
connect() %>%
  deploy(bnd) %>%
  set_vanity_url("a/vanity/url")

## End(Not run)
```

swap_vanity_url	<i>Swap Vanity URLs</i>
-----------------	-------------------------

Description

Swap the vanity URLs of two pieces of content. This function is deprecated; please use [swap_vanity_urls](#).

Usage

```
swap_vanity_url(from, to)
```

Arguments

from	A Content object
to	A Content object

Value

A list of the new vanity URLs for from and to

See Also

Other content functions: [content_delete\(\)](#), [content_item\(\)](#), [content_title\(\)](#), [content_update\(\)](#), [create_random_name\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_thumbnail\(\)](#), [delete_vanity_url\(\)](#), [deploy_repo\(\)](#), [get_bundles\(\)](#), [get_environment\(\)](#), [get_image\(\)](#), [get_job\(\)](#), [get_jobs\(\)](#), [get_log\(\)](#), [get_thumbnail\(\)](#), [get_vanity_url\(\)](#), [git](#), [has_thumbnail\(\)](#), [permissions](#), [set_image_path\(\)](#), [set_run_as\(\)](#), [set_thumbnail\(\)](#), [set_vanity_url\(\)](#), [swap_vanity_urls\(\)](#), [terminate_jobs\(\)](#), [verify_content_name\(\)](#)

swap_vanity_urls	<i>Swap Vanity URLs</i>
------------------	-------------------------

Description

Swap the vanity URLs of two pieces of content.

Usage

```
swap_vanity_urls(content_a, content_b)
```

Arguments

content_a	A Content object
content_b	A Content object

Value

A list of the new vanity URLs for content_a and content_b

See Also

Other content functions: [content_delete\(\)](#), [content_item\(\)](#), [content_title\(\)](#), [content_update\(\)](#), [create_random_name\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_thumbnail\(\)](#), [delete_vanity_url\(\)](#), [deploy_repo\(\)](#), [get_bundles\(\)](#), [get_environment\(\)](#), [get_image\(\)](#), [get_job\(\)](#), [get_jobs\(\)](#), [get_log\(\)](#), [get_thumbnail\(\)](#), [get_vanity_url\(\)](#), [git.has_thumbnail\(\)](#), [permissions](#), [set_image_path\(\)](#), [set_run_as\(\)](#), [set_thumbnail\(\)](#), [set_vanity_url\(\)](#), [swap_vanity_url\(\)](#), [terminate_jobs\(\)](#), [verify_content_name\(\)](#)

Task	<i>Task</i>
------	-------------

Description

Task
Task

Details

An R6 class that represents a Task

Public fields

connect The Connect instance.
task The task.
data The task data.

Methods

Public methods:

- [Task\\$new\(\)](#)
- [Task\\$get_connect\(\)](#)
- [Task\\$get_task\(\)](#)
- [Task\\$add_data\(\)](#)
- [Task\\$get_data\(\)](#)
- [Task\\$print\(\)](#)
- [Task\\$clone\(\)](#)

Method `new()`: Initialize this task.

Usage:

`Task$new(connect, task)`

Arguments:

connect The Connect instance.

task The task data.

Method `get_connect()`: Return the associated Connect instance.

Usage:

```
Task$get_connect()
```

Method `get_task()`: Return the underlying task.

Usage:

```
Task$get_task()
```

Method `add_data()`: Set the data.

Usage:

```
Task$add_data(data)
```

Arguments:

data The data.

Method `get_data()`: Get the data.

Usage:

```
Task$get_data()
```

Method `print()`: Print this object.

Usage:

```
Task$print(...)
```

Arguments:

... Unused.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
Task$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other R6 classes: [Bundle](#), [Content](#), [ContentTask](#), [Environment](#), [PositConnect](#), [Vanity](#), [Variant](#), [VariantSchedule](#), [VariantTask](#)

tbl_connect

*Connect Tibble***Description**

[Experimental] A lazy tibble that automatically pages through API requests when collected.

Usage

```
tbl_connect(
  src,
  from = c("users", "groups", "content", "usage_shiny", "usage_static", "audit_logs"),
  ...
)
```

Arguments

src	The source object
from	The type of tibble
...	Additional arguments that are not yet implemented

Value

A tbl_connect object

terminate_jobs

*Terminate Jobs***Description**

Register a job kill order for one or more jobs associated with a content item. Requires Connect 2022.10.0 or newer.

Usage

```
terminate_jobs(content, keys = NULL)
```

Arguments

content	A Content object, as returned by content_item()
keys	Optional. One or more job keys, which can be obtained using get_jobs(content). If no keys are provided, will terminate all active jobs for the provided content item.

Value

A data frame with the status of each termination request.

- `app_id`: The content item's identifier.
- `app_guid`: The content item's GUID.
- `job_key`: The job key.
- `job_id`: The job's identifier.
- `result`: The result string returned by Connect.
- `code`: An error code, NA if the request was successful.
- `error`: An error message, NA if the result was successful.

Note that `app_id`, `app_guid`, `job_id`, and `result` are NA if the request returns an error.

See Also

Other job functions: [get_job\(\)](#), [get_jobs\(\)](#), [get_log\(\)](#)

Other content functions: [content_delete\(\)](#), [content_item\(\)](#), [content_title\(\)](#), [content_update\(\)](#), [create_random_name\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_thumbnail\(\)](#), [delete_vanity_url\(\)](#), [deploy_repo\(\)](#), [get_bundles\(\)](#), [get_environment\(\)](#), [get_image\(\)](#), [get_job\(\)](#), [get_jobs\(\)](#), [get_log\(\)](#), [get_thumbnail\(\)](#), [get_vanity_url\(\)](#), [git_has_thumbnail\(\)](#), [permissions](#), [set_image_path\(\)](#), [set_run_as\(\)](#), [set_thumbnail\(\)](#), [set_vanity_url\(\)](#), [swap_vanity_url\(\)](#), [swap_vanity_urls\(\)](#), [verify_content_name\(\)](#)

Examples

```
## Not run:
client <- connect()
item <- content_item(client, "951bf3ad-82d0-4bca-bba8-9b27e35c49fa")
result <- terminate_jobs(item)

## End(Not run)
```

users_create_remote	<i>Create a Remote User</i>
---------------------	-----------------------------

Description

The remote user creation workflow involves authentication providers like LDAP that involve a queryable identity store. This helper wraps the API calls necessary to retrieve information about and then create such a user. It functions with a "fuzzy match" prefix by default, but if you want to instantiate users directly, you should set `exact = TRUE`.

Usage

```
users_create_remote(connect, prefix, expect = 1, check = TRUE, exact = FALSE)
```

Arguments

connect	An R6 Connect object.
prefix	character. The prefix of the user name to search for.
expect	number. Optional. The number of responses to expect for this search.
check	boolean. Optional. Whether to check for local existence first.
exact	boolean. Optional. Whether to only create users whose username exactly matches the provided prefix.

Details

NOTE: there can be problems with usernames that are not unique. Please open an issue if you run into any problems.

Value

The results of creating the users.

user_guid_from_username

User

Description

Get user details

Usage

```
user_guid_from_username(client, username)
```

Arguments

client	A Connect R6 object
username	The user's username

Details

`user_guid_from_username()` is a helper to retrieve a user GUID, given the user's username. It is useful in Shiny applications for using `session$user`

Vanity

Vanity

Description

Vanity

Vanity

Details

An R6 class that represents a Vanity URL

Super class

`connectapi::Content` -> Vanity

Public fields

`vanity` The vanity.

Methods

Public methods:

- `Vanity$new()`
- `Vanity$get_vanity()`
- `Vanity$print()`
- `Vanity$clone()`

Method `new()`: Initialize this vanity.

Usage:

`Vanity$new(connect, content, vanity)`

Arguments:

`connect` The Connect instance.

`content` The Content instance.

`vanity` The vanity data.

Method `get_vanity()`: Return the underlying vanity.

Usage:

`Vanity$get_vanity()`

Method `print()`: Print this object.

Usage:

`Vanity$print(...)`

Arguments:

... Unused.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
Vanity$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other R6 classes: [Bundle](#), [Content](#), [ContentTask](#), [Environment](#), [PositConnect](#), [Task](#), [Variant](#), [VariantSchedule](#), [VariantTask](#)

vanity_is_available	<i>Check to see if a vanity URL is currently in use</i>
---------------------	---

Description

[Experimental]

Usage

```
vanity_is_available(connect, vanity)
```

Arguments

<code>connect</code>	A Connect R6 object
<code>vanity</code>	string of the vanity URL to check

Value

logical indicating if the vanity URL is available.

See Also

Other audit functions: [audit_access_open\(\)](#), [audit_r_versions\(\)](#), [audit_runas\(\)](#)

Variant

Variant

Description

Variant

Variant

Details

An R6 class that represents a Variant

Super class

`connectapi::Content` -> Variant

Public fields

key The variant key.

variant The variant.

Methods

Public methods:

- `Variant$get_variant()`
- `Variant$get_variant_remote()`
- `Variant$new()`
- `Variant$send_mail()`
- `Variant$get_schedule()`
- `Variant$get_schedule_remote()`
- `Variant$get_subscribers()`
- `Variant$remove_subscriber()`
- `Variant$add_subscribers()`
- `Variant$render()`
- `Variant$renderings()`
- `Variant$update_variant()`
- `Variant$jobs()`
- `Variant$job()`
- `Variant$get_url()`
- `Variant$get_url_rev()`
- `Variant$get_dashboard_url()`
- `Variant$print()`
- `Variant$clone()`

Method `get_variant()`: Get the underlying variant data.

Usage:

`Variant$get_variant()`

Method `get_variant_remote()`: Get and store the (remote) variant data.

Usage:

`Variant$get_variant_remote()`

Method `new()`: Initialize this variant.

Usage:

`Variant$new(connect, content, key)`

Arguments:

`connect` The Connect instance.

`content` The Content instance.

`key` The variant key.

Method `send_mail()`: Mail previously rendered content.

Usage:

`Variant$send_mail(to = c("me", "collaborators", "collaborators_viewers"))`

Arguments:

`to` Targeting.

Method `get_schedule()`: Get the (remote) schedule data.

Usage:

`Variant$get_schedule()`

Method `get_schedule_remote()`: Get the (remote) schedule data.

Usage:

`Variant$get_schedule_remote()`

Method `get_subscribers()`: Get the subscribers.

Usage:

`Variant$get_subscribers()`

Method `remove_subscriber()`: Remove a named subscriber.

Usage:

`Variant$remove_subscriber(guid)`

Arguments:

`guid` User GUID.

Method `add_subscribers()`: Add named subscribers.

Usage:

`Variant$add_subscribers(guids)`

Arguments:

guids User GUIDs.

Method render(): Render this variant.

Usage:

Variant\$render()

Method renderings(): List the renderings of this variant.

Usage:

Variant\$renderings()

Method update_variant(): Update this variant.

Usage:

Variant\$update_variant(...)

Arguments:

... Target fields and values.

Method jobs(): Jobs for this variant.

Usage:

Variant\$jobs()

Method job(): Return single job for this variant.

Usage:

Variant\$job(key)

Arguments:

key The job key.

Method get_url(): Return the URL for this variant.

Usage:

Variant\$get_url()

Method get_url_rev(): Return the URL associated with one rendering for this variant.

Usage:

Variant\$get_url_rev(rev)

Arguments:

rev Rendering identifier.

Method get_dashboard_url(): Return the URL for this variant in the Posit Connect dashboard.

Usage:

Variant\$get_dashboard_url(pane = "access")

Arguments:

pane The pane in the dashboard to link to.

Method print(): Print this object.

Usage:
Variant\$print(...)
Arguments:
... Unused.

Method clone(): The objects of this class are cloneable with this method.
Usage:
Variant\$clone(deep = FALSE)
Arguments:
deep Whether to make a deep clone.

See Also

Other R6 classes: [Bundle](#), [Content](#), [ContentTask](#), [Environment](#), [PositConnect](#), [Task](#), [Vanity](#), [VariantSchedule](#), [VariantTask](#)

VariantSchedule	<i>VariantSchedule</i>
-----------------	------------------------

Description

VariantSchedule
VariantSchedule

Details

An R6 class that represents a Schedule

Super classes

[connectapi::Content](#) -> [connectapi::Variant](#) -> VariantSchedule

Public fields

schedule_data The schedule data.

Methods

- Public methods:**
- [VariantSchedule\\$new\(\)](#)
 - [VariantSchedule\\$GET\(\)](#)
 - [VariantSchedule\\$POST\(\)](#)
 - [VariantSchedule\\$DELETE\(\)](#)
 - [VariantSchedule\\$set_schedule\(\)](#)
 - [VariantSchedule\\$is_empty\(\)](#)

- [VariantSchedule#print\(\)](#)
- [VariantSchedule\\$get_schedule\(\)](#)
- [VariantSchedule\\$get_schedule_remote\(\)](#)
- [VariantSchedule\\$describe_schedule\(\)](#)
- [VariantSchedule\\$clone\(\)](#)

Method `new()`: Initialize this schedule.

Usage:

```
VariantSchedule$new(connect, content, key, schedule)
```

Arguments:

`connect` The Connect instance.

`content` The Content instance.

`key` The variant key.

`schedule` The schedule data.

Method `GET()`: Perform an HTTP GET request of the named API path. Returns an object parsed from the HTTP response.

Usage:

```
VariantSchedule$GET(path)
```

Arguments:

`path` API path.

Method `POST()`: Perform an HTTP POST request of the named API path. Returns an object parsed from the HTTP response.

Usage:

```
VariantSchedule$POST(path, body)
```

Arguments:

`path` API path.

`body` The HTTP payload.

Method `DELETE()`: Perform an HTTP DELETE request of the named API path. Returns the HTTP response object.

Usage:

```
VariantSchedule$DELETE(path)
```

Arguments:

`path` API path.

Method `set_schedule()`: Set the schedule for this variant

Usage:

```
VariantSchedule$set_schedule(...)
```

Arguments:

`...` Schedule fields.

Method `is_empty()`: Return if this variant has a schedule.

Usage:
`VariantSchedule$is_empty()`

Method `print()`: Print this object.

Usage:
`VariantSchedule$print(...)`
Arguments:
... Unused.

Method `get_schedule()`: Get the schedule data.

Usage:
`VariantSchedule$get_schedule()`

Method `get_schedule_remote()`: Get and store the (remote) schedule data.

Usage:
`VariantSchedule$get_schedule_remote()`

Method `describe_schedule()`: Description of the associated schedule.

Usage:
`VariantSchedule$describe_schedule()`

Method `clone()`: The objects of this class are cloneable with this method.

Usage:
`VariantSchedule$clone(deep = FALSE)`
Arguments:
deep Whether to make a deep clone.

See Also

Other R6 classes: [Bundle](#), [Content](#), [ContentTask](#), [Environment](#), [PositConnect](#), [Task](#), [Vanity](#), [Variant](#), [VariantTask](#)

VariantTask	<i>VariantTask</i>
-------------	--------------------

Description

VariantTask
VariantTask

Details

An R6 class that represents a Variant Task

Super classes

`connectapi::Content -> connectapi::Variant -> VariantTask`

Public fields

`task` The task.

`data` The variant data.

Methods**Public methods:**

- `VariantTask$new()`
- `VariantTask$get_task()`
- `VariantTask$add_data()`
- `VariantTask$get_data()`
- `VariantTask$print()`
- `VariantTask$clone()`

Method `new()`: Initialize this variant task.

Usage:

`VariantTask$new(connect, content, key, task)`

Arguments:

`connect` The Connect instance.

`content` The Content instance.

`key` The variant key.

`task` The task data.

Method `get_task()`: Return the underlying task.

Usage:

`VariantTask$get_task()`

Method `add_data()`: Set the data.

Usage:

`VariantTask$add_data(data)`

Arguments:

`data` The data.

Method `get_data()`: Get the data.

Usage:

`VariantTask$get_data()`

Method `print()`: Print this object.

Usage:

`VariantTask$print(...)`

Arguments:

... Unused.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
VariantTask$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other R6 classes: [Bundle](#), [Content](#), [ContentTask](#), [Environment](#), [PositConnect](#), [Task](#), [Vanity](#), [Variant](#), [VariantSchedule](#)

verify_content_name	<i>Verify Content Name</i>
---------------------	----------------------------

Description

Ensures that a content name fits the specifications / requirements of Posit Connect. Throws an error if content name is invalid. Content names (as of the time of writing) must be between 3 and 64 alphanumeric characters, dashes, and underscores

Usage

```
verify_content_name(name)
```

Arguments

name	The proposed content name
------	---------------------------

Value

The name (or an error if invalid)

See Also

connectapi::create_random_name

Other content functions: [content_delete\(\)](#), [content_item\(\)](#), [content_title\(\)](#), [content_update\(\)](#), [create_random_name\(\)](#), [dashboard_url\(\)](#), [dashboard_url_chr\(\)](#), [delete_thumbnail\(\)](#), [delete_vanity_url\(\)](#), [deploy_repo\(\)](#), [get_bundles\(\)](#), [get_environment\(\)](#), [get_image\(\)](#), [get_job\(\)](#), [get_jobs\(\)](#), [get_log\(\)](#), [get_thumbnail\(\)](#), [get_vanity_url\(\)](#), [git.has_thumbnail\(\)](#), [permissions](#), [set_image_path\(\)](#), [set_run_as\(\)](#), [set_thumbnail\(\)](#), [set_vanity_url\(\)](#), [swap_vanity_url\(\)](#), [swap_vanity_urls\(\)](#), [terminate_jobs\(\)](#)

Index

* R6 classes

- Bundle, [6](#)
- Content, [10](#)
- ContentTask, [16](#)
- Environment, [32](#)
- PositConnect, [73](#)
- Task, [96](#)
- Vanity, [101](#)
- Variant, [103](#)
- VariantSchedule, [106](#)
- VariantTask, [108](#)

* audit functions

- audit_access_open, [4](#)
- audit_r_versions, [5](#)
- audit_runas, [4](#)
- vanity_is_available, [102](#)

* content functions

- content_delete, [18](#)
- content_item, [18](#)
- content_title, [22](#)
- content_update, [23](#)
- create_random_name, [24](#)
- dashboard_url, [24](#)
- dashboard_url_chr, [25](#)
- delete_thumbnail, [27](#)
- delete_vanity_url, [28](#)
- deploy_repo, [30](#)
- get_bundles, [37](#)
- get_environment, [42](#)
- get_image, [46](#)
- get_job, [47](#)
- get_jobs, [48](#)
- get_log, [50](#)
- get_thumbnail, [58](#)
- get_vanity_url, [64](#)
- git, [68](#)
- has_thumbnail, [69](#)
- permissions, [71](#)
- set_image_path, [88](#)

- set_run_as, [89](#)
- set_thumbnail, [93](#)
- set_vanity_url, [94](#)
- swap_vanity_url, [95](#)
- swap_vanity_urls, [95](#)
- terminate_jobs, [98](#)
- verify_content_name, [110](#)

* deployment functions

- bundle_dir, [7](#)
- bundle_path, [7](#)
- bundle_static, [8](#)
- deploy, [28](#)
- download_bundle, [31](#)
- poll_task, [72](#)

* groups functions

- get_group_content, [44](#)
- get_group_members, [45](#)
- get_groups, [43](#)

* job functions

- get_job, [47](#)
- get_jobs, [48](#)
- get_log, [50](#)
- terminate_jobs, [98](#)

* packages functions

- get_content_packages, [41](#)
- get_packages, [53](#)

* schedule functions

- get_timezones, [59](#)
- get_variant_schedule, [67](#)
- set_schedule, [90](#)

* server management functions

- delete_runtime_cache, [26](#)
- get_runtime_caches, [56](#)

* thumbnail functions

- delete_thumbnail, [27](#)
- get_thumbnail, [58](#)
- has_thumbnail, [69](#)
- set_thumbnail, [93](#)

* variant functions

- get_variant_renderings, 66
 - get_variants, 66
- audit_access_open, 4, 4, 5, 102
- audit_r_versions, 4, 5, 102
- audit_runas, 4, 4, 5, 102
- browse_api_docs (browse_solo), 5
 - browse_connect (browse_solo), 5
 - browse_dashboard (browse_solo), 5
 - browse_solo, 5
- Bundle, 6, 16, 17, 33, 87, 97, 102, 106, 108, 110
- bundle_dir, 7, 8, 9, 29, 31, 72
- bundle_path, 7, 7, 9, 29, 31, 72
- bundle_static, 7, 8, 8, 29, 31, 72
- Connect (PositConnect), 73
- connect, 9
- connectapi::Content, 16, 32, 101, 103, 106, 109
- connectapi::Variant, 106, 109
- Content, 6, 10, 17, 24, 33, 87, 97, 102, 106, 108, 110
- content_add_group (permissions), 71
- content_add_user (permissions), 71
- content_delete, 18, 19, 22–25, 27, 28, 31, 38, 42, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93–96, 99, 110
- content_delete_group (permissions), 71
- content_delete_user (permissions), 71
- content_item, 18, 18, 22–25, 27, 28, 31, 38, 42, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93–96, 99, 110
- content_list_by_tag, 19
- content_list_guid_has_access (content_list_with_permissions), 20
- content_list_with_permissions, 20
- content_render, 21
- content_restart, 21
- content_title, 18, 19, 22, 23–25, 27, 28, 31, 38, 42, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93–96, 99, 110
- content_update, 18, 19, 22, 23, 24, 25, 27, 28, 31, 38, 42, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93–96, 99, 110
- content_update_access_type (content_update), 23
- content_update_owner (content_update), 23
- ContentTask, 6, 16, 16, 33, 87, 97, 102, 106, 108, 110
- create_random_name, 18, 19, 22, 23, 24, 25, 27, 28, 31, 38, 42, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93–96, 99, 110
- create_tag (get_tags), 56
- create_tag_tree (get_tags), 56
- dashboard_url, 18, 19, 22–24, 24, 25, 27, 28, 31, 38, 42, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93–96, 99, 110
 - dashboard_url_chr, 18, 19, 22–25, 25, 27, 28, 31, 38, 42, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93–96, 99, 110
- delete_bundle (get_bundles), 37
- delete_image (get_image), 46
- delete_runtime_cache, 26, 56
- delete_runtime_cache(), 56
- delete_tag (get_tags), 56
- delete_thumbnail, 18, 19, 22–25, 27, 28, 31, 38, 42, 46, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93–96, 99, 110
- delete_vanity_url, 18, 19, 22–25, 27, 28, 31, 38, 42, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93–96, 99, 110
- deploy, 7–9, 28, 31, 72
- deploy_current (deploy), 28
- deploy_repo, 18, 19, 22–25, 27, 28, 30, 38, 42, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93–96, 99, 110
- deploy_repo_enable (deploy_repo), 30
- deploy_repo_update (deploy_repo), 30
- download_bundle, 7–9, 29, 31, 72
- Environment, 6, 16, 17, 32, 87, 97, 102, 106, 108, 110
- filter_tag_tree_chr (get_tags), 56
- filter_tag_tree_id (get_tags), 56
- get_audit_logs, 33
- get_aws_content_credentials, 35
- get_aws_credentials, 36
- get_bundles, 18, 19, 22–25, 27, 28, 31, 37, 42, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93–96, 99, 110
- get_content, 38

- `get_content()`, 4, 5
- `get_content_packages`, 41, 54
- `get_content_permissions` (permissions), 71
- `get_content_tags` (get_tags), 56
- `get_environment`, 18, 19, 22–25, 27, 28, 31, 38, 42, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93–96, 99, 110
- `get_group_content`, 43, 44, 46
- `get_group_members`, 43, 44, 45
- `get_group_permission` (permissions), 71
- `get_groups`, 43, 44, 46
- `get_image`, 18, 19, 22–25, 27, 28, 31, 38, 42, 46, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93–96, 99, 110
- `get_job`, 18, 19, 22–25, 27, 28, 31, 38, 42, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93–96, 99, 110
- `get_job_list` (get_jobs), 48
- `get_jobs`, 18, 19, 22–25, 27, 28, 31, 38, 42, 47, 48, 50, 58, 65, 68, 70, 72, 88, 89, 93–96, 99, 110
- `get_log`, 18, 19, 22–25, 27, 28, 31, 38, 42, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93–96, 99, 110
- `get_my_permission` (permissions), 71
- `get_oauth_content_credentials`, 51
- `get_oauth_credentials`, 52
- `get_packages`, 41, 53
- `get_procs`, 54
- `get_runtime_caches`, 26, 56
- `get_runtime_caches()`, 26
- `get_runtimes`, 55
- `get_tag_data` (get_tags), 56
- `get_tags`, 56
- `get_thumbnail`, 18, 19, 22–25, 27, 28, 31, 38, 42, 46, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93–96, 99, 110
- `get_timezones`, 59, 67, 92
- `get_usage_shiny`, 59
- `get_usage_static`, 61
- `get_user_permission` (permissions), 71
- `get_users`, 63
- `get_vanity_url`, 18, 19, 22–25, 27, 28, 31, 38, 42, 47, 49, 50, 58, 64, 68, 70, 72, 88, 89, 93–96, 99, 110
- `get_vanity_urls`, 65
- `get_variant` (get_variants), 66
- `get_variant_default` (get_variants), 66
- `get_variant_renderings`, 66, 66
- `get_variant_schedule`, 59, 67, 92
- `get_variants`, 66, 67
- `git`, 18, 19, 22–25, 27, 28, 31, 38, 42, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93–96, 99, 110
- `groups_create_remote`, 69
- `has_image` (get_image), 46
- `has_thumbnail`, 18, 19, 22–25, 27, 28, 31, 38, 42, 46, 47, 49, 50, 58, 65, 68, 69, 72, 88, 89, 93–96, 99, 110
- `logical`, 92
- `page_cursor`, 70
- `page_offset` (page_cursor), 70
- `permissions`, 18, 19, 22–25, 27, 28, 31, 38, 42, 47, 49, 50, 58, 65, 68, 70, 71, 88, 89, 93–96, 99, 110
- `poll_task`, 7–9, 29, 31, 72
- `PositConnect`, 6, 16, 17, 33, 73, 97, 102, 106, 108, 110
- `promote`, 87
- `repo_check_account` (git), 68
- `repo_check_branches` (git), 68
- `repo_check_branches_ref` (git), 68
- `repo_check_manifest_dirs` (git), 68
- `schedule_describe` (set_schedule), 90
- `set_content_tag_tree` (get_tags), 56
- `set_content_tags` (get_tags), 56
- `set_environment_all` (get_environment), 42
- `set_environment_new` (get_environment), 42
- `set_environment_remove` (get_environment), 42
- `set_image_path`, 18, 19, 22–25, 27, 28, 31, 38, 42, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93–96, 99, 110
- `set_image_url` (set_image_path), 88
- `set_image_webshot` (set_image_path), 88
- `set_run_as`, 18, 19, 22–25, 27, 28, 31, 38, 42, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93–96, 99, 110
- `set_schedule`, 59, 67, 90

- set_schedule_day (set_schedule), 90
- set_schedule_dayofmonth (set_schedule), 90
- set_schedule_dayofweek (set_schedule), 90
- set_schedule_dayweekofmonth (set_schedule), 90
- set_schedule_hour (set_schedule), 90
- set_schedule_minute (set_schedule), 90
- set_schedule_remove (set_schedule), 90
- set_schedule_semimonth (set_schedule), 90
- set_schedule_week (set_schedule), 90
- set_schedule_weekday (set_schedule), 90
- set_schedule_year (set_schedule), 90
- set_thumbnail, 18, 19, 22–25, 27, 28, 31, 38, 42, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93, 94–96, 99, 110
- set_vanity_url, 18, 19, 22–25, 27, 28, 31, 38, 42, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93, 94, 95, 96, 99, 110
- swap_vanity_url, 18, 19, 22–25, 27, 28, 31, 38, 42, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93, 94, 95, 96, 99, 110
- swap_vanity_urls, 18, 19, 22–25, 27, 28, 31, 38, 42, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93–95, 95, 99, 110
- Task, 6, 16, 17, 33, 87, 96, 102, 106, 108, 110
- tbl_connect, 98
- terminate_jobs, 18, 19, 22–25, 27, 28, 31, 38, 42, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93–96, 98, 110
- user_guid_from_username, 100
- users_create_remote, 99
- Vanity, 6, 16, 17, 33, 87, 97, 101, 106, 108, 110
- vanity_is_available, 4, 5, 102
- Variant, 6, 16, 17, 33, 87, 97, 102, 103, 108, 110
- variant_render (get_variant_renderings), 66
- VariantSchedule, 6, 16, 17, 33, 87, 97, 102, 106, 106, 110
- VariantTask, 6, 16, 17, 21, 33, 87, 97, 102, 106, 108, 108
- verify_content_name, 18, 19, 22–25, 27, 28, 31, 38, 42, 47, 49, 50, 58, 65, 68, 70, 72, 88, 89, 93–96, 99, 110
- webshot2::webshot(), 88