

Package ‘contingencytables’

July 22, 2025

Title Statistical Analysis of Contingency Tables

Version 3.0.1

Description Provides functions to perform statistical inference of data organized in contingency tables. This package is a companion to the ``Statistical Analysis of Contingency Tables'' book by Fagerland et al. <ISBN 9781466588172>.

License GPL-3

Encoding UTF-8

RoxygenNote 7.3.2

URL <https://contingencytables.com/>

<https://ocbe-uio.github.io/contingencytables/>

BugReports <https://github.com/ocbe-uio/contingencytables/issues>

Imports MASS, boot, methods

Suggests testthat

Date 2024-08-28

NeedsCompilation no

Author Morten Wang Fagerland [aut],

Stian Lydersen [ctb],

Petter Laake [ctb],

Waldir Leoncio [cre],

Ole Christian Lingjærde [trl],

Brad J. Biggerstaff [ctb]

Maintainer Waldir Leoncio <w.l.netto@medisin.uio.no>

Repository CRAN

Date/Publication 2024-08-29 05:50:01 UTC

Contents

.onAttach	6
Adjusted_inv_sinh_CI_OR_2x2	6
Adjusted_inv_sinh_CI_ratio_2x2	7

Adjusted_log_CI_2x2	8
AgrestiCaffo_CI_2x2	9
AgrestiCoull_CI_1x2	9
Arcsine_CI_1x2	10
BaptistaPike_exact_conditional_CI_2x2	11
BaptistaPike_midP_CI_2x2	12
bentur_2009	12
Bhapkar_test_paired_cxc	13
Blaker_exact_CI_1x2	13
Blaker_exact_test_1x2	14
Blaker_midP_CI_1x2	15
Blaker_midP_test_1x2	16
BonettPrice_hybrid_Wilson_score_CI_CC_paired_2x2	16
BonettPrice_hybrid_Wilson_score_CI_paired_2x2	17
Bonferroni_type_CIs_paired_cxc	18
Bonferroni_type_CIs_rxc	18
Brant_test_2xc	19
BreslowDay_homogeneity_test_stratified_2x2	20
calculate_limit_lower	20
calculate_limit_upper	21
calc_prob	21
calc_Pvalue_4x2	22
calc_Pvalue_5x2	22
cavo_2012	23
Chacko_test_1xc	23
chap1	24
chap10	24
chap2	25
chap3	26
chap4	27
chap5	28
chap6	29
chap7	30
chap8	31
chap9	32
ClopperPearson_exact_CI_1x2	33
ClopperPearson_exact_CI_1x2_beta_version	33
ClopperPearson_midP_CI_1x2	34
CochranArmitage_CI_rx2	35
CochranArmitage_exact_cond_midP_tests_rx2	36
CochranArmitage_MH_tests_rx2	36
CochranMantelHaenszel_test_stratified_2x2	37
Cochran_Q_test_stratified_2x2	38
contingencytables	38
contingencytables_result	39
Cornfield_exact_conditional_CI_2x2	40
Cornfield_midP_CI_2x2	41
Cumulative_models_for_2xc	41

Cumulative_models_for_rxc	42
doll_hill_1950	43
Exact_binomial_test_1x2	43
Exact_cond_midP_linear_rank_tests_2xc	44
Exact_cond_midP_tests_rxc	45
Exact_cond_midP_unspecific_ordering_rx2	45
Exact_multinomial_test_1xc	46
Exact_unconditional_test_2x2	47
ezra_2010	48
fischer_1999	48
FisherFreemanHalton_asymptotic_test_rxc	49
Fisher_exact_test_2x2	49
Fisher_midP_test_2x2	50
FleissEveritt_test_paired_cxc	51
FleissLevinPaik_test_paired_cxc	51
fleiss_2003	52
fontanella_2008	52
gamma_coefficient_rxc	53
gamma_coefficient_rxc_bca	53
Gart_adjusted_logit_CI_2x2	54
Gold_Wald_CIs_1xc	55
Goodman_Wald_CIs_1xc	55
Goodman_Wald_CIs_for_diffs_1xc	56
Goodman_Wilson_score_CIs_1xc	57
hine_1989	57
hypothetical	58
Independence_smoothed_logit_CI_2x2	58
indredavik_2008	59
InverseVariance_estimate_stratified_2x2	59
Inv_sinh_CI_OR_2x2	60
Inv_sinh_CI_ratio_2x2	60
Jeffreys_CI_1x2	61
JonckheereTerpstra_test_rxc	62
Katz_log_CI_2x2	62
Kendalls_tau_b_rxc	63
Kendalls_tau_b_rxc_bca	64
Koopman_asymptotic_score_CI_2x2	64
KruskalWallis_asymptotic_test_rxc	65
lampasona_2013	66
ligarden_2010	66
linear_by_linear_test_rxc	67
list_functions	67
LR_CI_1x2	68
LR_test_1x2	69
LR_test_1xc	69
LR_test_2x2	70
lydersen_2012a	71
MantelHaenszel_estimate_stratified_2x2	71

MantelHaenszel_test_2xc	72
McNemarBowker_test_paired_cxc	72
McNemar_asymptotic_test_CC_paired_2x2	73
McNemar_asymptotic_test_paired_2x2	74
McNemar_exact_cond_test_paired_2x2	74
McNemar_exact_unconditional_test_paired_2x2	75
McNemar_midP_test_paired_2x2	76
Mee_asymptotic_score_CI_2x2	77
MidP_binomial_test_1x2	77
MidP_multinomial_test_1xc	78
MiettinenNurminen_asymptotic_score_CI_difference_2x2	79
MiettinenNurminen_asymptotic_score_CI_OR_2x2	80
MiettinenNurminen_asymptotic_score_CI_ratio_2x2	80
mills_graubard_1987	81
ML_estimates	82
ML_estimates_and_CIs_stratified_2x2	82
MOVER_R_Wilson_CI_OR_2x2	83
MOVER_R_Wilson_CI_ratio_2x2	84
MOVER_Wilson_score_CI_paired_2x2	84
Newcombe_hybrid_score_CI_2x2	85
Newcombe_square_and_add_CI_paired_2x2	86
Pearson_chi_squared_test_1xc	86
Pearson_chi_squared_test_2x2	87
Pearson_chi_squared_test_CC_2x2	88
Pearson_correlation_coefficient_rxc	89
Pearson_correlation_coefficient_rxc_bca	90
Pearson_LR_homogeneity_test_stratified_2x2	91
Pearson_LR_tests_cum_OR_2xc	91
Pearson_LR_tests_rxc	92
Pearson_LR_tests_unspecific_ordering_rx2	93
Pearson_LR_test_common_effect_stratified_2x2	94
Pearson_residuals_rxc	95
perondi_2004	95
peterson_2007	96
Peto_homogeneity_test_stratified_2x2	96
Peto_OR_estimate_stratified_2x2	97
PriceBonett_approximate_Bayes_CI_2x2	97
print.contingencytables_result	98
QuesenberryHurst_Wilson_score_CIs_1xc	99
RBG_test_and_CI_stratified_2x2	99
ritland_2007	100
Scheffe_type_CIs_paired_cxc	101
Scheffe_type_CIs_rxc	101
Score_test_1x2	102
Score_test_and_CI_marginal_mean_scores_paired_cxc	103
Score_test_CC_1x2	103
Score_test_for_effect_in_the_probit_model_2xc	104
score_test_statistic	105

singh_2010_1	105
snp6498169	106
Spearman_correlation_coefficient_rxc	106
Spearman_correlation_coefficient_rxc_bca	107
stratified_2x2_tables	108
Stuart_test_paired_cxc	108
table_7.3	109
table_7.4	109
table_7.5	110
table_7.6	111
table_7.7	111
table_7.8	112
table_7.9	113
Tango_asymptotic_score_CI_paired_2x2	113
Tang_asymptotic_score_CI_paired_2x2	114
tea	115
the_1x2_table_CIs	115
the_1x2_table_tests	116
the_1xc_table_CIs	117
the_1xc_table_tests	117
the_2x2_table_CIs_difference	118
the_2x2_table_CIs_OR	119
the_2x2_table_CIs_ratio	119
the_2x2_table_tests	120
the_2xc_table	121
the_paired_2x2_table_CIs_difference	122
the_paired_2x2_table_CIs_OR	122
the_paired_2x2_table_CIs_ratio	123
the_paired_2x2_table_tests	124
the_paired_cxc_table_nominal	124
the_paired_cxc_table_ordinal	125
the_rx2_table	126
the_rxc_table	126
Transformed_Blaker_exact_CI_paired_2x2	127
Transformed_Clopper_Pearson_exact_CI_paired_2x2	128
Transformed_Clopper_Pearson_midP_CI_paired_2x2	129
Transformed_Wilson_score_CI_paired_2x2	129
Trend_estimate_CI_tests_rx2	130
Uncorrected_asymptotic_score_CI_2x2	131
validateArguments	132
Wald_CI_1x2	133
Wald_CI_2x2	133
Wald_CI_AgrestiMin_paired_2x2	134
Wald_CI_BonettPrice_paired_2x2	135
Wald_CI_CC_1x2	135
Wald_CI_CC_2x2	136
Wald_CI_diff_CC_paired_2x2	137
Wald_CI_diff_paired_2x2	138

Wald_CI_OR_Laplace_paired_2x2 138

Wald_CI_OR_paired_2x2 139

Wald_CI_ratio_paired_2x2 140

Wald_test_1x2 140

Wald_test_and_CI_common_diff_stratified_2x2 141

Wald_test_and_CI_common_ratio_stratified_2x2 142

Wald_test_and_CI_marginal_mean_ranks_paired_cxc 143

Wald_test_and_CI_marginal_mean_scores_paired_cxc 144

Wald_test_CC_1x2 144

Wilson_score_CI_1x2 145

Wilson_score_CI_CC_1x2 146

Woolf_logit_CI_2x2 147

Woolf_test_and_CI_stratified_2x2 148

Z_unpooled_test_2x2 148

Index 150

.onAttach	<i>Prints welcome message on package load</i>
-----------	---

Description

Prints package version number and welcome message on package load

Usage

.onAttach(libname, pkgname)

Arguments

libname	library location. See ?base::.onAttach for details
pkgname	package name. See ?base::.onAttach for details

Adjusted_inv_sinh_CI_OR_2x2	<i>The adjusted inverse hyperbolic sine confidence interval for the odds ratio</i>
-----------------------------	--

Description

The adjusted inverse hyperbolic sine confidence interval for the odds ratio.
Described in Chapter 4 "The 2x2 Table"

Usage

Adjusted_inv_sinh_CI_OR_2x2(n, psi1 = 0.45, psi2 = 0.25, alpha = 0.05)

Arguments

n	the observed counts (a 2x2 matrix)
psi1	pseudo-frequency (should be > 0)
psi2	pseudo-frequency (should be > 0)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Adjusted_inv_sinh_CI_OR_2x2(lampasona_2013)
Adjusted_inv_sinh_CI_OR_2x2(ritland_2007)
```

Adjusted_inv_sinh_CI_ratio_2x2

The adjusted inverse hyperbolic sine confidence interval for the ratio of probabilities

Description

The adjusted inverse hyperbolic sine confidence interval for the ratio of probabilities
Described in Chapter 4 "The 2x2 Table"

Usage

```
Adjusted_inv_sinh_CI_ratio_2x2(
  n,
  psi1 = 0,
  psi2 = 0,
  psi3 = 0,
  psi4 = 1,
  alpha = 0.05
)
```

Arguments

n	the observed counts (a 2x2 matrix)
psi1	pseudo-frequency
psi2	pseudo-frequency
psi3	pseudo-frequency
psi4	pseudo-frequency
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Adjusted_inv_sinh_CI_ratio_2x2(perondi_2004)
Adjusted_inv_sinh_CI_ratio_2x2(ritland_2007)
```

Adjusted_log_CI_2x2	<i>The adjusted log confidence interval for the ratio of probabilities</i>
---------------------	--

Description

The adjusted log confidence interval for the ratio of probabilities

Described in Chapter 4 "The 2x2 Table"

Usage

```
Adjusted_log_CI_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Adjusted_log_CI_2x2(perondi_2004)
Adjusted_log_CI_2x2(ritland_2007)
```

AgrestiCaffo_CI_2x2	<i>The Agresti-Caffo confidence interval for the difference between probabilities</i>
---------------------	---

Description

The Agresti-Caffo confidence interval for the difference between probabilities
Described in Chapter 4 "The 2x2 Table"

Usage

```
AgrestiCaffo_CI_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
AgrestiCaffo_CI_2x2(perondi_2004)
AgrestiCaffo_CI_2x2(ritland_2007)
```

AgrestiCoull_CI_1x2	<i>The Agresti-Coull confidence interval for the binomial probability</i>
---------------------	---

Description

Described in Chapter 2 "The 1x2 Table and the Binomial Distribution"

Usage

```
AgrestiCoull_CI_1x2(X, n, alpha = 0.05)
```

Arguments

X	the number of successes
n	the total number of observations
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

References

Agresti A, Coull BA (1998) Approximate is better than "exact" for interval estimation of binomial proportions. *The American Statistician*; 52:119-126

See Also

Wald_CI_1x2

Examples

```
AgrestiCoull_CI_1x2(singh_2010["1st", "X"], singh_2010["1st", "n"])
AgrestiCoull_CI_1x2(singh_2010["2nd", "X"], singh_2010["2nd", "n"])
AgrestiCoull_CI_1x2(singh_2010["3rd", "X"], singh_2010["3rd", "n"])
with(singh_2010["4th", ], AgrestiCoull_CI_1x2(X, n)) # alternative syntax
AgrestiCoull_CI_1x2(ligarden_2010["X"], ligarden_2010["n"])
```

Arcsine_CI_1x2

Arcsine confidence interval

Description

The Arcsine confidence interval for the binomial probability (with Anscombe variance stabilizing transformation) Described in Chapter 2 "The 1x2 Table and the Binomial Distribution"

Usage

```
Arcsine_CI_1x2(X, n, alpha = 0.05)
```

Arguments

X	the number of successes
n	the total number of observations
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

References

Anscombe FJ (1948) The transformation of Poisson, binomial and negative binomial data. *Biometrika*; 35:246-254

Examples

```

Arcsine_CI_1x2(singh_2010["1st", "X"], singh_2010["1st", "n"])
Arcsine_CI_1x2(singh_2010["2nd", "X"], singh_2010["2nd", "n"])
Arcsine_CI_1x2(singh_2010["3rd", "X"], singh_2010["3rd", "n"])
with(singh_2010["4th", ], Arcsine_CI_1x2(X, n)) # alternative syntax
Arcsine_CI_1x2(ligarden_2010["X"], ligarden_2010["n"])

```

BaptistaPike_exact_conditional_CI_2x2

The Baptista-Pike exact conditional confidence interval for the odds ratio

Description

The Baptista-Pike exact conditional confidence interval for the odds ratio

Described in Chapter 4 "The 2x2 Table"

Usage

```
BaptistaPike_exact_conditional_CI_2x2(n, alpha = 0.05)
```

Arguments

n	the observed table (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```

BaptistaPike_exact_conditional_CI_2x2(tea)
BaptistaPike_exact_conditional_CI_2x2(perondi_2004)
BaptistaPike_exact_conditional_CI_2x2(lampasona_2013)
BaptistaPike_exact_conditional_CI_2x2(ritland_2007)

```

BaptistaPike_midP_CI_2x2

The Baptista-Pike mid-P confidence interval for the odds ratio

Description

The Baptista-Pike mid-P confidence interval for the odds ratio

Described in Chapter 4 "The 2x2 Table"

Usage

```
BaptistaPike_midP_CI_2x2(n, alpha = 0.05)
```

Arguments

n	the observed table (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
BaptistaPike_midP_CI_2x2(tea)
BaptistaPike_midP_CI_2x2(perondi_2004)
BaptistaPike_midP_CI_2x2(lampasona_2013)
BaptistaPike_midP_CI_2x2(ritland_2007)
```

bentur_2009

Airway hyper-responsiveness before and after stem cell transplantation

Description

Airway hyper-responsiveness before and after stem cell transplantation

Usage

```
bentur_2009
```

Format

An object of class `matrix` (inherits from `array`) with 2 rows and 2 columns.

References

Bentur et al. (2009)

Bhapkar_test_paired_cxc

The Bhapkar test for marginal homogeneity

Description

The Bhapkar test for marginal homogeneity

Described in Chapter 9 "The Paired cxc Table"

Usage

Bhapkar_test_paired_cxc(n)

Arguments

n the observed table (a cxc matrix)

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Bhapkar_test_paired_cxc(peterson_2007)
```

Blaker_exact_CI_1x2

The Blaker exact confidence interval

Description

The Blaker exact confidence interval for the binomial probability Described in Chapter 2 "The 1x2 Table and the Binomial Distribution"

Usage

```
Blaker_exact_CI_1x2(X, n, alpha = 0.05)
```

Arguments

X the number of successes
 n the total number of observations
 alpha the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

References

Blaker H (2000) Confidence curves and improved exact confidence intervals for discrete distributions. The Canadian Journal of Statistics; 28:783-798

Examples

```
Blaker_exact_CI_1x2(singh_2010["1st", "X"], singh_2010["1st", "n"])
Blaker_exact_CI_1x2(singh_2010["2nd", "X"], singh_2010["2nd", "n"])
Blaker_exact_CI_1x2(singh_2010["3rd", "X"], singh_2010["3rd", "n"])
with(singh_2010["4th", ], Blaker_exact_CI_1x2(X, n)) # alternative syntax
Blaker_exact_CI_1x2(ligarden_2010["X"], ligarden_2010["n"])
```

Blaker_exact_test_1x2 *The Blaker exact test*

Description

The Blaker exact test for the binomial probability (π) $H_0: \pi = \pi_0$ vs $H_A: \pi \neq \pi_0$ (two-sided)
Described in Chapter 2 "The 1x2 Table and the Binomial Distribution"

Usage

```
Blaker_exact_test_1x2(X, n, pi0)
```

Arguments

X	the number of successes
n	the total number of observations
pi0	a given probability

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

References

Blaker H (2000) Confidence curves and improved exact confidence intervals for discrete distributions. The Canadian Journal of Statistics; 28:783-798

Examples

```
Blaker_exact_test_1x2(singh_2010["1st", "X"], singh_2010["1st", "n"], pi0 = 0.513)
Blaker_exact_test_1x2(singh_2010["2nd", "X"], singh_2010["2nd", "n"], pi0 = 0.513)
Blaker_exact_test_1x2(singh_2010["3rd", "X"], singh_2010["3rd", "n"], pi0 = 0.513)
Blaker_exact_test_1x2(singh_2010["4th", "X"], singh_2010["4th", "n"], pi0 = 0.513)
Blaker_exact_test_1x2(ligarden_2010["X"], ligarden_2010["n"], pi0 = 0.5)
```

Blaker_midP_CI_1x2	<i>The Blaker mid-P confidence interval for the binomial probability</i>
--------------------	--

Description

The Blaker mid-P confidence interval for the binomial probability Described in Chapter 2 "The 1x2 Table and the Binomial Distribution"

Usage

```
Blaker_midP_CI_1x2(X, n, alpha = 0.05)
```

Arguments

X	the number of successes
n	the total number of observations
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

References

Blaker H (2000) Confidence curves and improved exact confidence intervals for discrete distributions. The Canadian Journal of Statistics; 28:783-798

Examples

```
Blaker_midP_CI_1x2(singh_2010["1st", "X"], singh_2010["1st", "n"])
Blaker_midP_CI_1x2(singh_2010["2nd", "X"], singh_2010["2nd", "n"])
Blaker_midP_CI_1x2(singh_2010["3rd", "X"], singh_2010["3rd", "n"])
with(singh_2010["4th", ], Blaker_midP_CI_1x2(X, n)) # alternative syntax
Blaker_midP_CI_1x2(ligarden_2010["X"], ligarden_2010["n"])
```

Blaker_midP_test_1x2 *The Blaker mid-P test*

Description

The Blaker mid-P test for the binomial probability (π) $H_0: \pi = \pi_0$ vs $H_A: \pi \neq \pi_0$ (two-sided)
Described in Chapter 2 "The 1x2 Table and the Binomial Distribution"

Usage

```
Blaker_midP_test_1x2(X, n, pi0)
```

Arguments

X	the number of successes
n	the total number of observations
pi0	a given probability

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

References

Blaker H (2000) Confidence curves and improved exact confidence intervals for discrete distributions. The Canadian Journal of Statistics; 28:783-798

Examples

```
Blaker_midP_test_1x2(singh_2010["1st", "X"], singh_2010["1st", "n"], pi0 = 0.513)
Blaker_midP_test_1x2(singh_2010["2nd", "X"], singh_2010["2nd", "n"], pi0 = 0.513)
Blaker_midP_test_1x2(singh_2010["3rd", "X"], singh_2010["3rd", "n"], pi0 = 0.513)
Blaker_midP_test_1x2(singh_2010["4th", "X"], singh_2010["4th", "n"], pi0 = 0.513)
Blaker_midP_test_1x2(ligarden_2010["X"], ligarden_2010["n"], pi0 = 0.5)
```

BonettPrice_hybrid_Wilson_score_CI_CC_paired_2x2

The Bonett-Price hybrid Wilson score confidence interval for the ratio of paired probabilities

Description

The Bonett-Price hybrid Wilson score confidence interval for the ratio of paired probabilities with continuity correction

Described in Chapter 8 "The Paired 2x2 Table"

Usage

```
BonettPrice_hybrid_Wilson_score_CI_CC_paired_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
BonettPrice_hybrid_Wilson_score_CI_CC_paired_2x2(bentur_2009)
BonettPrice_hybrid_Wilson_score_CI_CC_paired_2x2(cavo_2012)
```

BonettPrice_hybrid_Wilson_score_CI_paired_2x2

The Bonett-Price hybrid Wilson score confidence interval for the ratio of paired probabilities

Description

The Bonett-Price hybrid Wilson score confidence interval for the ratio of paired probabilities
Described in Chapter 8 "The Paired 2x2 Table"

Usage

```
BonettPrice_hybrid_Wilson_score_CI_paired_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
BonettPrice_hybrid_Wilson_score_CI_paired_2x2(bentur_2009)
BonettPrice_hybrid_Wilson_score_CI_paired_2x2(cavo_2012)
```

Bonferroni_type_CIs_paired_cxc

Bonferroni-type confidence intervals for differences of marginal probabilities

Description

Bonferroni-type confidence intervals for differences of marginal probabilities

Described in Chapter 9 "The Paired kxk Table"

Usage

```
Bonferroni_type_CIs_paired_cxc(n, alpha = 0.05)
```

Arguments

n	the observed table (a cxc matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Bonferroni_type_CIs_paired_cxc(peterson_2007)
```

Bonferroni_type_CIs_rxc

The Bonferroni-type simultaneous confidence intervals for the differences $\pi_{1li} - \pi_{1lj}$

Description

The Bonferroni-type simultaneous confidence intervals for the differences $\pi_{1li} - \pi_{1lj}$

Described in Chapter 7 "The rxc Table"

Usage

```
Bonferroni_type_CIs_rxc(n, alpha = 0.05)
```

Arguments

n	the observed counts (an rx2 vector)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Bonferroni_type_CIs_rxc(table_7.3)
```

 Brant_test_2xc

The Brant test for the proportional odds assumption

Description

The Brant test for the proportional odds assumption

Described in Chapter 6 "The Ordered 2xc Table"

Usage

```
Brant_test_2xc(n)
```

Arguments

n the observed table (a 2xc matrix)

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Brant_test_2xc(fontanella_2008)
Brant_test_2xc(lydersen_2012a)
```

```
BreslowDay_homogeneity_test_stratified_2x2
```

The Breslow-Day test of homogeneity of odds ratios over strata

Description

The Breslow-Day test of homogeneity of odds ratios over strata with Tarone correction
Described in Chapter 10 "Stratified 2x2 Tables and Meta-Analysis"

Usage

```
BreslowDay_homogeneity_test_stratified_2x2(n)
```

Arguments

`n` the observed table (a 2x2xk matrix, where k is the number of strata)

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
BreslowDay_homogeneity_test_stratified_2x2(doll_hill_1950)
BreslowDay_homogeneity_test_stratified_2x2(hine_1989)
```

```
calculate_limit_lower Calculate the lower limit of a confidence interval
```

Description

Calculate the lower limit of a confidence interval

Usage

```
calculate_limit_lower(...)
```

Arguments

`...` arguments passed to methods

Note

This function has little use to the user, it is exported so that it can be used by `stats::uniroot()`.

calculate_limit_upper	<i>Calculate the upper limit of a confidence interval</i>
-----------------------	---

Description

Calculate the upper limit of a confidence interval

Usage

```
calculate_limit_upper(...)
```

Arguments

... arguments passed to methods

Note

This function has little use to the user, it is exported so that it can be used by `stats::uniroot()`.

calc_prob	<i>Calculate probability</i>
-----------	------------------------------

Description

Calculate probability

Usage

```
calc_prob(...)
```

Arguments

... arguments passed to methods

Note

This function has little use to the user, it is exported for conformity to R package standards.

calc_Pvalue_4x2	<i>Calculate probability</i>
-----------------	------------------------------

Description

Calculate probability

Usage

```
calc_Pvalue_4x2(...)
```

Arguments

... arguments passed to methods

Note

This function has little use to the user, it is exported for conformity to R package standards.

calc_Pvalue_5x2	<i>Calculate probability</i>
-----------------	------------------------------

Description

Calculate probability

Usage

```
calc_Pvalue_5x2(...)
```

Arguments

... arguments passed to methods

Note

This function has little use to the user, it is exported for conformity to R package standards.

cavo_2012

Complete response before and after consolidation therapy

Description

Complete response before and after consolidation therapy

Usage

cavo_2012

Format

An object of class `matrix` (inherits from `array`) with 2 rows and 2 columns.

References

Cavo et al. (2012)

Chacko_test_1xc

The Chacko test for order-restriction

Description

Described in Chapter 3, "The 1xc Table and the Multinomial Distribution", Chacko (1966) derived a test based on the Pearson chi-square statistic to test the hypothesis that the categories of a multinomial variable with c possible outcomes have a natural ordering. The test statistic is asymptotically chi-squared distributed.

Usage

Chacko_test_1xc(n)

Arguments

`n` the observed counts (a 1xc vector, where c is the number of categories)

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

References

Chacko, V. J. (1966). Modified chi-square test for ordered alternatives. *Sankhyā: The Indian Journal of Statistics, Series B*, 185-190.

Fagerland MW, Lydersen S, Laake P (2017) *Statistical Analysis of Contingency Tables*. Chapman & Hall/CRC, Boca Raton, FL.

Examples

```
Chacko_test_1xc(hypothetical)
```

chap1

Chapter 1: Introduction

Description

There are no functions for Chapter 1 (Introduction), only from Chapters 2 to 10.

References

- Fagerland MW, Lydersen S, Laake P (2017) *Statistical Analysis of Contingency Tables*. Chapman & Hall/CRC, Boca Raton, FL
- <https://contingencytables.com/>
- <https://www.routledge.com/Statistical-Analysis-of-Contingency-Tables/Fagerland-Lydersen-Laake/p/book/978146658>

chap10

Chapter 10: Stratified 2x2 Tables and Meta-Analysis

Description

These are the functions related to chapter 10:

1. BreslowDay_homogeneity_test_stratified_2x2
2. CochranMantelHaenszel_test_stratified_2x2
3. Cochran_Q_test_stratified_2x2
4. InverseVariance_estimate_stratified_2x2
5. ML_estimates_and_CIs_stratified_2x2
6. MantelHaenszel_estimate_stratified_2x2
7. Pearson_LR_homogeneity_test_stratified_2x2
8. Pearson_LR_test_common_effect_stratified_2x2
9. Peto_homogeneity_test_stratified_2x2
10. Peto_OR_estimate_stratified_2x2

11. RBG_test_and_CI_stratified_2x2
12. Wald_test_and_CI_common_diff_stratified_2x2
13. Wald_test_and_CI_common_ratio_stratified_2x2
14. Woolf_test_and_CI_stratified_2x2
15. stratified_2x2_tables

Note

You can also print the list above with `list_functions(10)`.

References

- Fagerland MW, Lydersen S, Laake P (2017) Statistical Analysis of Contingency Tables. Chapman & Hall/CRC, Boca Raton, FL
- <https://contingencytables.com/>
- <https://www.routledge.com/Statistical-Analysis-of-Contingency-Tables/Fagerland-Lydersen-Laake/p/book/978146658>

Description

These are the functions related to chapter 2:

1. AgrestiCoull_CI_1x2
2. Arcsine_CI_1x2
3. Wald_CI_1x2
4. Blaker_exact_CI_1x2
5. Blaker_exact_test_1x2
6. Blaker_midP_CI_1x2
7. Blaker_midP_test_1x2
8. ClopperPearson_exact_CI_1x2
9. ClopperPearson_midP_CI_1x2
10. Exact_binomial_test_1x2
11. Jeffreys_CI_1x2
12. LR_CI_1x2
13. LR_test_1x2
14. MidP_binomial_test_1x2
15. Score_test_1x2
16. Score_test_CC_1x2
17. Wald_CI_CC_1x2

18. Wilson_score_CI_1x2
19. Wilson_score_CI_CC_1x2
20. the_1x2_table_CIs
21. Wald_test_1x2
22. Wald_test_CC_1x2
23. the_1x2_table_tests

Note

You can also print the list above with `list_functions(2)`.

References

- Fagerland MW, Lydersen S, Laake P (2017) Statistical Analysis of Contingency Tables. Chapman & Hall/CRC, Boca Raton, FL
- <https://contingencytables.com/>
- <https://www.routledge.com/Statistical-Analysis-of-Contingency-Tables/Fagerland-Lydersen-Laake/p/book/978146658>

Description

These are the functions related to chapter 3:

1. Chacko_test_1xc
2. Exact_multinomial_test_1xc
3. Gold_Wald_CIs_1xc
4. Goodman_Wald_CIs_1xc
5. Goodman_Wald_CIs_for_diffs_1xc
6. Goodman_Wilson_score_CIs_1xc
7. LR_test_1xc
8. MidP_multinomial_test_1xc
9. Pearson_chi_squared_test_1xc
10. QuesenberryHurst_Wilson_score_CIs_1xc
11. the_1xc_table_CIs
12. the_1xc_table_tests

Note

You can also print the list above with `list_functions(3)`.

References

- Fagerland MW, Lydersen S, Laake P (2017) Statistical Analysis of Contingency Tables. Chapman & Hall/CRC, Boca Raton, FL
- <https://contingencytables.com/>
- <https://www.routledge.com/Statistical-Analysis-of-Contingency-Tables/Fagerland-Lydersen-Laake/p/book/978146658>

Description

These are the functions related to chapter 4:

1. Adjusted_inv_sinh_CI_OR_2x2
2. Adjusted_inv_sinh_CI_ratio_2x2
3. Adjusted_log_CI_2x2
4. AgrestiCaffo_CI_2x2
5. Wald_CI_2x2
6. BaptistaPike_exact_conditional_CI_2x2
7. BaptistaPike_midP_CI_2x2
8. Cornfield_exact_conditional_CI_2x2
9. Cornfield_midP_CI_2x2
10. Fisher_exact_test_2x2
11. Exact_unconditional_test_2x2
12. Fisher_midP_test_2x2
13. Gart_adjusted_logit_CI_2x2
14. Independence_smoothed_logit_CI_2x2
15. Inv_sinh_CI_OR_2x2
16. Inv_sinh_CI_ratio_2x2
17. Katz_log_CI_2x2
18. Koopman_asymptotic_score_CI_2x2
19. LR_test_2x2
20. Mee_asymptotic_score_CI_2x2
21. MiettinenNurminen_asymptotic_score_CI_difference_2x2
22. MiettinenNurminen_asymptotic_score_CI_OR_2x2
23. MiettinenNurminen_asymptotic_score_CI_ratio_2x2
24. MOVER_R_Wilson_CI_OR_2x2
25. MOVER_R_Wilson_CI_ratio_2x2

26. Newcombe_hybrid_score_CI_2x2
27. Pearson_chi_squared_test_2x2
28. Pearson_chi_squared_test_CC_2x2
29. PriceBonett_approximate_Bayes_CI_2x2
30. Wald_CI_CC_2x2
31. Woolf_logit_CI_2x2
32. Uncorrected_asymptotic_score_CI_2x2
33. Z_unpooled_test_2x2
34. the_2x2_table_CIs_difference
35. the_2x2_table_CIs_OR
36. the_2x2_table_CIs_ratio
37. the_2x2_table_tests

Note

You can also print the list above with `list_functions(4)`.

References

- Fagerland MW, Lydersen S, Laake P (2017) Statistical Analysis of Contingency Tables. Chapman & Hall/CRC, Boca Raton, FL
- <https://contingencytables.com/>
- <https://www.routledge.com/Statistical-Analysis-of-Contingency-Tables/Fagerland-Lydersen-Laake/p/book/978146658>

Description

These are the functions related to chapter 5:

1. CochranArmitage_CI_rx2
2. CochranArmitage_exact_cond_midP_tests_rx2
3. CochranArmitage_MH_tests_rx2
4. Exact_cond_midP_unspecific_ordering_rx2
5. Pearson_LR_tests_unspecific_ordering_rx2
6. the_rx2_table
7. Trend_estimate_CI_tests_rx2

Note

You can also print the list above with `list_functions(5)`.

References

- Fagerland MW, Lydersen S, Laake P (2017) Statistical Analysis of Contingency Tables. Chapman & Hall/CRC, Boca Raton, FL
- <https://contingencytables.com/>
- <https://www.routledge.com/Statistical-Analysis-of-Contingency-Tables/Fagerland-Lydersen-Laake/p/book/978146658>

chap6*Chapter 6: The Ordered 2xc Table*

Description

These are the functions related to chapter 6:

1. Brant_test_2xc
2. Cumulative_models_for_2xc
3. Exact_cond_midP_linear_rank_tests_2xc
4. ClopperPearson_exact_CI_1x2_beta_version
5. Exact_cond_midP_unspecific_ordering_rx2
6. MantelHaenszel_test_2xc
7. Pearson_LR_tests_cum_OR_2xc
8. Score_test_for_effect_in_the_probit_model_2xc
9. the_2xc_table

Note

You can also print the list above with `list_functions(6)`.

References

- Fagerland MW, Lydersen S, Laake P (2017) Statistical Analysis of Contingency Tables. Chapman & Hall/CRC, Boca Raton, FL
- <https://contingencytables.com/>
- <https://www.routledge.com/Statistical-Analysis-of-Contingency-Tables/Fagerland-Lydersen-Laake/p/book/978146658>

Description

These are the functions related to chapter 7:

1. Bonferroni_type_CIs_rxc
2. Cumulative_models_for_rxc
3. Exact_cond_midP_tests_rxc
4. FisherFreemanHalton_asymptotic_test_rxc
5. gamma_coefficient_rxc_bca
6. gamma_coefficient_rxc
7. JonckheereTerpstra_test_rxc
8. Kendalls_tau_b_rxc
9. Kendalls_tau_b_rxc_bca
10. KruskalWallis_asymptotic_test_rxc
11. linear_by_linear_test_rxc
12. Pearson_correlation_coefficient_rxc
13. Pearson_correlation_coefficient_rxc_bca
14. Pearson_LR_tests_rxc
15. Pearson_residuals_rxc
16. Scheffe_type_CIs_rxc
17. Spearman_correlation_coefficient_rxc
18. Spearman_correlation_coefficient_rxc_bca
19. the_rxc_table

Note

You can also print the list above with `list_functions(7)`.

References

- Fagerland MW, Lydersen S, Laake P (2017) Statistical Analysis of Contingency Tables. Chapman & Hall/CRC, Boca Raton, FL
- <https://contingencytables.com/>
- <https://www.routledge.com/Statistical-Analysis-of-Contingency-Tables/Fagerland-Lydersen-Laake/p/book/978146658>

Description

These are the functions related to chapter 8:

1. BonettPrice_hybrid_Wilson_score_CI_CC_paired_2x2
2. BonettPrice_hybrid_Wilson_score_CI_paired_2x2
3. ClopperPearson_exact_CI_1x2_beta_version
4. McNemar_asymptotic_test_CC_paired_2x2
5. McNemar_asymptotic_test_paired_2x2
6. McNemar_exact_cond_test_paired_2x2
7. McNemar_exact_unconditional_test_paired_2x2
8. McNemar_midP_test_paired_2x2
9. Tang_asymptotic_score_CI_paired_2x2
10. Tango_asymptotic_score_CI_paired_2x2
11. MOVER_Wilson_score_CI_paired_2x2
12. Newcombe_square_and_add_CI_paired_2x2
13. Transformed_Blaker_exact_CI_paired_2x2
14. Transformed_Clopper_Pearson_exact_CI_paired_2x2
15. Transformed_Clopper_Pearson_midP_CI_paired_2x2
16. Transformed_Wilson_score_CI_paired_2x2
17. Wald_CI_diff_paired_2x2
18. Wald_CI_diff_CC_paired_2x2
19. Wald_CI_AgrestiMin_paired_2x2
20. Wald_CI_BonettPrice_paired_2x2
21. Wald_CI_OR_Laplace_paired_2x2
22. Wald_CI_OR_paired_2x2
23. Wald_CI_ratio_paired_2x2
24. the_paired_2x2_table_CIs_difference
25. the_paired_2x2_table_CIs_OR
26. the_paired_2x2_table_CIs_ratio
27. the_paired_2x2_table_tests

Note

You can also print the list above with `list_functions(8)`.

References

- Fagerland MW, Lydersen S, Laake P (2017) Statistical Analysis of Contingency Tables. Chapman & Hall/CRC, Boca Raton, FL
- <https://contingencytables.com/>
- <https://www.routledge.com/Statistical-Analysis-of-Contingency-Tables/Fagerland-Lydersen-Laake/p/book/978146658>

Description

These are the functions related to chapter 9:

1. Bhapkar_test_paired_cxc
2. Bonferroni_type_CIs_paired_cxc
3. FleissEveritt_test_paired_cxc
4. FleissLevinPaik_test_paired_cxc
5. McNemarBowker_test_paired_cxc
6. Scheffe_type_CIs_paired_cxc
7. Score_test_and_CI_marginal_mean_scores_paired_cxc
8. Stuart_test_paired_cxc
9. Wald_test_and_CI_marginal_mean_ranks_paired_cxc
10. Wald_test_and_CI_marginal_mean_scores_paired_cxc
11. the_paired_cxc_table_nominal
12. the_paired_cxc_table_ordinal

Note

You can also print the list above with `list_functions(9)`.

References

- Fagerland MW, Lydersen S, Laake P (2017) Statistical Analysis of Contingency Tables. Chapman & Hall/CRC, Boca Raton, FL
- <https://contingencytables.com/>
- <https://www.routledge.com/Statistical-Analysis-of-Contingency-Tables/Fagerland-Lydersen-Laake/p/book/978146658>

ClopperPearson_exact_CI_1x2

The Clopper-Pearson exact confidence interval

Description

The Clopper-Pearson exact confidence interval for the binomial probability Described in Chapter 2 "The 1x2 Table and the Binomial Distribution"

Usage

```
ClopperPearson_exact_CI_1x2(X, n, alpha = 0.05)
```

Arguments

X	the number of successes
n	the total number of observations
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
ClopperPearson_exact_CI_1x2(singh_2010["1st", "X"], singh_2010["1st", "n"])
ClopperPearson_exact_CI_1x2(singh_2010["2nd", "X"], singh_2010["2nd", "n"])
ClopperPearson_exact_CI_1x2(singh_2010["3rd", "X"], singh_2010["3rd", "n"])
with(singh_2010["4th", ], ClopperPearson_exact_CI_1x2(X, n)) # alternative syntax
ClopperPearson_exact_CI_1x2(ligarden_2010["X"], ligarden_2010["n"])
```

ClopperPearson_exact_CI_1x2_beta_version

The Clopper-Pearson exact confidence interval for the binomial probability (beta version)

Description

The Clopper-Pearson exact confidence interval for the binomial probability (defined via the beta distribution)

Described in Chapter 2 "The 1x2 Table and the Binomial Distribution"

Usage

```
ClopperPearson_exact_CI_1x2_beta_version(X, n, alpha = 0.05)
```

Arguments

X	the number of successes
n	the total number of observations
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

References

Brown LD, Cai T, DasGupta A (2001) Interval estimation for a binomial proportion. *Statistical Science*; 16:101-133

See Also

`ClopperPearson_exact_CI_1x2`

Examples

```
ClopperPearson_exact_CI_1x2_beta_version(singh_2010["1st", "X"], singh_2010["1st", "n"])
ClopperPearson_exact_CI_1x2_beta_version(singh_2010["2nd", "X"], singh_2010["2nd", "n"])
ClopperPearson_exact_CI_1x2_beta_version(singh_2010["3rd", "X"], singh_2010["3rd", "n"])
with(singh_2010["4th", ], ClopperPearson_exact_CI_1x2_beta_version(X, n)) # alternative syntax
ClopperPearson_exact_CI_1x2_beta_version(ligarden_2010["X"], ligarden_2010["n"])
```

`ClopperPearson_midP_CI_1x2`

The Clopper-Pearson mid-P confidence interval

Description

The Clopper-Pearson mid-P confidence interval for the binomial probability Described in Chapter 2 "The 1x2 Table and the Binomial Distribution"

Usage

```
ClopperPearson_midP_CI_1x2(X, n, alpha = 0.05)
```

Arguments

X	the number of successes
n	the total number of observations
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
ClopperPearson_midP_CI_1x2(singh_2010["1st", "X"], singh_2010["1st", "n"])
ClopperPearson_midP_CI_1x2(singh_2010["2nd", "X"], singh_2010["2nd", "n"])
ClopperPearson_midP_CI_1x2(singh_2010["3rd", "X"], singh_2010["3rd", "n"])
with(singh_2010["4th", ], ClopperPearson_midP_CI_1x2(X, n)) # alternative syntax
ClopperPearson_midP_CI_1x2(ligarden_2010["X"], ligarden_2010["n"])
```

CochranArmitage_CI_rx2

The Cochran-Armitage confidence interval for trend in the linear model

Description

The Cochran-Armitage confidence interval for trend in the linear model

Described in Chapter 5 "The Ordered rx2 Table"

Usage

```
CochranArmitage_CI_rx2(n, a = seq_len(nrow(n)), alpha = 0.05)
```

Arguments

<code>n</code>	the observed counts (an rx2 matrix)
<code>a</code>	scores assigned to the rows
<code>alpha</code>	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
CochranArmitage_CI_rx2(mills_graubard_1987, c(1, 2, 3, 4, 5))
CochranArmitage_CI_rx2(indredavik_2008, c(1, 2, 3, 4, 5))
```

CochranArmitage_exact_cond_midP_tests_rx2

The Cochran-Armitage exact conditional and mid-P tests

Description

The Cochran-Armitage exact conditional and mid-P tests

Described in Chapter 5 "The Ordered rx2 Table"

Usage

```
CochranArmitage_exact_cond_midP_tests_rx2(n, a)
```

Arguments

n	the observed counts (an rx2 matrix)
a	scores assigned to the rows

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
## Not run:
CochranArmitage_exact_cond_midP_tests_rx2(mills_graubard_1987, c(1, 2, 3, 4, 5))

## End(Not run)
CochranArmitage_exact_cond_midP_tests_rx2(indredavik_2008, c(1, 2, 3, 4, 5))
```

CochranArmitage_MH_tests_rx2

The Cochran-Armitage, modified Cochran-Armitage, and Mantel-Haenszel tests for trend

Description

Described in Chapter 5 "The Ordered rx2 Table"

Usage

```
CochranArmitage_MH_tests_rx2(n, a)
```

Arguments

`n` the observed counts (an rx2 matrix)
`a` scores assigned to the rows

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
CochranArmitage_MH_tests_rx2(mills_graubard_1987, c(1, 2, 3, 4, 5))
CochranArmitage_MH_tests_rx2(indredavik_2008, c(1, 2, 3, 4, 5))
```

CochranMantelHaenszel_test_stratified_2x2

The Cochran-Mantel-Haenszel test of a common odds ratio

Description

The Cochran-Mantel-Haenszel test of a common odds ratio
Described in Chapter 10 "Stratified 2x2 Tables and Meta-Analysis"

Usage

```
CochranMantelHaenszel_test_stratified_2x2(n)
```

Arguments

`n` the observed table (a 2x2xk matrix, where k is the number of strata)

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
CochranMantelHaenszel_test_stratified_2x2(doll_hill_1950)
CochranMantelHaenszel_test_stratified_2x2(hine_1989)
```

Cochran_Q_test_stratified_2x2	<i>The Cochran Q test of homogeneity of effects over strata</i>
-------------------------------	---

Description

The Cochran Q test of homogeneity of effects over strata
Described in Chapter 10 "Stratified 2x2 Tables and Meta-Analysis"

Usage

Cochran_Q_test_stratified_2x2(n, link = "linear", estimatetype = "MH")

Arguments

n the observed table (a 2x2xk matrix, where k is the number of strata)
link the link function ('linear', 'log', or 'logit')
estimatetype Mantel-Haenszel or inverse variance estimate ('MH' or 'IV')

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Cochran_Q_test_stratified_2x2(doll_hill_1950)
Cochran_Q_test_stratified_2x2(hine_1989)
```

contingencytables	<i>Statistical Analysis of Contingency tables</i>
-------------------	---

Description

Statistical Analysis of Contingency Tables is an invaluable tool for statistical inference in contingency tables. It covers effect size estimation, confidence intervals, and hypothesis tests for the binomial and the multinomial distributions, unpaired and paired 2x2 tables, rxc tables, ordered rx2 and 2xc tables, paired cxc tables, and stratified tables. This package provides functions that accompany the "Statistical Analysis of Contingency Tables" book by Fagerland et. al. <ISBN 9781466588172>.

Author(s)

Maintainer: Waldir Leoncio <w.l.netto@medisin.uio.no>

Authors:

- Morten Wang Fagerland <morten.fagerland@medisin.uio.no>

Other contributors:

- Stian Lydersen [contributor]
- Petter Laake [contributor]
- Ole Christian Lingjærde [translator]
- Brad J. Biggerstaff [contributor]

References

- Fagerland MW, Lydersen S, Laake P (2017) Statistical Analysis of Contingency Tables. Chapman & Hall/CRC, Boca Raton, FL
- <https://contingencytables.com/>
- <https://www.routledge.com/Statistical-Analysis-of-Contingency-Tables/Fagerland-Lydersen-Laake/p/book/978146658>
- <https://ocbe-uio.github.io/contingencytables/>

See Also

[print.contingencytables_result](#) to read about printing alternatives.

contingencytables_result
contingencytables_result class

Description

A class for output of the main functions on this package

Usage

```
contingencytables_result(statistics, print_structure)
```

Arguments

statistics	Either a value or a list of values to be filled by print_format
print_structure	Either a string of a function instructing how to print the values from statistics

Value

an object of class contingencytables_result

Author(s)

Waldir Leoncio

See Also

[print.contingencytables_result](#)

Cornfield_exact_conditional_CI_2x2

The Cornfield exact conditional confidence interval for the odds ratio

Description

The Cornfield exact conditional confidence interval for the odds ratio

Described in Chapter 4 "The 2x2 Table"

Usage

```
Cornfield_exact_conditional_CI_2x2(n, alpha = 0.05)
```

Arguments

n	the observed table (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Cornfield_exact_conditional_CI_2x2(tea)
Cornfield_exact_conditional_CI_2x2(perondi_2004)
Cornfield_exact_conditional_CI_2x2(lampasona_2013)
Cornfield_exact_conditional_CI_2x2(ritland_2007)
```

Cornfield_midP_CI_2x2 *The Cornfield mid-P confidence interval for the odds ratio*

Description

The Cornfield mid-P confidence interval for the odds ratio
 Described in Chapter 4 "The 2x2 Table"

Usage

```
Cornfield_midP_CI_2x2(n, alpha = 0.05)
```

Arguments

n	the observed table (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Cornfield_midP_CI_2x2(tea)
Cornfield_midP_CI_2x2(perondi_2004)
Cornfield_midP_CI_2x2(lampasona_2013)
Cornfield_midP_CI_2x2(ritland_2007)
```

Cumulative_models_for_2xc

Cumulative logit and probit models

Description

Cumulative logit and probit models
 Described in Chapter 6 "The Ordered 2xc Table"

Usage

```
Cumulative_models_for_2xc(n, linkfunction = "logit", alpha = 0.05)
```

Arguments

n	the observed table (a 2xc matrix) with at least 3 columns
linkfunction	either "logit" or "probit"
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Cumulative_models_for_2xc(fontanella_2008)
Cumulative_models_for_2xc(lydersen_2012a)
```

Cumulative_models_for_rxc

Cumulative logit and probit models

Description

Cumulative logit and probit models
Described in Chapter 7 "The rxc Table"

Usage

```
Cumulative_models_for_rxc(n, linkfunction = "logit", alpha = 0.05)
```

Arguments

n	the observed table (an rxc matrix) with at least 3 columns
linkfunction	either "logit" or "probit"
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Cumulative_models_for_rxc(table_7.5)
Cumulative_models_for_rxc(table_7.6)
```

doll_hill_1950	<i>Smoking and lung cancer</i>
----------------	--------------------------------

Description

Smoking and lung cancer

Usage

doll_hill_1950

Format

An object of class array of dimension 2 x 2 x 2.

References

Doll and Hill (1950)

Exact_binomial_test_1x2	<i>The exact binomial test for the binomial probability (pi)</i>
-------------------------	--

Description

$H_0: \pi = \pi_0$ vs $H_A: \pi \neq \pi_0$ (two-sided)

Described in Chapter 2 "The 1x2 Table and the Binomial Distribution"

Usage

Exact_binomial_test_1x2(X, n, pi0)

Arguments

X	the number of successes
n	the total number of observations
pi0	a given probability

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Exact_binomial_test_1x2(singh_2010["1st", "X"], singh_2010["1st", "n"], pi0 = 0.513)
Exact_binomial_test_1x2(singh_2010["2nd", "X"], singh_2010["2nd", "n"], pi0 = 0.513)
Exact_binomial_test_1x2(singh_2010["3rd", "X"], singh_2010["3rd", "n"], pi0 = 0.513)
Exact_binomial_test_1x2(singh_2010["4th", "X"], singh_2010["4th", "n"], pi0 = 0.513)
Exact_binomial_test_1x2(ligarden_2010["X"], ligarden_2010["n"], pi0 = 0.5)
```

Exact_cond_midP_linear_rank_tests_2xc

Exact conditional and mid-P linear rank tests

Description

Exact conditional and mid-P linear rank tests

Described in Chapter 6 "The Ordered 2xc Table"

Usage

```
Exact_cond_midP_linear_rank_tests_2xc(n, b = 0)
```

Arguments

n	the observed table (a 2xc matrix)
b	scores assigned to the columns (if b=0, midranks will be used as scores)

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Exact_cond_midP_linear_rank_tests_2xc(lydersen_2012a)
## Not run: Exact_cond_midP_linear_rank_tests_2xc(fontanella_2008)
```

Exact_cond_midP_tests_rxc

Exact conditional and mid-P tests for the rxc table

Description

Exact conditional and mid-P tests for the rxc table: the Fisher-Freeman-Halton, Pearson, likelihood ratio, Kruskal-Wallis, linear-by-linear, and Jonckheere-Terpstra tests.

Described in Chapter 7 "The rxc Table"

Usage

```
Exact_cond_midP_tests_rxc(n)
```

Arguments

n the observed counts (an rxc matrix)

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Note

Works only for 3x2 and 3x3 tables

Examples

```
Exact_cond_midP_tests_rxc(table_7.3) # a 3x2 table
## Not run:
  Exact_cond_midP_tests_rxc(table_7.6) # a 3x3 table

## End(Not run)
```

Exact_cond_midP_unspecific_ordering_rx2

The exact conditional and mid-P tests for unspecific ordering

Description

The exact conditional and mid-P tests for unspecific ordering. May also be used for 2xc tables, after flipping rows and columns (i.e. if n is a 2xc table, call this function with n' (the transpose of n) as the first argument).

Described in Chapter 5 "The Ordered rx2 Table"

Usage

```
Exact_cond_midP_unspecific_ordering_rx2(n, direction, statistic = "Pearson")
```

Arguments

n	the observed counts (an rx2 matrix)
direction	the direction of the success probabilities ("increasing" or "decreasing")
statistic	the Pearson test statistic ("Pearson") or the likelihood ratio test statistic ("LR"). Can also be used for cumulative ORs in 2xc tables with "PearsonCumOR" or "LRCumOR".

Value

An object of the [contingencytables_result](#) class, basically a subclass of [base::list\(\)](#). Use the [utils::str\(\)](#) function to see the specific elements returned.

Examples

```
# Chapter 6: Postoperative nausea (Lydersen et al., 2012a)
n <- t(lydersen_2012a)
Exact_cond_midP_unspecific_ordering_rx2(n, "decreasing")
Exact_cond_midP_unspecific_ordering_rx2(n, "decreasing", "PearsonCumOR")
```

Exact_multinomial_test_1xc

The exact multinomial test for multinomial probabilities

Description

The exact multinomial test for multinomial probabilities

Described in Chapter 3 "The 1xc Table and the Multinomial Distribution"

Usage

```
Exact_multinomial_test_1xc(n, pi0)
```

Arguments

n	the observed counts (a 1xc vector, where c is the number of categories)
pi0	given probabilities (a 1xc vector)

Value

An object of the [contingencytables_result](#) class, basically a subclass of [base::list\(\)](#). Use the [utils::str\(\)](#) function to see the specific elements returned.

Examples

```
# Genotype counts for SNP rs 6498169 in RA patients
Exact_multinomial_test_1xc(n = snp6498169$complete$n, pi0 = snp6498169$complete$pi0)

# subset of 10 patients
Exact_multinomial_test_1xc(n = snp6498169$subset$n, pi0 = snp6498169$subset$pi0)
```

Exact_unconditional_test_2x2

Exact unconditional test for association in 2x2 tables

Description

Exact unconditional test for association in 2x2 tables
 Described in Chapter 4 "The 2x2 Table"

Usage

```
Exact_unconditional_test_2x2(n, statistic = "Pearson", gamma = 1e-04)
```

Arguments

n	the observed counts (a 2x2 matrix)
statistic	'Pearson' (Suissa-Shuster test default), 'LR' (likelihood ratio), 'unpooled' (unpooled Z), or 'Fisher' (Fisher-Boschloo test)
gamma	parameter for the Berger and Boos procedure (default=0.0001 gamma=0: no adj)

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Note

Somewhat crude code with maximization over a simple partition of the nuisance parameter space into 'num_pi_values' equally spaced values (1000, hardcoded). This method could be improved with a better algorithm for the maximization however, it works well for most purposes. `plot()` the results to get an indication of the precision. A refinement of the maximization can be done with a manual restriction of the parameter space.

Examples

```
Exact_unconditional_test_2x2(tea)
Exact_unconditional_test_2x2(perondi_2004)
Exact_unconditional_test_2x2(lampasona_2013)
Exact_unconditional_test_2x2(ritland_2007)
```

ezra_2010

Floppy eyelid syndrome vs obstructive sleep apnea

Description

Floppy eyelid syndrome vs obstructive sleep apnea

Usage

ezra_2010

Format

An object of class `matrix` (inherits from `array`) with 2 rows and 2 columns.

References

Ezra et al. (2010)

fischer_1999

A comparison between serial and retrospective measurements

Description

A comparison between serial and retrospective measurements

Usage

fischer_1999

Format

An object of class `matrix` (inherits from `array`) with 5 rows and 5 columns.

References

Fischer et al. (1999)

FisherFreemanHalton_asymptotic_test_rxc

The Fisher-Freeman-Halton asymptotic test for unordered rxc tables

Description

The Fisher-Freeman-Halton asymptotic test for unordered rxc tables
Described in Chapter 7 "The rxc Table"

Usage

```
FisherFreemanHalton_asymptotic_test_rxc(n)
```

Arguments

n the observed counts (an rxc matrix)

Value

An object of the [contingencytables_result](#) class, basically a subclass of [base::list\(\)](#). Use the [utils::str\(\)](#) function to see the specific elements returned.

Note

May not give results for all tables, due to overflow

Examples

```
FisherFreemanHalton_asymptotic_test_rxc(table_7.3)
```

Fisher_exact_test_2x2 *The Fisher exact test for association in 2x2 tables*

Description

The Fisher exact test for association in 2x2 tables
Described in Chapter 4 "The 2x2 Table"

Usage

```
Fisher_exact_test_2x2(n, statistic = "Pearson")
```

Arguments

n the observed counts (a 2x2 matrix)
statistic 'hypergeometric' (i.e. Fisher-Irwin; default), 'Pearson', or 'LR' (likelihood ratio)

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Fisher_exact_test_2x2(tea)
Fisher_exact_test_2x2(perondi_2004)
Fisher_exact_test_2x2(lampasona_2013)
Fisher_exact_test_2x2(ritland_2007)
```

Fisher_midP_test_2x2 *The Fisher mid-P test for association in 2x2 tables*

Description

The Fisher mid-P test for association in 2x2 tables

Described in Chapter 4 "The 2x2 Table"

Usage

```
Fisher_midP_test_2x2(n, statistic = "hypergeometric")
```

Arguments

<code>n</code>	the observed counts (a 2x2 matrix)
<code>statistic</code>	'hypergeometric' (i.e. Fisher-Irwin default), 'Pearson', or 'LR' (likelihood ratio)

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Fisher_midP_test_2x2(tea)
Fisher_midP_test_2x2(perondi_2004)
Fisher_midP_test_2x2(lampasona_2013)
Fisher_midP_test_2x2(ritland_2007)
```

`FleissEveritt_test_paired_cxc`*The Fleiss-Everitt version of the Stuart test for marginal homogeneity*

Description

The Fleiss-Everitt version of the Stuart test for marginal homogeneity

Described in Chapter 9 "The Paired cxc Table"

Usage

```
FleissEveritt_test_paired_cxc(n)
```

Arguments

`n` the observed table (a cxc matrix)

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
FleissEveritt_test_paired_cxc(fleiss_2003)
```

`FleissLevinPaik_test_paired_cxc`*The Fleiss-Levin-Paik test for three-level ordinal outcomes*

Description

The Fleiss-Levin-Paik test for three-level ordinal outcomes

Described in Chapter 9 "The Paired cxc Table"

Usage

```
FleissLevinPaik_test_paired_cxc(n)
```

Arguments

`n` the observed table (a cxc matrix)

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Pretherapy susceptibility of pathogens *without the N / A category*
FleissLevinPaik_test_paired_cxc(peterson_2007[-4, -4])
```

fleiss_2003	<i>Table 13.6, page 382, of Fleiss et al. (2003)</i>
-------------	--

Description

Table 13.6, page 382, of Fleiss et al. (2003)

Usage

```
fleiss_2003
```

Format

An object of class `matrix` (inherits from `array`) with 3 rows and 3 columns.

References

Fleiss et al. (2003)

fontanella_2008	<i>The Adolescent Placement Study</i>
-----------------	---------------------------------------

Description

The Adolescent Placement Study

Usage

```
fontanella_2008
```

Format

An object of class `matrix` (inherits from `array`) with 2 rows and 4 columns.

References

Fontanella et al. (2008)

gamma_coefficient_rxc *The gamma coefficient*

Description

The gamma coefficient

Described in Chapter 7 "The rxc Table"

Usage

```
gamma_coefficient_rxc(n)
```

Arguments

n the observed table (an rxc matrix)

Value

An object of the [contingencytables_result](#) class, basically a subclass of [base::list\(\)](#). Use the [utils::str\(\)](#) function to see the specific elements returned.

Examples

```
gamma_coefficient_rxc(table_7.7)
gamma_coefficient_rxc(table_7.8)
gamma_coefficient_rxc(table_7.9)
```

gamma_coefficient_rxc_bca

The gamma coefficient with the bias-corrected and accelerated bootstrap confidence interval

Description

The gamma coefficient with the bias-corrected and accelerated bootstrap confidence interval

Described in Chapter 7 "The rxc Table"

Usage

```
gamma_coefficient_rxc_bca(n, nboot = 10000, alpha = 0.05)
```

Arguments

n the observed table (an rxc matrix)

nboot number of bootstrap samples

alpha the nominal significance level, used to compute a 100(1-alpha) confidence interval

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
set.seed(9623)
gamma_coefficient_rxc_bca(table_7.7, nboot = 800)
gamma_coefficient_rxc_bca(table_7.8, nboot = 200)
## Not run:
  gamma_coefficient_rxc_bca(table_7.9, nboot = 3000, alpha = 0.2)

## End(Not run)
```

Gart_adjusted_logit_CI_2x2

The Gart adjusted logit confidence interval for the odds ratio

Description

The Gart adjusted logit confidence interval for the odds ratio

Described in Chapter 4 "The 2x2 Table"

Usage

```
Gart_adjusted_logit_CI_2x2(n, alpha = 0.05)
```

Arguments

n	the observed table (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Gart_adjusted_logit_CI_2x2(lampasona_2013)
Gart_adjusted_logit_CI_2x2(ritland_2007)
```

Gold_Wald_CIs_1xc	<i>The Gold Wald simultaneous intervals for the multinomial probabilities</i>
-------------------	---

Description

The Gold Wald simultaneous intervals for the multinomial probabilities (with Scheffe adjustment)
Described in Chapter 3 "The 1xc Table and the Multinomial Distribution"

Usage

```
Gold_Wald_CIs_1xc(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 1xc vector, where c is the number of categories)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Gold_Wald_CIs_1xc(n = snp6498169$complete$n)
```

Goodman_Wald_CIs_1xc	<i>The Goodman Wald simultaneous intervals for the multinomial probabilities</i>
----------------------	--

Description

The Goodman Wald simultaneous intervals for the multinomial probabilities
(with Bonferroni adjustment)
Described in Chapter 3 "The 1xc Table and the Multinomial Distribution"

Usage

```
Goodman_Wald_CIs_1xc(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 1xc vector, where c is the number of categories)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Goodman_Wald_CIs_1xc(n = snp6498169$complete$n)
```

```
Goodman_Wald_CIs_for_diffs_1xc
```

The Goodman Wald simultaneous intervals for the differences between the

Description

The Goodman Wald simultaneous intervals for the differences between the multinomial probabilities (with Scheffe or Bonferroni adjustment)

Described in Chapter 3 "The 1xc Table and the Multinomial Distribution"

Usage

```
Goodman_Wald_CIs_for_diffs_1xc(n, alpha = 0.05, adjustment = "Bonferroni")
```

Arguments

<code>n</code>	the observed counts (a 1xc vector, where c is the number of categories)
<code>alpha</code>	the nominal level, e.g. 0.05 for 95% CIs
<code>adjustment</code>	Scheffe or Bonferroni adjustment ("Scheffe" or "Bonferroni")

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Goodman_Wald_CIs_for_diffs_1xc(n = snp6498169$complete$n)
```

Goodman_Wilson_score_CIs_1xc	<i>The Goodman Wilson score simultaneous intervals for the multinomial probabilities</i>
------------------------------	--

Description

The Goodman Wilson score simultaneous intervals for the multinomial probabilities (with Bonferroni adjustment)
Described in Chapter 3 "The 1xc Table and the Multinomial Distribution"

Usage

Goodman_Wilson_score_CIs_1xc(n, alpha = 0.05)

Arguments

n the observed counts (a 1xc vector, where c is the number of categories)
alpha the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

Goodman_Wilson_score_CIs_1xc(n = snp6498169\$complete\$n)

hine_1989	<i>Prophylactice use of Lidocaine in myocardial infarction</i>
-----------	--

Description

Prophylactice use of Lidocaine in myocardial infarction

Usage

hine_1989

Format

An object of class array of dimension 2 x 2 x 6.

References

Hine et al. (1989)

hypothetical	<i>Hypothetical experiment</i>
--------------	--------------------------------

Description

Hypothetical experiment

Usage

hypothetical

Format

An object of class numeric of length 5.

Independence_smoothed_logit_CI_2x2	<i>The Independence-smoothed logit confidence interval for the odds ratio</i>
------------------------------------	---

Description

The Independence-smoothed logit confidence interval for the odds ratio
Described in Chapter 4 "The 2x2 Table"

Usage

Independence_smoothed_logit_CI_2x2(n, alpha = 0.05)

Arguments

n the observed table (a 2x2 matrix)
alpha the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

Independence_smoothed_logit_CI_2x2(lampasona_2013)
Independence_smoothed_logit_CI_2x2(ritland_2007)

indredavik_2008	<i>Elevated troponin T levels in stroke patients</i>
-----------------	--

Description

Elevated troponin T levels in stroke patients

Usage

```
indredavik_2008
```

Format

An object of class `matrix` (inherits from `array`) with 5 rows and 2 columns.

References

Indredavik et al. (2008)

InverseVariance_estimate_stratified_2x2	<i>The inverse variance estimate of the overall effect across strata</i>
---	--

Description

The inverse variance estimate of the overall effect across strata
Described in Chapter 10 "Stratified 2x2 Tables and Meta-Analysis"

Usage

```
InverseVariance_estimate_stratified_2x2(n, link = "logit")
```

Arguments

<code>n</code>	the observed table (a 2x2xk matrix, where k is the number of strata)
<code>link</code>	the link function ('linear', 'log', or 'logit')

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
InverseVariance_estimate_stratified_2x2(doll_hill_1950)
InverseVariance_estimate_stratified_2x2(hine_1989)
```

Inv_sinh_CI_OR_2x2	<i>The inverse hyperbolic sine confidence interval for the odds ratio</i>
--------------------	---

Description

The inverse hyperbolic sine confidence interval for the odds ratio

Described in Chapter 4 "The 2x2 Table"

Usage

```
Inv_sinh_CI_OR_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Inv_sinh_CI_OR_2x2(lampasona_2013)
Inv_sinh_CI_OR_2x2(ritland_2007)
```

Inv_sinh_CI_ratio_2x2	<i>The inverse hyperbolic sine confidence interval for the ratio of probabilities</i>
-----------------------	---

Description

The inverse hyperbolic sine confidence interval for the ratio of probabilities

Described in Chapter 4 "The 2x2 Table"

Usage

```
Inv_sinh_CI_ratio_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Inv_sinh_CI_ratio_2x2(perondi_2004)
Inv_sinh_CI_ratio_2x2(ritland_2007)
```

Jeffreys_CI_1x2

Jeffreys confidence interval for the binomial probability

Description

Jeffreys confidence interval for the binomial probability

Described in Chapter 2 "The 1x2 Table and the Binomial Distribution"

Usage

```
Jeffreys_CI_1x2(X, n, alpha = 0.05)
```

Arguments

X	the number of successes
n	the total number of observations
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Jeffreys_CI_1x2(singh_2010["1st", "X"], singh_2010["1st", "n"])
Jeffreys_CI_1x2(singh_2010["2nd", "X"], singh_2010["2nd", "n"])
Jeffreys_CI_1x2(singh_2010["3rd", "X"], singh_2010["3rd", "n"])
with(singh_2010["4th", ], Jeffreys_CI_1x2(X, n)) # alternative syntax
Jeffreys_CI_1x2(ligarden_2010["X"], ligarden_2010["n"])
```

JonckheereTerpstra_test_rxc

The Jonckheere-Terpstra test for association

Description

The Jonckheere-Terpstra test for association

Described in Chapter 7 "The rxc Table"

Usage

```
JonckheereTerpstra_test_rxc(n)
```

Arguments

n the observed table (an rxc matrix)

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
JonckheereTerpstra_test_rxc(table_7.7)
JonckheereTerpstra_test_rxc(table_7.8)
JonckheereTerpstra_test_rxc(table_7.9)
```

Katz_log_CI_2x2

The Katz log confidence interval for the ratio of probabilities

Description

The Katz log confidence interval for the ratio of probabilities

Described in Chapter 4 "The 2x2 Table"

Usage

```
Katz_log_CI_2x2(n, alpha = 0.05)
```

Arguments

n the observed counts (a 2x2 matrix)
alpha the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Katz_log_CI_2x2(perondi_2004)
Katz_log_CI_2x2(ritland_2007)
```

Kendalls_tau_b_rxc	<i>Kendall's tau-b with confidence interval based on the Fieller standard deviation</i>
--------------------	---

Description

Kendall's tau-b with confidence interval based on the Fieller standard deviation
Described in Chapter 7 "The rxc Table"

Usage

```
Kendalls_tau_b_rxc(n, alpha = 0.05)
```

Arguments

- n the observed table (an rxc matrix)
- alpha the nominal significance level, used to compute a 100(1-alpha)% confidence interval

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Kendalls_tau_b_rxc(table_7.7)
Kendalls_tau_b_rxc(table_7.8)
Kendalls_tau_b_rxc(table_7.9)
```

Kendalls_tau_b_rxc_bca

Kendall's tau-b with the bias-corrected and accelerated bootstrap confidence interval

Description

Kendall's tau-b with the bias-corrected and accelerated bootstrap confidence interval

Described in Chapter 7 "The rxc Table"

Usage

```
Kendalls_tau_b_rxc_bca(n, nboot = 10000, alpha = 0.05)
```

Arguments

n	the observed table (an rxc matrix)
nboot	number of bootstrap samples
alpha	the nominal significance level, used to compute a 100(1-alpha) confidence interval

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
set.seed(9974)
Kendalls_tau_b_rxc_bca(table_7.7, nboot = 800)
Kendalls_tau_b_rxc_bca(table_7.8, nboot = 200)
## Not run:
  Kendalls_tau_b_rxc_bca(table_7.9)

## End(Not run)
```

Koopman_asymptotic_score_CI_2x2

The Koopman asymptotic score confidence interval for the ratio of probabilities

Description

The Koopman asymptotic score confidence interval for the ratio of probabilities

Described in Chapter 4 "The 2x2 Table"

Usage

```
Koopman_asymptotic_score_CI_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Note

This versions uses the score test statistic of the Miettinen-Nurminen interval without the variance correction term.

Examples

```
Koopman_asymptotic_score_CI_2x2(perondi_2004)
Koopman_asymptotic_score_CI_2x2(ritland_2007)
```

```
KruskalWallis_asymptotic_test_rxc
```

The Kruskal-Wallis asymptotic test for singly ordered rxc tables

Description

The Kruskal-Wallis asymptotic test for singly ordered rxc tables

Described in Chapter 7 "The rxc Table"

Usage

```
KruskalWallis_asymptotic_test_rxc(n)
```

Arguments

n	the observed counts (an rxc matrix)
---	-------------------------------------

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
KruskalWallis_asymptotic_test_rxc(table_7.5)
KruskalWallis_asymptotic_test_rxc(table_7.6)
```

`lampasona_2013`*A case-control study of GADA exposure on IPEX syndrome*

Description

A case-control study of GADA exposure on IPEX syndrome

Usage`lampasona_2013`**Format**

An object of class `matrix` (inherits from `array`) with 2 rows and 2 columns.

References

Lampasona et al. (2013)

`ligarden_2010`*Ligarden et al., 2010*

Description

Ligarden et al., 2010

Usage`ligarden_2010`**Format**

An object of class `numeric` of length 2.

References

ligarden_2010

linear_by_linear_test_rxc

The linear-by-linear test for association

Description

The linear-by-linear test for association

Described in Chapter 7 "The rxc Table"

Usage

```
linear_by_linear_test_rxc(n, a = seq_len(ncol(n)), b = seq_len(nrow(n)))
```

Arguments

n	the observed table (an rxc matrix)
a	scores assigned to the rows
b	scores assigned to the columns

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
linear_by_linear_test_rxc(table_7.7)
linear_by_linear_test_rxc(table_7.8)
linear_by_linear_test_rxc(table_7.9)
```

list_functions

List functions from a chapter

Description

Complements the `?chapX` command by printing a list of functions related to a particular chapter X on the R console.

Usage

```
list_functions(chap_num)
```

Arguments

chap_num	Number of book chapter (from 2 to 10)
----------	---------------------------------------

Value

List of functions from that chapter

Author(s)

Waldir Leoncio

LR_CI_1x2

The likelihood ratio confidence interval for the binomial probability

Description

The likelihood ratio confidence interval for the binomial probability. Described in Chapter 2 "The 1x2 Table and the Binomial Distribution"

Usage

```
LR_CI_1x2(X, n, alpha = 0.05)
```

Arguments

X	the number of successes
n	the total number of observations
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
LR_CI_1x2(singh_2010["1st", "X"], singh_2010["1st", "n"])
LR_CI_1x2(singh_2010["2nd", "X"], singh_2010["2nd", "n"])
LR_CI_1x2(singh_2010["3rd", "X"], singh_2010["3rd", "n"])
with(singh_2010["4th", ], LR_CI_1x2(X, n)) # alternative syntax
LR_CI_1x2(ligarden_2010["X"], ligarden_2010["n"])
```

LR_test_1x2

The likelihood ratio test for the binomial probability (pi)

Description

The likelihood ratio test for the binomial probability (pi) $H_0: \pi = \pi_0$ vs $H_A: \pi \neq \pi_0$ (two-sided). Described in Chapter 2 "The 1x2 Table and the Binomial Distribution".

Usage

```
LR_test_1x2(X, n, pi0)
```

Arguments

X	the number of successes
n	the total number of observations
pi0	a given probability

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
LR_test_1x2(singh_2010["1st", "X"], singh_2010["1st", "n"], pi0 = .5)
LR_test_1x2(singh_2010["2nd", "X"], singh_2010["2nd", "n"], pi0 = .5)
LR_test_1x2(singh_2010["3rd", "X"], singh_2010["3rd", "n"], pi0 = .5)
LR_test_1x2(singh_2010["4th", "X"], singh_2010["4th", "n"], pi0 = .5)
LR_test_1x2(ligarden_2010["X"], ligarden_2010["n"], pi0 = .5)
```

LR_test_1xc

The likelihood ratio test for multinomial probabilities

Description

The likelihood ratio test for multinomial probabilities

Described in Chapter 3 "The 1xc Table and the Multinomial Distribution"

Usage

```
LR_test_1xc(n, pi0)
```

Arguments

`n` the observed counts (a 1xc vector, where c is the number of categories)
`pi0` given probabilities (a 1xc vector)

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Genotype counts for SNP rs 6498169 in RA patients
LR_test_1xc(n = snp6498169$complete$n, pi0 = snp6498169$complete$pi0)
# subset of 10 patients
LR_test_1xc(n = snp6498169$subset$n, pi0 = snp6498169$subset$pi0)
```

LR_test_2x2

The likelihood ratio test for association in 2x2 tables

Description

The likelihood ratio test for association in 2x2 tables
Described in Chapter 4 "The 2x2 Table"

Usage

```
LR_test_2x2(n)
```

Arguments

`n` the observed counts (a 2x2 matrix)

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
LR_test_2x2(tea)
LR_test_2x2(perondi_2004)
LR_test_2x2(lampasona_2013)
LR_test_2x2(ritland_2007)
```

lydersen_2012a	<i>Postoperative nausea</i>
----------------	-----------------------------

Description

Postoperative nausea

Usage

```
lydersen_2012a
```

Format

An object of class `matrix` (inherits from `array`) with 2 rows and 4 columns.

References

Lydersen et al. (2012a)

MantelHaenszel_estimate_stratified_2x2	<i>The Mantel-Haenszel estimate of the overall effect across strata</i>
--	---

Description

The Mantel-Haenszel estimate of the overall effect across strata
Described in Chapter 10 "Stratified 2x2 Tables and Meta-Analysis"

Usage

```
MantelHaenszel_estimate_stratified_2x2(n, link = "logit")
```

Arguments

<code>n</code>	the observed table (a 2x2xk matrix, where k is the number of strata)
<code>link</code>	the link function ('linear', 'log', or 'logit')

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
MantelHaenszel_estimate_stratified_2x2(doll_hill_1950)
MantelHaenszel_estimate_stratified_2x2(hine_1989)
```

MantelHaenszel_test_2xc

The Mantel-Haenszel test of association with column scores

Description

The Mantel-Haenszel test of association with column scores

Described in Chapter 6 "The Ordered 2xc Table"

Usage

```
MantelHaenszel_test_2xc(n, b = 0)
```

Arguments

n	the observed counts (a 2xc matrix)
b	scores assigned to the columns (if b=0, midranks will be used as scores)

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
MantelHaenszel_test_2xc(lydersen_2012a)
```

McNemarBowker_test_paired_cxc

The McNemar-Bowker test for marginal symmetry

Description

The McNemar-Bowker test for marginal symmetry

Described in Chapter 9 "The Paired cxc Table"

Usage

```
McNemarBowker_test_paired_cxc(n)
```

Arguments

n	the observed table (a cxc matrix)
---	-----------------------------------

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Pretherapy susceptibility of pathogens (Peterson et al., 2007)
McNemarBowker_test_paired_cxc(peterson_2007)
```

```
McNemar_asymptotic_test_CC_paired_2x2
```

The McNemar asymptotic test with continuity correction

Description

The McNemar asymptotic test with continuity correction

Described in Chapter 8 "The Paired 2x2 Table"

Usage

```
McNemar_asymptotic_test_CC_paired_2x2(n)
```

Arguments

n the observed table (a 2x2 matrix)

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
McNemar_asymptotic_test_CC_paired_2x2(bentur_2009)
McNemar_asymptotic_test_CC_paired_2x2(cavo_2012)
McNemar_asymptotic_test_CC_paired_2x2(ezra_2010)
```

`McNemar_asymptotic_test_paired_2x2`*The McNemar asymptotic test*

Description

The McNemar asymptotic test

Described in Chapter 8 "The Paired 2x2 Table"

Usage

```
McNemar_asymptotic_test_paired_2x2(n)
```

Arguments

`n` the observed table (a 2x2 matrix)

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
McNemar_asymptotic_test_paired_2x2(bentur_2009)
McNemar_asymptotic_test_paired_2x2(cavo_2012)
McNemar_asymptotic_test_paired_2x2(ezra_2010)
```

`McNemar_exact_cond_test_paired_2x2`*The McNemar exact conditional test*

Description

The McNemar exact conditional test

Described in Chapter 8 "The Paired 2x2 Table"

Usage

```
McNemar_exact_cond_test_paired_2x2(n)
```

Arguments

`n` the observed table (a 2x2 matrix)

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
McNemar_exact_cond_test_paired_2x2(bentur_2009)
McNemar_exact_cond_test_paired_2x2(cavo_2012)
McNemar_exact_cond_test_paired_2x2(ezra_2010)
```

McNemar_exact_unconditional_test_paired_2x2

The McNemar exact unconditional test

Description

The McNemar exact unconditional test

Described in Chapter 8 "The Paired 2x2 Table"

Usage

```
McNemar_exact_unconditional_test_paired_2x2(
  n,
  gamma = 1e-04,
  num_pi_values = 1000L
)
```

Arguments

<code>n</code>	the observed table (a 2x2 matrix)
<code>gamma</code>	parameter for the Berger and Boos procedure (default=0.0001; gamma=0: no adj)
<code>num_pi_values</code>	number of values to use in the partition of the nuisance parameter space (default=1000)

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Note

Somewhat crude code with maximization over a simple partition of the nuisance parameter space into 'num_pi_values' equally spaced values. The number may be changed. This method could be improved with a better algorithm for the maximization; however, it works well for most purposes. Try `showplot=1` to get an indication of the precision. A refinement of the maximization can be done with a manual restriction of the parameter space.

Examples

```
McNemar_exact_unconditional_test_paired_2x2(bentur_2009)
## Not run:
  McNemar_exact_unconditional_test_paired_2x2(cavo_2012, gamma = 0)
  McNemar_exact_unconditional_test_paired_2x2(ezra_2010)

## End(Not run)
```

McNemar_midP_test_paired_2x2
The McNemar mid-P test

Description

The McNemar mid-P test

Described in Chapter 8 "The Paired 2x2 Table"

Usage

```
McNemar_midP_test_paired_2x2(n)
```

Arguments

n the observed table (a 2x2 matrix)

Value

An object of the [contingencytables_result](#) class, basically a subclass of [base::list\(\)](#). Use the [utils::str\(\)](#) function to see the specific elements returned.

Examples

```
McNemar_midP_test_paired_2x2(bentur_2009)
McNemar_midP_test_paired_2x2(cavo_2012)
McNemar_midP_test_paired_2x2(ezra_2010)
```

Mee_asymptotic_score_CI_2x2

The Mee asymptotic score confidence interval for the difference between probabilities

Description

The Mee asymptotic score confidence interval for the difference between probabilities

Described in Chapter 4 "The 2x2 Table"

Usage

```
Mee_asymptotic_score_CI_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# An RCT of high vs standard dose of epinephrine (Perondi et al., 2004):
Mee_asymptotic_score_CI_2x2(perondi_2004)

# The association between CHRNA4 genotype and XFS (Ritland et al., 2007):
Mee_asymptotic_score_CI_2x2(ritland_2007)
```

MidP_binomial_test_1x2

The mid-P binomial test for the binomial probability (pi)

Description

The mid-P binomial test for the binomial probability (pi) $H_0: \pi = \pi_0$ vs $H_A: \pi \neq \pi_0$ (two-sided) Described in Chapter 2 "The 1x2 Table and the Binomial Distribution"

Usage

```
MidP_binomial_test_1x2(X, n, pi0)
```

Arguments

<code>X</code>	the number of successes
<code>n</code>	the total number of observations
<code>pi0</code>	a given probability

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# The number of 1st order male births (Singh et al. 2010, adapted)
MidP_binomial_test_1x2(singh_2010["1st", "X"], singh_2010["1st", "n"], pi0 = .5)
# The number of 2nd order male births (Singh et al. 2010, adapted)
MidP_binomial_test_1x2(singh_2010["2nd", "X"], singh_2010["2nd", "n"], pi0 = .5)
# The number of 3rd order male births (Singh et al. 2010, adapted)
MidP_binomial_test_1x2(singh_2010["3rd", "X"], singh_2010["3rd", "n"], pi0 = .5)
# The number of 4th order male births (Singh et al. 2010, adapted)
MidP_binomial_test_1x2(singh_2010["4th", "X"], singh_2010["4th", "n"], pi0 = .5)
# Ligarden et al. (2010, adapted)
MidP_binomial_test_1x2(ligarden_2010["X"], ligarden_2010["n"], pi0 = .5)
```

MidP_multinomial_test_1xc

The mid-P multinomial test for multinomial probabilities

Description

The mid-P multinomial test for multinomial probabilities

Described in Chapter 3 "The 1xc Table and the Multinomial Distribution"

Usage

```
MidP_multinomial_test_1xc(n, pi0)
```

Arguments

<code>n</code>	the observed counts (a 1xc vector, where c is the number of categories)
<code>pi0</code>	given probabilities (a 1xc vector)

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Genotype counts for SNP rs 6498169 in RA patients
MidP_multinomial_test_1xc(n = snp6498169$complete$n, pi0 = snp6498169$complete$pi0)

# subset of 10 patients
MidP_multinomial_test_1xc(n = snp6498169$subset$n, pi0 = snp6498169$subset$pi0)
```

MiettinenNurminen_asymptotic_score_CI_difference_2x2

The Miettinen-Nurminen asymptotic score confidence interval for the

Description

The Miettinen-Nurminen asymptotic score confidence interval for the difference between probabilities

Described in Chapter 4 "The 2x2 Table"

Usage

```
MiettinenNurminen_asymptotic_score_CI_difference_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# An RCT of high vs standard dose of epinephrine (Perondi et al., 2004):
MiettinenNurminen_asymptotic_score_CI_difference_2x2(perondi_2004)
# The association between CHRNA4 genotype and XFS (Ritland et al., 2007):
MiettinenNurminen_asymptotic_score_CI_difference_2x2(ritland_2007)
```

MiettinenNurminen_asymptotic_score_CI_OR_2x2

The Miettinen-Nurminen asymptotic score CI for the odds ratio

Description

The Miettinen-Nurminen asymptotic score confidence interval for the odds ratio

Described in Chapter 4 "The 2x2 Table"

Usage

```
MiettinenNurminen_asymptotic_score_CI_OR_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of [base::list\(\)](#). Use the [utils::str\(\)](#) function to see the specific elements returned.

Examples

```
# A case-control study of GADA exposure on IPEX syndrome (Lampasona et al., 2013)
MiettinenNurminen_asymptotic_score_CI_OR_2x2(lampasona_2013)
# The association between CHRNA4 genotype and XFS (Ritland et al., 2007)
MiettinenNurminen_asymptotic_score_CI_OR_2x2(ritland_2007)
```

MiettinenNurminen_asymptotic_score_CI_ratio_2x2

The Miettinen-Nurminen asymptotic score confidence interval for the ratio of probabilities

Description

The Miettinen-Nurminen asymptotic score confidence interval for the ratio of probabilities

Described in Chapter 4 "The 2x2 Table"

Usage

```
MiettinenNurminen_asymptotic_score_CI_ratio_2x2(n, alpha = 0.05)
```


Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# An RCT of high vs standard dose of epinephrine (Perondi et al., 2004)
MiettinenNurminen_asymptotic_score_CI_ratio_2x2(perondi_2004)
# The association between CHRNA4 genotype and XFS (Ritland et al., 2007)
MiettinenNurminen_asymptotic_score_CI_ratio_2x2(ritland_2007)
```

mills_graubard_1987	<i>Alcohol consumption and malformations</i>
---------------------	--

Description

Alcohol consumption and malformations

Usage

```
mills_graubard_1987
```

Format

An object of class `matrix` (inherits from `array`) with 5 rows and 2 columns.

References

Mills and Graubard (1987)

ML_estimates	<i>Calculate ML estimates</i>
--------------	-------------------------------

Description

Calculate ML estimates

Usage

```
ML_estimates(...)
```

Arguments

... arguments passed to methods

Note

This function has little use to the user, it is exported for conformity to R package standards.

ML_estimates_and_CIs_stratified_2x2	<i>Maximum likelihood estimates with CIs of the grouping and strata effects</i>
-------------------------------------	---

Description

Maximum likelihood estimates with CIs of the grouping and strata effects

Described in Chapter 10 "Stratified 2x2 Tables and Meta-Analysis"

Usage

```
ML_estimates_and_CIs_stratified_2x2(n, link = "log", alpha = 0.05)
```

Arguments

n	the observed table (a 2x2xk matrix, where k is the number of strata)
link	the link function ('linear', 'log', or 'logit')
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the [utils::str\(\)](#) function to see the specific elements returned.

Examples

```
# Smoking and lung cancer (Doll and Hill, 1950)
ML_estimates_and_CIs_stratified_2x2(doll_hill_1950)

# Prophylactic use of Lidocaine in myocardial infarction (Hine et al., 1989)
ML_estimates_and_CIs_stratified_2x2(hine_1989)
```

MOVER_R_Wilson_CI_OR_2x2

The MOVER-R Wilson confidence interval for the odds ratio

Description

The MOVER-R Wilson confidence interval for the odds ratio

Described in Chapter 4 "The 2x2 Table"

Usage

```
MOVER_R_Wilson_CI_OR_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# A case-control study of GADA exposure on IPEX syndrome (Lampasona et al., 2013):
MOVER_R_Wilson_CI_OR_2x2(lampasona_2013)

# The association between CHRNA4 genotype and XFS (Ritland et al., 2007):
MOVER_R_Wilson_CI_OR_2x2(ritland_2007)
```

MOVER_R_Wilson_CI_ratio_2x2

The MOVER-R Wilson confidence interval for the ratio of probabilities

Description

The MOVER-R Wilson confidence interval for the ratio of probabilities

Described in Chapter 4 "The 2x2 Table"

Usage

```
MOVER_R_Wilson_CI_ratio_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of [base::list\(\)](#). Use the [utils::str\(\)](#) function to see the specific elements returned.

Examples

```
# An RCT of high vs standard dose of epinephrine (Perondi et al., 2004)
MOVER_R_Wilson_CI_ratio_2x2(perondi_2004)

# The association between CHRNA4 genotype and XFS (Ritland et al., 2007)
MOVER_R_Wilson_CI_ratio_2x2(ritland_2007)
```

MOVER_Wilson_score_CI_paired_2x2

The MOVER Wilson score confidence interval for the ratio of paired probabilities

Description

The MOVER Wilson score confidence interval for the ratio of paired probabilities

Described in Chapter 8 "The Paired 2x2 Table"

Usage

```
MOVER_Wilson_score_CI_paired_2x2(n, alpha = 0.05)
```

Arguments

n the observed counts (a 2x2 matrix)
 alpha the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
MOVER_Wilson_score_CI_paired_2x2(bentur_2009)
MOVER_Wilson_score_CI_paired_2x2(cavo_2012)
```

Newcombe_hybrid_score_CI_2x2

The Newcombe hybrid score confidence interval for the difference between probabilities

Description

The Newcombe hybrid score confidence interval for the difference between probabilities
 Described in Chapter 4 "The 2x2 Table"

Usage

```
Newcombe_hybrid_score_CI_2x2(n, alpha = 0.05)
```

Arguments

n the observed counts (a 2x2 matrix)
 alpha the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# An RCT of high vs standard dose of epinephrine (Perondi et al., 2004)
Newcombe_hybrid_score_CI_2x2(perondi_2004)

# The association between CHRNA4 genotype and XFS (Ritland et al., 2007)
Newcombe_hybrid_score_CI_2x2(ritland_2007)
```

Newcombe_square_and_add_CI_paired_2x2

The Newcombe square-and-add confidence interval for the difference

Description

The Newcombe square-and-add confidence interval for the difference between paired probabilities.
Described in Chapter 8 "The Paired 2x2 Table"

Usage

```
Newcombe_square_and_add_CI_paired_2x2(n, alpha = 0.05)
```

Arguments

n	the observed table (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Airway hyper-responsiveness before and after stem cell transplantation
# (Bentur et al., 2009)
Newcombe_square_and_add_CI_paired_2x2(bentur_2009)

# Complete response before and after consolidation therapy
# (Cavo et al., 2012)
Newcombe_square_and_add_CI_paired_2x2(cavo_2012)
```

Pearson_chi_squared_test_1xc

The Pearson chi-squared test for multinomial probabilities

Description

The Pearson chi-squared test for multinomial probabilities
Described in Chapter 3 "The 1xc Table and the Multinomial Distribution"

Usage

```
Pearson_chi_squared_test_1xc(n, pi0)
```

Arguments

`n` the observed counts (a 1xc vector, where c is the number of categories)
`pi0` given probabilities (a 1xc vector)

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Genotype counts for SNP rs 6498169 in RA patients
Pearson_chi_squared_test_1xc(n = snp6498169$complete$n, pi0 = snp6498169$complete$pi0)
# subset of 10 patients
Pearson_chi_squared_test_1xc(n = snp6498169$subset$n, pi0 = snp6498169$subset$pi0)
```

Pearson_chi_squared_test_2x2

The Pearson chi-squared test for association in 2x2 tables

Description

The Pearson chi-squared test for association in 2x2 tables
 Described in Chapter 4 "The 2x2 Table"

Usage

```
Pearson_chi_squared_test_2x2(n)
```

Arguments

`n` the observed counts (a 2x2 matrix)

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Example: A lady tasting a cup of tea
Pearson_chi_squared_test_2x2(tea)

# Example: Perondi et al. (2004)
Pearson_chi_squared_test_2x2(perondi_2004)

# Example: Lampasona et al. (2013)
Pearson_chi_squared_test_2x2(lampasona_2013)
```

```
# Example: Ritland et al. (2007)
Pearson_chi_squared_test_2x2(ritland_2007)
```

Pearson_chi_squared_test_CC_2x2

The Pearson chi-squared test for association in 2x2 tables

Description

The Pearson chi-squared test for association in 2x2 tables
with continuity correction

Described in Chapter 4 "The 2x2 Table"

Usage

```
Pearson_chi_squared_test_CC_2x2(n)
```

Arguments

n the observed counts (a 2x2 matrix)

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Example: A lady tasting a cup of tea
Pearson_chi_squared_test_CC_2x2(tea)

# Example: Perondi et al. (2004)
Pearson_chi_squared_test_CC_2x2(perondi_2004)

# Example: Lampasona et al. (2013)
Pearson_chi_squared_test_CC_2x2(lampasona_2013)

# Example: Ritland et al. (2007)
Pearson_chi_squared_test_CC_2x2(ritland_2007)
```

`Pearson_correlation_coefficient_rxc`*The Pearson correlation coefficient*

Description

The Pearson correlation coefficient

Described in Chapter 7 "The rxc Table"

Usage

```
Pearson_correlation_coefficient_rxc(  
  n,  
  a = seq_len(nrow(n)),  
  b = seq_len(ncol(n)),  
  alpha = 0.05  
)
```

Arguments

<code>n</code>	the observed table (an rxc matrix)
<code>a</code>	scores assigned to the rows
<code>b</code>	scores assigned to the columns
<code>alpha</code>	the nominal significance level, used to compute a 100(1-alpha) confidence interval

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the [utils::str\(\)](#) function to see the specific elements returned.

Examples

```
Pearson_correlation_coefficient_rxc(table_7.7)  
Pearson_correlation_coefficient_rxc(table_7.8)  
Pearson_correlation_coefficient_rxc(table_7.9)
```

Pearson_correlation_coefficient_rxc_bca

The Pearson correlation coefficient with the bias-corrected and accelerated

Description

The Pearson correlation coefficient with the bias-corrected and accelerated bootstrap confidence interval
Described in Chapter 7 "The rxc Table"

Usage

```
Pearson_correlation_coefficient_rxc_bca(
  n,
  nboot = 10000,
  a = seq_len(nrow(n)),
  b = seq_len(ncol(n)),
  alpha = 0.05
)
```

Arguments

n	the observed table (an rxc matrix)
nboot	number of bootstrap samples
a	scores assigned to the rows
b	scores assigned to the columns
alpha	the nominal significance level, used to compute a 100(1-alpha) confidence interval

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
set.seed(3509)
Pearson_correlation_coefficient_rxc_bca(table_7.7, nboot = 800)
Pearson_correlation_coefficient_rxc_bca(table_7.8, nboot = 200)
## Not run:
  Pearson_correlation_coefficient_rxc_bca(table_7.9)

## End(Not run)
```

Pearson_LR_homogeneity_test_stratified_2x2

The Pearson chi-squared and likelihood ratio tests for homogeneity over strata

Description

The Pearson chi-squared and likelihood ratio tests for homogeneity over strata
Described in Chapter 10 "Stratified 2x2 Tables and Meta-Analysis"

Usage

```
Pearson_LR_homogeneity_test_stratified_2x2(n, link = "logit")
```

Arguments

n	the observed table (a 2x2xk matrix, where k is the number of strata)
link	the link function ('linear', 'log', or 'logit')

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Smoking and lung cancer (Doll and Hill, 1950)
Pearson_LR_homogeneity_test_stratified_2x2(doll_hill_1950)

# Prophylactic use of Lidocaine in myocardial infarction (Hine et al., 1989)
Pearson_LR_homogeneity_test_stratified_2x2(hine_1989)
```

Pearson_LR_tests_cum_OR_2xc

The Pearson chi-squared and likelihood ratio tests for cumulative ORs in 2xc tables

Description

The Pearson chi-squared and likelihood ratio tests for cumulative ORs in 2xc tables
Described in Chapter 6 "The Ordered 2xc Table"

Usage

```
Pearson_LR_tests_cum_OR_2xc(n, direction = "decreasing")
```

Arguments

`n` the observed counts (a 2xc matrix)
`direction` the direction of column probabilities ("increasing" or "decreasing")

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Postoperative nausea (Lydersen et al., 2012a)
Pearson_LR_tests_cum_OR_2xc(lydersen_2012a)
```

Pearson_LR_tests_rxc	<i>The Pearson chi-squared and likelihood ratio tests for association in rxc tables</i>
----------------------	---

Description

The Pearson chi-squared and likelihood ratio tests for association in rxc tables
 Described in Chapter 7 "The rxc Table"

Usage

```
Pearson_LR_tests_rxc(n)
```

Arguments

`n` the observed counts (an rxc matrix)

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Examples from Chapter 5 (ordered rx2 tables)

## Alcohol consumption and malformations (Mills and Graubard, 1987):
Pearson_LR_tests_rxc(mills_graubard_1987)

## Elevated troponin T levels in stroke patients (Indredavik et al., 2008):
Pearson_LR_tests_rxc(indredavik_2008)

# Examples from Chapter 6 (ordered 2xc tables)
## The Adolescent Placement Study (Fontanella et al., 2008):
```

```

Pearson_LR_tests_rxc(fontanella_2008)

## Postoperative nausea (Lydersen et al., 2012a):
Pearson_LR_tests_rxc(lydersen_2012a)

# Examples from Chapter 7 (unordered rxc tables)

## Treatment for ear infection (van Balen et al., 2003):
Pearson_LR_tests_rxc(table_7.3)

## Psychiatric diagnoses vs PA (Mangerud et al., 2004):
Pearson_LR_tests_rxc(table_7.4)

## Psychiatric diag. vs BMI (Mangerud et al., 2004):
Pearson_LR_tests_rxc(table_7.5)

```

```
Pearson_LR_tests_unspecific_ordering_rx2
```

The Pearson chi-squared and likelihood ratio tests for unspecific ordering in rx2 tables

Description

The Pearson chi-squared and likelihood ratio tests for unspecific ordering in rx2 tables. Described in Chapter 5 "The Ordered rx2 Table". May also be used for 2xc tables, after flipping rows and columns (i.e. if `n` is a 2xc table, call this function with `n'` (the transpose of `n`) as the first argument).

Usage

```
Pearson_LR_tests_unspecific_ordering_rx2(n, direction)
```

Arguments

<code>n</code>	the observed counts (an rx2 matrix)
<code>direction</code>	the direction of the success probabilities ("increasing" or "decreasing")

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the [utils::str\(\)](#) function to see the specific elements returned.

Examples

```

# Chapter 5: Alcohol consumption and malformations (Mills and Graubard, 1987)
Pearson_LR_tests_unspecific_ordering_rx2(mills_graubard_1987, "increasing")

# Chapter 5: Elevated troponin T levels in stroke patients (Indredavik et al., 2008)
Pearson_LR_tests_unspecific_ordering_rx2(indredavik_2008, "decreasing")

```

```
# Chapter 6: Postoperative nausea (Lydersen et al., 2012a)
Pearson_LR_tests_unspecific_ordering_rx2(t(lydersen_2012a), "decreasing")
```

```
Pearson_LR_test_common_effect_stratified_2x2
```

The Pearson chi-squared and likelihood ratio tests of a common difference

Description

The Pearson chi-squared and likelihood ratio tests of a common difference between probabilities (link = 'linear'), ratio of probabilities (link = 'log'), or odds ratio (link = 'logit')

Described in Chapter 10 "Stratified 2x2 Tables and Meta-Analysis"

Usage

```
Pearson_LR_test_common_effect_stratified_2x2(n, link = "logit")
```

Arguments

n	the observed table (a 2x2xk matrix, where k is the number of strata)
link	the link function ('linear', 'log', or 'logit')

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Smoking and lung cancer (Doll and Hill, 1950)
Pearson_LR_test_common_effect_stratified_2x2(doll_hill_1950)

# Prophylactic use of Lidocaine in myocardial infarction (Hine et al., 1989)
Pearson_LR_test_common_effect_stratified_2x2(hine_1989)
```

Pearson_residuals_rxc *The Pearson residuals and the standardized Pearson residuals*

Description

The Pearson residuals and the standardized Pearson residuals
Described in Chapter 7 "The rxc Table"

Usage

```
Pearson_residuals_rxc(n)
```

Arguments

n the observed counts (an rxc matrix)

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
## Treatment for ear infection (van Balen et al., 2003):
Pearson_residuals_rxc(table_7.3)

## Psychiatric diagnoses vs PA (Mangerud et al., 2004):
Pearson_residuals_rxc(table_7.4)

## Psychiatric diag. vs BMI (Mangerud et al., 2004):
Pearson_residuals_rxc(table_7.5)
```

perondi_2004 *An RCT of high vs standard dose of epinephrine*

Description

An RCT of high vs standard dose of epinephrine

Usage

```
perondi_2004
```

Format

An object of class `matrix` (inherits from `array`) with 2 rows and 2 columns.

References

Perondi et al. (2004)

peterson_2007	<i>Pretherapy susceptibility of pathogens</i>
---------------	---

Description

Pretherapy susceptibility of pathogens

Usage

peterson_2007

Format

An object of class `matrix` (inherits from `array`) with 4 rows and 4 columns.

References

Peterson et al. (2007)

Peto_homogeneity_test_stratified_2x2	<i>The Peto test for homogeneity of odds ratios over strata</i>
--------------------------------------	---

Description

The Peto test for homogeneity of odds ratios over strata

Described in Chapter 10 "Stratified 2x2 Tables and Meta-Analysis"

Usage

Peto_homogeneity_test_stratified_2x2(n)

Arguments

n the observed table (a 2x2xk matrix, where k is the number of strata)

Examples

```
# Smoking and lung cancer (Doll and Hill, 1950)
Peto_homogeneity_test_stratified_2x2(doll_hill_1950)
```

```
# Prophylactic use of Lidocaine in myocardial infarction (Hine et al., 1989)
Peto_homogeneity_test_stratified_2x2(hine_1989)
```

Peto_OR_estimate_stratified_2x2

The Peto estimate of the common odds ratio across strata

Description

The Peto estimate of the common odds ratio across strata

Described in Chapter 10 "Stratified 2x2 Tables and Meta-Analysis"

Usage

```
Peto_OR_estimate_stratified_2x2(n)
```

Arguments

n the observed table (a 2x2xk matrix, where k is the number of strata)

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Smoking and lung cancer (Doll and Hill, 1950)
Peto_OR_estimate_stratified_2x2(doll_hill_1950)
```

```
# Prophylactic use of Lidocaine in myocardial infarction (Hine et al., 1989)
Peto_OR_estimate_stratified_2x2(hine_1989)
```

PriceBonett_approximate_Bayes_CI_2x2

The Price-Bonett approximate Bayes confidence interval for the ratio of probabilities

Description

The Price-Bonett approximate Bayes confidence interval for the ratio of probabilities

Described in Chapter 4 "The 2x2 Table"

Usage

```
PriceBonett_approximate_Bayes_CI_2x2(n, a = 1.25, b = 2.5, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
a, b	parameters of the beta distribution
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# An RCT of high vs standard dose of epinephrine (Perondi et al., 2004)
PriceBonett_approximate_Bayes_CI_2x2(perondi_2004)

# The association between CHRNA4 genotype and XFS (Ritland et al., 2007)
PriceBonett_approximate_Bayes_CI_2x2(ritland_2007)
```

```
print.contingencytables_result
```

Output from a contingency tables method

Description

Output from a contingency tables method

Usage

```
## S3 method for class 'contingencytables_result'
print(x, as_list = FALSE, ...)
```

Arguments

x	The output from a function from the <code>contingencytables</code> package
as_list	Print the elements of x as a list
...	unused (kept for consistency with the generic <code>base::print()</code>)

QuesenberryHurst_Wilson_score_CIs_1xc

The Quesenberry-Hurst Wilson score simultaneous intervals for the multinomial probabilities

Description

The Quesenberry-Hurst Wilson score simultaneous intervals for the multinomial probabilities (with Scheffe adjustment)

Described in Chapter 3 "The 1xc Table and the Multinomial Distribution"

Usage

```
QuesenberryHurst_Wilson_score_CIs_1xc(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 1xc vector, where c is the number of categories)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Genotype counts for SNP rs 6498169 in RA patients
QuesenberryHurst_Wilson_score_CIs_1xc(n = snp6498169$complete$n)
```

RBG_test_and_CI_stratified_2x2

The RBG test and CI for a common odds ratio

Description

The RBG test and CI for a common odds ratio

(A Wald-type test and CI based on the Mantel-Haenszel estimate)

Described in Chapter 10 "Stratified 2x2 Tables and Meta-Analysis"

Usage

```
RBG_test_and_CI_stratified_2x2(n, alpha = 0.05)
```

Arguments

`n` the observed table (a 2x2xk matrix, where k is the number of strata)
`alpha` the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Smoking and lung cancer (Doll and Hill, 1950)
RBG_test_and_CI_stratified_2x2(doll_hill_1950)

# Prophylactic use of Lidocaine in myocardial infarction (Hine et al., 1989)
RBG_test_and_CI_stratified_2x2(hine_1989)
```

`ritland_2007`*The association between CHRNA4 genotype and XFS*

Description

The association between CHRNA4 genotype and XFS

Usage

```
ritland_2007
```

Format

An object of class `matrix` (inherits from `array`) with 2 rows and 2 columns.

References

Ritland et al. (2007)

Scheffe_type_CIs_paired_cxc	<i>Scheffe-type confidence intervals for differences of marginal probabilities</i>
-----------------------------	--

Description

Scheffe-type confidence intervals for differences of marginal probabilities
Described in Chapter 9 "The Paired kxk Table"

Usage

Scheffe_type_CIs_paired_cxc(n, alpha = 0.05)

Arguments

n the observed table (a cxc matrix)
alpha the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Pretherapy susceptibility of pathogens (Peterson et al., 2007)
Scheffe_type_CIs_paired_cxc(peterson_2007)
```

Scheffe_type_CIs_rxc	<i>The Scheffe-type simultaneous confidence intervals for the differences $\pi_{1li} - \pi_{1lj}$</i>
----------------------	--

Description

The Scheffe-type simultaneous confidence intervals for the differences $\pi_{1li} - \pi_{1lj}$
Described in Chapter 7 "The rxc Table"

Usage

Scheffe_type_CIs_rxc(n, alpha = 0.05)

Arguments

n the observed counts (an rx2 vector)
alpha the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Example: Treatment for ear infection
Scheffe_type_CIs_rxc(table_7.3)
```

Score_test_1x2	<i>The score test for the binomial probability (pi)</i>
----------------	---

Description

The score test for the binomial probability (pi) $H_0: \pi = \pi_0$ vs $H_A: \pi \neq \pi_0$ (two-sided) Described in Chapter 2 "The 1x2 Table and the Binomial Distribution"

Usage

```
Score_test_1x2(X, n, pi0)
```

Arguments

- X the number of successes
- n the total number of observations
- pi0 a given probability

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# The number of 1st order male births (Singh et al. 2010, adapted)
Score_test_1x2(singh_2010["1st", "X"], singh_2010["1st", "n"], pi0 = .5)
# The number of 2nd order male births (Singh et al. 2010, adapted)
Score_test_1x2(singh_2010["2nd", "X"], singh_2010["2nd", "n"], pi0 = .5)
# The number of 3rd order male births (Singh et al. 2010, adapted)
Score_test_1x2(singh_2010["3rd", "X"], singh_2010["3rd", "n"], pi0 = .5)
# The number of 4th order male births (Singh et al. 2010, adapted)
Score_test_1x2(singh_2010["4th", "X"], singh_2010["4th", "n"], pi0 = .5)
# Ligarden et al. (2010, adapted)
Score_test_1x2(ligarden_2010["X"], ligarden_2010["n"], pi0 = .5)
```

 Score_test_and_CI_marginal_mean_scores_paired_cxc

Score test and CI marginal mean scores paired CxC

Description

The score test and confidence interval for the difference between marginal mean scores Described in Chapter 9 "The Paired cxc Table"

Usage

```
Score_test_and_CI_marginal_mean_scores_paired_cxc(
  n,
  a = seq_len(nrow(n)),
  alpha = 0.05
)
```

Arguments

n	the observed table (a cxc matrix)
a	scores assigned to the outcome categories
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# A comparison between serial and retrospective measurements
# (Fischer et al., 1999)
a <- c(8, 3.5, 0, -3.5, -8)
Score_test_and_CI_marginal_mean_scores_paired_cxc(fischer_1999, a)
```

 Score_test_CC_1x2

The score test with continuity correction for the

Description

The score test with continuity correction for the binomial probability (π). H_0 : $\pi = \pi_0$ vs H_A : $\pi \neq \pi_0$ (two-sided). Described in Chapter 2 "The 1x2 Table and the Binomial Distribution"

Usage

```
Score_test_CC_1x2(X, n, pi0)
```

Arguments

X	the number of successes
n	the total number of observations
pi0	a given probability

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# The number of 1st order male births (Singh et al. 2010, adapted)
Score_test_CC_1x2(singh_2010["1st", "X"], singh_2010["1st", "n"], pi0 = .5)
# The number of 2nd order male births (Singh et al. 2010, adapted)
Score_test_CC_1x2(singh_2010["2nd", "X"], singh_2010["2nd", "n"], pi0 = .5)
# The number of 3rd order male births (Singh et al. 2010, adapted)
Score_test_CC_1x2(singh_2010["3rd", "X"], singh_2010["3rd", "n"], pi0 = .5)
# The number of 4th order male births (Singh et al. 2010, adapted)
Score_test_CC_1x2(singh_2010["4th", "X"], singh_2010["4th", "n"], pi0 = .5)
# Ligarden et al. (2010, adapted)
Score_test_CC_1x2(ligarden_2010["X"], ligarden_2010["n"], pi0 = .5)
```

Score_test_for_effect_in_the_probit_model_2xc

Score test for effect in the cumulative probit model

Description

The score test for effect in the cumulative probit model described in Chapter 6 "The Ordered 2xc Table"

Usage

```
Score_test_for_effect_in_the_probit_model_2xc(n, alphahat0)
```

Arguments

n	the observed counts (a 2xc matrix)
alphahat0	a column vector with c-1 estimated coefficients (α_j) under the null hypothesis ($\beta = 0$)

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Note

Must give the alphahats under the null hypothesis as input, because Matlab does not calculate an intercept-only probit model (and this may apply to R code as well). alphahat0 can be calculated in, for instance, Stata.

Examples

```
# The Adolescent Placement Study (Fontanella et al., 2008)
alphahat0 <- c(-1.246452, -0.5097363, 0.2087471)
Score_test_for_effect_in_the_probit_model_2xc(fontanella_2008, alphahat0)

# Postoperative nausea (Lydersen et al., 2012a)
alphahat0 <- c(-0.1923633, 0.5588396, 1.271953)
Score_test_for_effect_in_the_probit_model_2xc(lydersen_2012a, alphahat0)
```

score_test_statistic	<i>Calculate ML estimates</i>
----------------------	-------------------------------

Description

Calculate ML estimates

Usage

```
score_test_statistic(...)
```

Arguments

... arguments passed to methods

Note

This function has little use to the user, it is exported for conformity to R package standards.

singh_2010_1	<i>The number of n-th order male births</i>
--------------	---

Description

The number of n-th order male births

Usage

```
singh_2010
```

Format

An object of class `data.frame` with 4 rows and 2 columns.

References

Singh et al. (2010)

snp6498169	<i>Genotype counts for SNP rs 6498169 in RA patients</i>
------------	--

Description

Genotype counts for SNP rs 6498169 in RA patients

Usage

snp6498169

Format

An object of class `list` of length 2.

Spearman_correlation_coefficient_rxc	<i>The Spearman correlation coefficient</i>
--------------------------------------	---

Description

The Spearman correlation coefficient
Described in Chapter 7 "The rxc Table"

Usage

`Spearman_correlation_coefficient_rxc(n, alpha = 0.05)`

Arguments

n	the observed table (an rxc matrix)
alpha	the nominal significance level, used to compute a 100(1-alpha)% confidence interval

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Spearman_correlation_coefficient_rxc(table_7.7)
Spearman_correlation_coefficient_rxc(table_7.8)
Spearman_correlation_coefficient_rxc(table_7.9)
```

```
Spearman_correlation_coefficient_rxc_bca
```

The Spearman correlation coefficient with the bias-corrected and accelerated

Description

The Spearman correlation coefficient with the bias-corrected and accelerated bootstrap confidence interval
Described in Chapter 7 "The rxc Table"

Usage

```
Spearman_correlation_coefficient_rxc_bca(n, nboot = 10000, alpha = 0.05)
```

Arguments

n	the observed table (an rxc matrix)
nboot	number of bootstrap samples
alpha	the nominal significance level, used to compute a 100(1-alpha) confidence interval

Value

An object of the [contingencytables_result](#) class, basically a subclass of [base::list\(\)](#). Use the [utils::str\(\)](#) function to see the specific elements returned.

Examples

```
set.seed(2921)
Spearman_correlation_coefficient_rxc_bca(table_7.7, nboot = 800)
Spearman_correlation_coefficient_rxc_bca(table_7.8, nboot = 200)
## Not run:
  Spearman_correlation_coefficient_rxc_bca(table_7.9)

## End(Not run)
```

stratified_2x2_tables *Stratified 2x2 tables*

Description

Stratified 2x2 tables

Usage

```
stratified_2x2_tables(n, alpha = 0.05)
```

Arguments

n the observed table (a 2x2xk matrix, where k is the number of strata)
alpha the nominal level, e.g. 0.05 for 95% CIs

Value

NULL. This function should be called for its printed output

Examples

```
# Smoking and lung cancer (Doll and Hill, 1950)
stratified_2x2_tables(doll_hill_1950)

# Prophylactice use of Lidocaine in myocardial infarction (Hine et al., 1989)
stratified_2x2_tables(hine_1989)
```

Stuart_test_paired_cxc

The Stuart test for marginal homogeneity

Description

The Stuart test for marginal homogeneity
Described in Chapter 9 "The Paired cxc Table"

Usage

```
Stuart_test_paired_cxc(n)
```

Arguments

n the observed table (a cxc matrix)

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Pretherapy susceptibility of pathogens (Peterson et al., 2007)
Stuart_test_paired_cxc(peterson_2007)
```

table_7.3	<i>Treatment for ear infection</i>
-----------	------------------------------------

Description

Status after 21 days treatment of the ear infection acute otitis externa (Van Balen et al., 2003).

Van Balen et al. (2003) report a randomized, double-blind, controlled trial comparing three treatments for an ear infection. The numbers and proportions of patients reported cured and not cured after 21 days of treatment are summarized in Table 7.3. Because there is no ordering between the treatments, we regard Table 7.3 as an unordered 3×2 table.

Usage

```
table_7.3
vanbalen_2003
```

Format

An object of class `matrix` (inherits from `array`) with 3 rows and 2 columns.

References

Fagerland MW, Lydersen S, Laake P (2017)
 Van Balen et al. (2003)

table_7.4	<i>Psychiatric Diagnoses and Physical Activity</i>
-----------	--

Description

Psychiatric diagnoses and participation in team sports (Mangerud et al., 2014)

Table 7.4 shows the number of subjects participating in team sports within each of six psychiatric diagnoses, based on data from a study of physical activity in adolescents aged 13 to 18 years who were referred to a child and adolescent psychiatric clinic from 2009 to 2001 (Mangerud et al., 2014). The psychiatric diagnoses are unordered, and we shall treat this as an unordered 6×2 table

Usage

```
table_7.4
mangerud_2014_PA
```

Format

An object of class *matrix* (inherits from *array*) with 6 rows and 2 columns.

References

Fagerland MW, Lydersen S, Laake P (2017)

table_7.5	<i>Psychiatric diag. vs BMI with hyperkinetic disorders as reference category</i>
-----------	---

Description

Psychiatric diagnoses and weight categories based on age- and sex-adjusted BMI (Mangerud et al., 2014).

Table 7.5 shows the number of thin, normal weight, and overweight subjects within each of six psychiatric diagnoses, based on the same study as in Section 7.2.2 (Mangerud et al., 2014). Body mass index (BMI) is calculated as the weight in kg divided by the squared height in meters. In subjects aged 18 years or older, the cut-off points for being categorized as thin, normal weight, and overweight are BMI less than 18.5, BMI between 18.5 and 25, and BMI above 25, respectively. For younger subjects (below 18 years of age), the categorization was done following internationally adopted cut-off points for age and sex (Cole et al., 2000, 2007). For example, the cut-off point for being overweight at age 13 is 21.91 for males and 22.58 for females.

Usage

```
table_7.5
mangerud_2014_BMI
```

Format

An object of class *matrix* (inherits from *array*) with 6 rows and 3 columns.

References

Fagerland MW, Lydersen S, Laake P (2017)
Mangerud et al. (2014)

table_7.6	<i>Low Birth Weight vs psychiatric morbidity with control as reference category</i>
-----------	---

Description

Categories of birth weight and psychiatric problems at age 20 years (Lund et al., 2012).

Lund et al. (2012) report psychiatric morbidity in young adulthood in two low birth weight groups and a control group. The subjects were born between 1986 and 1988. The very low birth weight (VLBW) group consisted of babies born preterm with birth weight up to 1500 grams. The small for gestational age at term (SGA) group was born at term with birth weight below the 10th percentile adjusted for gestational age, sex, and parity. The control group was born at term, and was not small for gestational age. Table 7.6 shows the severity level of psychiatric problems at age 20 years. We shall regard the birth groups as unordered; however, the diagnostic groups are naturally ordered. Hence, Table 7.6 is a singly ordered 3×3 table with unordered rows and ordered columns.

Usage

```
table_7.6
lund_2012
```

Format

An object of class `matrix` (inherits from `array`) with 3 rows and 3 columns.

References

Fagerland MW, Lydersen S, Laake P (2017)
 Lund et al. (2012)

table_7.7	<i>Colorectal cancer (Table 7.7)</i>
-----------	--------------------------------------

Description

Duration of symptoms and tumor stage for patients treated for colorectal cancer (Jullumstroe et al., 2009).

Early detection and treatment of colorectal cancer is beneficial, because advanced stages of colorectal cancer have poorer prognosis. Table 7.7 displays duration of symptoms (rows) versus tumor stage (columns) in a study of 784 patients treated for colorectal cancer at a regional hospital in Norway from 1980 to 2004 (Jullumstroe et al., 2009). The rows as well as the columns are ordered, and Table 7.7 can be regarded as a doubly ordered 4×4 table.

Usage

```
table_7.7
jullumstroe_2009
```

Format

An object of class `matrix` (inherits from `array`) with 4 rows and 4 columns.

References

Fagerland MW, Lydersen S, Laake P (2017)
Jullumstroe et al. (2009)

table_7.8	<i>Breast Tumor</i>
-----------	---------------------

Description

Nuclear pleomorphism from fine needle aspiration smears and breast tumor type (Bofin et al., 2004).
Bofin et al. (2004) studied associations between different findings in fine needle aspiration (FNA) smears from breast tumors and the final histological diagnosis of tumor type in 133 patients. The aim of the study was to identify variables developed from FNA smears that could differentiate between the different tumor diagnoses. Table 7.8 presents the cross-classification of the FNA variable nuclear pleomorphism with tumor types. Both variables can be considered as ordered, with tumor type ordered from benign (as in NPBD) to most malignant (as in IDC).

Usage

```
table_7.8
bofin_2004
```

Format

An object of class `matrix` (inherits from `array`) with 3 rows and 5 columns.

References

Fagerland MW, Lydersen S, Laake P (2017)
Bofin et al. (2004)

table_7.9	<i>Self-rated health (Table 7.9)</i>
-----------	--------------------------------------

Description

Self-rated health for 12 to 17 years old adolescents in Young-HUNT 1 and four years later in Young-HUNT 2 (Breidablik et al., 2008).

In the HUNT study (Nord-Trøndelag county health survey), one of the questions is: “How is your overall health at the moment?” The outcome categories are “Very good”, “Good”, “Not very good”, and “Poor”. Table 7.9 shows the counts for the adolescents aged 12 to 17 years in 1995 to 1997 (Young-HUNT 1), and for the same individuals four years later (Young-HUNT 2; Breidablik et al. (2008)). Both the rows and the columns are ordered. In this example, it may be appropriate to regard self-rated health as an unobserved (latent) continuous variable, where only a categorized version has been observed. Table 7.9 is actually an example of a paired $c \times c$ table with ordinal data.

Usage

```
table_7.9
breidablik_2008
```

Format

An object of class *matrix* (inherits from *array*) with 4 rows and 4 columns.

References

Fagerland MW, Lydersen S, Laake P (2017)
Breidablik et al. (2008)

Tango_asymptotic_score_CI_paired_2x2	<i>The Tango asymptotic score confidence interval for the difference between paired probabilities</i>
--------------------------------------	---

Description

The Tango asymptotic score confidence interval for the difference between paired probabilities
Described in Chapter 8 "The Paired 2x2 Table"

Usage

```
Tango_asymptotic_score_CI_paired_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Airway hyper-responsiveness before and after stem cell transplantation
# (Bentur et al., 2009)
Tango_asymptotic_score_CI_paired_2x2(bentur_2009)

# Complete response before and after consolidation therapy
# (Cavo et al., 2012)
Tango_asymptotic_score_CI_paired_2x2(cavo_2012)
```

Tang_asymptotic_score_CI_paired_2x2

The Tang asymptotic score confidence interval for the ratio of paired probabilities

Description

The Tang asymptotic score confidence interval for the ratio of paired probabilities
Described in Chapter 8 "The Paired 2x2 Table"

Usage

```
Tango_asymptotic_score_CI_paired_2x2(n, alpha = 0.05)
```

Arguments

n	the observed table (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Airway hyper-responsiveness before and after stem cell transplantation
# (Bentur et al., 2009)
Tang_asymptotic_score_CI_paired_2x2(bentur_2009)

# Complete response before and after consolidation therapy
# (Cavo et al., 2012)
Tang_asymptotic_score_CI_paired_2x2(cavo_2012)
```

tea	<i>A lady tasting a cup of tea</i>
-----	------------------------------------

Description

A lady tasting a cup of tea

Usage

```
tea
```

Format

An object of class `matrix` (inherits from `array`) with 2 rows and 2 columns.

the_1x2_table_CIs	<i>The 1x2 Table CIs</i>
-------------------	--------------------------

Description

The 1x2 Table CIs

Usage

```
the_1x2_table_CIs(X, n, alpha = 0.05)
```

Arguments

- X the number of successes
- n the total number of observations
- alpha the nominal level, e.g. 0.05 for 95% CIs

Value

NULL. This function should be called for its printed output

Examples

```
# The number of 1st order male births (Singh et al. 2010)
the_1x2_table_CIs(singh_2010["1st", "X"], singh_2010["1st", "n"])
# The number of 2nd order male births (Singh et al. 2010)
the_1x2_table_CIs(singh_2010["2nd", "X"], singh_2010["2nd", "n"])
# The number of 3rd order male births (Singh et al. 2010)
the_1x2_table_CIs(singh_2010["3rd", "X"], singh_2010["3rd", "n"])
# The number of 4th order male births (Singh et al. 2010)
with(singh_2010["4th", ], the_1x2_table_CIs(X, n)) # alternative syntax
# Ligarden et al. (2010)
the_1x2_table_CIs(ligarden_2010["X"], ligarden_2010["n"])
```

the_1x2_table_tests	<i>The 1x2 Table tests</i>
---------------------	----------------------------

Description

The 1x2 Table tests

Usage

```
the_1x2_table_tests(X, n, pi0)
```

Arguments

X	the number of successes
n	the total number of observations
pi0	a given probability

Value

NULL. This function should be called for its printed output

Examples

```
# Example: The number of 1st order male births (Singh et al. 2010)
the_1x2_table_tests(singh_2010["1st", "X"], singh_2010["1st", "n"], pi0 = 0.513)
# Example: The number of 2nd order male births (Singh et al. 2010)
the_1x2_table_tests(singh_2010["2nd", "X"], singh_2010["2nd", "n"], pi0 = 0.513)
# Example: The number of 3rd order male births (Singh et al. 2010)
the_1x2_table_tests(singh_2010["3rd", "X"], singh_2010["3rd", "n"], pi0 = 0.513)
# Example: The number of 4th order male births (Singh et al. 2010)
the_1x2_table_tests(singh_2010["4th", "X"], singh_2010["4th", "n"], pi0 = 0.513)
# Example: Ligarden et al. (2010)
the_1x2_table_tests(ligarden_2010["X"], ligarden_2010["n"], pi0 = 0.5)
```

the_1xc_table_CIs	<i>The 1xc table CIs</i>
-------------------	--------------------------

Description

The 1xc table CIs

Usage

```
the_1xc_table_CIs(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 1xc vector, where c is the number of categories)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

NULL. This function should be called for its printed output

Examples

```
# Genotype counts for SNP rs 6498169 in RA patients
the_1xc_table_CIs(n = snp6498169$complete$n)
```

the_1xc_table_tests	<i>The 1xc table tests</i>
---------------------	----------------------------

Description

The 1xc table tests

Usage

```
the_1xc_table_tests(n, pi0, chacko.test = FALSE)
```

Arguments

n	the observed counts (a 1xc vector, where c is the number of categories)
pi0	given probabilities (a 1xc vector)
chacko.test	if TRUE, only performs the Chacko test

Value

NULL. This function should be called for its printed output

Examples

```
# Genotype counts for SNP rs 6498169 in RA patients
the_1xc_table_tests(n = snp6498169$complete$n, pi0 = snp6498169$complete$pi0)
# subset of 10 patients
the_1xc_table_tests(n = snp6498169$subset$n, pi0 = snp6498169$subset$pi0)
# Example for the Chacko test: Hypothetical experiment
the_1xc_table_tests(n = hypothetical, pi0 = c(0.402, 0.479, 0.119), TRUE)
```

```
the_2x2_table_CIs_difference
```

The 2x2 table CIs difference

Description

Wrapper for _CI_2x2 functions on Chapter 4.

Usage

```
the_2x2_table_CIs_difference(n, alpha = 0.05)
```

Arguments

n	frequency matrix
alpha	type I error

Value

NULL. This function should be called for its printed output

Examples

```
# An RCT of high vs standard dose of epinephrine (Perondi et al., 2004)
the_2x2_table_CIs_difference(perondi_2004)

# The association between CHRNA4 genotype and XFS (Ritland et al., 2007)
the_2x2_table_CIs_difference(ritland_2007)
```

the_2x2_table_CIs_OR *The 2x2 table CIs odds ratio*

Description

Wrapper for _CI_OR_2x2 functions on Chapter 4.

Usage

```
the_2x2_table_CIs_OR(n, alpha = 0.05)
```

Arguments

n	frequency matrix
alpha	type I error

Value

NULL. This function should be called for its printed output

Examples

```
# Example: A lady tasting a cup of tea
the_2x2_table_CIs_OR(tea)

# Example: Perondi et al. (2004)
the_2x2_table_CIs_OR(perondi_2004)

# Example: Lampasona et al. (2013)
the_2x2_table_CIs_OR(lampasona_2013)

# Example: Ritland et al. (2007)
the_2x2_table_CIs_OR(ritland_2007)
```

the_2x2_table_CIs_ratio
The 2x2 table CIs ratio

Description

Wrapper for _CI_2x2 functions on Chapter 4.

Usage

```
the_2x2_table_CIs_ratio(n, alpha = 0.05)
```

Arguments

n	frequency matrix
alpha	type I error

Value

NULL. This function should be called for its printed output

See Also

the_2x2_table_CIs_difference the_2x2_table_CIs_OR the_2x2_table_tests

Examples

```
# An RCT of high vs standard dose of epinephrine (Perondi et al., 2004)
the_2x2_table_CIs_ratio(perondi_2004)

# The association between CHRNA4 genotype and XFS (Ritland et al., 2007)
the_2x2_table_CIs_ratio(ritland_2007)
```

the_2x2_table_tests	<i>The 2x2 table tests</i>
---------------------	----------------------------

Description

Wrapper for _test_2x2 functions on Chapter 4.

Usage

```
the_2x2_table_tests(n, gamma = 1e-04)
```

Arguments

n	frequency matrix
gamma	parameter for the Berger and Boos procedure

Value

NULL. This function should be called for its printed output

Examples

```
# Example: A lady tasting a cup of tea
the_2x2_table_tests(tea)

# Example: Lampasona et al. (2013)
the_2x2_table_tests(lampasona_2013)

## Not run:
  the_2x2_table_tests(perondi_2004) # Example: Perondi et al. (2004)
  the_2x2_table_tests(ritland_2007) # Example: Ritland et al. (2007)

## End(Not run)
```

the_2xc_table	<i>The 2xc table</i>
---------------	----------------------

Description

The 2xc table

Usage

```
the_2xc_table(n, alpha = 0.05, direction = "increasing")
```

Arguments

n	the total number of observations
alpha	the nominal level, e.g. 0.05 for 95% CIs
direction	the direction of the success probabilities

Value

NULL. This function should be called for its printed output.

Examples

```
## Not run:
# The Adolescent Placement Study (Fontanella et al., 2008)
the_2xc_table(fontanella_2008)

# Postoperative nausea (Lydersen et al., 2012a)
the_2xc_table(lydersen_2012a, direction = "decreasing")

## End(Not run)
```

```
the_paired_2x2_table_CIs_difference
```

The Paired 2x2 table CIs difference

Description

The Paired 2x2 table CIs difference

Usage

```
the_paired_2x2_table_CIs_difference(n, alpha = 0.05)
```

Arguments

n	frequency matrix
alpha	type I error

Value

NULL. This function should be called for its printed output.

Examples

```
# Airway hyper-responsiveness before and after stem cell transplantation
# (Bentur et al., 2009)
the_paired_2x2_table_CIs_difference(bentur_2009)

# Complete response before and after consolidation therapy
# (Cavo et al., 2012)
the_paired_2x2_table_CIs_difference(cavo_2012)
```

```
the_paired_2x2_table_CIs_OR
```

The Paired 2x2 table CIs OR

Description

The Paired 2x2 table CIs OR

Usage

```
the_paired_2x2_table_CIs_OR(n, alpha = 0.05)
```

Arguments

n	frequency matrix
alpha	type I error

Value

NULL. This function should be called for its printed output.

Examples

```
the_paired_2x2_table_CIs_OR(ezra_2010)
```

```
the_paired_2x2_table_CIs_ratio
```

The Paired 2x2 table CIs ratio

Description

The Paired 2x2 table CIs ratio

Usage

```
the_paired_2x2_table_CIs_ratio(n, alpha = 0.05)
```

Arguments

n	frequency matrix
alpha	type I error

Value

NULL. This function should be called for its printed output.

Examples

```
# Airway hyper-responsiveness before and after stem cell transplantation
# (Bentur et al., 2009)
the_paired_2x2_table_CIs_ratio(bentur_2009)

# Complete response before and after consolidation therapy
# (Cavo et al., 2012)
the_paired_2x2_table_CIs_ratio(cavo_2012)
```

<code>the_paired_2x2_table_tests</code>
<i>The Paired 2x2 table tests</i>

Description

The Paired 2x2 table tests

Usage

```
the_paired_2x2_table_tests(n, gamma = 1e-04, num_pi_values = 1000L)
```

Arguments

<code>n</code>	frequency matrix
<code>gamma</code>	parameter for the Berger and Boos procedure
<code>num_pi_values</code>	number of values to use in the partition of the nuisance parameter space (default=1000)

Value

NULL. This function should be called for its printed output.

Examples

```
the_paired_2x2_table_tests(bentur_2009)
the_paired_2x2_table_tests(cavo_2012, gamma = 0, num_pi_values = 10)
the_paired_2x2_table_tests(ezra_2010, gamma = 0, num_pi_values = 20)
```

<code>the_paired_cxc_table_nominal</code>
<i>The Paired CxC table - nominal</i>

Description

The Paired CxC table - nominal

Usage

```
the_paired_cxc_table_nominal(n, alpha = 0.05)
```

Arguments

<code>n</code>	the total number of observations
<code>alpha</code>	the nominal level, e.g. 0.05 for 95% CIs

Value

NULL. This function should be called for its printed output.

Examples

```
# Pretherapy susceptibility of pathogens (Peterson et al., 2007)
the_paired_cxc_table_nominal(peterson_2007)
```

```
the_paired_cxc_table_ordinal
      The Paired CxC table - ordinal
```

Description

The Paired CxC table - ordinal

Usage

```
the_paired_cxc_table_ordinal(n, a = seq_len(nrow(n)), alpha = 0.05)
```

Arguments

n	the total number of observations
a	scores assigned to the outcome categories
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

NULL. This function should be called for its printed output.

Examples

```
the_paired_cxc_table_ordinal(fischer_1999, c(8, 3.5, 0, -3.5, -8))
```

the_rx2_table	<i>The rx2 table</i>
---------------	----------------------

Description

The rx2 table

Usage

```
the_rx2_table(n, alpha = 0.05, direction = "increasing", skip_exact = FALSE)
```

Arguments

n	the total number of observations
alpha	the nominal level, e.g. 0.05 for 95% CIs
direction	the direction of the success probabilities
skip_exact	If FALSE, skips the exact conditional and mid-P tests for unspecific ordering (often saves calculation time) ("increasing" or "decreasing")

Value

NULL. This function should be called for its printed output.

Examples

```
the_rx2_table(mills_graubard_1987, skip_exact = TRUE)
the_rx2_table(indredavik_2008, direction = "decreasing", skip_exact = TRUE)
```

the_rxc_table	<i>The rxc table</i>
---------------	----------------------

Description

The rxc table

Usage

```
the_rxc_table(n, alpha = 0.05, nboot = 10000)
```

Arguments

n	the total number of observations
alpha	the nominal level, e.g. 0.05 for 95% CIs
nboot	number of bootstrap samples. If 0, skips tests that use bootstrapping

Value

NULL. This function should be called for its printed output.

Examples

```
set.seed(8047)
# Unordered tables

## Treatment for ear infection (van Balen et al., 2003)
the_rxc_table(table_7.3, nboot = 200)

## Psychiatric diagnoses vs PA (Mangerud et al., 2004)
the_rxc_table(table_7.4, nboot = 0)

# Singly ordered tables

## Psychiatric diag. vs BMI (Mangerud et al., 2004)
the_rxc_table(table_7.5, nboot = 0)

## Low birth weight vs psychiatric morbidity (Lund et al., 2012)
the_rxc_table(table_7.6, nboot = 150)

# Doubly ordered tables

## Colorectal cancer (Jullumstroe et al., 2009)
the_rxc_table(table_7.7, nboot = 0)

## Breast Tumor (Bofin et al., 2004)
the_rxc_table(table_7.8, nboot = 200)

## Self-rated health (Breidablik et al., 2008)
the_rxc_table(table_7.9, nboot = 0)
```

Transformed_Blaker_exact_CI_paired_2x2

The Transformed Blaker exact confidence interval for the conditional odds ratio

Description

The Transformed Blaker exact confidence interval for the conditional odds ratio

Described in Chapter 8 "The Paired 2x2 Table"

Usage

Transformed_Blaker_exact_CI_paired_2x2(n, alpha = 0.05)

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Transformed_Blaker_exact_CI_paired_2x2(ezra_2010)
```

```
Transformed_Clopper_Pearson_exact_CI_paired_2x2
```

The Transformed Clopper-Pearson exact confidence interval for the conditional odds ratio

Description

The Transformed Clopper-Pearson exact confidence interval for the conditional odds ratio

Described in Chapter 8 "The Paired 2x2 Table"

Usage

```
Transformed_Clopper_Pearson_exact_CI_paired_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Transformed_Clopper_Pearson_exact_CI_paired_2x2(ezra_2010)
```

Transformed_Clopper_Pearson_midP_CI_paired_2x2

The Transformed Clopper-Pearson mid-P confidence interval for the conditional odds ratio

Description

The Transformed Clopper-Pearson mid-P confidence interval for the conditional odds ratio
Described in Chapter 8 "The Paired 2x2 Table"

Usage

```
Transformed_Clopper_Pearson_midP_CI_paired_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Transformed_Clopper_Pearson_midP_CI_paired_2x2(ezra_2010)
```

Transformed_Wilson_score_CI_paired_2x2

The Transformed Wilson score confidence interval for the conditional odds ratio

Description

The Transformed Wilson score confidence interval for the conditional odds ratio
Described in Chapter 8 "The Paired 2x2 Table"

Usage

```
Transformed_Wilson_score_CI_paired_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Transformed_Wilson_score_CI_paired_2x2(ezra_2010)
```

```
Trend_estimate_CI_tests_rx2
```

Trend estimate for linear and logit models

Description

Trend estimate for linear and logit models

- The Wald test and CI
- Likelihood ratio test
- The Pearson goodness-of-fit test
- Likelihood ratio (deviance) goodness-of-fit test

Described in Chapter 5 "The Ordered rx2 Table"

Usage

```
Trend_estimate_CI_tests_rx2(
  n,
  a = seq_len(nrow(n)),
  linkfunction = "logit",
  alpha = 0.05
)
```

Arguments

<code>n</code>	the observed counts (an rx2 matrix)
<code>a</code>	scores assigned to the rows
<code>linkfunction</code>	Link function for the binomial distribution see <code>?family</code> for more details
<code>alpha</code>	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Alcohol consumption and malformations (Mills and Graubard, 1987)
Trend_estimate_CI_tests_rx2(mills_graubard_1987, 1:5)

# Elevated troponin T levels in stroke patients (Indredavik et al., 2008)
Trend_estimate_CI_tests_rx2(indredavik_2008, 1:5)
```

```
Uncorrected_asymptotic_score_CI_2x2
```

The uncorrected asymptotic score confidence interval for the odds ratio

Description

The uncorrected asymptotic score confidence interval for the odds ratio
Described in Chapter 4 "The 2x2 Table"

Usage

```
Uncorrected_asymptotic_score_CI_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# A case-control study of GADA exposure on IPEX syndrome
# (Lampasona et al., 2013):
Uncorrected_asymptotic_score_CI_2x2(lampasona_2013)

# The association between CHRNA4 genotype and XFS (Ritland et al., 2007):
Uncorrected_asymptotic_score_CI_2x2(ritland_2007)
```

validateArguments	<i>Validate arguments of a function</i>
-------------------	---

Description

This is an internal function used by user-level functions to validate their arguments.

Usage

```
validateArguments(x, types = "default")
```

Arguments

x	named list containing function arguments and their values
types	named vector of types for x

Details

Accepted validation types are:

- "counts"
- "positive"
- "probability"
- "linear, log or logit"
- "MH or IV"
- "logit or probit"
- "increasing or decreasing"
- A vector of possible values

Value

Nothing if all arguments fit their type. An error message otherwise.

Note

Types are evaluated alphabetically, and errors accuse no more than one invalid argument at a time.

Author(s)

Waldir Leoncio

Examples

```
Adjusted_inv_sinh_CI_OR_2x2(ritland_2007)
## Not run: Adjusted_inv_sinh_CI_OR_2x2(-ritland_2007)
```

Wald_CI_1x2

The Wald confidence interval for the binomial probability

Description

Described in Chapter 2 "The 1x2 Table and the Binomial Distribution"

Usage

```
Wald_CI_1x2(X, n, alpha = 0.05)
```

Arguments

X	the number of successes
n	the total number of observations
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
Wald_CI_1x2(singh_2010["1st", "X"], singh_2010["1st", "n"])
Wald_CI_1x2(singh_2010["2nd", "X"], singh_2010["2nd", "n"])
Wald_CI_1x2(singh_2010["3rd", "X"], singh_2010["3rd", "n"])
with(singh_2010["4th", ], Wald_CI_1x2(X, n)) # alternative syntax
Wald_CI_1x2(ligarden_2010["X"], ligarden_2010["n"]) # Ligarden et al. (2010)
```

Wald_CI_2x2

The Wald confidence interval for the difference between probabilities

Description

The Wald confidence interval for the difference between probabilities
 Described in Chapter 4 "The 2x2 Table"

Usage

```
Wald_CI_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# An RCT of high vs standard dose of epinephrine (Perondi et al., 2004):
Wald_CI_2x2(n = perondi_2004)
# The association between CHRNA4 genotype and XFS (Ritland et al., 2007):
Wald_CI_2x2(n = ritland_2007)
```

Wald_CI_AgrestiMin_paired_2x2

The Wald confidence interval for the difference between paired probabilities

Description

The Wald confidence interval for the difference between paired probabilities with the pseudo-frequency adjustment suggested by Agresti and Min (2005)
Described in Chapter 8 "The Paired 2x2 Table"

Usage

```
Wald_CI_AgrestiMin_paired_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Airway hyper-responsiveness before and after stem cell transplantation
# (Bentur et al., 2009)
Wald_CI_AgrestiMin_paired_2x2(bentur_2009)

# Complete response before and after consolidation therapy
# (Cavo et al., 2012)
Wald_CI_AgrestiMin_paired_2x2(cavo_2012)
```

Wald_CI_BonettPrice_paired_2x2

The Wald confidence interval for the difference between paired probabilities

Description

The Wald confidence interval for the difference between paired probabilities with the pseudo-frequency adjustment suggested by Bonett and Price(2012) Described in Chapter 8 "The Paired 2x2 Table"

Usage

```
Wald_CI_BonettPrice_paired_2x2(n, alpha = 0.05)
```

Arguments

n the observed counts (a 2x2 matrix)
alpha the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of [base::list\(\)](#). Use the [utils::str\(\)](#) function to see the specific elements returned.

Examples

```
# Airway hyper-responsiveness before and after stem cell transplantation
# (Bentur et al., 2009)
Wald_CI_BonettPrice_paired_2x2(bentur_2009)

# Complete response before and after consolidation therapy
# (Cavo et al., 2012)
Wald_CI_BonettPrice_paired_2x2(cavo_2012)
```

Wald_CI_CC_1x2

The Wald CI with CC for the binomial probability

Description

The Wald confidence interval with continuity correction for the binomial probability. Described in Chapter 2 "The 1x2 Table and the Binomial Distribution"

Usage

```
Wald_CI_CC_1x2(X, n, alpha = 0.05)
```

Arguments

X	the number of successes
n	the total number of observations
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# The number of 1st order male births (Singh et al. 2010)
Wald_CI_CC_1x2(singh_2010["1st", "X"], singh_2010["1st", "n"])
# The number of 2nd order male births (Singh et al. 2010)
Wald_CI_CC_1x2(singh_2010["2nd", "X"], singh_2010["2nd", "n"])
# The number of 3rd order male births (Singh et al. 2010)
Wald_CI_CC_1x2(singh_2010["3rd", "X"], singh_2010["3rd", "n"])
# The number of 4th order male births (Singh et al. 2010)
with(singh_2010["4th", ], Wald_CI_CC_1x2(X, n)) # alternative syntax
# Ligarden et al. (2010)
Wald_CI_CC_1x2(ligarden_2010["X"], ligarden_2010["n"])
```

Wald_CI_CC_2x2

The Wald confidence interval for the difference between probabilities

Description

The Wald confidence interval for the difference between probabilities with Yates's continuity correction. Described in Chapter 4 "The 2x2 Table"

Usage

```
Wald_CI_CC_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# An RCT of high vs standard dose of epinephrine (Perondi et al., 2004)
Wald_CI_CC_2x2(perondi_2004)

# The association between CHRNA4 genotype and XFS (Ritland et al., 2007)
Wald_CI_CC_2x2(ritland_2007)
```

Wald_CI_diff_CC_paired_2x2

The Wald confidence interval for the difference between paired probabilities

Description

The Wald confidence interval for the difference between paired probabilities with continuity correction

Described in Chapter 8 "The Paired 2x2 Table"

Usage

```
Wald_CI_diff_CC_paired_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of [base::list\(\)](#). Use the [utils::str\(\)](#) function to see the specific elements returned.

Examples

```
# Airway hyper-responsiveness before and after stem cell transplantation
# (Bentur et al., 2009)
Wald_CI_diff_CC_paired_2x2(bentur_2009)

# Complete response before and after consolidation therapy
# (Cavo et al., 2012)
Wald_CI_diff_CC_paired_2x2(cavo_2012)
```

Wald_CI_diff_paired_2x2

The Wald confidence interval for the difference between paired probabilities

Description

The Wald confidence interval for the difference between paired probabilities

Described in Chapter 8 "The Paired 2x2 Table"

Usage

```
Wald_CI_diff_paired_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of [base::list\(\)](#). Use the [utils::str\(\)](#) function to see the specific elements returned.

Examples

```
# Airway hyper-responsiveness before and after stem cell transplantation
# (Bentur et al., 2009)
Wald_CI_diff_paired_2x2(bentur_2009)

# Complete response before and after consolidation therapy
# (Cavo et al., 2012)
Wald_CI_diff_paired_2x2(cavo_2012)
```

Wald_CI_OR_Laplace_paired_2x2

The Wald confidence interval for the conditional odds ratio with Laplace adjustment

Description

The Wald confidence interval for the conditional odds ratio with Laplace adjustment

Described in Chapter 8 "The Paired 2x2 Table"

Usage

```
Wald_CI_OR_Laplace_paired_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of [base::list\(\)](#). Use the [utils::str\(\)](#) function to see the specific elements returned.

Examples

```
Wald_CI_OR_Laplace_paired_2x2(ezra_2010)
```

Wald_CI_OR_paired_2x2 *The Wald confidence interval for the conditional odds ratio*

Description

The Wald confidence interval for the conditional odds ratio
Described in Chapter 8 "The Paired 2x2 Table"

Usage

```
Wald_CI_OR_paired_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of [base::list\(\)](#). Use the [utils::str\(\)](#) function to see the specific elements returned.

Examples

```
Wald_CI_OR_paired_2x2(ezra_2010)
```

Wald_CI_ratio_paired_2x2

The Wald confidence interval for the ratio of paired probabilities

Description

The Wald confidence interval for the ratio of paired probabilities

Described in Chapter 8 "The Paired 2x2 Table"

Usage

```
Wald_CI_ratio_paired_2x2(n, alpha = 0.05)
```

Arguments

n	the observed counts (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Airway hyper-responsiveness before and after stem cell transplantation
# (Bentur et al., 2009)
Wald_CI_ratio_paired_2x2(bentur_2009)

# Complete response before and after consolidation therapy
# (Cavo et al., 2012)
Wald_CI_ratio_paired_2x2(cavo_2012)
```

Wald_test_1x2

The Wald test for the binomial probability (pi)

Description

The Wald test for the binomial probability (π)

H_0 : $\pi = \pi_0$ vs H_A : $\pi \neq \pi_0$ (two-sided)

Usage

```
Wald_test_1x2(X, n, pi0)
```

Arguments

X	the number of successes
n	the total number of observations
pi0	a given probability

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# The number of 1st order male births (adapted from Singh et al. 2010)
Wald_test_1x2(singh_2010["1st", "X"], singh_2010["1st", "n"], pi0 = 0.1)
# The number of 2nd order male births (adapted from Singh et al. 2010)
Wald_test_1x2(singh_2010["2nd", "X"], singh_2010["2nd", "n"], pi0 = 0.1)
# The number of 3rd order male births (adapted from Singh et al. 2010)
Wald_test_1x2(singh_2010["3rd", "X"], singh_2010["3rd", "n"], pi0 = 0.1)
# The number of 4th order male births (adapted from Singh et al. 2010)
Wald_test_1x2(singh_2010["4th", "X"], singh_2010["4th", "n"], pi0 = 0.1)
# Ligarden et al. (2010)
Wald_test_1x2(ligarden_2010["X"], ligarden_2010["n"], pi0 = 0.1)
```

Wald_test_and_CI_common_diff_stratified_2x2

The Wald test and CI for a common difference between probabilities

Description

The Wald test and CI for a common difference between probabilities based on either the Mantel-Haenszel or inverse variance estimate

Described in Chapter 10 "Stratified 2x2 Tables and Meta-Analysis"

Usage

```
Wald_test_and_CI_common_diff_stratified_2x2(
  n,
  estimatetype = "MH",
  alpha = 0.05
)
```

Arguments

n	the observed table (a 2x2xk matrix, where k is the number of strata)
estimatetype	Mantel-Haenszel or inverse variance estimate ('MH' or 'IV')
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Smoking and lung cancer (Doll and Hill, 1950)
Wald_test_and_CI_common_diff_stratified_2x2(doll_hill_1950)

# Prophylactice use of Lidocaine in myocardial infarction (Hine et al., 1989)
Wald_test_and_CI_common_diff_stratified_2x2(hine_1989)
```

Wald_test_and_CI_common_ratio_stratified_2x2

The Wald test and CI for a common ratio of probabilities

Description

The Wald test and CI for a common ratio of probabilities
 based on either the Mantel-Haenszel or inverse variance estimate
 Described in Chapter 10 "Stratified 2x2 Tables and Meta-Analysis"

Usage

```
Wald_test_and_CI_common_ratio_stratified_2x2(
  n,
  estimatetype = "MH",
  alpha = 0.05
)
```

Arguments

<code>n</code>	the observed table (a 2x2xk matrix, where k is the number of strata)
<code>estimatetype</code>	Mantel-Haenszel or inverse variance estimate ('MH' or 'IV')
<code>alpha</code>	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the `contingencytables_result` class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Smoking and lung cancer (Doll and Hill, 1950)
Wald_test_and_CI_common_ratio_stratified_2x2(doll_hill_1950)

# Prophylactice use of Lidocaine in myocardial infarction (Hine et al., 1989)
Wald_test_and_CI_common_ratio_stratified_2x2(hine_1989)
```

```
Wald_test_and_CI_marginal_mean_ranks_paired_cxc
```

*The Wald test and confidence interval for the difference between
marginal mean ranks / ridits*

Description

The Wald test and confidence interval for the difference between marginal mean ranks / ridits

Described in Chapter 9 "The Paired cxc Table"

Usage

```
Wald_test_and_CI_marginal_mean_ranks_paired_cxc(n, alpha = 0.05)
```

Arguments

n	the observed table (a cxc matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of [base::list\(\)](#). Use the [utils::str\(\)](#) function to see the specific elements returned.

Examples

```
# A comparison between serial and retrospective measurements
# (Fischer et al., 1999)
Wald_test_and_CI_marginal_mean_ranks_paired_cxc(fischer_1999)
```

Wald_test_and_CI_marginal_mean_scores_paired_cxc

The Wald test and confidence interval for the difference between marginal mean scores

Description

The Wald test and confidence interval for the difference between marginal mean scores

Described in Chapter 9 "The Paired cxc Table"

Usage

```
Wald_test_and_CI_marginal_mean_scores_paired_cxc(
  n,
  a = seq_len(nrow(n)),
  alpha = 0.05
)
```

Arguments

n	the observed table (a cxc matrix)
a	scores assigned to the outcome categories
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# A comparison between serial and retrospective measurements
# (Fischer et al., 1999)
a <- c(8, 3.5, 0, -3.5, -8)
Wald_test_and_CI_marginal_mean_scores_paired_cxc(fischer_1999, a)
```

Wald_test_CC_1x2

The Wald test with continuity correction for the binomial probability

Description

The Wald test with continuity correction for the binomial probability (π)

H_0 : $\pi = \pi_0$ vs H_A : $\pi \neq \pi_0$ (two-sided)

Usage

```
Wald_test_CC_1x2(X, n, pi0)
```

Arguments

X	the number of successes
n	the total number of observations
pi0	a given probability

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# The number of 1st order male births (adapted from Singh et al. 2010)
Wald_test_CC_1x2(singh_2010["1st", "X"], singh_2010["1st", "n"], pi0 = 0.1)
# The number of 2nd order male births (adapted from Singh et al. 2010)
Wald_test_CC_1x2(singh_2010["2nd", "X"], singh_2010["2nd", "n"], pi0 = 0.1)
# The number of 3rd order male births (adapted from Singh et al. 2010)
Wald_test_CC_1x2(singh_2010["3rd", "X"], singh_2010["3rd", "n"], pi0 = 0.1)
# The number of 4th order male births (adapted from Singh et al. 2010)
Wald_test_CC_1x2(singh_2010["4th", "X"], singh_2010["4th", "n"], pi0 = 0.1)
# Ligarden et al. (2010)
Wald_test_CC_1x2(ligarden_2010["X"], ligarden_2010["n"], pi0 = 0.1)
```

Wilson_score_CI_1x2	<i>The Wilson score confidence interval</i>
---------------------	---

Description

The Wilson score confidence interval

Usage

```
Wilson_score_CI_1x2(X, n, alpha = 0.05)
```

Arguments

X	the number of successes
n	the total number of observations
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

References

Reference Wilson EB (1927) Probable inference, the law of succession, and statistical inference. Journal of the American Statistical Association 22:209-212

Examples

```
# birth order 1, Singh et al. (2010)
Wilson_score_CI_1x2(singh_2010["1st", "X"], singh_2010["1st", "n"])
# birth order 2, Singh et al. (2010)
Wilson_score_CI_1x2(singh_2010["2nd", "X"], singh_2010["2nd", "n"])
# birth order 3, Singh et al. (2010)
Wilson_score_CI_1x2(singh_2010["3rd", "X"], singh_2010["3rd", "n"])
# birth order 4, Singh et al. (2010)
with(singh_2010["4th", ], Wilson_score_CI_1x2(X, n)) # alternative syntax
# Ligarden (2010)
Wilson_score_CI_1x2(ligarden_2010["X"], ligarden_2010["n"])
```

Wilson_score_CI_CC_1x2

The Wilson score confidence interval with continuity correction for the binomial probability

Description

Described in Chapter 2 "The 1x2 Table and the Binomial Distribution"

Usage

```
Wilson_score_CI_CC_1x2(X, n, alpha = 0.05)
```

Arguments

X	the number of successes
n	the total number of observations
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the [utils::str\(\)](#) function to see the specific elements returned.

References

Reference Wilson EB (1927) Probable inference, the law of succession, and statistical inference. Journal of the American Statistical Association; 22:209-212

Examples

```
# The number of 1st order male births (Singh et al. 2010)
Wilson_score_CI_CC_1x2(singh_2010["1st", "X"], singh_2010["1st", "n"])
# The number of 2nd order male births (Singh et al. 2010)
Wilson_score_CI_CC_1x2(singh_2010["2nd", "X"], singh_2010["2nd", "n"])
# The number of 3rd order male births (Singh et al. 2010)
Wilson_score_CI_CC_1x2(singh_2010["3rd", "X"], singh_2010["3rd", "n"])
# The number of 4th order male births (Singh et al. 2010)
with(singh_2010["4th", ], Wilson_score_CI_CC_1x2(X, n)) # alternative syntax
# Ligarden et al. (2010)
Wilson_score_CI_CC_1x2(ligarden_2010["X"], ligarden_2010["n"])
```

Woolf_logit_CI_2x2	<i>The Woolf logit confidence interval for the odds ratio</i>
--------------------	---

Description

The Woolf logit confidence interval for the odds ratio

Described in Chapter 4 "The 2x2 Table"

Usage

```
Woolf_logit_CI_2x2(n, alpha = 0.05)
```

Arguments

n	the observed table (a 2x2 matrix)
alpha	the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# A case-control study of GADA exposure on IPEX syndrome
# (Lampasona et al., 2013):
Woolf_logit_CI_2x2(lampasona_2013)

# The association between CHRNA4 genotype and XFS (Ritland et al., 2007):
Woolf_logit_CI_2x2(ritland_2007)
```

Woolf_test_and_CI_stratified_2x2

The Woolf test and CI for a common odds ratio

Description

The Woolf test and CI for a common odds ratio
 (A Wald-type test and CI based on the inverse variance estimate)
 Described in Chapter 10 "Stratified 2x2 Tables and Meta-Analysis"

Usage

```
Woolf_test_and_CI_stratified_2x2(n, alpha = 0.05)
```

Arguments

n the observed table (a 2x2xk matrix, where k is the number of strata)
 alpha the nominal level, e.g. 0.05 for 95% CIs

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Smoking and lung cancer (Doll and Hill, 1950)
Woolf_test_and_CI_stratified_2x2(doll_hill_1950)

# Prophylactice use of Lidocaine in myocardial infarction (Hine et al., 1989)
Woolf_test_and_CI_stratified_2x2(hine_1989)
```

Z_unpooled_test_2x2 *The Z-unpooled test for association in 2x2 tables*

Description

The Z-unpooled test for association in 2x2 tables
 Described in Chapter 4 "The 2x2 Table"

Usage

```
Z_unpooled_test_2x2(n)
```

Arguments

n the observed counts (a 2x2 matrix)

Value

An object of the [contingencytables_result](#) class, basically a subclass of `base::list()`. Use the `utils::str()` function to see the specific elements returned.

Examples

```
# Example: A lady tasting a cup of tea
Z_unpooled_test_2x2(tea)

# Example: Perondi et al. (2004)
Z_unpooled_test_2x2(perondi_2004)

# Example: Lampasona et al. (2013)
Z_unpooled_test_2x2(lampasona_2013)

# Example: Ritland et al. (2007)
Z_unpooled_test_2x2(ritland_2007)
```

Index

* datasets

bentur_2009, 12
cavo_2012, 23
doll_hill_1950, 43
ezra_2010, 48
fischer_1999, 48
fleiss_2003, 52
fontanella_2008, 52
hine_1989, 57
hypothetical, 58
indredavik_2008, 59
lampasona_2013, 66
ligarden_2010, 66
lydersen_2012a, 71
mills_graubard_1987, 81
perondi_2004, 95
peterson_2007, 96
ritland_2007, 100
singh_2010_1, 105
snp6498169, 106
table_7.3, 109
table_7.4, 109
table_7.5, 110
table_7.6, 111
table_7.7, 111
table_7.8, 112
table_7.9, 113
tea, 115
.onAttach, 6

Adjusted_inv_sinh_CI_OR_2x2, 6
Adjusted_inv_sinh_CI_ratio_2x2, 7
Adjusted_log_CI_2x2, 8
AgrestiCaffo_CI_2x2, 9
AgrestiCoull_CI_1x2, 9
Arcsine_CI_1x2, 10

BaptistaPike_exact_conditional_CI_2x2, 11
BaptistaPike_midP_CI_2x2, 12

base::list(), 7–20, 23, 33–38, 40–47, 49–65, 67–95, 97–104, 106, 107, 109, 114, 128–131, 133–149
base::print(), 98
bentur_2009, 12
Bhapkar_test_paired_cxc, 13
Blaker_exact_CI_1x2, 13
Blaker_exact_test_1x2, 14
Blaker_midP_CI_1x2, 15
Blaker_midP_test_1x2, 16
bofin_2004 (table_7.8), 112
BonettPrice_hybrid_Wilson_score_CI_CC_paired_2x2, 16
BonettPrice_hybrid_Wilson_score_CI_paired_2x2, 17
Bonferroni_type_CIs_paired_cxc, 18
Bonferroni_type_CIs_rxc, 18
Brant_test_2xc, 19
breidablik_2008 (table_7.9), 113
BreslowDay_homogeneity_test_stratified_2x2, 20

calc_prob, 21
calc_Pvalue_4x2, 22
calc_Pvalue_5x2, 22
calculate_limit_lower, 20
calculate_limit_upper, 21
cavo_2012, 23
Chacko_test_1xc, 23
chap1, 24
chap10, 24
chap2, 25
chap3, 26
chap4, 27
chap5, 28
chap6, 29
chap7, 30
chap8, 31
chap9, 32
ClopperPearson_exact_CI_1x2, 33

- ClopperPearson_exact_CI_1x2_beta_version, 33
- ClopperPearson_midP_CI_1x2, 34
- Cochran_Q_test_stratified_2x2, 38
- CochranArmitage_CI_rx2, 35
- CochranArmitage_exact_cond_midP_tests_rx2, 36
- CochranArmitage_MH_tests_rx2, 36
- CochranMantelHaenszel_test_stratified_2x2, 37
- contingencytables, 38, 98
- contingencytables-package (contingencytables), 38
- contingencytables_result, 7–20, 23, 33–38, 39, 40–47, 49–65, 67–95, 97–104, 106, 107, 109, 114, 128–131, 133–149
- Cornfield_exact_conditional_CI_2x2, 40
- Cornfield_midP_CI_2x2, 41
- Cumulative_models_for_2xc, 41
- Cumulative_models_for_rxc, 42
- doll_hill_1950, 43
- Exact_binomial_test_1x2, 43
- Exact_cond_midP_linear_rank_tests_2xc, 44
- Exact_cond_midP_tests_rxc, 45
- Exact_cond_midP_unspecific_ordering_rx2, 45
- Exact_multinomial_test_1xc, 46
- Exact_unconditional_test_2x2, 47
- ezra_2010, 48
- fischer_1999, 48
- Fisher_exact_test_2x2, 49
- Fisher_midP_test_2x2, 50
- FisherFreemanHalton_asymptotic_test_rxc, 49
- fleiss_2003, 52
- FleissEveritt_test_paired_cxc, 51
- FleissLevinPaik_test_paired_cxc, 51
- fontanella_2008, 52
- gamma_coefficient_rxc, 53
- gamma_coefficient_rxc_bca, 53
- Gart_adjusted_logit_CI_2x2, 54
- Gold_Wald_CIs_1xc, 55
- Goodman_Wald_CIs_1xc, 55
- Goodman_Wald_CIs_for_diffs_1xc, 56
- Goodman_Wilson_score_CIs_1xc, 57
- hine_1989, 57
- hypothetical, 58
- Independence_smoothed_logit_CI_2x2, 58
- indredavik_2008, 59
- Inv_sinh_CI_OR_2x2, 60
- Inv_sinh_CI_ratio_2x2, 60
- InverseVariance_estimate_stratified_2x2, 59
- Jeffreys_CI_1x2, 61
- JonckheereTerpstra_test_rxc, 62
- jullumstroe_2009 (table_7.7), 111
- Katz_log_CI_2x2, 62
- Kendalls_tau_b_rxc, 63
- Kendalls_tau_b_rxc_bca, 64
- Koopman_asymptotic_score_CI_2x2, 64
- KruskalWallis_asymptotic_test_rxc, 65
- lampasona_2013, 66
- ligarden_2010, 66
- linear_by_linear_test_rxc, 67
- list_functions, 67
- LR_CI_1x2, 68
- LR_test_1x2, 69
- LR_test_1xc, 69
- LR_test_2x2, 70
- lund_2012 (table_7.6), 111
- lydersen_2012a, 71
- mangerud_2014_BMI (table_7.5), 110
- mangerud_2014_PA (table_7.4), 109
- MantelHaenszel_estimate_stratified_2x2, 71
- MantelHaenszel_test_2xc, 72
- McNemar_asymptotic_test_CC_paired_2x2, 73
- McNemar_asymptotic_test_paired_2x2, 74
- McNemar_exact_cond_test_paired_2x2, 74
- McNemar_exact_unconditional_test_paired_2x2, 75
- McNemar_midP_test_paired_2x2, 76
- McNemarBowker_test_paired_cxc, 72
- Mee_asymptotic_score_CI_2x2, 77
- MidP_binomial_test_1x2, 77
- MidP_multinomial_test_1xc, 78

- MiettinenNurminen_asymptotic_score_CI_difference_2x2, [101](#)
[79](#)
 MiettinenNurminen_asymptotic_score_CI_OR_2x2, [102](#)
[80](#)
 MiettinenNurminen_asymptotic_score_CI_ratio_2x2, [103](#)
[80](#)
 mills_graubard_1987, [81](#)
 ML_estimates, [82](#)
 ML_estimates_and_CIs_stratified_2x2, [82](#)
 MOVER_R_Wilson_CI_OR_2x2, [83](#)
 MOVER_R_Wilson_CI_ratio_2x2, [84](#)
 MOVER_Wilson_score_CI_paired_2x2, [84](#)

 Newcombe_hybrid_score_CI_2x2, [85](#)
 Newcombe_square_and_add_CI_paired_2x2, [86](#)

 Pearson_chi_squared_test_1xc, [86](#)
 Pearson_chi_squared_test_2x2, [87](#)
 Pearson_chi_squared_test_CC_2x2, [88](#)
 Pearson_correlation_coefficient_rxc, [89](#)
 Pearson_correlation_coefficient_rxc_bca, [90](#)
 Pearson_LR_homogeneity_test_stratified_2x2, [91](#)
 Pearson_LR_test_common_effect_stratified_2x2, [94](#)
 Pearson_LR_tests_cum_OR_2xc, [91](#)
 Pearson_LR_tests_rxc, [92](#)
 Pearson_LR_tests_unspecific_ordering_rx2, [93](#)
 Pearson_residuals_rxc, [95](#)
 perondi_2004, [95](#)
 peterson_2007, [96](#)
 Peto_homogeneity_test_stratified_2x2, [96](#)
 Peto_OR_estimate_stratified_2x2, [97](#)
 PriceBonett_approximate_Bayes_CI_2x2, [97](#)
 print.contingencytables_result, [39](#), [40](#), [98](#)

 QuesenberryHurst_Wilson_score_CIs_1xc, [99](#)

 RBG_test_and_CI_stratified_2x2, [99](#)
 ritland_2007, [100](#)

 Scheffe_type_CIs_paired_cxc, [101](#)
 Scheffe_type_CIs_rxc, [101](#)
 Score_test_1x2, [102](#)
 Score_test_and_CI_marginal_mean_scores_paired_cxc, [103](#)
 Score_test_CC_1x2, [103](#)
 Score_test_for_effect_in_the_probit_model_2xc, [104](#)
 score_test_statistic, [105](#)
 singh_2010 (singh_2010_1), [105](#)
 singh_2010_1, [105](#)
 snp6498169, [106](#)
 Spearman_correlation_coefficient_rxc, [106](#)
 Spearman_correlation_coefficient_rxc_bca, [107](#)
 stats::uniroot(), [20](#), [21](#)
 stratified_2x2_tables, [108](#)
 Stuart_test_paired_cxc, [108](#)

 table_7.3, [109](#)
 table_7.4, [109](#)
 table_7.5, [110](#)
 table_7.6, [111](#)
 table_7.7, [111](#)
 table_7.8, [112](#)
 table_7.9, [113](#)
 Tang_asymptotic_score_CI_paired_2x2, [114](#)
 Tango_asymptotic_score_CI_paired_2x2, [113](#)
 tea, [115](#)
 the_1x2_table_CIs, [115](#)
 the_1x2_table_tests, [116](#)
 the_1xc_table_CIs, [117](#)
 the_1xc_table_tests, [117](#)
 the_2x2_table_CIs_difference, [118](#)
 the_2x2_table_CIs_OR, [119](#)
 the_2x2_table_CIs_ratio, [119](#)
 the_2x2_table_tests, [120](#)
 the_2xc_table, [121](#)
 the_paired_2x2_table_CIs_difference, [122](#)
 the_paired_2x2_table_CIs_OR, [122](#)
 the_paired_2x2_table_CIs_ratio, [123](#)
 the_paired_2x2_table_tests, [124](#)
 the_paired_cxc_table_nominal, [124](#)
 the_paired_cxc_table_ordinal, [125](#)
 the_rx2_table, [126](#)

the_rxc_table, [126](#)
Transformed_Blaker_exact_CI_paired_2x2,
 [127](#)
Transformed_Clopper_Pearson_exact_CI_paired_2x2,
 [128](#)
Transformed_Clopper_Pearson_midP_CI_paired_2x2,
 [129](#)
Transformed_Wilson_score_CI_paired_2x2,
 [129](#)
Trend_estimate_CI_tests_rx2, [130](#)

Uncorrected_asymptotic_score_CI_2x2,
 [131](#)
utils::str(), [7–20](#), [23](#), [33–38](#), [40–47](#),
 [49–65](#), [67–95](#), [97–104](#), [106](#), [107](#),
 [109](#), [114](#), [128–131](#), [133–149](#)

validateArguments, [132](#)
vanbalen_2003 (table_7.3), [109](#)

Wald_CI_1x2, [133](#)
Wald_CI_2x2, [133](#)
Wald_CI_AgrestiMin_paired_2x2, [134](#)
Wald_CI_BonettPrice_paired_2x2, [135](#)
Wald_CI_CC_1x2, [135](#)
Wald_CI_CC_2x2, [136](#)
Wald_CI_diff_CC_paired_2x2, [137](#)
Wald_CI_diff_paired_2x2, [138](#)
Wald_CI_OR_Laplace_paired_2x2, [138](#)
Wald_CI_OR_paired_2x2, [139](#)
Wald_CI_ratio_paired_2x2, [140](#)
Wald_test_1x2, [140](#)
Wald_test_and_CI_common_diff_stratified_2x2,
 [141](#)
Wald_test_and_CI_common_ratio_stratified_2x2,
 [142](#)
Wald_test_and_CI_marginal_mean_ranks_paired_cxc,
 [143](#)
Wald_test_and_CI_marginal_mean_scores_paired_cxc,
 [144](#)
Wald_test_CC_1x2, [144](#)
Wilson_score_CI_1x2, [145](#)
Wilson_score_CI_CC_1x2, [146](#)
Woolf_logit_CI_2x2, [147](#)
Woolf_test_and_CI_stratified_2x2, [148](#)

Z_unpooled_test_2x2, [148](#)