Package 'dadjokeapi'

July 22, 2025

Type Package

Title Return a Random Dad Joke

Version 1.0.2

URL https://github.com/jhollist/dadjokeapi/

BugReports https://github.com/jhollist/dadjokeapi/issues/

Maintainer Jeffrey Hollister <hollister.jeff@epa.gov>

Description What is funnier than a dad joke? A dad joke in R! This package utilizes the API for <https://icanhazdadjoke.com> and returns dad jokes from several API endpoints.

License MIT + file LICENSE

Depends R (>= 3.5.0)

Imports httr, beepr, curl, dplyr, png

LazyData true

RoxygenNote 7.1.1

Suggests testthat, mockery

NeedsCompilation no

Author Jeffrey Hollister [aut, cre],
Antoine Bichat [ctb],
Brett Langdon [cph]

Repository CRAN

Date/Publication 2021-03-01 09:20:09 UTC

Contents

groan 2
groan_id 2
groan_image 3
groan_search 3

Index **5**

groan *Function to return random dad joke*

Description

This function returns a random dad joke(s) from https://icanhazdadjoke.com. as a message and invisibly as a character.

Usage

```
groan(sting = TRUE)
```

Arguments

sting	Plays a joke sting after the joke. Sound from https://archive.org/details/Rimshot_254

Value

Invisibly returns a two item list with the first item holding the joke as a character and the second item containing the joke id as a character.

Examples

```
groan(sting = FALSE)
```

groan_id *Function to return a specific dad joke*

Description

This function returns a specific dad joke from https://icanhazdadjoke.com using its dad joke ID.

Usage

```
groan_id(joke_id)
```

Arguments

joke_id	A specific dad joke ID to return

Value

Returns a two item list with the first item holding the joke as a character and the second item containing the joke id as a character.

Examples

```
groan_id("GlGBIY0wAAd")
```

`groan_image` *Function to return a specific dad joke as an image*

Description

This function returns a specific dad joke as a png from https://icanhazdadjoke.com using its dad joke ID.

Usage

```
groan_image(joke_id)
```

Arguments

`joke_id`	A specific dad joke ID to return

Value

Returns a png array from readPNG.

Examples

```
joke_png <- groan_image("GlGBIY0wAAd")
```

`groan_search` *Function to search and return dad jokes with specific terms*

Description

This function returns a specific dad joke as a png from https://icanhazdadjoke.com using its dad joke ID.

Usage

```
groan_search(term)
```

Arguments

`term`	A term to search https://icanhazdadjoke.com

Value

Returns a tibble of joke and joke id for jokes that contain the search term.

Examples

```
groan_search(term = "cat")
```

Index

groan, 2
groan_id, 2
groan_image, 3
groan_search, 3