

Package ‘easyORtables’

July 22, 2025

Title Easy Odds Ratio Tables
Version 0.0.1
Description Creates text, 'LaTeX', Markdown, or Bootstrap-styled HTML-formatted odds ratio tables with confidence intervals for multiple logistic regression models.
License MIT + file LICENSE
Encoding UTF-8
Imports stats, knitr, kableExtra, MASS
RoxygenNote 7.3.1
NeedsCompilation no
Author Neil Mehta [aut, cre] (ORCID: <<https://orcid.org/0000-0002-1245-1103>>)
Maintainer Neil Mehta <neilmhta@gmail.com>
Repository CRAN
Date/Publication 2024-06-18 14:20:02 UTC

Contents

create_OR_table	1
Index	3

create_OR_table	<i>Create Odds Ratio Table</i>
-----------------	--------------------------------

Description

This function creates a table displaying odds ratios with confidence intervals for logistic regression models.

Usage

```
create_OR_table(  
  ...,  
  output_format = c("markdown", "latex", "html", "plaintext"),  
  bootstrap_options = NULL  
)
```

Arguments

... One or more logistic regression models.

output_format The output format for the table. Can be "markdown", "latex", "html", or "plaintext". Default is "plaintext".

bootstrap_options A character vector of Bootstrap table styles for HTML output. Default is NULL.

Value

Displays a formatted table of odds ratios with confidence intervals.

Examples

```
# Simulate data  
set.seed(123)  
dataset <- data.frame(  
  response = sample(c(0, 1), 100, replace = TRUE),  
  var1 = rnorm(100),  
  var2 = rnorm(100),  
  var3 = rnorm(100)  
)  
  
# Fit logistic regression models  
model1 <- glm(response ~ var1 + var2, family = binomial, data = dataset)  
model2 <- glm(response ~ var1 + var2 + var3, family = binomial, data = dataset)  
  
# Create OR table as plaintext  
create_OR_table(model1, model2)  
  
# Create OR table with custom bootstrap options and HTML  
create_OR_table(model1, model2, output_format="html", bootstrap_options = c("striped", "hover"))
```

Index

`create_OR_table`, [1](#)