

Package ‘experiences’

July 22, 2025

Type Package

Title Experience Research

Version 0.1.1

Description Provides convenience functions for researching experiences including user, customer, patient, employee, and other human experiences. It provides a suite of tools to simplify data exploration such as benchmarking, comparing groups, and checking for differences. The outputs translate statistical approaches in applied experience research to human readable output.

License MIT + file LICENSE

Encoding UTF-8

Imports cli, dplyr, huxtable, magrittr, scales, stringr, tibble

RoxxygenNote 7.2.1

NeedsCompilation no

Author Joe Chelladurai [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-8477-3753>>)

Maintainer Joe Chelladurai <joe.chelladurai@outlook.com>

Repository CRAN

Date/Publication 2022-10-31 14:10:12 UTC

Contents

compare_benchmark_event	2
compare_benchmark_score	3
compare_benchmark_time	3
t_dist_one_tailed	4
t_dist_two_tailed	5

Index	6
--------------	----------

`compare_benchmark_event`*Compare Probability of an Event with Benchmark*

Description

Compare Probability of an Event with Benchmark

Usage

```
compare_benchmark_event(  
  benchmark,  
  event,  
  total,  
  event_type = "",  
  notes = c("minimal", "technical")  
)
```

Arguments

<code>benchmark</code>	benchmark
<code>event</code>	event
<code>total</code>	total
<code>event_type</code>	Optional: a string describing the type of event. For example, success, failure, etc.
<code>notes</code>	whether output should contain minimal, technical, or executive type of notes.

Value

list of event rate, probability, notes

Examples

```
compare_benchmark_event(benchmark = 0.7,  
  event = 10,  
  total = 12,  
  event_type = "success",  
  notes = "minimal")
```

`compare_benchmark_score`*Compare Score with a Benchmark*

Description

Compare Score with a Benchmark

Usage

```
compare_benchmark_score(  
  data,  
  benchmark,  
  alpha,  
  tail = "one",  
  remove_missing = TRUE  
)
```

Arguments

<code>data</code>	a column or vector of scores
<code>benchmark</code>	benchmark
<code>alpha</code>	alpha
<code>tail</code>	one-tailed or two-tailed test
<code>remove_missing</code>	TRUE/FALSE remove missing values? (default is TRUE)

Value

lower_ci, upper_ci, t, probability

Examples

```
data <- 68 + 17 * scale(rnorm(20)) # 68 = mean, 17 = sd  
compare_benchmark_score(data, benchmark = 60, alpha = 0.5)
```

`compare_benchmark_time`*Compare Time with a Benchmark*

Description

Compare Time with a Benchmark

Usage

```
compare_benchmark_time(benchmark, time, alpha, remove_missing = FALSE)
```

Arguments

- benchmark benchmark
- time a column or vector of time values
- alpha alpha
- remove_missing TRUE/FALSE remove missing values?

Value

lower_ci, upper_ci, t, probability

Examples

```
compare_benchmark_time(time = c(60, 53, 70, 42, 62, 43, 81),
                          benchmark = 60,
                          alpha = 0.05)
```

t_dist_one_tailed	<i>T distribution - one-tailed</i>
-------------------	------------------------------------

Description

T distribution - one-tailed

Usage

```
t_dist_one_tailed(t_score, degrees_of_freedom)
```

Arguments

- t_score t value
- degrees_of_freedom degrees of freedom

Value

value

t_dist_two_tailed	<i>T distribution - two-tailed</i>
-------------------	------------------------------------

Description

T distribution - two-tailed

Usage

t_dist_two_tailed(t_score, degrees_of_freedom)

Arguments

t_score t value
degrees_of_freedom degrees of freedom

Value

value

Index

`compare_benchmark_event`, [2](#)
`compare_benchmark_score`, [3](#)
`compare_benchmark_time`, [3](#)

`t_dist_one_tailed`, [4](#)
`t_dist_two_tailed`, [5](#)