

Package ‘feather’

July 22, 2025

Title R Bindings to the Feather 'API'

Version 0.3.5

Description Read and write feather files, a lightweight binary columnar data store designed for maximum speed.

Encoding UTF-8

License Apache License 2.0

LazyData true

URL <https://github.com/wesm/feather>

BugReports <https://github.com/wesm/feather/issues>

LinkingTo Rcpp

Imports Rcpp, tibble (>= 2.0.0), hms

Suggests testthat

SystemRequirements little-endian platform

RoxygenNote 6.1.1

NeedsCompilation yes

Author Hadley Wickham [aut, cre],
RStudio [cph],
Feather developers [ctb] (Bundled feather library),
Google [ctb] (Bundled flatbuffers code),
LevelDB Authors [ctb]

Maintainer Hadley Wickham <hadley@rstudio.com>

Repository CRAN

Date/Publication 2019-09-15 00:10:22 UTC

Contents

feather	2
feather_metadata	2
read_feather	3

Index	4
--------------	----------

feather	<i>Access a feather store like a data frame</i>
---------	---

Description

These functions permit using a feather dataset much like a regular (read-only) data frame.

Usage

```
feather(path)
```

Arguments

path	Path to feather file
------	----------------------

Value

An object of class feather

feather_metadata	<i>Retrieve metadata about a feather file</i>
------------------	---

Description

Returns the dimensions, field names, and types; and optional dataset description.

Usage

```
feather_metadata(path)
```

Arguments

path	Path to feather file
------	----------------------

Value

A list with class "feather_metadata".

read_feather	<i>Read and write feather files.</i>
--------------	--------------------------------------

Description

Read and write feather files.

Usage

```
read_feather(path, columns = NULL)
```

```
write_feather(x, path)
```

Arguments

path	Path to feather file
columns	Columns to read (names or indexes). Default: Read all columns.
x	A data frame to write to disk

Value

Both functions return a tibble/data frame. `write_feather` invisibly returns `x` (so you can use this function in a pipeline).

Examples

```
mtcars2 <- read_feather(feather_example("mtcars.feather"))
mtcars2
```

Index

`feather`, [2](#)

`feather_metadata`, [2](#)

`read_feather`, [3](#)

`write_feather(read_feather)`, [3](#)