

Package ‘flexlsx’

July 22, 2025

Type Package

Title Exporting 'flextable' to 'xlsx' Files

Version 0.3.5

Description Exports 'flextable' objects to 'xlsx' files,
utilizing functionalities provided by 'flextable' and 'openxlsx2'.

License MIT + file LICENSE

Encoding UTF-8

Imports dplyr (>= 1.1.1), grDevices, openxlsx2 (>= 1.0.0), purrr,
Rcpp, rlang, stringi, tibble, tidyr (>= 1.0.0)

Suggests covr, gtsummary, flextable (>= 0.9.5), testthat (>= 3.0.0),
officer

Depends R (>= 4.1.0)

RoxygenNote 7.3.2

Config/testthat/edition 3

URL <https://github.com/pteridin/flexlsx>

BugReports <https://github.com/pteridin/flexlsx/issues>

LinkingTo Rcpp

NeedsCompilation yes

Author Tobias Heidler [aut, cre, cph] (ORCID:
<<https://orcid.org/0000-0001-9193-0980>>)

Maintainer Tobias Heidler <flexlsx@heidler.ovh>

Repository CRAN

Date/Publication 2025-04-25 23:20:12 UTC

Contents

ftpart_to_style_tibble	2
ft_to_style_tibble	3
ft_to_xlsx_border	3

get_dim_colwise	4
get_dim_ranges	4
get_dim_rowwise	5
handle_null_border	5
merge_resolve_type	6
prepare_color	6
style_to_hash	7
wb_add_caption	7
wb_add_flextable	8
wb_apply_border	9
wb_apply_cell_styles	9
wb_apply_content	10
wb_apply_merge	10
wb_apply_text_styles	11
wb_change_cell_width	11
wb_change_row_height	12
Index	13

ftpart_to_style_tibble	<i>Converts a flextable-part to a tibble styles</i>
------------------------	---

Description

[Experimental]
[Experimental]

Usage

```
ftpart_to_style_tibble(ft_part, part = c("header", "body", "footer"))
```

Arguments

ft_part the part of the flextable to extract the style from
part the name of the part

Value

a [tibble](#)

ft_to_style_tibble	<i>Converts a flextable to a tibble with style information</i>
--------------------	--

Description

[Experimental]

Usage

```
ft_to_style_tibble(  
  ft,  
  offset_rows = 0L,  
  offset_cols = 0L,  
  offset_caption_rows = 0L  
)
```

Arguments

ft	a flextable
offset_rows	offsets the start-row
offset_cols	offsets the start-columns
offset_caption_rows	number of rows to offset the caption by

Value

a [tibble](#)

ft_to_xlsx_border	<i>Determines the border style</i>
-------------------	------------------------------------

Description

[Experimental]

Usage

```
ft_to_xlsx_border(border_color, border_width, border_style)
```

Arguments

border_color	the color of the border
border_width	a numeric vector determining the border-width
border_style	the flextable style name of the border

Details

openxlsx2/Excel does handle borders differently than flextable. This function maps the flextable border styles to the Excel border styles.

Value

a factor of xlsx border styles

get_dim_colwise	<i>Groups each row with same style each column</i>
-----------------	--

Description

[Experimental]

Usage

get_dim_colwise(df_rows)

Arguments

df_rows [tibble](#) of row-wise aggregates style

Value

[tibble](#) of column-wise aggregates style

get_dim_ranges	<i>Retrieves dims of same style rows within same column</i>
----------------	---

Description

[Experimental]

Usage

get_dim_ranges(df_x)

Arguments

df_x styling information incl. col_id & row_id

Value

merged styles as a [tibble](#)

get_dim_rowwise	<i>Groups each column with same style each row</i>
-----------------	--

Description

[Experimental]

Usage

```
get_dim_rowwise(df_x, df_style_hashed)
```

Arguments

- df_x styling information incl. col_id & row_id
- df_style_hashed [tibble](#) of hashed style information

Value

[tibble](#) of row-wise aggregates style information

handle_null_border	<i>Where there is no border return NULL</i>
--------------------	---

Description

[Experimental]

Usage

```
handle_null_border(border_style)
```

Arguments

- border_style the openxlsx2 style of the border

Value

border_style or NULL

merge_resolve_type	<i>Determine problematic merges</i>
--------------------	-------------------------------------

Description

Determine problematic merges

Usage

```
merge_resolve_type(df_to_merge)
```

Arguments

df_to_merge The data.frame containing information about the cells to merge

Value

df_to_merge is extended by is_encapsulated and is_need_resolve

prepare_color	<i>Prepares the color for content style</i>
---------------	---

Description

Converts a color name to the hexadecimal RGB-value Removes "transparent" color

Usage

```
prepare_color(color_name)
```

Arguments

color_name The name of the color

Value

The hexadecimal RGB-value

style_to_hash	<i>Retrieves hashed style information</i>
---------------	---

Description

[Experimental]

Converts each style to an individual integer hash for easy comparison and aggregation.

Usage

```
style_to_hash(df_x)
```

Arguments

df_x	styling information incl. col_id & row_id
------	---

Value

hashed style information as a [tibble](#)

wb_add_caption	<i>Adds a caption to an excel file</i>
----------------	--

Description

[Experimental]

Usage

```
wb_add_caption(  
  wb,  
  sheet,  
  ft,  
  offset_rows = offset_rows,  
  offset_cols = offset_cols  
)
```

Arguments

wb	an openxlsx2 workbook
sheet	an openxlsx2 workbook sheet
ft	a flextable
offset_rows	zero-based row offset
offset_cols	zero-based column offset

wb_add_flextable	<i>Adds a flextable to an openxlsx2 workbook sheet</i>
------------------	--

Description

[Experimental]

Usage

```
wb_add_flextable(
  wb,
  sheet = openxlsx2::current_sheet(),
  ft,
  start_col = 1,
  start_row = 1,
  offset_caption_rows = 0L,
  dims = NULL
)
```

Arguments

wb	an openxlsx2 workbook
sheet	an openxlsx2 workbook sheet
ft	a flextable
start_col	a vector specifying the starting column to write to.
start_row	a vector specifying the starting row to write to.
offset_caption_rows	number of rows to offset the caption by
dims	Spreadsheet dimensions that will determine start_col and start_row: "A1", "A1:B2", "A:B"

Value

an openxlsx2 workbook

Examples

```
if (requireNamespace("flextable", quietly = TRUE)) {
  # Create a flextable
  ft <- flextable::as_flextable(table(mtcars[, c("am", "cyl")]))

  # Create a workbook
  wb <- openxlsx2::wb_workbook()$add_worksheet("mtcars")

  # Add flextable to workbook
  wb <- wb_add_flextable(wb, "mtcars", ft)
```



```
# Workbook can now be saved wb$save(),  
# opened wb$open() - or removed  
rm(wb)  
}
```

wb_apply_border	<i>Applies the border styles</i>
-----------------	----------------------------------

Description

[Experimental]

Usage

```
wb_apply_border(wb, sheet, df_style)
```

Arguments

wb	the workbook
sheet	the sheet of the workbook
df_style	the styling tibble from ft_to_style_tibble

wb_apply_cell_styles	<i>Applies the cell styles</i>
----------------------	--------------------------------

Description

[Experimental]

Usage

```
wb_apply_cell_styles(wb, sheet, df_style)
```

Arguments

wb	the workbook
sheet	the sheet of the workbook
df_style	the styling tibble from ft_to_style_tibble

wb_apply_content	<i>Applies the content</i>
------------------	----------------------------

Description

[Experimental]

Usage

```
wb_apply_content(wb, sheet, df_style)
```

Arguments

- wb the [workbook](#)
- sheet the sheet of the workbook
- df_style the styling tibble from [ft_to_style_tibble](#)

wb_apply_merge	<i>Merges cells</i>
----------------	---------------------

Description

[Experimental]

Usage

```
wb_apply_merge(wb, sheet, df_style)
```

Arguments

- wb the [workbook](#)
- sheet the sheet of the workbook
- df_style the styling tibble from [ft_to_style_tibble](#)

Value

df_style tibble

wb_apply_text_styles *Applies the text styles*

Description

[Experimental]

Usage

```
wb_apply_text_styles(wb, sheet, df_style)
```

Arguments

wb	the workbook
sheet	the sheet of the workbook
df_style	the styling tibble from ft_to_style_tibble

wb_change_cell_width *Changes the cell width*

Description

Changes the cell width

Usage

```
wb_change_cell_width(wb, sheet, ft, offset_cols)
```

Arguments

wb	an openxlsx2 workbook
sheet	an openxlsx2 workbook sheet
ft	a flextable
offset_cols	zero-based column offset

wb_change_row_height	<i>Changes the row height</i>
----------------------	-------------------------------

Description

Changes the row height

Usage

```
wb_change_row_height(wb, sheet, df_style)
```

Arguments

wb	an openxlsx2 workbook
sheet	an openxlsx2 workbook sheet
df_style	the styling tibble from ft_to_style_tibble

Index

flextable, [3](#)
ft_to_style_tibble, [3](#), [9–12](#)
ft_to_xlsx_border, [3](#)
ftpart_to_style_tibble, [2](#)

get_dim_colwise, [4](#)
get_dim_ranges, [4](#)
get_dim_rowwise, [5](#)

handle_null_border, [5](#)

merge_resolve_type, [6](#)

prepare_color, [6](#)

style_to_hash, [7](#)

tibble, [2–5](#), [7](#)

wb_add_caption, [7](#)
wb_add_flextable, [8](#)
wb_apply_border, [9](#)
wb_apply_cell_styles, [9](#)
wb_apply_content, [10](#)
wb_apply_merge, [10](#)
wb_apply_text_styles, [11](#)
wb_change_cell_width, [11](#)
wb_change_row_height, [12](#)
workbook, [9–11](#)