

Package ‘fr’

July 22, 2025

Title Frictionless Standards

Version 0.5.2

Description A ``tabular-data-resource" (<<https://specs.frictionlessdata.io/tabular-data-resource/>>) is a simple format to describe a singular tabular data resource such as a CSV file. It includes support both for metadata such as author and title and a schema to describe the data, for example the types of the fields/columns in the data. Create a tabular-data-resource by providing a data.frame and specifying metadata. Write and read tabular-data-resources to and from disk.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.2

Imports cli, purrr, vroom, S7 (>= 0.1.1), tibble, tidyselect, yaml, dplyr, rlang

Suggests testthat (>= 3.0.0), withr, fs, knitr, rmarkdown, curl

Config/testthat/edition 3

Config/testthat/parallel true

URL <https://github.com/cole-brokamp/fr>,
<https://cole-brokamp.github.io/fr/>

BugReports <https://github.com/cole-brokamp/fr/issues>

VignetteBuilder knitr

NeedsCompilation no

Author Cole Brokamp [aut, cre, cph] (ORCID:
<<https://orcid.org/0000-0002-0289-3151>>),
Tomasz Kalinowski [ctb]

Maintainer Cole Brokamp <cole@colebrokamp.com>

Repository CRAN

Date/Publication 2024-11-07 19:10:02 UTC

Contents

as_data_frame	2
as_fr_field	3
as_fr_tdr	4
as_list	4
dplyr_methods	5
is_fr_field	6
read_fr_tdr	7
update_field	7
write_fr_tdr	8
Index	9

as_data_frame	Coerce a fr_tdr object into a data frame
---------------	--

Description

Equivalent to `as.data.frame()`; directly using `tibble::as_tibble()` also works because its input is first coerced with `as.data.frame()`

Usage

```
as_data_frame(x, ...)
```

Arguments

- x a [fr_tdr](#) object
- ... ignored

Value

a data frame

Examples

```
as_fr_tdr(mtcars, name = "mtcars") |>  
  as_data_frame()
```

as_fr_field	<i>Coerce character, factor, numeric, logical, and Date vectors into fr_field objects</i>
-------------	---

Description

The supported classes of R objects are converted to the corresponding frictionless type:

R class	fr type
character()	string
factor()	string (with <code>enum(constraints = levels(x))</code>)
numeric(), integer()	number
logical()	boolean
Date	date

Usage

```
as_fr_field(x, ...)
```

Arguments

x	a character, factor, numeric, integer, logical, or Date vector
...	<dynamic-dots> required (name) and optional (title, description) field descriptors

Value

a [fr_field](#) object

Examples

```
as_fr_field(1:10, "example_integer") # -> frictionless number
as_fr_field((1:10) * 0.1, "example_double") # -> frictionless number
as_fr_field(letters, "example_character") # -> frictionless string
as_fr_field(factor(letters), "example_factor") # -> frictionless string with enum constraints
as_fr_field(c(TRUE, FALSE, TRUE), "example_logical") # -> frictionless boolean
as_fr_field(as.Date(c("2023-04-23", "2004-12-31")), "example_date") # -> frictionless date
```

as_fr_tdr	Coerce a data frame into a <code>fr_tdr</code> object
-----------	---

Description

Coerce a data frame into a `fr_tdr` object

Usage

```
as_fr_tdr(x, ...)
```

Arguments

x	a data.frame
...	<dynamic-dots> required (name) and optional tabular-data-resource properties (e.g., path, version, title, homepage, description)

Details

Use the `.template` argument to provide a template `fr_tdr` object from which table-specific (i.e. "name", "version", "title", "homepage", "description") and field-specific metadata will be copied; note that all metadata provided in `...` will be ignored if this argument is provided

Value

a `fr_tdr` object

Examples

```
as_fr_tdr(mtcars, name = "mtcars")
S7::prop(as_fr_tdr(mtcars, name = "mtcars"), "schema")
```

as_list	Coerce a <code>fr_tdr</code> object into a list
---------	---

Description

equivalent to `as.list()`

Usage

```
as_list(x, ...)
```

Arguments

x	a <code>fr_tdr</code> object
...	ignored

Value

a list representing the frictionless metadata descriptor

Examples

```
as_fr_tdr(mtcars, name = "mtcars") |>
  as_list()
```

dplyr_methods

dplyr methods for fr_tdr objects

Description

Some basic dplyr functions are re-implemented here for `fr_tdr` objects. The input is converted with `as.data.frame()` before being passed to the dplyr function. The resulting tibble object is converted back into a `fr_tdr` object, matching table- and field-specific metadata where possible by using `as_fr_tdr()` and specifying the `.template` argument.

dplyr	fr
<code>mutate()</code>	<code>fr_mutate()</code>
<code>rename()</code>	<code>fr_rename()</code>
<code>select()</code>	<code>fr_select()</code>
<code>filter()</code>	<code>fr_filter()</code>
<code>summarise()</code>	<code>fr_summarise()</code>
<code>arrange()</code>	<code>fr_arrange()</code>

Usage

```
fr_mutate(x, ...)

fr_rename(x, ...)

fr_select(x, ...)

fr_filter(x, ...)

fr_summarize(x, ...)

fr_arrange(x, ...)
```

Arguments

```
x          a fr_tdr object
...        passed to the underlying dplyr function
```

Value

a `fr_tdr` object

Examples

```
read_fr_tdr(fs::path_package("fr", "hamilton_poverty_2020")) |>
  fr_mutate(next_year = year + 1) |>
  fr_rename(new_year = next_year) |>
  fr_select(-new_year) |>
  fr_filter(fraction_poverty > 0.1) |>
  fr_summarize(median_poverty_fraction = median(fraction_poverty)) |>
  fr_arrange(median_poverty_fraction)
```

is_fr_field

Test if an object is a `fr_field` object

Description

Test if an object is a `fr_field` object

Usage

```
is_fr_field(x)
```

Arguments

`x` an object to test

Value

TRUE if object is a `fr_field` object, FALSE otherwise

Examples

```
is_fr_field(letters)
is_fr_field(as_fr_field(letters, "letters"))
```

read_fr_tdr	<i>read a tabular-data-resource into R</i>
-------------	--

Description

read a tabular-data-resource into R

Usage

```
read_fr_tdr(file)
```

Arguments

file	Either a path to a file, a connection, or literal data (either a single string or a raw vector). <code>file</code> can also be a character vector containing multiple filepaths or a list containing multiple connections. Files ending in <code>.gz</code>, <code>.bz2</code>, <code>.xz</code>, or <code>.zip</code> will be automatically uncompressed. Files starting with <code>http://</code>, <code>https://</code>, <code>ftp://</code>, or <code>ftps://</code> will be automatically downloaded. Remote <code>gz</code> files can also be automatically downloaded and decompressed. Literal data is most useful for examples and tests. To be recognised as literal data, wrap the input with <code>I()</code>.
------	---

Details

A file path (or url) representing a folder that contains a "tabular-data-resource.yaml" can be used in `file`.

Value

a `fr_tdr` object

Examples

```
read_fr_tdr(fs::path_package("fr", "hamilton_poverty_2020"))
```

update_field	<i>add or update field-specific metadata in a fr_tdr object</i>
--------------	---

Description

add or update field-specific metadata in a `fr_tdr` object

Usage

```
update_field(x, field, ...)
```

Arguments

x a `fr_tdr` object
 field character name of field in x to update
 ... **table schema field descriptors** (e.g., title, description)

Value

an `fr_tdr` object containing the updated field

Examples

```

my_mtcars <-
  mtcars |>
  as_fr_tdr(name = "mtcars") |>
  update_field("mpg", title = "Miles Per Gallon")

S7::prop(my_mtcars, "schema")

```

write_fr_tdr	<i>write a fr_tdr object to disk</i>
--------------	--------------------------------------

Description

The name property of the `fr_tdr` object is used to write a frictionless tabular-data-resource to disk. For example, if `name = "my_data"`, then a folder named `my_data` would be created with (1) `my_data.csv` and (2) `tabular-data-resource.yaml`.

Usage

```
write_fr_tdr(x, dir)
```

Arguments

x a `fr_tdr` object to write to disk
 dir path to directory where tabular-data-resource folder will be created

Value

x (invisibly)

Index

`as_data_frame`, [2](#)
`as_fr_field`, [3](#)
`as_fr_tdr`, [4](#)
`as_list`, [4](#)

`dplyr_methods`, [5](#)

`fr_arrange` (`dplyr_methods`), [5](#)
`fr_field`, [3](#), [6](#)
`fr_filter` (`dplyr_methods`), [5](#)
`fr_mutate` (`dplyr_methods`), [5](#)
`fr_rename` (`dplyr_methods`), [5](#)
`fr_select` (`dplyr_methods`), [5](#)
`fr_summarize` (`dplyr_methods`), [5](#)
`fr_tdr`, [2](#), [4–8](#)

`is_fr_field`, [6](#)

`read_fr_tdr`, [7](#)

`update_field`, [7](#)

`write_fr_tdr`, [8](#)