

Package ‘jdenticon’

July 22, 2025

Title A Wrapper for the Node.js 'Jdenticon' Library

Version 0.1.1

Description A Wrapper for the Node.js 'Jdenticon' <<https://jdenticon.com/>> Library. Uses 'esbuild' <<https://esbuild.github.io/>> to reduce user dependencies.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.2.1

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

Imports fs, processx, yesno, magick, glue, jsonlite

NeedsCompilation no

Author Matt Roumaya [aut, cre, cph] (ORCID: <<https://orcid.org/0000-0002-8009-2771>>),
Richard D. Morey [ctb] (ORCID: <<https://orcid.org/0000-0001-9220-3179>>)

Maintainer Matt Roumaya <matthewroumaya@gmail.com>

Repository CRAN

Date/Publication 2023-04-24 17:10:02 UTC

Contents

jdenticon	2
jdenticon_npm_install	3
Index	4

jdenticon

Create a Jdenticon.

Description

Create a Jdenticon.

Usage

```
jdenticon(
  value = NULL,
  filePath = tempdir(),
  fileName = glue("jdenticon_{size}_{value}"),
  size = "100",
  config = NULL,
  type = "png",
  preview = interactive() && Sys.getenv("RSTUDIO") == "1",
  return_list = FALSE
)
```

Arguments

value	character Value to be converted to hexadecimal hash to render Jdenticon. Cannot contain characters that are reserved for filepaths:
filePath	character File path to save Jdenticon .png to. If NULL, defaults to current working directory.
fileName	character File name to save Jdenticon .png as. If NULL, defaults to temp_jdenticon_{value}.
size	numeric Size of Jdenticon. Default == 100.
config	list of jdenticon configuration options (see the jdenticon documentation)
type	Image type (default 'png', or 'svg')
preview	boolean Preview Jdenticon in viewer pane?
return_list	boolean Return full list object with all settings?

Value

Path to Jdenticon icon file, or (if return_list is true) a list with all parameters (including path).

Examples

```
## Not run:
jdenticon(value = 'mango')

## End(Not run)
```

jdenticon_npm_install *Install jdenticon npm dependency.*

Description

Install jdenticon npm dependency.

Usage

```
jdenticon_npm_install(force = FALSE)
```

Arguments

force	boolean If TRUE, automatically proceeds with npm installation. If FALSE (default), prompts user before proceeding with npm installation.
-------	--

Value

Updated inst/node_modules folder.

Examples

```
## Not run:  
jdenticon_npm_install(force = TRUE)  
  
## End(Not run)
```

Index

jdenticon, [2](#)

jdenticon_npm_install, [3](#)