

Package ‘journalabbr’

July 22, 2025

Type Package

Title Journal Abbreviations for BibTeX Documents

Version 0.4.3

Description Since the reference management software (such as 'Zotero', 'Mendeley') exports Bib file journal abbreviation is not detailed enough, the 'journalabbr' package only abbreviates the journal field of Bib file, and then outputs a new Bib file for generating reference format with journal abbreviation on other software (such as 'texstudio'). The abbreviation table is from 'JabRef'. At the same time, 'Shiny' application is provided to generate 'thebibliography', a reference format that can be directly used for latex paper writing based on 'Rmd' files.

License GPL (>= 3)

URL <https://github.com/zoushucai/journalabbr>

BugReports <https://github.com/zoushucai/journalabbr/issues>

Encoding UTF-8

Depends R (>= 4.3.0)

Imports data.table (>= 1.14.0), stringr (>= 1.4.0), purrr (>= 1.0.0),
httr (>= 1.4.0), shiny (>= 1.7.0), tidytable (>= 0.11.0),
stringi (>= 1.7.0)

Suggests testthat (>= 3.0.0), rmarkdown, knitr, rclipboard, tinytex,
DT, covr

RoxygenNote 7.3.1

Config/testthat/edition 3

Date 2024-02-21

NeedsCompilation no

Author ShuCai Zou [aut, cre],
Yu Chen [aut]

Maintainer ShuCai Zou <zscmoyujian@163.com>

Repository CRAN

Date/Publication 2024-02-21 14:20:02 UTC

Contents

abbr_bib	2
add_abbrtable	3
read_bib2dt	4
replace_field_journal	5
run_example	6
write_dt2bib	6
Index	7

abbr_bib	<i>Journal field abbreviation of BibTeX file.</i>
----------	---

Description

Input Bib file with complete journal, output a .bib file and return a data object.
Input Bib file with complete journal, output a .bib file, this function only carries out journal abbreviations, and the rest is output as it is.

Usage

```
abbr_bib(  
  file,  
  out.file = tempfile(fileext = ".bib"),  
  author.connect = c("nothing", "\\&", "&", "and"),  
  user.csv = "",  
  ...  
)  
  
abbr_bib_only_journal(  
  file,  
  out.file = tempfile(fileext = ".bib"),  
  user.csv = "",  
  ...  
)
```

Arguments

- file character, file path to write the .bib file.
- out.file character, file path to write the .bib file.
- author.connect character, what symbols are used to connect multiple authors, 'nothing', '\\&', '&', 'and', where 'nothing' stand for do nothing(default).
- user.csv character, csv file path, Users can customize the path of journal abbreviation. The csv file requires semicolon to segment data without header. The first column is the full name of the journal and the second column is the journal abbreviation.
- ... (generalized), Parameters from data.table::fread.

Value

output a new Bib file and return a data.table object.

Examples

```
require(journalabbr)
path <- system.file("extdata", "testfile_2.bib", package = "journalabbr", mustWork = TRUE)
temptab <- abbr_bib(file = path, out.file = tempfile(fileext = ".bib"))

# add user csv
csvpath <- system.file("extdata", "myabbr.csv", package = "journalabbr", mustWork = TRUE)
temptab1 <- abbr_bib(file = path, out.file = tempfile(fileext = ".bib"), user.csv = csvpath)

# no return value
abbr_bib_only_journal(file = path, out.file = tempfile(fileext = ".bib"), user.csv = csvpath)
```

add_abbrtable	<i>Add user's journal abbreviation table</i>
---------------	--

Description

Add user's journal abbreviation table

Usage

```
add_abbrtable(file, ...)
```

Arguments

file	character, bib file path
...	see also data.table::fread

Value

a data.table

Examples

```
csvpath <- system.file("extdata", "myabbr.csv", package = "journalabbr", mustWork = TRUE)
abbrtable_user <- add_abbrtable(file = csvpath, header = FALSE, sep = ",")
colnames(abbrtable_user)
```

read_bib2dt	<i>Parse a BibTeX file to a data.table.</i>
-------------	---

Description

The BibTeX file is read, parsed, tidied and written to a data.table.

Usage

```
read_bib2dt(file)
```

Arguments

file	character, path or URL to a bib file.
------	---------------------------------------

Details

Read, parse and collate bibtex file to form a data.table. Different BIB may produce different data.table columns.

Value

A data.table.

Author(s)

ShuCai Zou

Examples

```
# Read from .bib file:
file1 <- system.file("extdata", "testfile_1.bib", package = "journalabbr", mustWork = TRUE)
dt1 <- read_bib2dt(file1)
colnames(dt1)

file2 <- system.file("extdata", "testfile_2.bib", package = "journalabbr", mustWork = TRUE)
dt2 <- read_bib2dt(file2)
colnames(dt2)
```

replace_field_journal	<i>Replace field journal with built-in data sets and user provided data sets.</i>
-----------------------	---

Description

Replace field journal with built-in data sets and user provided data sets.

Replace field author

Usage

```
replace_field_journal(dt, abbrtable_user)

replace_field_author(
  dt,
  author.connect = c("nothing", "\\&", "&", "and")
)
```

Arguments

`dt` is data.table, the object returned by the function read_bib2dt.

`abbrtable_user` data.table, the object returned by the function add_abbrtable.

`author.connect` is character, what symbols are used to connect multiple authors, 'nothing', '\\&', '&', 'and', where 'nothing' stand for do nothing(default).

Value

data.table

data.table

Examples

```
csvpath <- system.file("extdata", "myabbr.csv", package = "journalabbr", mustWork = TRUE)
abbrtable_user <- add_abbrtable(file = csvpath, header = FALSE, sep = ",")
colnames(abbrtable_user)

file <- system.file("extdata", "testfile_2.bib", package = "journalabbr", mustWork = TRUE)
dt <- read_bib2dt(file)

newdt <- replace_field_journal(dt, abbrtable_user)
newdt1 <- replace_field_author(dt, author.connect = "and")
newdt2 <- replace_field_author(dt, author.connect = "&")
```

run_example

The Shiny Program for the 'journalabbr' Package

Description

The Shiny Program for the 'journalabbr' Package

Usage

```
run_example()
```

write_dt2bib

Export a BibTeX data.table to a .bib file.

Description

The BibTeX data.table is written to a .bib file.

Usage

```
write_dt2bib(dt, file = tempfile(fileext = ".bib"))
```

Arguments

dt	data.table, in the format as returned by read_bib2dt .
file	character, file path to write the .bib file.

Value

file as a character string, invisibly.

Examples

```
# Read from .bib file:
require(journalabbr)
file <- system.file("extdata", "testfile_2.bib", package = "journalabbr", mustWork = TRUE)
bib <- read_bib2dt(file)

# Write to .bib file:
write_dt2bib(bib, file = tempfile(fileext = ".bib"))
```

Index

abbr_bib, [2](#)
abbr_bib_only_journal (abbr_bib), [2](#)
add_abbrtable, [3](#)

read_bib2dt, [4](#), [6](#)
replace_field_author
 (replace_field_journal), [5](#)
replace_field_journal, [5](#)
run_example, [6](#)

write_dt2bib, [6](#)