

Package ‘json64’

July 22, 2025

Type Package

Title A 'Base64' Encode/Decode Package with Support for JSON
Output/Input and UTF-8

Version 0.1.3

Author Mauricio Santelices

Maintainer Mauricio Santelices <m.santelicesa@gmail.com>

Description Encode/Decode 'base64', with support for JSON format, using two functions: `j_encode()` and `j_decode()`. 'Base64' is a group of similar binary-to-text encoding schemes that represent binary data in an ASCII string format by translating it into a radix-64 representation, used when there is a need to encode binary data that needs to be stored and transferred over media that are designed to deal with textual data, ensuring that the data will remain intact and without modification during transport. <https://developer.mozilla.org/en-US/docs/Web/API/WindowBase64/Base64_encoding_and_decoding> On the other side, JSON (JavaScript Object Notation) is a lightweight data-interchange format. Easy to read, write, parse and generate. It is based on a subset of the JavaScript Programming Language. JSON is a text format that is completely language independent but uses conventions that are familiar to programmers of the C-family of languages, including C, C++, C#, Java, JavaScript, Perl, Python, and many others. JSON structure is built around name:value pairs and ordered list of values. <<https://www.json.org>> The first function, `j_encode()`, let you transform a `data.frame` or list to a 'base64' encoded JSON (or JSON string). The `j_decode()` function takes a 'base64' string (could be an encoded JSON) and transform it to a `data.frame` (or list, depending of the JSON structure).

License MIT + file LICENSE

Imports jsonlite

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

NeedsCompilation no

Repository CRAN

Date/Publication 2019-06-03 14:20:03 UTC

Contents

j_decode	2
j_encode	2
Index	4

j_decode	<i>Decoding Function</i>
----------	--------------------------

Description

Used to decode a base64 string. By default the function expects an encoded json.

Usage

```
j_decode(str, json = TRUE)
```

Arguments

- str The string to be decoded.
- json Defaults to TRUE. If TRUE, the function expects str to be an encoded json and will return a data.frame or list, depending on JSON structure. If FALSE, the function will return an string.

Examples

```
# Decode an encoded string:

str <- "SGVsbG8gV29ybGQh"
j_decode(str, json = FALSE)

# Decode an encoded json:

encoded_json <- "W3sibXNnIjogIkh1bGxvIFdvcmxkISIscJqc29uIjogdHJ1ZX1d"
j_decode(encoded_json)
```

j_encode	<i>Encoding Function</i>
----------	--------------------------

Description

Used to encode a data.frame or list. By default, the output will be a base64 encoded JSON.

Usage

```
j_encode(data, json = TRUE)
```

Arguments

<code>data</code>	A list or data.frame to encode.
<code>json</code>	Defaults to TRUE. If TRUE, the output will be a base64 encoded JSON, else, the output will be an encoded string.

Examples

```
# Transform a data.frame to an encoded JSON string
df <- iris
encoded <- j_encode(df, json = TRUE)
```

Index

* **decode**

j_decode, [2](#)

* **encode**

j_encode, [2](#)

j_decode, [2](#)

j_encode, [2](#)