

Package ‘matrixStrucTest’

July 22, 2025

Version 1.0.0

Date 2019-07-14

Title Tests of Matrix Structure for Construct Validation

Description Tests for block-diagonal structure in symmetric matrices (e.g. correlation matrices) under the null hypothesis of exchangeable off-diagonal elements. As described in Segal et al. (2019), these tests can be useful for construct validation either by themselves or as a complement to confirmatory factor analysis. Monte Carlo methods are used to approximate the permutation p-value with Hubert's Gamma (Hubert, 1976) and a t-statistic. This package also implements the chi-squared statistic described by Steiger (1980). Please see Segal, et al. (2019) <[doi:10.1007/s11336-018-9647-4](https://doi.org/10.1007/s11336-018-9647-4)> for more information.

Depends R (>= 3.1)

Suggests ggplot2, reshape2

Author Brian D. Segal [aut, cre]

Maintainer Brian D. Segal <bdsegal@umich.edu>

License GPL (>= 3)

URL <https://github.com/bdsegal/matrixStrucTest>

LazyData true

RoxygenNote 6.1.1

NeedsCompilation no

Repository CRAN

Date/Publication 2019-07-18 06:35:48 UTC

Contents

big5	2
deltaSub	4
makeGroupList	5
matrixStrucTest	5
matrixStrucTestSub	7
multiSub	8
prepBoxPlots	9

print.mst	10
sigmaRhoFun	10
sigmaZFun	11
X2Fun	11

Index	12
--------------	-----------

big5	<i>Big Five personality questionnaire</i>
------	---

Description

A dataset containing answers to a Big Five Personality Test conducted by <http://personality-testing.info>. These data were collected (c. 2012) through an interactive online personality test. The test was constructed with items from the International Personality Item Pool. Participants were informed that their responses would be recorded and used for research at the beginning of the test and asked to confirm their consent at the end of the test. The items were rated on a five point scale where 1=Disagree, 3=Neutral, 5=Agree. All were presented on one page in the order E1, N1, A1, C1, O1, E2,...

Usage

big5

Format

A data frame with 19,719 rows of 57 variables:

race 1=Mixed Race, 2=Arctic (Siberian, Eskimo), 3=Caucasian (European), 4=Caucasian (Indian), 5=Caucasian (Middle East), 6=Caucasian (North African, Other), 7=Indigenous Australian, 8=Native American, 9=North East Asian (Mongol, Tibetan, Korean Japanese, etc), 10=Pacific (Polynesian, Micronesian, etc), 11=South East Asian (Chinese, Thai, Malay, Filipino, etc), 12=West African, Bushmen, Ethiopian, 13=Other

age Entered as text (individuals reporting age < 13 were not recorded)

engnat Response to "is English your native language?". 1=yes, 2=no

gender 1=Male, 2=Female, 3=Other

hand "What hand do you use to write with?". 1=Right, 2=Left, 3=Both

country The participant's technical location. ISO country code

source How the participant came to the test. Based on HTTP Referer. 1=from another page on the test website, 2=from google, 3=from facebook, 4=from any url with ".edu" in its domain name, 6=other source, or HTTP Referer not provided

E1 I am the life of the party.

E2 I don't talk a lot.

E3 I feel comfortable around people.

E4 I keep in the background.

- E5** I start conversations.
- E6** I have little to say.
- E7** I talk to a lot of different people at parties.
- E8** I don't like to draw attention to myself.
- E9** I don't mind being the center of attention.
- E10** I am quiet around strangers.
- N1** I get stressed out easily.
- N2** I am relaxed most of the time.
- N3** I worry about things.
- N4** I seldom feel blue.
- N5** I am easily disturbed.
- N6** I get upset easily.
- N7** I change my mood a lot.
- N8** I have frequent mood swings.
- N9** I get irritated easily.
- N10** I often feel blue.
- A1** I feel little concern for others.
- A2** I am interested in people.
- A3** I insult people.
- A4** I sympathize with others' feelings.
- A5** I am not interested in other people's problems.
- A6** I have a soft heart.
- A7** I am not really interested in others.
- A8** I take time out for others.
- A9** I feel others' emotions.
- A10** I make people feel at ease.
- C1** I am always prepared.
- C2** I leave my belongings around.
- C3** I pay attention to details.
- C4** I make a mess of things.
- C5** I get chores done right away.
- C6** I often forget to put things back in their proper place.
- C7** I like order.
- C8** I shirk my duties.
- C9** I follow a schedule.
- C10** I am exacting in my work.
- O1** I have a rich vocabulary.

- O2** I have difficulty understanding abstract ideas.
- O3** I have a vivid imagination.
- O4** I am not interested in abstract ideas.
- O5** I have excellent ideas.
- O6** I do not have a good imagination.
- O7** I am quick to understand things.
- O8** I use difficult words.
- O9** I spend time reflecting on things.
- O10** I am full of ideas.

Details

This dataset is for demonstration purposes only. Please see <http://personality-testing.info/privacypolicy.html> and <http://personality-testing.info/about> for more information.

Source

http://personality-testing.info/_rawdata/

deltaSub

Sub-routine to create Delta matrix

Description

This sub-routine outputs 1 if *i* and *j* are in at least one group together, and 0 otherwise, and is called by `matrixStrucTest` and `prepBoxPlots`.

Usage

```
deltaSub(i, j, group_list)
```

Arguments

<i>i</i>	First index
<i>j</i>	Second index
<i>group_list</i>	List of indices for each block

makeGroupList	<i>Convert character string in lavaan syntax into a list of indices</i>
---------------	---

Description

This sub-routine is called by matrixStrucTest and prepBoxPlots.

Usage

```
makeGroupList(groups, A)
```

Arguments

groups	Character string in lavaan syntax specifying groups
A	A Distance or similarity matrix. Must have column names

Value

group_list List of column indices of A corresponding to each group

matrixStrucTest	<i>Permutation p-values for Gamma and t-statistics</i>
-----------------	--

Description

This function computes permutation p-values for Hubert's Gamma and t-statistics for both overall and block-specific tests.

Usage

```
matrixStrucTest(A, group_list = NULL, groups = NULL, B = 1000,
  absolute = TRUE)
```

Arguments

A	Distance or similarity matrix, e.g. correlation
group_list	List of column indices of A for each group. Either groups or group_list but not both must be supplied.
groups	CFA model in lavaan syntax. Either groups or group_list but not both must be supplied.
B	Number of Monte Carlo resamples (defaults to B=1000)
absolute	Use the absolute values of A (defaults to TRUE)

Value

pt_overall_one_sided: Overall one-sided p-value using t statistic
 pt_overall_two_sided: Overall two-sided p-value using t statistic
 pt_multi_one_sided: Block-specific one-sided p-values using t statistic
 pt_multi_two_sided: Block-specific two-sided p-values using t statistic
 t0 Observed overall: t statistic
 t0k: Observed block-specific t statistic
 t_overall: Vector of overall t statistics from permuted A
 t_max_one_sided: Vector of max t statistics from permuted A (one-sided)
 t_max_two_sided: Vector of max t statistics from permuted A (two-sided)
 pG_overall_one_sided: Overall one-sided p-value using Hubert's Gamma
 pG_overall_two_sided: Overall two-sided p-value using Hubert's Gamma
 pG_multi_one_sided: Block-specific one-sided p-values using Hubert's Gamma
 pG_multi_two_sided: Block-specific two-sided p-values using Hubert's Gamma
 Gamma0: Observed overall Hubert's Gamma
 Gamma0k: Observed block-specific Hubert's Gamma
 Gamma_overall: Vector of Hubert's Gamma statistics from permuted A
 Gamma_max_one_sided: Vector of max Hubert's Gamma statistics from permuted A (one-sided)
 Gamma_max_two_sided: Vector of max Hubert's Gamma statistics from permuted A (two-sided)
 B: number of Monte Carlo resamples
 group_list: List of column/row indices corresponding to each group

Examples

```

# example for matrixStrucTest package
library(matrixStrucTest)
data("big5")

# get column numbers for questionnaire items
items <- grep("[0-9]", colnames(big5))

# compute Spearman's correlation matrix
A <- cor(big5[, items], use = "complete.obs", method = "spearman")

# specify the groups
groups <- "extrovert ~ E1 + E2 + E3 + E4 + E5 + E6 + E7 + E8 + E9 + E10
          neurotic ~ N1 + N2 + N3 + N4 + N5 + N6 + N7 + N8 + N9 + N10
          agreeable ~ A1 + A2 + A3 + A4 + A5 + A6 + A7 + A8 + A9 + A10
          conscientious ~ C1 + C2 + C3 + C4 + C5 + C6 + C7 + C8 + C9 + C10
          open ~ O1 + O2 + O3 + O4 + O5 + O6 + O7 + O8 + O9 + O10"

# compute permutation p-values
# Note: Using small B for fast checking on CRAN. Set B >= 1000 in practice.
result <- matrixStrucTest(A = A, groups = groups, B = 100, absolute = TRUE)

```

```

# Note: two-sided p-values from Hubert's Gamma printed by default
#       other results available by directing accessing them from the
#       returned object
result

# Alternative approach for specifying the groups as a list of column/row indices
extrovert <- grep("E", colnames(A))
neurotic <- grep("N", colnames(A))
agreeable <- grep("A", colnames(A))
conscientious <- grep("C", colnames(A))
open <- grep("O", colnames(A))

# put blocks/groups in list
group_list <- list(extrovert = extrovert,
                   neurotic = neurotic,
                   agreeable = agreeable,
                   conscientious = conscientious,
                   open = open)

# Note: Using small B for fast checking on CRAN. Set B >= 1000 in practice.
result <- matrixStrucTest(A = A, group_list = group_list, B = 100, absolute = TRUE)

# Note: two-sided p-values from Hubert's Gamma printed by default
#       other results available by directing accessing them from the
#       returned object
result

# Visualize groups
library(ggplot2)
library(reshape2)

ord <- unlist(result$group_list)
diag(A) <- NA # remove diagonals from color scale
Am <- melt(A[ord, ord])
names(Am) <- c("x", "y", "value")
Am$y <- factor(Am$y, levels = rev(levels(Am$y)))

ggplot(aes(x = x, y = y, fill = abs(value)), data = Am)+
  geom_tile()+
  theme_bw(18)+
  scale_fill_gradient2(space="Lab", name="abs(Cor)", lim = c(0, 1))+
  labs(x = "", y = "")+
  theme(axis.text.x = element_text(angle = 90, vjust = .35, hjust=1))

```

matrixStrucTestSub

Compute Gamma and t-statistics for a single permutation

Description

This sub-routine is called by `matrixStrucTest` and `prepBoxPlots`.

Usage

```
matrixStrucTestSub(A, group_list_ord, Delta, multi_group_ind, A_upper_ind,
K)
```

Arguments

- A Distance or similarity matrix, e.g. correlation
- group_list_ord List of groupings for ordered matrix A
- Delta Delta matrix
- multi_group_ind List of indicator matrices for membership in block k test
- A_upper_ind indicator matrix for upper triangular elements
- K Total number of hypothesized blocks

Value

- Gamma_overall: Overall Hubert’s Gamma
- Gamma_multi: Block-specific Hubert’s Gamma
- t_overall: Overall t-statistic (unequal variance)
- t_multi: Block-specific t-statistics
- Ak_list: List of values in A used for each block-specific test
- Deltak_list: List of values in Delta used for each block-specific test
- A_upper: Upper triangular elements of A (used for box plot function)
- Delta_upper: Upper triangular elements of Delta (used for box plot function)

multiSub	<i>Sub-routine to create Delta matrix for block-specific tests</i>
----------	--

Description

This sub-routine outputs TRUE if either i or j are in group, FALSE otherwise, and is called by matrixStrucTest and prepBoxPlots.

Usage

```
multiSub(i, j, group)
```

Arguments

- i First index
- j Second index
- group Indices for items in group

prepBoxPlots	<i>Prepare data for box plots</i>
--------------	-----------------------------------

Description

This function prepares the data for making box plots.

Usage

```
prepBoxPlots(A, groups = NULL, group_list = NULL, absolute = TRUE)
```

Arguments

A	Distance or similarity matrix, e.g. correlation
groups	CFA model in lavaan syntax. Either groups or group_list but not both must be supplied.
group_list	List of groupings. Either groups or group_list but not both must be supplied.
absolute	Use the absolute values of A (defaults to TRUE)

Value

multi: data frame for making box plots for block-specific tests

overall: data frame for making box plots for overall test

Examples

```
library(matrixStrucTest)
library(ggplot2)

data("big5")

# get column numbers for questionnaire items
items <- grep("[0-9]", colnames(big5))

# compute Spearman's correlation matrix
A <- cor(big5[, items], use = "complete.obs", method = "spearman")

groups <- "extrovert ~ E1 + E2 + E3 + E4 + E5 + E6 + E7 + E8 + E9 + E10
          neurotic ~ N1 + N2 + N3 + N4 + N5 + N6 + N7 + N8 + N9 + N10
          agreeable ~ A1 + A2 + A3 + A4 + A5 + A6 + A7 + A8 + A9 + A10
          conscientious ~ C1 + C2 + C3 + C4 + C5 + C6 + C7 + C8 + C9 + C10
          open ~ O1 + O2 + O3 + O4 + O5 + O6 + O7 + O8 + O9 + O10"

# Make box plots contrasting within and between group correlations
box <- prepBoxPlots(A = A, groups = groups, absolute = TRUE)

ggplot(aes(x = as.factor(delta), y = a), data = box$overall)+
  geom_boxplot()+
```

```
theme_bw(22)+
labs(x = expression(Delta), y="|a|")

dev.new(width = 12, height = 5)
ggplot(aes(x = as.factor(delta), y = a), data = box$multi)+
  geom_boxplot()+
  facet_grid(~block)+
  theme_bw(22)+
labs(x = expression(Delta), y = "|a|")
```

print.mst	<i>Print results from matrixStrucTest</i>
-----------	---

Description

This function prints results from an object returned by matrixStrucTest.

Usage

```
## S3 method for class 'mst'
print(x, ...)
```

Arguments

x	Output from matrixStrucTest
...	Further arguments passed to print

sigmaRhoFun	<i>Sub-routine to compute OLS estimates of covariance between correlations</i>
-------------	--

Description

This sub-routine is called by X2fun.

Usage

```
sigmaRhoFun(j, k, h, m, A)
```

Arguments

j	First index
k	Second index
h	Third index
m	Fourth index
A	Correlation matrix

sigmaZFun	<i>Sub-routine to get covariance of z-transformed variables</i>
-----------	---

Description

This sub-routine is called by X2fun.

Usage

```
sigmaZFun(s, t, index, A, Sigma)
```

Arguments

s	First index
t	Second index
index	Matrix with two columns with index pairs given by rows
A	Correlation matrix
Sigma	Variance-covariances of correlation matrix A

X2Fun	<i>Goodness-of-fit chi-squared statistic described by Steiger (1980).</i>
-------	---

Description

This function computed the goodness-of-fit chi-squared statistic described by Steiger (1980). Reference: Steiger, J. H. (1980). Tests for comparing elements of a correlation matrix. Psychological Bulletin, 87(2) 245-251.

Usage

```
X2Fun(data, group_list, corMethod = "spearman")
```

Arguments

data	Data frame
group_list	List of column indices of A for each group
corMethod	Type of correlations; passed to cor()

Index

- * **datasets**
 - big5, [2](#)
- * **matrixStrucTest**
 - print.mst, [10](#)
- * **print**
 - print.mst, [10](#)
- big5, [2](#)
- deltaSub, [4](#)
- makeGroupList, [5](#)
- matrixStrucTest, [5](#)
- matrixStrucTestSub, [7](#)
- multiSub, [8](#)
- prepBoxPlots, [9](#)
- print.mst, [10](#)
- sigmaRhoFun, [10](#)
- sigmaZFun, [11](#)
- X2Fun, [11](#)