

Package ‘modisfast’

July 23, 2025

Title Fast and Efficient Access to MODIS Earth Observation Data

Version 1.0.2

Description Programmatic interface to several NASA Earth Observation 'OPeNDAP' servers (Open-source Project for a Network Data Access Protocol) (<<https://www.opendap.org/>>). Allows for easy downloads of MODIS subsets, as well as other Earth Observation data-cubes, in a time-saving and efficient way : by sampling it at the very downloading phase (spatially, temporally and dimensionally).

License GPL (>= 3)

URL <https://github.com/ptaconet/modisfast>

BugReports <https://github.com/ptaconet/modisfast/issues>

Depends R (>= 2.10)

Imports curl, dplyr, httr, lubridate, magrittr, parallel, purrr,
rvest, sf, stats, stringr, terra, xml2, cli

Suggests ggplot2, knitr, mapview, rmarkdown, spelling, testthat,
apeears

Encoding UTF-8

LazyData true

RoxygenNote 7.3.1

Language en-US

Config/testthat/start-first mf_login, mf_list_collections,
mf_list_variables, mf_get_url, mf_download_data, mf_import_data

NeedsCompilation no

Author Paul Taconet [aut, cre, cph] (ORCID:
<<https://orcid.org/0000-0001-7429-7204>>),
Nicolas Moiroux [fnd] (ORCID: <<https://orcid.org/0000-0001-6755-6167>>),
French National Research Institute for Sustainable Development, IRD
[fnd]

Maintainer Paul Taconet <paul.taconet@gmail.com>

Repository CRAN

Date/Publication 2025-07-17 15:40:08 UTC

Contents

entomological_data	2
mf_download_data	3
mf_get_opt_param	5
mf_get_url	6
mf_import_data	9
mf_list_collections	11
mf_list_variables	12
mf_login	12
mf_modisfast	13
Index	16

entomological_data	<i>Example dataset containing abundances of mosquitoes vectors of malaria. Used in article 'use_case'.</i>
--------------------	--

Description

Example dataset containing abundances of mosquitoes vectors of malaria. Used in article 'use_case'.

Usage

entomological_data

Format

- ## 'entomological_data' A data frame with 232 rows and 6 columns:
- mission** number of the entomological survey
 - date** date of the survey
 - village** 3-digit code for the village of the survey
 - X, Y** longitude and latitude of the center of the village
 - n** number of mosquitoes collected

Source

<<https://doi.org/10.15468/v8fvyn>>

mf_download_data	<i>Download several datasets given their URLs and destination path</i>
------------------	--

Description

This function enables to download datasets. In a data import workflow, this function is typically used after a call to the [mf_get_url](#) function. The output value of [mf_get_url](#) can be used as input of parameter `df_to_dl` of [mf_download_data](#).

The download can be parallelized.

Usage

```
mf_download_data(
  df_to_dl,
  path = tempfile("modisfast_"),
  parallel = FALSE,
  num_workers = parallel::detectCores() - 1,
  credentials = NULL,
  verbose = "inform",
  min_filesize = 5000
)
```

Arguments

<code>df_to_dl</code>	data.frame. Urls and destination files of dataset to download. Typically output of mf_get_url . See Details for the structure
<code>path</code>	string. Target folder for the data to download. Default : temporary folder.
<code>parallel</code>	boolean. Parallelize the download ? Default to FALSE
<code>num_workers</code>	integer. Number of workers in case of parallel download. Default to number of workers available in the machine minus one.
<code>credentials</code>	vector string of length 2 with username and password. optional if the function mf_login was previously executed.
<code>verbose</code>	string. Verbose mode ("quiet", "inform", or "debug"). Default "inform".
<code>min_filesize</code>	integer. Minimum file size expected (in bites) for one file downloaded. If files downloaded are less than this value, the files will be downloaded again. Default 5000.

Details

Parameter `df_to_dl` must be a data.frame with the following minimal structure :

id_roi An id for the ROI (character string)

collection Collection (character string)

name

url URL of the file to download (character string)

Value

a data.frame with the same structure of the input data.frame df_to_dl + columns providing details of the data downloaded. The additional columns are :

fileDI Boolean (dataset downloaded or failure)

dlStatus Download status : 1 = download ok ; 2 = download error ; 3 = dataset was already existing in destination file

fileSize File size on disk (in bites)

Examples

```
## Not run:

### Login to EOSDIS Earthdata with your username and password
log <- mf_login(credentials = c("earthdata_un", "earthdata_pw"))

### Set-up parameters of interest
coll <- "MOD11A1.061"

bands <- c("LST_Day_1km", "LST_Night_1km")

time_range <- as.Date(c("2017-01-01", "2017-01-30"))

roi <- sf::st_as_sf(
  data.frame(
    id = "roi_test",
    geom = "POLYGON ((-5.82 9.54, -5.42 9.55, -5.41 8.84, -5.81 8.84, -5.82 9.54))"
  ),
  wkt = "geom", crs = 4326
)

### Get the URLs of the data
(urls_mod11a1 <- mf_get_url(
  collection = coll,
  variables = bands,
  roi = roi,
  time_range = time_range
))

### Download the data
res_dl <- mf_download_data(urls_mod11a1)

### Import the data as terra::SpatRast
modis_ts <- mf_import_data(dirname(res_dl$destfile[1]), collection = coll)

### Plot the data
terra::plot(modis_ts)

## End(Not run)
```

mf_get_opt_param	<i>Precompute the parameter opt_param of the function mf_get_url</i>
------------------	--

Description

Precompute the parameter opt_param to further provide as input of the [mf_get_url](#) function. Useful to speed-up the overall processing time.

Usage

```
mf_get_opt_param(collection, roi, credentials = NULL, verbose = "inform")
```

Arguments

collection	string. mandatory. Collection of interest (see details of mf_get_url).
roi	object of class sf. mandatory. Area of region of interest. Must be a Simple feature collection with geometry type POLYGON, composed of one or several rows (i.e. one or several ROIs), and with at least two columns: 'id' (an identifier for the roi) and 'geom' (the geometry).
credentials	vector string of length 2 with username and password. optional if the function mf_login was previously executed.
verbose	string. Verbose mode ("quiet", "inform", or "debug"). Default "inform".

Details

When it is needed to loop the function [mf_get_url](#) over several time frames, it is advised to previously run the function `mf_get_opt_param` and provide the output as input `opt_param` parameter of the [mf_get_url](#) function. This will save much time, as internal parameters will be calculated only once.

Value

a list with the following named objects :

roiSpatialIndexBound OPeNDAP indices for the spatial coordinates of the bounding box of the ROI (minLat, maxLat, minLon, maxLon)

availableVariables Variables available for the collection of interest

roiSpatialBound The spatial coordinates of the bounding box of the ROI expressed in the CRS of the collection

OpenDAPXVector The X (longitude) vector

OpenDAPYVector The Y (longitude) vector

OpenDAPtimeVector The time vector, or NULL if the collection does not have a time vector

modis_tile The MODIS tile(s) number(s) for the ROI or NULL if the collection is not MODIS

Examples

```
## Not run:

# Login to Earthdata

log <- mf_login(credentials = c("earthdata_un", "earthdata_pw"))

# Get the optional parameters for the collection MOD11A1.061 and the following roi :
roi <- sf::st_as_sf(
  data.frame(
    id = "roi_test",
    geom = "POLYGON ((-5.82 9.54, -5.42 9.55, -5.41 8.84, -5.81 8.84, -5.82 9.54))"
  ),
  wkt = "geom", crs = 4326
)

opt_param_mod11a1 <- mf_get_opt_param("MOD11A1.061", roi)
str(opt_param_mod11a1)

# Now we can provide opt_param_mod11a1 as input parameter of the function mf_get_url().

time_ranges <- list(
  as.Date(c("2016-01-01", "2016-01-31")),
  as.Date(c("2017-01-01", "2017-01-31")),
  as.Date(c("2018-01-01", "2018-01-31")),
  as.Date(c("2019-01-01", "2019-01-31"))
)

(urls_mod11a1 <- map(.x = time_ranges, ~ mf_get_url(
  collection = "MOD11A1.061",
  variables = c("LST_Day_1km", "LST_Night_1km", "QC_Day", "QC_Night"),
  roi = roi,
  time_range = .x,
  opt_param = opt_param_mod11a1
)))

## End(Not run)
```

mf_get_url

Build the URL(s) of the data to download

Description

Builds the OPeNDAP URL(s) of the spatiotemporal datacube to download, given a collection, variables, region and time range of interest.

Usage

```
mf_get_url(
```

```

    collection,
    variables = NULL,
    roi,
    time_range,
    output_format = "nc4",
    single_netcdf = TRUE,
    opt_param = NULL,
    credentials = NULL,
    verbose = "inform"
)

```

Arguments

collection	string. mandatory. Collection of interest (see details of mf_get_url).
variables	string vector. optional. Variables to retrieve for the collection of interest. If not specified (default) all available variables will be extracted (see details of mf_get_url).
roi	object of class sf. mandatory. Area of region of interest. Must be a Simple feature collection with geometry type POLYGON, composed of one or several rows (i.e. one or several ROIs), and with at least two columns: 'id' (an identifier for the roi) and 'geom' (the geometry).
time_range	date(s) / POSIXlt of interest . mandatory. Single date/datetime or time frame : vector with start and end dates/times (see details).
output_format	string. Output data format. optional. Available options are : "nc4" (default), "ascii", "json"
single_netcdf	boolean. optional. Get the URL either as a single file that encompasses the whole time frame (TRUE) or as multiple files (1 for each date) (FALSE). Default to TRUE. Currently enabled only for MODIS and VIIRS collections.
opt_param	list of optional arguments. optional. (see details).
credentials	vector string of length 2 with username and password. optional if the function mf_login was previously executed.
verbose	string. Verbose mode ("quiet", "inform", or "debug"). Default "inform".

Details

Argument collection : Collections available can be retrieved with the function [mf_list_collections](#)

Argument variables : For each collection, variables available can be retrieved with the function [mf_list_variables](#)

Argument time_range : Can be provided either as i) a single date (e.g. as.Date("2017-01-01")) or ii) a time frame provided as two bounding dates (starting and ending time) (e.g. as.Date(c("2010-01-01", "2010-01-30")) or iii) a POSIXlt single time (e.g. as.POSIXlt("2010-01-01 18:00:00")) or iv) a POSIXlt time range (e.g. as.POSIXlt(c("2010-01-01 18:00:00", "2010-01-02 09:00:00"))) for the half-hourly collection (GPM_3IMERGHH.06). If POSIXlt, hours must be provided in GMT.

Argument single_netcdf : for MODIS and VIIRS products from LP DAAC: download the data as a single file encompassing the whole time frame (TRUE) or as multiple files : one for each date, which is the behaviour for the other collections - GPM and SMAP) (FALSE) ?

Argument `opt_param` : list of parameters related to the queried OPeNDAP server and the roi. See [mf_get_opt_param](#) for additional details. This list can be retrieved outside the function with the function [mf_get_opt_param](#). If not provided, it will be automatically calculated within the [mf_get_url](#) function. However, providing it fastens the processing time. It might be particularly useful to precompute it with [mf_get_opt_param](#) in case the function is used within a loop for a single ROI.

Argument `credentials` : Login to the OPeNDAP servers is required to use the function. Login can be done either within the function or outside with the function [mf_login](#)

Value

a data.frame with one row for each dataset to download and 5 columns :

id_roi Identifier of the ROI

time_start Start Date/time for the dataset

collection Name of the collection

name Indicative name for the dataset

url https OPeNDAP URL of the dataset

maxFileSizeEstimated Maximum estimated data size for the dataset (in bites)

Examples

```
## Not run:

### First login to EOSDIS Earthdata with username and password.
# To create an account go to : https://urs.earthdata.nasa.gov/.
username <- "earthdata_un"
password <- "earthdata_pw"
log <- mf_login(credentials = c(username, password))

### Get the URLs to download the following datasets :
# MODIS Terra LST Daily (MOD11A1.061) (collection)
# Day + Night bands (LST_Day_1km,LST_Night_1km) (variables)
# over a 50km x 70km region of interest (roi)
# for the time frame 2017-01-01 to 2017-01-30 (30 days) (time_range)

roi <- sf::st_as_sf(
  data.frame(
    id = "roi_test",
    geom = "POLYGON ((-5.82 9.54, -5.42 9.55, -5.41 8.84, -5.81 8.84, -5.82 9.54))"
  ),
  wkt = "geom", crs = 4326
)

time_range <- as.Date(c("2017-01-01", "2017-01-30"))

(urls_mod11a1 <- mf_get_url(
  collection = "MOD11A1.061",
  variables = c("LST_Day_1km", "LST_Night_1km"),
  roi = roi,
```

```

    time_range = time_range
  ))

  ## Download the data :

  res_dl <- mf_download_data(urls_mod11a1)

  ## Import as terra::SpatRaster

  modis_ts <- mf_import_data(dirname(res_dl$destfile[1]), collection = "MOD11A1.061")

  ## Plot the data

  terra::plot(modis_ts)

  ## End(Not run)

```

mf_import_data	<i>Import datasets downloaded using modisfast as a terra::SpatRaster object</i>
----------------	---

Description

Import datasets downloaded using modisfast as a terra::SpatRaster object

Usage

```

mf_import_data(
  path,
  collection,
  output_class = "SpatRaster",
  proj_epsg = NULL,
  roi_mask = NULL,
  vrt = FALSE,
  verbose = "inform",
  ...
)

```

Arguments

path	character string. mandatory. The path to the local directory where the data are stored.
collection	string. mandatory. Collection of interest (see details of mf_get_url).
output_class	character string. Output object class. Currently only "SpatRaster" implemented.
proj_epsg	numeric. EPSG of the desired projection for the output raster (default : source projection of the data).
roi_mask	SpatRaster or SpatVector or sf. Area beyond which data will be masked. Typically, the input ROI of mf_get_url (default : NULL (no mask))

vrt	boolean. Import virtual raster instead of SpatRaster. Useful for very large files. (default : FALSE)
verbose	string. Verbose mode ("quiet", "inform", or "debug"). Default "inform".
...	not used

Value

a terra::SpatRast object

Note

Although the data downloaded through modisfast could be imported with any netcdf-compliant R package (terra, stars, ncdf4, etc.), care must be taken. In fact, depending on the collection, some “issues” were raised. These issues are independent from modisfast : they result most of time of a lack of full implementation of the OPeNDAP framework by the data providers. Namely, these issues are :

- for MODIS and VIIRS collections : CRS has to be provided
- for GPM collections : CRS has to be provided + data have to be flipped

The function [mf_import_data](#) includes the processing that needs to be done at the data import phase in order to safely use the data as terra objects.

Also note that reprojecting over large ROIs using the argument proj_epsg might take long. In this case, setting the argument vrt to TRUE might be a solution.

Examples

```
## Not run:

### Login to EOSDIS Earthdata with your username and password
log <- mf_login(credentials = c("earthdata_un", "earthdata_pw"))

### Set-up parameters of interest
coll <- "MOD11A1.061"

bands <- c("LST_Day_1km", "LST_Night_1km")

time_range <- as.Date(c("2017-01-01", "2017-01-30"))

roi <- sf::st_as_sf(
  data.frame(
    id = "roi_test",
    geom = "POLYGON ((-5.82 9.54, -5.42 9.55, -5.41 8.84, -5.81 8.84, -5.82 9.54))"
  ),
  wkt = "geom", crs = 4326
)

### Get the URLs of the data
(urls_mod11a1 <- mf_get_url(
  collection = coll,
  variables = bands,
```

```

    roi = roi,
    time_range = time_range
  ))

  ### Download the data
  res_dl <- mf_download_data(urls_mod11a1)

  ### Import the data as terra::SpatRast
  modis_ts <- mf_import_data(dirname(res_dl$destfile[1]), collection = coll)

  ### Plot the data
  terra::plot(modis_ts)

  ## End(Not run)

```

mf_list_collections	<i>Get the collections available for download with the modisfast package</i>
---------------------	--

Description

Get the collections available for download using the package and a set of related information

Usage

```
mf_list_collections()
```

Value

A data.frame with the collections available, and a set of related information for each one. Main columns are :

collection Collection short name

source Data provider

long_name Collection long name

doi DOI of the collection

start_date First available date for the collection

url_opendapserver URL of the OPeNDAP server of the data

Examples

```
(head(mf_list_collections()))
```

mf_list_variables	<i>Get information for the variables (bands) available for a given collection</i>
-------------------	---

Description

Get the variables available for a given collection, along with a set of related information for each.

Usage

```
mf_list_variables(collection, credentials = NULL, verbose = "inform")
```

Arguments

collection	string. mandatory. Collection of interest (see details of mf_get_url).
credentials	vector string of length 2 with username and password. optional if the function mf_login was previously executed.
verbose	string. Verbose mode ("quiet", "inform", or "debug"). Default "inform".

Value

A data.frame with the variables available for the collection, and a set of related information for each variable. The variables marked as "extractable" in the column "extractable_with_modisfast" can be provided as input parameter variables of the function [mf_get_url](#)

Examples

```
## Not run:
# login to Earthdata
log <- mf_login(c("earthdata_un", "earthdata_pw"))

# Get the variables available for the collection MOD11A1.061
(df_varinfo <- mf_list_variables("MOD11A1.061"))

## End(Not run)
```

mf_login	<i>Login to EOSDIS EarthData account</i>
----------	--

Description

Login to EOSDIS EarthData before querying servers and download data

Usage

```
mf_login(credentials, verbose = "inform")
```

Arguments

credentials vector string of length 2 with username and password. optional if the function [mf_login](#) was previously executed.

verbose string. Verbose mode ("quiet", "inform", or "debug"). Default "inform".

Details

An EOSDIS EarthData account is mandatory to download the data. You can create a free account here : <https://urs.earthdata.nasa.gov/>.

Value

None.

Examples

```
## Not run:
username <- "earthdata_un"
password <- "earthdata_pw"
mf_login(credentials = c(username, password))

## End(Not run)
```

mf_modisfast	<i>Download (and possibly import) MODIS, VIIRS and GPM Earth Observation data</i>
--------------	---

Description

Download and possibly import MODIS, VIIRS and GPM Earth Observation data quickly and efficiently. This function is a wrapper for [mf_login](#), [mf_get_url](#), [mf_download_data](#) and [mf_import_data](#). Whenever possible, users should prefer executing the functions [mf_login](#), [mf_get_url](#), [mf_download_data](#) and [mf_import_data](#) sequentially rather than using this high-level function

Usage

```
mf_modisfast(
  collection,
  variables,
  roi,
  time_range,
  path = tempfile("modisfast_"),
  earthdata_username,
  earthdata_password,
  parallel = FALSE,
  verbose = "inform",
```

```
import = TRUE,
...
)
```

Arguments

collection	string. mandatory. Collection of interest (see details of mf_get_url).
variables	string vector. optional. Variables to retrieve for the collection of interest. If not specified (default) all available variables will be extracted (see details of mf_get_url).
roi	object of class sf. mandatory. Area of region of interest. Must be a Simple feature collection with geometry type POLYGON, composed of one or several rows (i.e. one or several ROIs), and with at least two columns: 'id' (an identifier for the roi) and 'geom' (the geometry).
time_range	date(s) / POSIXlt of interest . mandatory. Single date/datetime or time frame : vector with start and end dates/times (see details).
path	string. Target folder for the data to download. Default : temporary folder.
earthdata_username	EarthData username
earthdata_password	EarthData username
parallel	boolean. Parallelize the download ? Default to FALSE
verbose	string. Verbose mode ("quiet", "inform", or "debug"). Default "inform".
import	boolean. Import the data as a SpatRast object ? default TRUE. FALSE will download the data but not import them it in R.
...	Further arguments to be passed to mf_import_data

Value

if the parameter `import` is set to `TRUE`, a `terra::SpatRast` object ; else a `data.frame` providing details of the data downloaded (see output of [mf_download_data](#)).

See Also

[mf_login](#), [mf_get_url](#), [mf_download_data](#), [mf_import_data](#)

Examples

```
## Not run:

### Set-up parameters of interest
coll <- "MOD11A1.061"

bands <- c("LST_Day_1km", "LST_Night_1km")

time_range <- as.Date(c("2017-01-01", "2017-01-30"))
```

```
roi <- sf::st_as_sf(
  data.frame(
    id = "roi_test",
    geom = "POLYGON ((-5.82 9.54, -5.42 9.55, -5.41 8.84, -5.81 8.84, -5.82 9.54))"
  ),
  wkt = "geom", crs = 4326
)

### Download and import the data
modis_ts <- mf_modisfast(
  collection = coll,
  variables = bands,
  roi = roi,
  time_range = time_range,
  earthdata_username = "earthdata_un",
  earthdata_password = "earthdata_pw"
)

### Plot the data
terra::plot(modis_ts)

## End(Not run)
```

Index

* **datasets**

entomological_data, [2](#)

entomological_data, [2](#)

mf_download_data, [3](#), [3](#), [13](#), [14](#)

mf_get_opt_param, [5](#), [8](#)

mf_get_url, [3](#), [5](#), [6](#), [7–9](#), [12–14](#)

mf_import_data, [9](#), [10](#), [13](#), [14](#)

mf_list_collections, [7](#), [11](#)

mf_list_variables, [7](#), [12](#)

mf_login, [3](#), [5](#), [7](#), [8](#), [12](#), [12](#), [13](#), [14](#)

mf_modisfast, [13](#)