

Package ‘pwr2’

July 23, 2025

Type Package

Title Power and Sample Size Analysis for One-way and Two-way ANOVA Models

Version 1.0

Date 2017-05-01

Author Pengcheng Lu, Junhao Liu, Devin Koestler

Maintainer Pengcheng Lu <plu2@kumc.edu>

Description

User friendly functions for power and sample size analysis at one-way and two-way ANOVA settings take either effect size or delta and sigma as arguments. They are designed for both one-way and two-way ANOVA settings. In addition, a function for plotting power curves is available for power comparison, which can be easily visualized by statisticians and clinical researchers.

License GPL-2

NeedsCompilation no

Repository CRAN

Date/Publication 2017-05-06 05:22:35 UTC

Contents

pwr2-package	2
pwr.1way	3
pwr.2way	4
pwr.plot	5
ss.1way	6
ss.2way	7
Index	9

pwr2-package

Power and Sample Size Analysis for One-way and Two-way ANOVA Models

Description

User friendly functions for power and sample size analysis at one-way and two-way ANOVA settings take either effect size or delta and sigma as arguments. They are designed for both one-way and two-way ANOVA settings. In addition, a function for plotting power curves is available for power comparison, which can be easily visualized by statisticians and clinical researchers.

Details

Package: SPA
Type: Package
Version: 1.0
Date: 2017-05-01
License: GPL-2

There are major five functions in the package. The `pwr.lway` and `pwr.2way` functions provide the power analysis for one-way and two-way ANOVA models. The `ss.lway` and `ss.2way` functions provide the sample size calculation for one-way and two-way ANOVA models. The `pwr.plot` function illustrates drawing power curves for different parameter settings.

Author(s)

Pengcheng Lu, Junhao Liu, and Devin Koestler.

Maintainer: Pengcheng Lu <plu2@kumc.edu>

References

[1] Angela Dean & Daniel Voss (1999). Design and Analysis of Experiments. Springer.

Examples

```
## Example 1
pwr.2way(a=3, b=3, alpha=0.05, size.A=4, size.B=5, f.A=0.8, f.B=0.4)
pwr.2way(a=3, b=3, alpha=0.05, size.A=4, size.B=5, delta.A=4, delta.B=2, sigma.A=2, sigma.B=2)

## Example 2
ss.2way(a=3, b=3, alpha=0.05, beta=0.1, delta.A=1, delta.B=2, sigma.A=2, sigma.B=2, B=100)

## Example 3
n <- seq(2, 30, by=4)
f <- seq(0.1, 1.0, length.out=10)
pwr.plot(n=n, k=5, f=f, alpha=0.05)
```

pwr.lway

*Power calculation for balanced one-way ANOVA models***Description**

Calculate power for one-way ANOVA models.

Usage

```
pwr.lway(k=k, n=n, alpha=alpha, f=NULL, delta=delta, sigma=sigma)
```

Arguments

k	Number of groups
n	Sample size per group
f	Effect size
alpha	Significant level (Type I error probability)
delta	The smallest difference among k groups
sigma	Standard deviation, i.e. square root of variance

Details

If effect size f is known, plug it in to the function; If delta and sigma are known instead of effect size, put NULL to f.

Value

Object of class "power.htest", a list of the arguments (including the computed one) augmented with "method" and "note" elements.

Author(s)

Pengcheng Lu, Junhao Liu, and Devin Koestler.

References

Angela Dean & Daniel Voss (1999). Design and Analysis of Experiments. Springer.

Examples

```
## Example 1
pwr.lway(k=5, n=15, alpha=0.05, delta=1.5, sigma=1)
pwr.lway(k=5, n=15, f=NULL, alpha=0.05, delta=1.5, sigma=1)

## Example 2
pwr.lway(k=5, n=15, f=0.4, alpha=0.05)
```

`pwr.2way`*Power calculation for balanced two-way ANOVA models*

Description

Calculate power for two-way ANOVA models.

Usage

```
pwr.2way(a=a, b=b, alpha=alpha, size.A=size.A, size.B=size.B, f.A=NULL, f.B=NULL,  
delta.A=NULL, delta.B=NULL, sigma.A=NULL, sigma.B=NULL)
```

Arguments

<code>a</code>	Number of groups in Factor A
<code>b</code>	Number of groups in Factor B
<code>alpha</code>	Significant level (Type I error probability)
<code>size.A</code>	Sample size per group in Factor A
<code>size.B</code>	Sample size per group in Factor B
<code>f.A</code>	Effect size of Factor A
<code>f.B</code>	Effect size of Factor B
<code>delta.A</code>	The smallest difference among a groups in Factor A
<code>delta.B</code>	The smallest difference among b groups in Factor B
<code>sigma.A</code>	Standard deviation, i.e. square root of variance in Factor A
<code>sigma.B</code>	Standard deviation, i.e. square root of variance in Factor B

Details

If effect sizes `f.A` and `f.B` are known, plug them in to the function; If `delta.A` and `sigma.A` are known instead of `f.A`, put `NULL` to `f.A`. Similarly as `delta.B` and `sigma.B`.

Value

Object of class "power.htest", a list of the arguments (including the computed one) augmented with "method" and "note" elements.

Author(s)

Pengcheng Lu, Junhao Liu, and Devin Koestler.

References

Angela Dean & Daniel Voss (1999). Design and Analysis of Experiments. Springer.

Examples

```
## Example 1
pwr.2way(a=3, b=3, alpha=0.05, size.A=4, size.B=5, f.A=0.8, f.B=0.4)

## Example 2
pwr.2way(a=3, b=3, alpha=0.05, size.A=4, size.B=5, delta.A=4, delta.B=2, sigma.A=2, sigma.B=2)
pwr.2way(a=3, b=3, alpha=0.05, size.A=4, size.B=5, f.A=NULL, f.B=NULL,
delta.A=4, delta.B=2, sigma.A=2, sigma.B=2)
```

pwr.plot	<i>Power curves for different parameter settings (sample size and effect size) in balanced one-way ANOVA models</i>
----------	---

Description

Draw power curves for different parameter settings in balanced one-way ANOVA models.

Usage

```
pwr.plot(n=n, k=k, f=f, alpha=alpha)
```

Arguments

n	Sample size per group
k	Number of groups
f	Effect size
alpha	Significant level (Type I error probability)

Details

This function demonstrates drawing power curves for different sample size and effect size settings. N and f can be either a single value or a sequence of values, but they cannot be single values simultaneously. The combination of them could be (a sequence of n, a sequence of f), (a sequence of n, a single f), or (a single n, a sequence of f).

Author(s)

Pengcheng Lu, Junhao Liu, and Devin Koestler.

References

Angela Dean & Daniel Voss (1999). Design and Analysis of Experiments. Springer.

Examples

```
## Example 1
n <- seq(2, 30, by=4)
f <- 0.5
pwr.plot(n=n, k=5, f=f, alpha=0.05)

## Example 2
n <- 20
f <- seq(0.1, 1.0, length.out=10)
pwr.plot(n=n, k=5, f=f, alpha=0.05)

## Example 3
n <- seq(2, 30, by=4)
f <- seq(0.1, 1.0, length.out=10)
pwr.plot(n=n, k=5, f=f, alpha=0.05)
```

ss.1way

Sample size calculation for balanced one-way ANOVA models

Description

Calculate sample size for one-way ANOVA models.

Usage

```
ss.1way(k=k, alpha=alpha, beta=beta, f=NULL, delta=delta, sigma=sigma, B=B)
```

Arguments

k	Number of groups
alpha	Significant level (Type I error probability)
beta	Type II error probability (Power=1-beta)
f	Effect size
delta	The smallest difference among k group
sigma	Standard deviation, i.e. square root of variance
B	Iteration times, default number is 100

Details

Beta is the type II error probability which equals 1-power. For example, if the target power is 85% ($=0.85$), the corresponding beta equals 0.15. If effect size f is known, plug it in to the function; If delta and sigma are known instead of effect size, put NULL to f, or just miss f argument.

Value

Object of class "power.htest", a list of the arguments (including the computed one) augmented with "method" and "note" elements.

Author(s)

Pengcheng Lu, Junhao Liu, and Devin Koestler.

References

Angela Dean & Daniel Voss (1999). Design and Analysis of Experiments. Springer.

Examples

```
## Example 1
ss.1way(k=5, alpha=0.05, beta=0.1, f=1.5, B=100)

## Example 2
ss.1way(k=5, alpha=0.05, beta=0.1, delta=1.5, sigma=1, B=100)
ss.1way(k=5, alpha=0.05, beta=0.1, f=NULL, delta=1.5, sigma=1, B=100)
```

ss.2way

Sample size calculation for balanced two-way ANOVA models

Description

Calculate sample size for two-way ANOVA models.

Usage

```
ss.2way(a=a, b=b, alpha=alpha, beta=beta, f.A=NULL, f.B=NULL,
delta.A=NULL, delta.B=NULL, sigma.A=NULL, sigma.B=NULL, B=B)
```

Arguments

a	Number of groups in Factor A
b	Number of groups in Factor B
alpha	Significant level (Type I error probability)
beta	Type II error probability (Power=1-beta)
f.A	Effect size of Factor A
f.B	Effect size of Factor B
delta.A	The smallest difference among a groups in Factor A
delta.B	The smallest difference among b groups in Factor B
sigma.A	Standard deviation, i.e. square root of variance in Factor A
sigma.B	Standard deviation, i.e. square root of variance in Factor B
B	Iteration times, default number is 100

Details

Beta is the type II error probability which equals 1-power. For example, if the target power is 85% ($=0.85$), the corresponding beta equals 0.15. If effect size f is known, plug it in to the function; If delta and sigma are known instead of effect size, put NULL to f .

Value

Object of class "power.htest", a list of the arguments (including the computed one) augmented with "method" and "note" elements.

Author(s)

Pengcheng Lu, Junhao Liu, and Devin Koestler.

References

Angela Dean & Daniel Voss (1999). Design and Analysis of Experiments. Springer.

Examples

```
## Example 1
ss.2way(a=3, b=3, alpha=0.05, beta=0.1, f.A=0.4, f.B=0.2, B=100)
ss.2way(a=3, b=3, alpha=0.05, beta=0.1, f.A=0.4, f.B=0.2,
delta.A=NULL, delta.B=NULL, sigma.A=NULL, sigma.B=NULL, B=100)

## Example 2
ss.2way(a=3, b=3, alpha=0.05, beta=0.1, delta.A=1, delta.B=2, sigma.A=2, sigma.B=2, B=100)
```

Index

- * **ANOVA**
 - pwr2-package, [2](#)
 - * **Graph**
 - pwr.plot, [5](#)
 - * **One-Way ANOVA**
 - pwr.1way, [3](#)
 - ss.1way, [6](#)
 - * **Power Curve**
 - pwr.plot, [5](#)
 - * **Power**
 - pwr.1way, [3](#)
 - pwr.2way, [4](#)
 - pwr2-package, [2](#)
 - * **Sample Size**
 - pwr2-package, [2](#)
 - ss.1way, [6](#)
 - ss.2way, [7](#)
 - * **Two-Way ANOVA**
 - pwr.2way, [4](#)
 - ss.2way, [7](#)
- pwr.1way, [3](#)
pwr.2way, [4](#)
pwr.plot, [5](#)
pwr2 (pwr2-package), [2](#)
pwr2-package, [2](#)
- ss.1way, [6](#)
ss.2way, [7](#)