

Package ‘pylintR’

July 23, 2025

Type Package

Title Lint 'Python' Files with a R Command or a 'RStudio' Addin

Version 0.1.0

Author Stéphane Laurent

Maintainer Stéphane Laurent <laurent_step@outlook.fr>

Description Allow to run 'pylint' on Python files with a R command or a 'RStudio' addin. The report appears in the RStudio viewer pane as a formatted HTML file.

License GPL-3

Encoding UTF-8

SystemRequirements pylint

URL <https://github.com/stla/pylintR>

BugReports <https://github.com/stla/pylintR/issues>

Imports fansi, utils, htmlwidgets, rstudioapi

RoxxygenNote 7.1.2

NeedsCompilation no

Repository CRAN

Date/Publication 2021-10-12 09:00:01 UTC

Contents

pylint	2
pylintR-shiny	2
Index	4

pylint

Run 'pylint' on a file or a folder

Description

Run 'pylint' on a file or a folder.

Usage

```
pylint(modules)
```

Arguments

modules one or more Python files, or a folder containing Python files

Value

A htmlwidget object.

Examples

```
## Not run:
sample_code_file <- system.file("sample_code.py", package = "pylintR")
code_lines <- readLines(sample_code_file)
nlines <- length(code_lines)
# Here is the code:
cat(paste0(format(seq_len(nlines), width = 2), " ", code_lines), sep = "\n")
# let's copy this Python file in a temporary folder
file_copy <- tempfile(fileext = ".py")
file.copy(sample_code_file, file_copy)
wd <- setwd(tempdir())
# let's lint it with pylint:
pylint(basename(file_copy))
# restore current directory
setwd(wd)

## End(Not run)
```

pylintR-shiny

Shiny bindings for pylintR

Description

Output and render functions for using 'pylintR' within Shiny applications and interactive Rmd documents.

Usage

```
pylintROutput(outputId, width = "100%", height = "400px")
```

```
renderPylintR(expr, env = parent.frame(), quoted = FALSE)
```

Arguments

outputId	output variable to read from
width, height	a valid CSS unit (like "100%", "400px", "auto") or a number, which will be coerced to a string and have "px" appended
expr	an expression that generates an output of <code>pylint</code>
env	the environment in which to evaluate expr
quoted	whether expr is a quoted expression (with <code>quote()</code>); this is useful if you want to save an expression in a variable

Value

`pylintROutput` returns an output element that can be included in a Shiny UI definition, and `renderPylintR` returns a `shiny.render.function` object that can be included in a Shiny server definition.

Index

`pylint`, [2](#), [3](#)

`pylintR-shiny`, [2](#)

`pylintROutput` (`pylintR-shiny`), [2](#)

`renderPylintR` (`pylintR-shiny`), [2](#)