

Package ‘rTPC’

July 23, 2025

Type Package

Title Fitting and Analysing Thermal Performance Curves

Version 1.0.4

Maintainer Daniel Padfield <d.padfield@exeter.ac.uk>

Description Helps to fit thermal performance curves (TPCs). 'rTPC' contains 26 model formulations previously used to fit TPCs and has helper functions to set sensible start parameters, upper and lower parameter limits and estimate parameters useful in downstream analyses, such as cardinal temperatures, maximum rate and optimum temperature. See Padfield et al. (2021) <[doi:10.1111/2041-210X.13585](https://doi.org/10.1111/2041-210X.13585)>.

License GPL-3

URL <https://github.com/padpadpadpad/rTPC>

BugReports <https://github.com/padpadpadpad/rTPC/issues>

Depends R (>= 2.10)

Imports stats

Suggests boot, broom, car, forcats, ggplot2, ggrepel, knitr, minpack.lm, MuMIn, nls.multstart, nlstools, patchwork, progress, RColorBrewer, rmarkdown, stringr, testthat, tidyverse

VignetteBuilder knitr

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

NeedsCompilation no

Author Daniel Padfield [aut, cre],
Hannah O'Sullivan [aut]

Repository CRAN

Date/Publication 2023-08-17 06:40:06 UTC

Contents

bacteria_tpc	3
beta_2012	4
boatman_2017	5
briere2_1999	7
calc_params	9
chlorella_tpc	10
delong_2017	11
deutsch_2008	12
flinn_1991	14
gaussian_1987	16
get_breadth	17
get_ctmax	18
get_ctmin	19
get_e	19
get_eh	20
get_lower_lims	20
get_model_names	21
get_q10	21
get_rmax	22
get_skewness	22
get_start_vals	23
get_thermalsafetymargin	23
get_thermaltolerance	24
get_topt	24
get_upper_lims	25
hinshelwood_1947	26
joehnk_2008	27
johnsonlewin_1946	29
kamykowski_1985	31
lactin2_1995	32
lrf_1991	34
modifiedgaussian_2006	36
oneill_1972	37
pawar_2018	39
quadratic_2008	41
ratkowsky_1983	43
rezende_2019	44
sharpeschoolfull_1981	46
sharpeschoolhigh_1981	48
sharpeschoollow_1981	50
spain_1982	51
thomas_2012	53
thomas_2017	55
weibull_1995	56

Index

bacteria_tpc*Example thermal performance curves of bacterial growth*

Description

A dataset containing example data of growth rates of the bacteria *Pseudomonas fluorescens* in the presence and absence of its phage, phi2. Growth rates were measured across a range of assay temperatures to incorporate the entire thermal performance of the bacteria. The dataset is the cleaned version so some data points have been omitted. There are multiple independent measurements per temperature for each treatment.

Usage

```
data("bacteria_tpc")
```

Format

A data frame with 649 rows and 7 variables:

phage whether the bacteria was grown with or without phage

temp the assay temperature at which the growth rate was measured (degrees centigrade)

rate estimated growth rate per hour

Source

Daniel Padfield

References

Padfield, D., Castledine, M., & Buckling, A. (2020). Temperature-dependent changes to host–parasite interactions alter the thermal performance of a bacterial host. *The ISME Journal*, 14(2), 389-398.

Examples

```
data("bacteria_tpc")
library(ggplot2)
ggplot(bacteria_tpc) +
  geom_point(aes(temp, rate, col = phage))
```

beta_2012

*Beta model for fitting thermal performance curves***Description**

Beta model for fitting thermal performance curves

Usage

```
beta_2012(temp, a, b, c, d, e)
```

Arguments

temp	temperature in degrees centigrade
a	dimensionless parameter
b	dimensionless parameter
c	dimensionless parameter
d	dimensionless parameter
e	dimensionless parameter

Details

Equation:

$$rate = \frac{a \left(\frac{temp - b + \frac{c(d-1)}{d+e-2}}{c} \right)^{d-1} \cdot \left(1 - \frac{temp - b + \frac{c(d-1)}{d+e-2}}{c} \right)^{e-1}}{\left(\frac{d-1}{d+e-2} \right)^{d-1} \cdot \left(\frac{e-1}{d+e-2} \right)^{e-1}}$$

Start values in `get_start_vals` are derived from the data or sensible values from the literature.

Limits in `get_lower_lims` and `get_upper_lims` are derived from the data or based extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model difficult to fit.

Author(s)

Daniel Padfield

References

Niehaus, Amanda C., et al. Predicting the physiological performance of ectotherms in fluctuating thermal environments. *Journal of Experimental Biology* 215.4: 694-701 (2012)

Examples

```
# load in ggplot
library(ggplot2)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'beta_2012')
# fit model
mod <- nls.multstart::nls_multstart(rate~beta_2012(temp = temp, a, b, c, d, e),
data = d,
iter = c(7,7,7,7,7),
start_lower = start_vals - 10,
start_upper = start_vals + 10,
lower = get_lower_lims(d$temp, d$rate, model_name = 'beta_2012'),
upper = get_upper_lims(d$temp, d$rate, model_name = 'beta_2012'),
supp_errors = 'Y',
convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()
```

boatman_2017

Boatman model for fitting thermal performance curves

Description

Boatman model for fitting thermal performance curves

Usage

```
boatman_2017(temp, rmax, tmin, tmax, a, b)
```

Arguments

temp	temperature in degrees centigrade
rmax	the rate at optimum temperature
tmin	low temperature (°C) at which rates become negative
tmax	high temperature (°C) at which rates become negative
a	shape parameter to adjust the skewness of the curve
b	shape parameter to adjust the kurtosis of the curve

Details

Equation:

$$rate = r_{max} \cdot \left(\sin \left(\pi \left(\frac{temp - t_{min}}{t_{max} - t_{min}} \right)^a \right) \right)^b$$

Start values in `get_start_vals` are derived from the data or sensible values from the literature.

Limits in `get_lower_lims` and `get_upper_lims` are derived from the data or based extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model easy to fit.

References

Boatman, T. G., Lawson, T., & Geider, R. J. A key marine diazotroph in a changing ocean: The interacting effects of temperature, CO₂ and light on the growth of *Trichodesmium erythraeum* IMS101. PLoS ONE, 12, e0168796 (2017)

Examples

```
# load in ggplot
library(ggplot2)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'boatman_2017')
# fit model
mod <- nls.multstart::nls_multstart(rate~boatman_2017(temp = temp, rmax, tmin, tmax, a, b),
data = d,
iter = c(4,4,4,4,4),
```

```

start_lower = start_vals - 10,
start_upper = start_vals + 10,
lower = get_lower_lims(d$temp, d$rate, model_name = 'boatman_2017'),
upper = get_upper_lims(d$temp, d$rate, model_name = 'boatman_2017'),
supp_errors = 'Y',
convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()

```

briere2_1999

*Briere2 model for fitting thermal performance curves***Description**

Briere2 model for fitting thermal performance curves

Usage

```
briere2_1999(temp, tmin, tmax, a, b)
```

Arguments

temp	temperature in degrees centigrade
tmin	low temperature (°C) at which rates become negative
tmax	high temperature (°C) at which rates become negative
a	scale parameter to adjust maximum rate of the curve
b	shape parameter to adjust the asymmetry of the curve

Details

Equation:

$$rate = a \cdot temp \cdot (temp - t_{min}) \cdot (t_{max} - temp)^{\frac{1}{b}}$$

Start values in `get_start_vals` are derived from the data or sensible values from the literature.

Limits in `get_lower_lims` and `get_upper_lims` are derived from the data or based extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model easy to fit.

References

Brière, J.F., Pracros, P., Le Roux, A.Y., Pierre, J.S., A novel rate model of temperature-dependent development for arthropods. *Environmental Entomology*, 28, 22–29 (1999)

Examples

```
# load in ggplot
library(ggplot2)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'briere2_1999')
# fit model
mod <- nls.multstart::nls_multstart(rate~briere2_1999(temp = temp, tmin, tmax, a, b),
  data = d,
  iter = c(4,4,4,4),
  start_lower = start_vals - 10,
  start_upper = start_vals + 10,
  lower = get_lower_lims(d$temp, d$rate, model_name = 'briere2_1999'),
  upper = get_upper_lims(d$temp, d$rate, model_name = 'briere2_1999'),
  supp_errors = 'Y',
  convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()
```

`calc_params`*Calculate extra parameters of a thermal performance curve*

Description

Calculate extra parameters of a thermal performance curve

Usage

```
calc_params(model)
```

Arguments

`model` nls model object that contains a model of a thermal performance curve

Details

Currently estimates:

- maximum rate (rmax) using `get_rmax()`
- optimum temperature (topt) using `get_topt()`
- critical thermal maximum (ctmax) using `get_ctmax()`
- critical thermal minimum (ctmin) using `get_ctmin()`
- activation energy (e) using `get_e()`
- deactivation energy (eh) using `get_eh()`
- q10 value using `get_q10()`
- thermal safety margin using `get_thermalsafetymargin()`
- thermal tolerance using `get_thermaltolerance()`
- thermal performance breadth using `get_breadth()`
- skewness using `get_skewness()`

Value

a dataframe containing the estimates of key TPC traits for a given model object. If any parameters cannot be calculated for a thermal performance curve, they will return NA.

chlorella_tpc*Example metabolic thermal performance curves*

Description

A dataset containing example data of rates of photosynthesis and respiration of the phytoplankton *Chlorella vulgaris*. Instantaneous rates of metabolism were made across a range of assay temperatures to incorporate the entire thermal performance of the populations. The dataset is the cleaned version so some datapoints have been omitted.

Usage

```
data("chlorella_tpc")
```

Format

A data frame with 649 rows and 7 variables:

curve_id a unique value for each separate curve

growth_temp the growth temperature that the culture was maintained at before measurements were taken (degrees centigrade)

process whether the cultures had been kept for a long time at their growth temperature (adaptation/~100 generations) or a short time (a measure of acclimation/~10 generations)

flux whether the curve depicts respiration or gross photosynthesis

temp the assay temperature at which the metabolic rate was measured (degrees centigrade)

rate the metabolic rate measured (micro mol O2 micro gram C-1 hr-1)

Source

Daniel Padfield

References

Padfield, D., Yvon-durocher, G., Buckling, A., Jennings, S. & Yvon-durocher, G. (2015). Rapid evolution of metabolic traits explains thermal adaptation in phytoplankton, *Ecology Letters*, 19, 133-142.

Examples

```
data("chlorella_tpc")
library(ggplot2)
ggplot(chlorella_tpc) +
  geom_point(aes(temp, rate, col = process)) +
  facet_wrap(~ growth_temp + flux)
```

delong_2017	<i>DeLong enzyme-assisted Arrhenius model for fitting thermal performance curves</i>
-------------	--

Description

DeLong enzyme-assisted Arrhenius model for fitting thermal performance curves

Usage

`delong_2017(temp, c, eb, ef, tm, ehc)`

Arguments

temp	temperature in degrees centigrade
c	potential reaction rate
eb	baseline energy needed for the reaction to occur (eV)
ef	temperature dependence of folding the enzymes used in the metabolic reaction, relative to the melting temperature (eV)
tm	melting temperature in degrees centigrade
ehc	temperature dependence of the heat capacity between the folded and unfolded state of the enzymes, relative to the melting temperature (eV)

Details

Equation:

$$rate = c \cdot \exp \frac{-(e_b - (e_f(1 - \frac{temp+273.15}{t_m}) + e_{hc} \cdot ((temp + 273.15) - t_m - (temp + 273.15) \cdot \ln(\frac{temp+273.15}{t_m}))))}{k \cdot (temp + 273.15)}$$

where k is Boltzmann's constant with a value of 8.62e-05 and tm is actually tm - 273.15

Start values in `get_start_vals` are derived from the data or sensible values from the literature.

Limits in `get_lower_lims` and `get_upper_lims` are derived from the data or based extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model easy to fit.

References

DeLong, John P., et al. The combined effects of reactant kinetics and enzyme stability explain the temperature dependence of metabolic rates. *Ecology and evolution* 7.11 (2017): 3940-3950.

Examples

```
# load in ggplot
library(ggplot2)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'delong_2017')
# fit model
mod <- nls.multstart::nls_multstart(rate~delong_2017(temp = temp, c, eb, ef, tm,ehc),
data = d,
iter = c(4,4,4,4,4),
start_lower = start_vals - 10,
start_upper = start_vals + 10,
lower = get_lower_lims(d$temp, d$rate, model_name = 'delong_2017'),
upper = get_upper_lims(d$temp, d$rate, model_name = 'delong_2017'),
supp_errors = 'Y',
convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()
```

deutsch_2008

Modified deutsch model for fitting thermal performance curves

Description

Modified deutsch model for fitting thermal performance curves

Usage

```
deutsch_2008(temp, rmax, topt, ctmx, a)
```

Arguments

temp	temperature in degrees centigrade
rmax	maximum rate at optimum temperature
topt	optimum temperature (°C)
ctmax	critical thermal maximum (°C)
a	related to the full curve width

Details

Equation:

$$\begin{aligned} \text{if } temp < t_{opt} : rate &= r_{max} \cdot \exp\left(-\left(\frac{temp - t_{opt}}{2a}\right)^2\right) \\ \text{if } temp > t_{opt} : rate &= r_{max} \cdot \left(1 - \left(\frac{temp - t_{opt}}{t_{opt} - ct_{max}}\right)^2\right) \end{aligned}$$

Start values in `get_start_vals` are derived from the data.

Limits in `get_lower_lims` and `get_upper_lims` are based on extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model easy to fit.

References

Deutsch, C. A., Tewksbury, J. J., Huey, R. B., Sheldon, K. S., Ghalambor, C. K., Haak, D. C., & Martin, P. R. Impacts of climate warming on terrestrial ectotherms across latitude. *Proceedings of the National Academy of Sciences*, 105(18), 6668-6672. (2008)

Examples

```
# load in ggplot
library(ggplot2)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'deutsch_2008')
# fit model
mod <- nls.multstart::nls_multstart(rate~deutsch_2008(temp = temp, rmax, topt, ctmax, a),
```

```

data = d,
iter = c(4,4,4,4),
start_lower = start_vals - 10,
start_upper = start_vals + 10,
lower = get_lower_lims(d$temp, d$rate, model_name = 'deutsch_2008'),
upper = get_upper_lims(d$temp, d$rate, model_name = 'deutsch_2008'),
supp_errors = 'Y',
convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()

```

flinn_1991

*Flinn model for fitting thermal performance curves***Description**

Flinn model for fitting thermal performance curves

Usage

```
flinn_1991(temp, a, b, c)
```

Arguments

temp	temperature in degrees centigrade
a	parameter that controls the height of the curve
b	parameter that controls the slope of the initial increase of the curve
c	parameter that controls the position and steepness of the decline of the curve

Details

Equation:

$$rate = \frac{1}{1 + a + b \cdot temp + c \cdot temp^2}$$

Start values in `get_start_vals` are derived from previous methods from the literature.

Limits in `get_lower_lims` and `get_upper_lims` are based on extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model easy to fit.

References

Flinn PW Temperature-dependent functional response of the parasitoid *Cephalonomia waterstoni* (Gahan) (Hymenoptera, Bethyridae) attacking rusty grain beetle larvae (Coleoptera, Cucujidae). *Environmental Entomology*, 20, 872–876, (1991)

Examples

```
# load in ggplot
library(ggplot2)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'flinn_1991')
# fit model
mod <- nls.multstart::nls_multstart(rate~flinn_1991(temp = temp, a, b, c),
data = d,
iter = c(4,4,4),
start_lower = start_vals - 1,
start_upper = start_vals + 1,
lower = get_lower_lims(d$temp, d$rate, model_name = 'flinn_1991'),
upper = get_upper_lims(d$temp, d$rate, model_name = 'flinn_1991'),
supp_errors = 'Y',
convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()
```

gaussian_1987

Gaussian model for fitting thermal performance curves

Description

Gaussian model for fitting thermal performance curves

Usage

```
gaussian_1987(temp, rmax, topt, a)
```

Arguments

temp	temperature in degrees centigrade
rmax	maximum rate at optimum temperature
topt	optimum temperature (°C)
a	related to the full curve width

Details

Equation:

$$rate = r_{max} \cdot \exp\left(-0.5\left(\frac{|temp - topt|}{a}\right)^2\right)$$

Start values in `get_start_vals` are derived from the data

Limits in `get_lower_lims` and `get_upper_lims` are based on extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model easy to fit.

References

Lynch, M., Gabriel, W., Environmental tolerance. The American Naturalist. 129, 283–303. (1987)

Examples

```

# load in ggplot
library(ggplot2)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'gaussian_1987')
# fit model
mod <- nls.multstart::nls_multstart(rate~gaussian_1987(temp = temp,rmax, topt,a),
data = d,
iter = c(4,4,4),
start_lower = start_vals - 10,
start_upper = start_vals + 10,
lower = get_lower_lims(d$temp, d$rate, model_name = 'gaussian_1987'),
upper = get_upper_lims(d$temp, d$rate, model_name = 'gaussian_1987'),
supp_errors = 'Y',
convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()

```

get_breadth	<i>Estimate thermal performance breadth of a thermal performance curve</i>
-------------	--

Description

Estimate thermal performance breadth of a thermal performance curve

Usage

```
get_breadth(model, level = 0.8)
```

Arguments

model	nls model object that contains a model of a thermal performance curve
level	proportion of maximum rate over which thermal performance breadth is calculated

Details

Thermal performance breadth is calculated as the range of temperatures over which a curve's rate is at least 0.8 of peak. This defaults to a proportion of 0.8 but can be changed using the `level` argument.

Value

Numeric estimate of thermal performance breadth (in °C)

get_ctmax	<i>Estimate the critical thermal maximum of a thermal performance curve</i>
-----------	---

Description

Estimate the critical thermal maximum of a thermal performance curve

Usage

```
get_ctmax(model)
```

Arguments

model	nls model object that contains a model of a thermal performance curve
-------	---

Details

Critical thermal maximum is calculated by predicting over a temperature range 50 °C beyond the maximum value in the dataset. The predicted rate value closest to 0 is then extracted. When this is impossible due to the curve formula (i.e the Sharpe-Schoolfield model), the temperature where the rate is 5 percent of the maximum rate is estimated. Predictions are done every 0.001 °C so the estimate of the critical thermal maximum should be accurate up to 0.001 °C.

Value

Numeric estimate of critical thermal maximum (°C)

get_ctmin	<i>Estimate the critical thermal minimum of a thermal performance curve</i>
-----------	---

Description

Estimate the critical thermal minimum of a thermal performance curve

Usage

```
get_ctmin(model)
```

Arguments

model	nls model object that contains a model of a thermal performance curve
-------	---

Details

Optimum temperature is calculated by predicting over a temperature range 50 degrees lower than the minimum value in the dataset. The predicted rate value closest to 0 is then extracted. When this is impossible due to the curve formula (i.e the Sharpe-Schoolfield model), the temperature where the rate is 5 percent of the maximum rate is estimated. Predictions are done every 0.001 °C value so the estimate of the critical thermal minimum should be accurate up to 0.001 °C.

Value

Numeric estimate of critical thermal minimum (°C)

get_e	<i>Estimate the activation energy of a thermal performance curve</i>
-------	--

Description

Estimate the activation energy of a thermal performance curve

Usage

```
get_e(model)
```

Arguments

model	nls model object that contains a model of a thermal performance curve
-------	---

Details

Fits a modified-Boltzmann equation to all raw data below the optimum temperature (°C; as estimated by get_topt).

Value

Numeric estimate of activation energy (eV)

get_eh

Estimate the deactivation energy of a thermal performance curve

Description

Estimate the deactivation energy of a thermal performance curve

Usage

```
get_eh(model)
```

Arguments

model nls model object that contains a model of a thermal performance curve

Details

Fits a modified-Boltzmann equation to all raw data beyond the optimum temperature (°C; as estimated by get_topt).

Value

Numeric estimate of activation energy (eV)

get_lower_lims

Set broad lower limits on parameter values

Description

Sets wide lower limits on parameter values for each TPC model

Usage

```
get_lower_lims(x, y, model_name)
```

Arguments

x vector of temperature values
y vector of rate values
model_name the name of the model being fitted

Value

Named list of lower limits given the data and model being fitted

Author(s)

Daniel Padfield

get_model_names	<i>Lists the models available in rTPC</i>
-----------------	---

Description

Lists the models available in rTPC

Usage

```
get_model_names()
```

Value

character vector of thermal performance curves available in rTPC

Examples

```
get_model_names()
```

get_q10	<i>Estimate the q10 value of a thermal performance curve</i>
---------	--

Description

Estimate the q10 value of a thermal performance curve

Usage

```
get_q10(model)
```

Arguments

model	nls model object that contains a model of a thermal performance curve
-------	---

Details

Fits the q10 portion of rezende_2019 to all raw data below the optimum temperature (°C; as estimated by get_topt).

Value

Numeric estimate of q10 value

`get_rmax`*Estimate maximum rate of a thermal performance curve*

Description

Estimate maximum rate of a thermal performance curve

Usage

```
get_rmax(model)
```

Arguments

`model` nls model object that contains a model of a thermal performance curve

Details

Maximum rate is calculated by predicting over the temperature range using the previously estimated parameters and picking the maximum rate value. Predictions are done every 0.001 °C.

Value

Numeric estimate of maximum rate

`get_skewness`*Estimates skewness of a thermal performance curve*

Description

Estimates skewness of a thermal performance curve

Usage

```
get_skewness(model)
```

Arguments

`model` nls model object that contains a model of a thermal performance curve

Details

Skewness is calculated from the values of activation energy (e) and deactivation energy (eh) as: $\text{skewness} = e - eh$. A negative skewness indicates the TPC is left skewed, the drop after the optimum is steeper than the rise up to the optimum. A positive skewness means that the TPC is right skewed and a value of 0 would mean the curve is symmetrical around the optimum.

Value

Numeric estimate of skewness

get_start_vals	<i>Estimate start values for TPC fitting</i>
----------------	--

Description

Estimates sensible start values for fitting thermal performance curves

Usage

```
get_start_vals(x, y, model_name)
```

Arguments

x	vector of temperature values
y	vector of rate values
model_name	the name of the model being fitted

Value

Named list of start parameters given the data and model being fitted

Author(s)

Daniel Padfield

get_thermalsafetymargin	<i>Estimate thermal safety margin of a thermal performance curve</i>
-------------------------	--

Description

Estimate thermal safety margin of a thermal performance curve

Usage

```
get_thermalsafetymargin(model)
```

Arguments

model	nls model object that contains a model of a thermal performance curve
-------	---

Details

Thermal safety margin is calculated as: $CT_{max} - T_{opt}$. This is calculated using the functions `get_ctmax` and `get_topt`.

Value

Numeric estimate of thermal safety margin (in °C)

<code>get_thermaltolerance</code>	<i>Estimate thermal tolerance of a thermal performance curve</i>
-----------------------------------	--

Description

Estimate thermal tolerance of a thermal performance curve

Usage

```
get_thermaltolerance(model)
```

Arguments

<code>model</code>	nls model object that contains a model of a thermal performance curve
--------------------	---

Details

Thermal tolerance is calculated as: $CT_{max} - CT_{min}$. This is calculated using the functions `get_ctmax` and `get_ctmin`.

Value

Thermal tolerance (in °C)

<code>get_topt</code>	<i>Estimate optimum temperature of a thermal performance curve</i>
-----------------------	--

Description

Estimate optimum temperature of a thermal performance curve

Usage

```
get_topt(model)
```

Arguments

<code>model</code>	nls model object that contains a model of a thermal performance curve
--------------------	---

Details

Optimum temperature (°C) is calculated by predicting over the temperature range using the previously estimated parameters and keeping the temperature where the largest rate value occurs. Predictions are done every 0.001 °C so the estimate of optimum temperature should be accurate up to 0.001 °C.

Value

Numeric estimate of optimum temperature (in °C)

get_upper_lims	<i>Set broad upper limits on parameter values</i>
----------------	---

Description

Sets wide upper limits on parameter values for each TPC model

Usage

```
get_upper_lims(x, y, model_name)
```

Arguments

x	vector of temperature values
y	vector of rate values
model_name	the name of the model being fitted

Value

Named list of upper limits given the data and model being fitted

Author(s)

Daniel Padfield

hinshelwood_1947

Hinshelwood model for fitting thermal performance curves

Description

Hinshelwood model for fitting thermal performance curves

Usage

hinshelwood_1947(temp, a, e, b, eh)

Arguments

temp	temperature in degrees centigrade
a	pre-exponential constant for the activation energy
e	activation energy (eV)
b	pre-exponential constant for the deactivation energy
eh	de-activation energy (eV)

Details

Equation:

$$rate = a \cdot \exp^{\frac{-e}{k \cdot (temp + 273.15)}} - b \cdot \exp^{\frac{-e_h}{k \cdot (temp + 273.15)}}$$

where k is Boltzmann's constant with a value of 8.62e-05

Start values in get_start_vals are taken from the literature.

Limits in get_lower_lims and get_upper_lims are based on extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model difficult to fit.

References

Hinshelwood C.N. The Chemical Kinetics of the Bacterial Cell. Oxford University Press. (1947)

Examples

```

# load in ggplot
library(ggplot2)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'hinshelwood_1947')
# fit model
mod <- nls.multstart::nls_multstart(rate~hinshelwood_1947(temp = temp,a, e, b, eh),
data = d,
iter = c(5,5,5,5),
start_lower = start_vals - 1,
start_upper = start_vals + 1,
lower = get_lower_lims(d$temp, d$rate, model_name = 'hinshelwood_1947'),
upper = get_upper_lims(d$temp, d$rate, model_name = 'hinshelwood_1947'),
supp_errors = 'Y',
convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()

```

joehnk_2008

*Jöhnk model for fitting thermal performance curves***Description**

Jöhnk model for fitting thermal performance curves

Usage

```
joehnk_2008(temp, rmax, topt, a, b, c)
```

Arguments

temp temperature in degrees centigrade

rmax	the rate at optimum temperature
topt	optimum temperature (°C)
a	parameter with no biological meaning
b	parameter with no biological meaning
c	parameter with no biological meaning

Details

Equation:

$$rate = r_{max} \left(1 + a \left(\left(b^{temp - t_{opt}} - 1 \right) - \frac{\ln(b)}{\ln(c)} (c^{temp - t_{opt}} - 1) \right) \right)$$

Start values in `get_start_vals` are derived from the data or sensible values from the literature.

Limits in `get_lower_lims` and `get_upper_lims` are based on extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model easy to fit.

References

Joehnk, Klaus D., et al. Summer heatwaves promote blooms of harmful cyanobacteria. *Global change biology* 14.3: 495-512 (2008)

Examples

```
# load in ggplot
library(ggplot2)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'joehnk_2008')
# fit model
mod <- nls.multstart::nls_multstart(rate~joehnk_2008(temp = temp, rmax, topt, a, b, c),
data = d,
iter = c(3,3,3,3,3),
start_lower = start_vals - 10,
start_upper = start_vals + 10,
lower = get_lower_lims(d$temp, d$rate, model_name = 'joehnk_2008'),
upper = get_upper_lims(d$temp, d$rate, model_name = 'joehnk_2008'),
```

```

supp_errors = 'Y',
convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()

```

johnsonlewin_1946

*Johnson-Lewin model for fitting thermal performance curves***Description**

Johnson-Lewin model for fitting thermal performance curves

Usage

```
johnsonlewin_1946(temp, r0, e, eh, topt)
```

Arguments

temp	temperature in degrees centigrade
r0	scaling parameter
e	activation energy (eV)
eh	high temperature de-activation energy (eV)
topt	optimum temperature (°C)

Details

Equation:

$$rate = \frac{r_0 \cdot \exp\left(\frac{-e}{k \cdot (temp + 273.15)}\right)}{1 + \exp\left(\frac{e_h - \left(\frac{e_h}{(t_{opt} + 273.15)} + k \cdot \ln\left(\frac{e}{e_h - e}\right)\right) \cdot (temp + 273.15)}{k \cdot (temp + 273.15)}\right)}$$

where k is Boltzmann's constant with a value of 8.62e-05.

Start values in get_start_vals are derived from the data.

Limits in get_lower_lims and get_upper_lims are derived from the data or based extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model difficult to fit.

References

Johnson, Frank H., and Isaac Lewin. The growth rate of *E. coli* in relation to temperature, quinine and coenzyme. *Journal of Cellular and Comparative Physiology* 28.1 (1946): 47-75.

Examples

```
# load in ggplot
library(ggplot2)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'johnsonlewin_1946')
# fit model
mod <- suppressWarnings(
  nls.multstart::nls_multstart(rate~johnsonlewin_1946(temp = temp, r0, e, eh, topt),
    data = d,
    iter = c(5,5,5,5),
    start_lower = start_vals - 1,
    start_upper = start_vals + 1,
    lower = get_lower_lims(d$temp, d$rate, model_name = 'johnsonlewin_1946'),
    upper = get_upper_lims(d$temp, d$rate, model_name = 'johnsonlewin_1946'),
    supp_errors = 'Y',
    convergence_count = FALSE)
)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()
```

kamykowski_1985

*Kamykowski model for fitting thermal performance curves***Description**

Kamykowski model for fitting thermal performance curves

Usage

```
kamykowski_1985(temp, tmin, tmax, a, b, c)
```

Arguments

temp	temperature in degrees centigrade
tmin	low temperature (°C) at which rates become negative
tmax	high temperature (°C) at which rates become negative
a	parameter with no biological meaning
b	parameter with no biological meaning
c	parameter with no biological meaning

Details

Equation:

$$rate = a \cdot (1 - \exp^{-b \cdot (temp - t_{min})}) \cdot (1 - \exp^{-c \cdot (t_{max} - temp)})$$

Start values in `get_start_vals` are derived from the data or sensible values from the literature.

Limits in `get_lower_lims` and `get_upper_lims` are derived from the data or based extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model easy to fit.

References

Kamykowski, Daniel. A survey of protozoan laboratory temperature studies applied to marine dinoflagellate behaviour from a field perspective. Contributions in Marine Science. (1985).

Examples

```
# load in ggplot
library(ggplot2)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'kamykowski_1985')
# fit model
mod <- nls.multstart::nls_multstart(rate~kamykowski_1985(temp = temp, tmin, tmax, a, b, c),
data = d,
iter = c(3,3,3,3,3),
start_lower = start_vals - 10,
start_upper = start_vals + 10,
lower = get_lower_lims(d$temp, d$rate, model_name = 'kamykowski_1985'),
upper = get_upper_lims(d$temp, d$rate, model_name = 'kamykowski_1985'),
supp_errors = 'Y',
convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()
```

lactin2_1995

*Lactin2 model for fitting thermal performance curves***Description**

Lactin2 model for fitting thermal performance curves

Usage

```
lactin2_1995(temp, a, b, tmax, delta_t)
```

Arguments

temp temperature in degrees centigrade

a	constant that determines the steepness of the rising portion of the curve
b	constant that determines the height of the overall curve
tmax	the temperature at which the curve begins to decelerate beyond the optimum (°C)
delta_t	thermal safety margin (°C)

Details

Equation:

$$rate == exp^{a \cdot temp} - exp^{a \cdot t_{max} - \left(\frac{t_{max} - temp}{\delta_t} \right)} + b$$

Start values in `get_start_vals` are derived from the data or sensible values from the literature.

Limits in `get_lower_lims` and `get_upper_lims` are derived from the data or based extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model easy to fit.

References

Lactin, D.J., Holliday, N.J., Johnson, D.L. & Craigen, R. Improved rate models of temperature-dependent development by arthropods. *Environmental Entomology* 24, 69-75 (1995)

Examples

```
# load in ggplot
library(ggplot2)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'lactin2_1995')
# fit model
mod <- nls.multstart::nls_multstart(rate~lactin2_1995(temp = temp, a, b, tmax, delta_t),
data = d,
iter = c(3,3,3,3),
start_lower = start_vals - 10,
start_upper = start_vals + 10,
lower = get_lower_lims(d$temp, d$rate, model_name = 'lactin2_1995'),
upper = get_upper_lims(d$temp, d$rate, model_name = 'lactin2_1995'),
supp_errors = 'Y',
```

```

convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()

```

lrf_1991	<i>Lobry-Rosso-Flandros (LRF) model for fitting thermal performance curves</i>
----------	--

Description

Lobry-Rosso-Flandros (LRF) model for fitting thermal performance curves

Usage

```
lrf_1991(temp, rmax, topt, tmin, tmax)
```

Arguments

temp	temperature in degrees centigrade
rmax	maximum rate at optimum temperature
topt	optimum temperature (°C)
tmin	low temperature (°C) at which rates become negative
tmax	high temperature (°C) at which rates become negative

Details

Equation:

$$rate = rmax \cdot \frac{(temp - t_{max}) \cdot (temp - t_{min})^2}{(t_{opt} - t_{min}) \cdot ((t_{opt} - t_{min}) \cdot (temp - t_{opt}) - (t_{opt} - t_{max}) \cdot (t_{opt} + t_{min} - 2 \cdot temp))}$$

Start values in `get_start_vals` are derived from the data.

Limits in `get_lower_lims` and `get_upper_lims` are derived from the data or based extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model easy to fit.

Author(s)

Daniel Padfield

References

Rosso, L., Lobry, J. R., & Flandrois, J. P. An unexpected correlation between cardinal temperatures of microbial growth highlighted by a new model. *Journal of Theoretical Biology*, 162(4), 447-463. (1993)

Examples

```
# load in ggplot
library(ggplot2)
library(nls.multstart)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'sharpeschoolhigh_1981')
# fit model
mod <- nls_multstart(rate~lrf_1991(temp = temp, rmax, topt, tmin, tmax),
  data = d,
  iter = c(3,3,3,3),
  start_lower = start_vals - 10,
  start_upper = start_vals + 10,
  lower = get_lower_lims(d$temp, d$rate, model_name = 'lrf_1991'),
  upper = get_upper_lims(d$temp, d$rate, model_name = 'lrf_1991'),
  supp_errors = 'Y',
  convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
```

```
geom_line(aes(temp, .fitted), col = 'blue') +
theme_bw()
```

modifiedgaussian_2006 *Modified gaussian model for fitting thermal performance curves*

Description

Modified gaussian model for fitting thermal performance curves

Usage

```
modifiedgaussian_2006(temp, rmax, topt, a, b)
```

Arguments

temp	temperature in degrees centigrade
rmax	maximum rate at optimum temperature
topt	optimum temperature
a	related to full curve width
b	allows for asymmetry in the curve fit

Details

Equation:

$$rate = r_{max} \cdot \exp \left[-0.5 \left(\frac{|temp - t_{opt}|}{a} \right)^b \right]$$

Start values in `get_start_vals` are derived from the data and `gaussian_1987`

Limits in `get_lower_lims` and `get_upper_lims` are based on extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model difficult to fit.

References

Angilletta Jr, M. J. (2006). Estimating and comparing thermal performance curves. *Journal of Thermal Biology*, 31(7), 541-545.

Examples

```

# load in ggplot
library(ggplot2)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'modifiedgaussian_2006')
# fit model
mod <- nls.multstart::nls_multstart(rate~modifiedgaussian_2006(temp = temp, rmax, topt, a, b),
data = d,
iter = c(3,3,3,3),
start_lower = start_vals - 10,
start_upper = start_vals + 10,
lower = get_lower_lims(d$temp, d$rate, model_name = 'modifiedgaussian_2006'),
upper = get_upper_lims(d$temp, d$rate, model_name = 'modifiedgaussian_2006'),
supp_errors = 'Y',
convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()

```

oneill_1972

*O'Neill model for fitting thermal performance curves***Description**

O'Neill model for fitting thermal performance curves

Usage

```
oneill_1972(temp, rmax, ctmx, topt, q10)
```

Arguments

temp temperature in degrees centigrade

rmax	maximum rate at optimum temperature
ctmax	high temperature (°C) at which rates become negative
topt	optimum temperature (°C)
q10	defines the fold change in performance as a result of increasing the temperature by 10 °C

Details

Equation:

$$rate = r_{max} \cdot \left(\frac{ct_{max} - temp}{ct_{max} - t_{opt}} \right)^x \cdot exp^{x \cdot \frac{temp - t_{opt}}{ct_{max} - t_{opt}}}$$

$$where : x = \frac{w^2}{400} \cdot \left(1 + \sqrt{1 + \frac{40}{w}} \right)^2$$

$$and : w = (q_{10} - 1) \cdot (ct_{max} - t_{opt})$$

Start values in `get_start_vals` are derived from the data and previous values in the literature

Limits in `get_lower_lims` and `get_upper_lims` are based on extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model easy to fit.

References

O'Neill, R.V., Goldstein, R.A., Shugart, H.H., Mankin, J.B. Terrestrial Ecosystem Energy Model. Eastern Deciduous Forest Biome Memo Report Oak Ridge. The Environmental Sciences Division of the Oak Ridge National Laboratory. (1972)

Examples

```
# load in ggplot
library(ggplot2)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'oneill_1972')
# fit model
mod <- nls.multstart::nls_multstart(rate~oneill_1972(temp = temp, rmax, ctmax, topt, q10),
data = d,
```

```

iter = c(4,4,4,4),
start_lower = start_vals - 10,
start_upper = start_vals + 10,
lower = get_lower_lims(d$temp, d$rate, model_name = 'oneill_1972'),
upper = get_upper_lims(d$temp, d$rate, model_name = 'oneill_1972'),
supp_errors = 'Y',
convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()

```

pawar_2018

Pawar model for fitting thermal performance curves

Description

Pawar model for fitting thermal performance curves

Usage

```
pawar_2018(temp, r_tref, e, eh, topt, tref)
```

Arguments

temp	temperature in degrees centigrade
r_tref	rate at the standardised temperature, tref
e	activation energy (eV)
eh	high temperature de-activation energy (eV)
topt	optimum temperature (°C)
tref	standardisation temperature in degrees centigrade. Temperature at which rates are not inactivated by high temperatures

Details

This model is a modified version of `sharpeschoolhigh_1981` that explicitly models the optimum temperature. Equation:

$$rate = \frac{r_{tref} \cdot \exp^{\frac{-e}{k}(\frac{1}{temp+273.15} - \frac{1}{t_{ref}+273.15})}}{1 + (\frac{e}{e_h - e}) \cdot \exp^{\frac{e_h}{k}(\frac{1}{t_{opt}+273.15} - \frac{1}{temp+273.15})}}$$

where k is Boltzmann's constant with a value of $8.62e-05$.

Start values in `get_start_vals` are derived from the data.

Limits in `get_lower_lims` and `get_upper_lims` are derived from the data or based extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model easy to fit.

Author(s)

Daniel Padfield

References

Kontopoulos, Dimitrios - Georgios, Bernardo García-Carreras, Sofía Sal, Thomas P. Smith, and Samraat Pawar. Use and Misuse of Temperature Normalisation in Meta-Analyses of Thermal Responses of Biological Traits. *PeerJ*. 6 (2018),

Examples

```
# load in ggplot
library(ggplot2)
library(nls.multstart)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'pawar_2018')
# fit model
mod <- nls_multstart(rate~pawar_2018(temp = temp, r_tref, e, eh, topt, tref = 20),
  data = d,
  iter = c(3,3,3,3),
  start_lower = start_vals - 10,
  start_upper = start_vals + 10,
```

```

lower = get_lower_lims(d$temp, d$rate, model_name = 'pawar_2018'),
upper = get_upper_lims(d$temp, d$rate, model_name = 'pawar_2018'),
supp_errors = 'Y',
convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()

```

quadratic_2008

*Quadratic model for fitting thermal performance curves***Description**

Quadratic model for fitting thermal performance curves

Usage

```
quadratic_2008(temp, a, b, c)
```

Arguments

temp	temperature in degrees centigrade
a	parameter that defines the rate at 0 °C
b	parameter with no biological meaning
c	parameter with no biological meaning

Details

Equation:

$$rate = a + b \cdot temp + c \cdot temp^2$$

Start values in `get_start_vals` are derived from the data using previous methods in the literature

Limits in `get_lower_lims` and `get_upper_lims` are based on extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model easy to fit.

References

Montagnes, David JS, et al. Short-term temperature change may impact freshwater carbon flux: a microbial perspective. *Global Change Biology* 14.12: 2823-2838. (2008)

Examples

```
# load in ggplot
library(ggplot2)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'quadratic_2008')
# fit model
mod <- nls.multstart::nls_multstart(rate~quadratic_2008(temp = temp, a, b, c),
data = d,
iter = c(4,4,4),
start_lower = start_vals - 10,
start_upper = start_vals + 10,
lower = get_lower_lims(d$temp, d$rate, model_name = 'quadratic_2008'),
upper = get_upper_lims(d$temp, d$rate, model_name = 'quadratic_2008'),
supp_errors = 'Y',
convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()
```

ratkowsky_1983

Ratkowsky model for fitting thermal performance curves

Description

Ratkowsky model for fitting thermal performance curves

Usage

```
ratkowsky_1983(temp, tmin, tmax, a, b)
```

Arguments

temp	temperature in degrees centigrade
tmin	low temperature (°C) at which rates become negative
tmax	high temperature (°C) at which rates become negative
a	parameter defined as $\sqrt{\text{rate}}/(\text{temp} - t_{\min})$
b	empirical parameter needed to fit the data for temperatures beyond the optimum temperature

Details

Equation:

$$\text{rate} = (a \cdot (\text{temp} - t_{\min}))^2 \cdot (1 - \exp(b \cdot (\text{temp} - t_{\max})))^2$$

Start values in `get_start_vals` are derived from the data and previous values in the literature.

Limits in `get_lower_lims` and `get_upper_lims` are based on extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model easy to fit.

References

Ratkowsky, D.A., Lowry, R.K., McMeekin, T.A., Stokes, A.N., Chandler, R.E., Model for bacterial growth rate throughout the entire biokinetic temperature range. J. Bacteriol. 154: 1222–1226 (1983)

Examples

```

# load in ggplot
library(ggplot2)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'ratkowsky_1983')
# fit model
mod <- nls.multstart::nls_multstart(rate~ratkowsky_1983(temp = temp, tmin, tmax, a, b),
data = d,
iter = c(4,4,4,4),
start_lower = start_vals - 10,
start_upper = start_vals + 10,
lower = get_lower_lims(d$temp, d$rate, model_name = 'ratkowsky_1983'),
upper = get_upper_lims(d$temp, d$rate, model_name = 'ratkowsky_1983'),
supp_errors = 'Y',
convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()

```

rezende_2019

*Rezende model for fitting thermal performance curves***Description**

Rezende model for fitting thermal performance curves

Usage

```
rezende_2019(temp, q10, a, b, c)
```

Arguments

temp temperature in degrees centigrade

q10	defines the fold change in performance as a result of increasing the temperature by 10 °C
a	parameter describing shifts in rate
b	parameter threshold temperature (°C) beyond which the downward curve starts
c	parameter controlling the rate of decline beyond the threshold temperature, b

Details

Equation:

$$\begin{aligned} \text{if } temp < b : rate &= a \cdot 10^{\frac{\log_{10}(q_{10})}{(\frac{10}{temp})}} \\ \text{if } temp > b : rate &= a \cdot 10^{\frac{\log_{10}(q_{10})}{(\frac{10}{temp})}} \cdot \left(1 - c \cdot (b - temp)^2\right) \end{aligned}$$

Start values in `get_start_vals` are derived from the data and previous values in the literature.

Limits in `get_lower_lims` and `get_upper_lims` are based on extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model easy to fit.

References

Rezende, Enrico L., and Francisco Bozinovic. Thermal performance across levels of biological organization. *Philosophical Transactions of the Royal Society B* 374.1778 (2019): 20180549.

Examples

```
# load in ggplot
library(ggplot2)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'rezende_2019')
# fit model
mod <- nls.multstart::nls_multstart(rate~rezende_2019(temp = temp, q10, a, b, c),
data = d,
iter = c(4,4,4,4),
start_lower = start_vals - 10,
start_upper = start_vals + 10,
lower = get_lower_lims(d$temp, d$rate, model_name = 'rezende_2019'),
```

```

upper = get_upper_lims(d$temp, d$rate, model_name = 'rezende_2019'),
supp_errors = 'Y',
convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()

```

sharpeschoolfull_1981 *Full Sharpe-Schoolfield model for fitting thermal performance curves*

Description

Full Sharpe-Schoolfield model for fitting thermal performance curves

Usage

```
sharpeschoolfull_1981(temp, r_tref, e, el, tl, eh, th, tref)
```

Arguments

temp	temperature in degrees centigrade
r_tref	rate at the standardised temperature, tref
e	activation energy (eV)
el	low temperature de-activation energy (eV)
tl	temperature (°C) at which enzyme is 1/2 active and 1/2 suppressed due to low temperatures
eh	high temperature de-activation energy (eV)
th	temperature (°C) at which enzyme is 1/2 active and 1/2 suppressed due to high temperatures
tref	standardisation temperature in degrees centigrade. Temperature at which rates are not inactivated by either high or low temperatures

Details

Equation:

$$rate = \frac{r_{tref} \cdot \exp^{\frac{-e}{k}(\frac{1}{temp+273.15} - \frac{1}{t_{ref}+273.15})}}{1 + \exp^{\frac{e_l}{k}(\frac{1}{t_l} - \frac{1}{temp+273.15})} + \exp^{\frac{e_h}{k}(\frac{1}{t_h} - \frac{1}{temp+273.15})}}$$

where k is Boltzmann's constant with a value of 8.62e-05.

Start values in `get_start_vals` are derived from the data.

Limits in `get_lower_lims` and `get_upper_lims` are derived from the data or based extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model easy to fit.

Author(s)

Daniel Padfield

References

Schoolfield, R. M., Sharpe, P. J. & Magnuson, C. E. Non-linear regression of biological temperature-dependent rate models based on absolute reaction-rate theory. *Journal of Theoretical Biology* 88, 719-731 (1981)

Examples

```
# load in ggplot
library(ggplot2)
library(nls.multstart)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'sharpeschoolfull_1981')
# fit model
mod <- nls_multstart(rate~sharpeschoolfull_1981(temp = temp, r_tref, e, el, tl, eh, th, tref = 20),
  data = d,
  iter = c(3,3,3,3,3,3),
  start_lower = start_vals - 10,
  start_upper = start_vals + 10,
  lower = get_lower_lims(d$temp, d$rate, model_name = 'sharpeschoolfull_1981'),
  upper = get_upper_lims(d$temp, d$rate, model_name = 'sharpeschoolfull_1981'),
  supp_errors = 'Y',
```

```

convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()

```

sharpeschoolhigh_1981 *Sharpe-Schoolfield model (high temperature inactivation only) for fitting thermal performance curves*

Description

Sharpe-Schoolfield model (high temperature inactivation only) for fitting thermal performance curves

Usage

```
sharpeschoolhigh_1981(temp, r_tref, e, eh, th, tref)
```

Arguments

temp	temperature in degrees centigrade
r_tref	rate at the standardised temperature, tref
e	activation energy (eV)
eh	high temperature de-activation energy (eV)
th	temperature (°C) at which enzyme is 1/2 active and 1/2 suppressed due to high temperatures
tref	standardisation temperature in degrees centigrade. Temperature at which rates are not inactivated by high temperatures

Details

Equation:

$$rate = \frac{r_{tref} \cdot \exp\left(\frac{-e}{k} \left(\frac{1}{temp+273.15} - \frac{1}{t_{ref}+273.15} \right)\right)}{1 + \exp\left(\frac{e_h}{k} \left(\frac{1}{t_h} - \frac{1}{temp+273.15} \right)\right)}$$

where k is Boltzmann's constant with a value of 8.62e-05.

Start values in get_start_vals are derived from the data.

Limits in get_lower_lims and get_upper_lims are derived from the data or based extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model easy to fit.

Author(s)

Daniel Padfield

References

Schoolfield, R. M., Sharpe, P. J. & Magnuson, C. E. Non-linear regression of biological temperature-dependent rate models based on absolute reaction-rate theory. *J. Theor. Biol.* 88, 719-731 (1981)

Examples

```
# load in ggplot
library(ggplot2)
library(nls.multstart)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'sharpeschoolhigh_1981')
# fit model
mod <- nls_multstart(rate~sharpeschoolhigh_1981(temp = temp, r_tref, e, eh, th, tref = 20),
  data = d,
  iter = c(3,3,3,3),
  start_lower = start_vals - 10,
  start_upper = start_vals + 10,
  lower = get_lower_lims(d$temp, d$rate, model_name = 'sharpeschoolhigh_1981'),
  upper = get_upper_lims(d$temp, d$rate, model_name = 'sharpeschoolhigh_1981'),
  supp_errors = 'Y',
  convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()
```

sharpeschoollow_1981	<i>Sharpe-Schoolfield model (low temperature inactivation only) for fitting thermal performance curves</i>
----------------------	--

Description

Sharpe-Schoolfield model (low temperature inactivation only) for fitting thermal performance curves

Usage

```
sharpeschoollow_1981(temp, r_tref, e, el, tl, tref)
```

Arguments

temp	temperature in degrees centigrade
r_tref	rate at the standardised temperature, tref
e	activation energy (eV)
el	low temperature de-activation energy (eV)
tl	temperature (°C) at which enzyme is 1/2 active and 1/2 suppressed due to low temperatures
tref	standardisation temperature in degrees centigrade. Temperature at which rates are not inactivated by high temperatures

Details

Equation:

$$rate = \frac{r_{tref} \cdot \exp^{\frac{-e}{k}(\frac{1}{temp+273.15} - \frac{1}{t_{ref}+273.15})}}{1 + \exp^{\frac{e_l}{k}(\frac{1}{t_l} - \frac{1}{temp+273.15})}}$$

where k is Boltzmann's constant with a value of 8.62e-05.

Start values in get_start_vals are derived from the data.

Limits in get_lower_lims and get_upper_lims are derived from the data or based extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model easy to fit.

Author(s)

Daniel Padfield

References

Schoolfield, R. M., Sharpe, P. J. & Magnuson, C. E. Non-linear regression of biological temperature-dependent rate models based on absolute reaction-rate theory. *J. Theor. Biol.* 88, 719-731 (1981)

Examples

```
# load in ggplot
library(ggplot2)
library(nls.multstart)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'sharpeschoollow_1981')
# fit model
mod <- nls_multstart(rate~sharpeschoollow_1981(temp = temp, r_tref, e, el, tl, tref = 20),
  data = d,
  iter = c(3,3,3,3),
  start_lower = start_vals - 10,
  start_upper = start_vals + 10,
  lower = get_lower_lims(d$temp, d$rate, model_name = 'sharpeschoollow_1981'),
  upper = get_upper_lims(d$temp, d$rate, model_name = 'sharpeschoollow_1981'),
  supp_errors = 'Y',
  convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()
```

Description

Spain model for fitting thermal performance curves

Usage

```
spain_1982(temp, a, b, c, r0)
```

Arguments

temp	temperature in degrees centigrade
a	constant that determines the steepness of the rising portion of the curve
b	constant that determines the position of topt
c	constant that determines the steepness of the decreasing part of the curve
r0	the apparent rate at 0 °C

Details

Equation:

$$rate = r_0 \cdot \exp^{a \cdot temp} \cdot (1 - b \cdot \exp^{c \cdot temp})$$

Start values in `get_start_vals` are derived from the data or plucked from thin air.

Limits in `get_lower_lims` and `get_upper_lims` are derived from the data or plucked from thin air.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model easy to fit.

References

BASIC Microcomputer Models in Biology. Addison-Wesley, Reading, MA. 1982

Examples

```
# load in ggplot
library(ggplot2)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'spain_1982')
# fit model
```

```

mod <- nls.multstart::nls_multstart(rate~spain_1982(temp = temp, a, b, c, r0),
  data = d,
  iter = c(3,3,3,3),
  start_lower = start_vals - 1,
  start_upper = start_vals + 1,
  lower = get_lower_lims(d$temp, d$rate, model_name = 'spain_1982'),
  upper = get_upper_lims(d$temp, d$rate, model_name = 'spain_1982'),
  supp_errors = 'Y',
  convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()

```

thomas_2012

*Thomas model (2012) for fitting thermal performance curves***Description**

Thomas model (2012) for fitting thermal performance curves

Usage

```
thomas_2012(temp, a, b, c, topt)
```

Arguments

temp	temperature in degrees centigrade
a	arbitrary constant
b	arbitrary constant
c	the range of temperatures over which growth rate is positive, or the thermal niche width (°C)
topt	determines the location of the maximum of the quadratic portion of this function. When b = 0, tref would equal topt

Details

Equation:

$$rate = a \cdot \exp^{b \cdot temp} \left(1 - \left(\frac{temp - t_{opt}}{c} \right)^2 \right)$$

Start values in `get_start_vals` are derived from the data.

Limits in `get_lower_lims` and `get_upper_lims` are derived from the data or based on extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model easy to fit.

References

Thomas, Mridul K., et al. A global pattern of thermal adaptation in marine phytoplankton. *Science* 338.6110, 1085-1088 (2012)

Examples

```
# load in ggplot
library(ggplot2)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'thomas_2012')
# fit model
mod <- nls.multstart::nls_multstart(rate~thomas_2012(temp = temp, a, b, c, topt),
data = d,
iter = c(4,4,4,4),
start_lower = start_vals - 1,
start_upper = start_vals + 2,
lower = get_lower_lims(d$temp, d$rate, model_name = 'thomas_2012'),
upper = get_upper_lims(d$temp, d$rate, model_name = 'thomas_2012'),
supp_errors = 'Y',
convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)
```

```
# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()
```

thomas_2017

*Thomas model (2017) for fitting thermal performance curves***Description**

Thomas model (2017) for fitting thermal performance curves

Usage

```
thomas_2017(temp, a, b, c, d, e)
```

Arguments

temp	temperature in degrees centigrade
a	birth rate at 0 °C
b	describes the exponential increase in birth rate with increasing temperature
c	temperature-independent mortality term
d	along with e controls the exponential increase in mortality rates with temperature
e	along with d controls the exponential increase in mortality rates with temperature

Details

Equation:

$$rate = a \cdot \exp^{b \cdot temp} - (c + d \cdot \exp^{e \cdot temp})$$

Start values in `get_start_vals` are derived from the data.

Limits in `get_lower_lims` and `get_upper_lims` are derived from the data or based on extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model easy to fit.

References

Thomas, Mridul K., et al. Temperature–nutrient interactions exacerbate sensitivity to warming in phytoplankton. *Global change biology* 23.8 (2017): 3269-3280.

Examples

```
# load in ggplot
library(ggplot2)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'thomas_2017')
# fit model
mod <- nls.multstart::nls_multstart(rate~thomas_2017(temp = temp, a, b, c, d, e),
data = d,
iter = c(3,3,3,3,3),
start_lower = start_vals - 10,
start_upper = start_vals + 10,
lower = get_lower_lims(d$temp, d$rate, model_name = 'thomas_2017'),
upper = get_upper_lims(d$temp, d$rate, model_name = 'thomas_2017'),
supp_errors = 'Y',
convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()
```

weibull_1995

Weibull model for fitting thermal performance curves

Description

Weibull model for fitting thermal performance curves

Usage

```
weibull_1995(temp, a, topt, b, c)
```

Arguments

temp	temperature in degrees centigrade
a	scale the height of the curve
topt	optimum temperature
b	defines the breadth of the curve
c	defines the curve shape

Details

Equation:

$$rate = a \cdot \left(\frac{c-1}{c} \right)^{\frac{1-c}{c}} \left(\frac{temp - t_{opt}}{b} + \left(\frac{c-1}{c} \right)^{\frac{1}{c}} \right)^{c-1} \exp \left(- \left(\frac{temp - t_{opt}}{b} + \left(\frac{c-1}{c} \right)^{\frac{1}{c}} \right)^c + \frac{c-1}{c} \right)$$

Start values in `get_start_vals` are derived from the data.

Limits in `get_lower_lims` and `get_upper_lims` are derived from the data or based extreme values that are unlikely to occur in ecological settings.

Value

a numeric vector of rate values based on the temperatures and parameter values provided to the function

Note

Generally we found this model easy to fit.

References

Angilletta Jr, Michael J. Estimating and comparing thermal performance curves. *Journal of Thermal Biology* 31.7 (2006): 541-545.

Examples

```
# load in ggplot
library(ggplot2)

# subset for the first TPC curve
data('chlorella_tpc')
d <- subset(chlorella_tpc, curve_id == 1)

# get start values and fit model
start_vals <- get_start_vals(d$temp, d$rate, model_name = 'weibull_1995')
# fit model
mod <- nls.multstart::nls_multstart(rate~weibull_1995(temp = temp, a, topt, b, c),
data = d,
iter = c(4,4,4,4),
start_lower = start_vals - 10,
start_upper = start_vals + 10,
```

```
lower = get_lower_lims(d$temp, d$rate, model_name = 'weibull_1995'),
upper = get_upper_lims(d$temp, d$rate, model_name = 'weibull_1995'),
supp_errors = 'Y',
convergence_count = FALSE)

# look at model fit
summary(mod)

# get predictions
preds <- data.frame(temp = seq(min(d$temp), max(d$temp), length.out = 100))
preds <- broom::augment(mod, newdata = preds)

# plot
ggplot(preds) +
  geom_point(aes(temp, rate), d) +
  geom_line(aes(temp, .fitted), col = 'blue') +
  theme_bw()
```

Index

* dataset

bacteria_tpc, [3](#)
chlorella_tpc, [10](#)

bacteria_tpc, [3](#)
beta_2012, [4](#)
boatman_2017, [5](#)
briere2_1999, [7](#)

calc_params, [9](#)
chlorella_tpc, [10](#)

delong_2017, [11](#)
deutsch_2008, [12](#)

flinn_1991, [14](#)

gaussian_1987, [16](#)
get_breadth, [17](#)
get_breadth(), [9](#)
get_ctmax, [18](#)
get_ctmax(), [9](#)
get_ctmin, [19](#)
get_ctmin(), [9](#)
get_e, [19](#)
get_e(), [9](#)
get_eh, [20](#)
get_eh(), [9](#)
get_lower_lims, [20](#)
get_model_names, [21](#)
get_q10, [21](#)
get_q10(), [9](#)
get_rmax, [22](#)
get_rmax(), [9](#)
get_skewness, [22](#)
get_skewness(), [9](#)
get_start_vals, [23](#)
get_thermalsafetymargin, [23](#)
get_thermalsafetymargin(), [9](#)
get_thermaltolerance, [24](#)
get_thermaltolerance(), [9](#)

get_topt, [24](#)
get_topt(), [9](#)
get_upper_lims, [25](#)

hinshelwood_1947, [26](#)

joehnk_2008, [27](#)
johnsonlewin_1946, [29](#)

kamykowski_1985, [31](#)

lactin2_1995, [32](#)
lrf_1991, [34](#)

modifiedgaussian_2006, [36](#)

oneill_1972, [37](#)

pawar_2018, [39](#)

quadratic_2008, [41](#)

ratkowsky_1983, [43](#)
rezende_2019, [44](#)

sharpeschoolfull_1981, [46](#)
sharpeschoolhigh_1981, [48](#)
sharpeschoollow_1981, [50](#)
spain_1982, [51](#)

thomas_2012, [53](#)
thomas_2017, [55](#)

weibull_1995, [56](#)