

# Package ‘rfold’

July 23, 2025

**Type** Package

**Title** Working with many R Folders Within an R Package

**Version** 0.2.0

**Description** Allows developers to work with many R folders inside a package. It offers functionalities to transfer R scripts (saved outside the R folder) into the R folder while making additional checks.

**License** MIT + file LICENSE

**Encoding** UTF-8

**URL** <https://github.com/feddelegrand7/rfold>

**BugReports** <https://github.com/feddelegrand7/rfold/issues>

**Imports** cli (>= 3.6.1), fs (>= 1.5.0), glue, here (>= 1.0.1), usethis (>= 2.0.1)

**RoxygenNote** 7.1.1

**Suggests** testthat (>= 3.0.0)

**Config/testthat/edition** 3

**NeedsCompilation** no

**Author** Mohamed El Fodil Ihaddaden [aut, cre]

**Maintainer** Mohamed El Fodil Ihaddaden <ihaddaden.fodeil@gmail.com>

**Repository** CRAN

**Date/Publication** 2024-02-12 15:50:02 UTC

## Contents

rfold . . . . .	2
<b>Index</b>	<b>3</b>

---

rfold	<i>Transfer .R files into the R directory</i>
-------	---

---

**Description**

Transfer .R files into the R directory

**Usage**

```
rfold(folders_to_ignore = NULL, script_name_prefix = "DO_NOT_EDIT_")
```

**Arguments**

`folders_to_ignore`

a string vector of plain names folders that should be ignored where transferring .R files into the main R folder (for example a dev folder). Defaults to NULL

`script_name_prefix`

characters string of length 1 that will be appended to the start of the .R scripts when transferring them to the R folder. Defaults to 'DO\_NOT\_EDIT\_', set it to NULL for no appending

**Value**

called for the side effect of transferring all R files

# Index

rfold, [2](#)