

Package ‘rmarchingcubes’

July 23, 2025

Type Package

Title Calculate 3D Contour Meshes Using the Marching Cubes Algorithm

Version 0.1.3

Date 2021-06-14

Author S. H. Wilks <sw463@cam.ac.uk> [aut, cre],
Thomas Lewiner <lewiner@gmail.com> [aut]

Maintainer S. H. Wilks <sw463@cam.ac.uk>

Description A port of the C++ routine for applying the marching cubes algorithm written by Thomas Lewiner et al. (2012) <[doi:10.1080/10867651.2003.10487582](https://doi.org/10.1080/10867651.2003.10487582)> into an R package. The package supplies the `contour3d()` function, which takes a 3-dimensional array of voxel data and calculates the vertices, vertex normals, and faces for a 3d mesh representing the contour(s) at a given level.

URL <https://github.com/shwilks/rmarchingcubes>

BugReports <https://github.com/shwilks/rmarchingcubes/issues>

Language en-US

License MIT + file LICENSE

Imports Rcpp (>= 1.0.5)

LinkingTo Rcpp, RcppArmadillo

RoxygenNote 7.1.1

Suggests rmarkdown, knitr, testthat (>= 3.0.0)

Config/testthat/edition 3

VignetteBuilder knitr

NeedsCompilation yes

Repository CRAN

Date/Publication 2021-06-16 22:30:07 UTC

Contents

contour3d	2
Index	3

`contour3d`*Compute Isosurface, a Three Dimension Contour*

Description

Computes a 3D contours or isosurface by the marching cubes algorithm.

Usage

```
contour3d(griddata, level, x, y, z)
```

Arguments

<code>griddata</code>	A three dimensional array from which to calculate the contour
<code>level</code>	The level at which to construct the contour surface
<code>x, y, z</code>	locations of grid planes at which values in <code>griddata</code> are measured

Value

Returns a list with coordinates of each surface vertex, indices of the vertices that make up each triangle, and surface normals at each vertex

Index

contour3d, [2](#)