

Package ‘samplingin’

July 23, 2025

Title Dynamic Survey Sampling Solutions

Version 1.1.1

Description A robust solution employing the SRS (Simple Random Sampling), systematic and PPS (Probability Proportional to Size) sampling methods, ensuring a methodical and representative selection of data. Seamlessly allocate predetermined allocations to smaller levels.

License MIT + file LICENSE

Depends R (>= 2.10)

Imports base, data.table, dplyr, magrittr, rlang, sampling, stats, utils

Suggests knitr, rmarkdown

VignetteBuilder knitr

Encoding UTF-8

LazyData true

RoxygenNote 7.2.1

NeedsCompilation no

Author Choerul Afifanto [aut, cre, cph]

Maintainer Choerul Afifanto <choerulafifanto@gmail.com>

Repository CRAN

Date/Publication 2024-09-28 00:20:02 UTC

Contents

alokasi_dt	2
doSampling	2
get_allocation	5
pop_dt	6
round_preserve_sum	7
Index	8

alokasi_dt	<i>Example of Allocation Data</i>
------------	-----------------------------------

Description

Example of Allocation Data for Sampling Purposes

Usage

alokasi_dt

Format

alokasi_dt:

A data frame with 34 rows and 3 columns:

kdprov province code

jml_kabkota Population or number of regencies/cities

n_primary Sample Allocation ...

doSampling	<i>Select Samples Given its Parameters</i>
------------	--

Description

Samples selection using systematic or PPS (Probability Proportional to Size) sampling method.

Usage

```
doSampling(
  pop,
  alloc,
  nsample,
  type,
  strata = NULL,
  ident = c("kdprov", "kdkab"),
  implicitby = NULL,
  method = "systematic",
  auxVar = NA,
  seed = 1,
  predetermined_rn = NULL,
  is_secondary = FALSE,
  verbose = TRUE
)
```

Arguments

pop	pop dataframe
alloc	allocation dataframe
nsample	variable on alloc df as allocation sample
type	type value for sample classification ('U' = Primary Samples, 'P' = Secondary Samples)
strata	strata variable, must available on both pop and alloc dataframe
ident	group by on allocation dataframe
implicitby	variable used as implicit stratification
method	method of sampling : "systematic" (the default), "srs" or "pps"
auxVar	auxiliary variable for pps sampling (method = "pps")
seed	seed
predetermined_rn	predetermined random number variable on allocation dataframe, the default value is NULL, random number will be generated randomly
is_secondary	if the value is TRUE, it will maintains existing primary samples and selects units that have not been selected as samples (FALSE as default)
verbose	verbose (TRUE as default)

Value

list of population data ("pop"), selected samples ("sampledf"), and details of sampling process ("details")

Examples

```
library(samplingin)
library(magrittr)
library(dplyr)

# Simple Random Sampling (SRS)
dtSampling_srs = doSampling(
  pop      = pop_dt
  , alloc  = alokasi_dt
  , nsample = "n_primary"
  , type   = "U"
  , ident  = c("kdprov")
  , method = "srs"
  , auxVar = "Total"
  , seed   = 7892
)

# Population data with flag sample
pop_dt = dtSampling_srs$pop

# Selected Samples
```

```

dsampel = dtSampling_srs$sampledf

# Details of sampling process
rincian = dtSampling_srs$details

# PPS Sampling
dtSampling_pps = doSampling(
  pop      = pop_dt
  , alloc  = alokasi_dt
  , nsample = "n_primary"
  , type   = "U"
  , ident  = c("kdprov")
  , method = "pps"
  , auxVar = "Total"
  , seed   = 1234
)

# Population data with flag sample
pop_dt = dtSampling_pps$pop

# Selected Samples
dsampel = dtSampling_pps$sampledf

# Details of sampling process
rincian = dtSampling_pps$details

# Systematic Sampling
dtSampling_sys = doSampling(
  pop      = pop_dt
  , alloc  = alokasi_dt
  , nsample = "n_primary"
  , type   = "U"
  , ident  = c("kdprov")
  , method = "systematic"
  , seed   = 4321
)

# Population data with flag sample
pop_dt = dtSampling_sys$pop

# Selected Samples
dsampel = dtSampling_sys$sampledf

# Details of sampling process
rincian = dtSampling_sys$details

# Systematic Sampling (Secondary Samples)

alokasi_dt_p = alokasi_dt %>%
  mutate(n_secondary = 2 * n_primary)

dtSampling_sys_p = doSampling(
  pop      = dtSampling_sys$pop

```

```

    , alloc      = alokasi_dt_p
    , nsample    = "n_secondary"
    , type       = "P"
    , ident      = c("kdprov")
    , method     = "systematic"
    , seed       = 6789
    , is_secondary = TRUE
  )

# Population data with flag sample
pop_dt = dtSampling_sys_p$pop

# Selected Samples
dsampel = dtSampling_sys_p$sampelf

# Details of sampling process
rincian = dtSampling_sys_p$details

# Systematic Sampling with predetermined random number (predetermined_rn parameter)
alokasi_dt_rn = alokasi_dt %>% rowwise() %>% mutate(ar = runif(n(),0,1)) %>% ungroup

dtSampling_sys = doSampling(
  pop      = pop_dt
  , alloc  = alokasi_dt_rn
  , nsample = "n_primary"
  , type    = "U"
  , ident   = c("kdprov")
  , method  = "systematic"
  , predetermined_rn = "ar"
  , seed    = 4321
)

# Population data with flag sample
pop_dt = dtSampling_sys$pop

# Selected Samples
dsampel = dtSampling_sys$sampelf

# Details of sampling process
rincian = dtSampling_sys$details

```

get_allocation

Allocate Predetermined Allocations to Smaller Levels

Description

Allocate predetermined allocations to smaller levels using proportional allocation method

Usage

```
get_allocation(data, n_alloc, group, pop_var = "jml", secondary = 0)
```

Arguments

data	population tabulation dataframe
n_alloc	total allocation dataframe
group	group of allocation level to be obtained
pop_var	population variable in data
secondary	how many times the secondary sample compares to primary sample

Value

allocation at more detailed level

Examples

```
library(samplingin)
library(magrittr)

contoh_alokasi = alokasi_dt %>%
  dplyr::select(-n_primary) %>%
  dplyr::mutate(nasional = 1)

alokasi_dt = get_allocation(
  data = contoh_alokasi
  , n_alloc = 100
  , group = c("nasional")
  , pop_var = "jml_kabkota"
)
```

pop_dt	<i>Indonesian Population (SP2020)</i>
--------	---------------------------------------

Description

Tabulation of Indonesia’s population based on the results of the 2020 population census by re-gency/city and gender

Usage

```
pop_dt
```

Format

pop_dt:
A data frame with 514 rows and 8 columns:
idkab region id
kdprov province code
kdkab regency/city code
nmprov province name
nmkab regency/city name
Laki-laki Male Population
Perempuan Female Population
Total Total Population ...

Source

<https://sensus.bps.go.id/main/index/sp2020>

round_preserve_sum	<i>round_preserve_sum</i>
--------------------	---------------------------

Description

round_preserve_sum

Usage

round_preserve_sum(x, digits = 0)

Arguments

x	a number
digits	0 (default)

Index

* **datasets**

alokasi_dt, [2](#)

pop_dt, [6](#)

alokasi_dt, [2](#)

doSampling, [2](#)

get_allocation, [5](#)

pop_dt, [6](#)

round_preserve_sum, [7](#)