

Package ‘shiny.telemetry’

July 23, 2025

Type Package

Title 'Shiny' App Usage Telemetry

Version 0.3.1

Description Enables instrumentation of 'Shiny' apps for tracking user session events such as input changes, browser type, and session duration. These events can be sent to any of the available storage backends and analyzed using the included 'Shiny' app to gain insights about app usage and adoption.

License LGPL-3

URL <https://appsilon.github.io/shiny.telemetry/>,
<https://github.com/Appsilon/shiny.telemetry>

BugReports <https://github.com/Appsilon/shiny.telemetry/issues>

Imports checkmate, digest, dplyr (>= 1.1.0), glue, htmltools, httr2, jsonlite, lifecycle, logger, lubridate, odbc, purrr, R6, rlang, RSQLite, shiny, stringr, tidyr

Suggests box, config, DT, knitr, mongolite, plotly, plumber, RColorBrewer, RMariaDB, rmarkdown, RPostgres, RPostgreSQL, scales, semantic.dashboard (>= 0.1.1), shiny.semantic (>= 0.2.0), shinyjs, testthat (>= 3.1.7), timevis, withr

VignetteBuilder knitr

Config/testthat/edition 3

Encoding UTF-8

Language en-US

RoxygenNote 7.3.2

NeedsCompilation no

Author André Veríssimo [aut, cre],
Kamil Żyła [aut],
Krystian Igras [aut],
Reclé Vibal [aut],
Arun Kodati [aut],
Wahaduzzaman Khan [aut],
Appsilon Sp. z o.o. [cph]

Maintainer André Veríssimo <opensource+andre@appsilon.com>
Repository CRAN
Date/Publication 2024-10-15 08:00:02 UTC

Contents

analytics_app	2
build_id_from_secret	3
build_token	3
DataStorage	4
DataStorageLogFile	5
DataStorageMariaDB	6
DataStorageMongoDB	7
DataStorageMSSQLServer	9
DataStoragePlumber	11
DataStoragePostgreSQL	12
DataStorageSQLFamily	14
DataStorageSQLite	14
date_from_null	15
date_to_null	16
Telemetry	16
use_telemetry	23
Index	25

analytics_app	<i>Run example telemetry analytics dashboard</i>
---------------	--

Description

Run example telemetry analytics dashboard

Usage

```
analytics_app(data_storage)
```

Arguments

data_storage data_storage instance that will handle all backend read and writes.

Value

An object that represents the analytics app. Printing the object or passing it to shiny::runApp() will run it.

build_id_from_secret	<i>Builds id from a secret that can be used in open communication</i>
----------------------	---

Description

This is used in shiny.telemetry, but also externally with the Plumber endpoint.

Usage

```
build_id_from_secret(secret)
```

Arguments

secret	string that contains information that should not be publicly available
--------	--

Value

A string with an hash of the secret.

Examples

```
build_id_from_secret("some_random_secret_generated_with_uuid:UUIDgenerate")
```

build_token	<i>Builds hash for a call</i>
-------------	-------------------------------

Description

Function that takes creates a signature for the values using a secret.

Usage

```
build_token(values, secret = NULL)
```

Arguments

values	R object that is going to be signed
secret	string that contains the shared secret to sign the communication. It can be NULL on both telemetry and in plumber API to disable this communication feature

Details

This is used in shiny.telemetry, but also externally with the Plumber endpoint.

Value

A string that contains an hash to uniquely identify the parameters.

Examples

```
build_token(values = list(list(1, 2, 3), 2, 2, 3, "bb"))
build_token(values = list(list(1, 2, 3), 1, 2, 3, "bb"))
build_token(values = list(list(1, 2, 3), 1, 2, 3, "bb"), secret = "abc")
build_token(values = list(list(1, 2, 3), 1, 2, 3, "bb"), secret = "abd")
```

DataStorage

Data Storage abstract class to handle all the read/write operations

Description

Abstract R6 Class that encapsulates all the operations needed by Shiny.telemetry to read and write. This removes the complexity from the functions and uses a unified API.

Active bindings

`event_bucket` string that identifies the bucket to store user related and action data

Methods

Public methods:

- `DataStorage$new()`
- `DataStorage$insert()`
- `DataStorage$read_event_data()`
- `DataStorage$close()`
- `DataStorage$clone()`

Method `new()`: initialize data storage object common with all providers

Usage:

`DataStorage$new()`

Method `insert()`: Insert new data

Usage:

`DataStorage$insert(app_name, type, session = NULL, details = NULL, time = NULL)`

Arguments:

`app_name` string with name of dashboard (the version can be also included in this string)

`type` string that identifies the event type to store

`session` (optional) string that identifies a session where the event was logged

`details` atomic element of list with data to save in storage

`time` date time value indicates the moment the record was generated in UTC. By default it should be NULL and determined automatically, but in cases where it should be defined, use `Sys.time()` or `lubridate::now(tzone = "UTC")` to generate it.

Returns: Nothing. This method is called for side effects.

Method `read_event_data()`: read all user data from SQLite.

Usage:

```
DataStorage$read_event_data(date_from = NULL, date_to = NULL, app_name = NULL)
```

Arguments:

`date_from` (optional) date representing the starting day of results.

`date_to` (optional) date representing the last day of results.

`app_name` (optional) string identifying the Dashboard-specific event data

Method `close()`: Close the connection if necessary

Usage:

```
DataStorage$close()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
DataStorage$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

DataStorageLogFile	<i>Data storage class for JSON Log File</i>
--------------------	---

Description

Implementation of the [DataStorage](#) R6 class to a JSON log file backend using a unified API for read/write operations

Super class

```
shiny.telemetry::DataStorage -> DataStorageLogFile
```

Active bindings

`event_bucket` string that identifies the file path to store user related and action data

Methods

Public methods:

- [DataStorageLogFile\\$new\(\)](#)
- [DataStorageLogFile\\$clone\(\)](#)

Method `new()`: Initialize the data storage class

Usage:

```
DataStorageLogFile$new(log_file_path)
```

Arguments:

`log_file_path` string with path to JSON log file user actions

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
DataStorageLogFile$new(log_file_path = log_file_path)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
log_file_path <- tempfile(fileext = ".txt")
data_storage <- DataStorageLogFile$new(log_file_path = log_file_path)

data_storage$insert("example", "test_event", "session1")
data_storage$insert("example", "input", "s1", list(id = "id"))
data_storage$insert("example", "input", "s1", list(id = "id2", value = 32))

data_storage$insert(
  "example", "test_event_3_days_ago", "session1",
  time = lubridate::as_datetime(lubridate::today() - 3)
)

data_storage$read_event_data()
data_storage$read_event_data(Sys.Date() - 1, Sys.Date() + 1)

file.remove(log_file_path)
```

DataStorageMariaDB	<i>Data storage class with MariaDB / MySQL provider</i>
--------------------	---

Description

Implementation of the [DataStorage](#) R6 class to MariaDB backend using a unified API for read/write operations

Super classes

```
shiny.telemetry::DataStorage -> shiny.telemetry::DataStorageSQLFamily -> DataStorageMariaDB
```

Methods

Public methods:

- [DataStorageMariaDB\\$new\(\)](#)
- [DataStorageMariaDB\\$clone\(\)](#)

Method `new()`: Initialize the data storage class

Usage:

```
DataStorageMariaDB$new(
  username = NULL,
  password = NULL,
  hostname = "127.0.0.1",
  port = 3306,
  dbname = "shiny_telemetry"
)
```

Arguments:

username string with a MariaDB username.
 password string with the password for the username.
 hostname string with hostname of MariaDB instance.
 port numeric value with the port number of MariaDB instance.
 dbname string with the name of the database in the MariaDB instance.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
DataStorageMariaDB$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## Not run:
data_storage <- DataStorageMariaDB$new(user = "mariadb", password = "mysecretpassword")

data_storage$insert("example", "test_event", "session1")
data_storage$insert("example", "input", "s1", list(id = "id1"))
data_storage$insert("example", "input", "s1", list(id = "id2", value = 32))

data_storage$insert(
  "example", "test_event_3_days_ago", "session1",
  time = lubridate::as_datetime(lubridate::today() - 3)
)

data_storage$read_event_data()
data_storage$read_event_data(Sys.Date() - 1, Sys.Date() + 1)
data_storage$close()

## End(Not run)
```

DataStorageMongoDB

Data storage class with MongoDB provider

Description

Implementation of the [DataStorage](#) R6 class to MongoDB backend using a unified API for read/write operations

Super class

`shiny.telemetry::DataStorage -> DataStorageMongoDB`

Methods**Public methods:**

- `DataStorageMongoDB$new()`
- `DataStorageMongoDB$clone()`

Method `new()`: Initialize the data storage class

Usage:

```
DataStorageMongoDB$new(
  hostname = "localhost",
  port = 27017,
  username = NULL,
  password = NULL,
  authdb = NULL,
  dbname = "shiny_telemetry",
  options = NULL,
  ssl_options = mongolite::ssl_options()
)
```

Arguments:

`hostname` the hostname or IP address of the MongoDB server.

`port` the port number of the MongoDB server (default is 27017).

`username` the username for authentication (optional).

`password` the password for authentication (optional).

`authdb` the default authentication database (optional).

`dbname` name of database (default is "shiny_telemetry").

`options` Additional connection options in a named list format (e.g., `list(ssl = "true", replicaSet = "myreplicaset")`) (optional).

`ssl_options` additional connection options such as SSL keys/certs (default is `mongolite::ssl_options()`).

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
DataStorageMongoDB$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
## Not run:
data_storage <- DataStorageMongoDB$new(
  host = "localhost",
  db = "test",
  ssl_options = mongolite::ssl_options()
)
```

```

data_storage$insert("example", "test_event", "session1")
data_storage$insert("example", "input", "s1", list(id = "id1"))
data_storage$insert("example", "input", "s1", list(id = "id2", value = 32))

data_storage$insert(
  "example", "test_event_3_days_ago", "session1",
  time = lubridate::as_datetime(lubridate::today() - 3)
)

data_storage$read_event_data()
data_storage$read_event_data(Sys.Date() - 1, Sys.Date() + 1)
data_storage$close()

## End(Not run)

```

DataStorageMSSQLServer

Data storage class with MS SQL Server provider

Description

Implementation of the [DataStorage](#) R6 class to MS SQL Server backend using a unified API for read/write operations. This provider requires a configured and named ODBC driver to be set up on your system, for example, "ODBC Driver 17 for SQL Server" or "ODBC Driver 18 for SQL Server".

Note that MS SQL Server support requires a subtly different database schema: the time field is stored as a DATETIME rather than a TIMESTAMP.

Super classes

[shiny.telemetry::DataStorage](#) -> [shiny.telemetry::DataStorageSQLFamily](#) -> DataStorageMSSQLServer

Methods

Public methods:

- [DataStorageMSSQLServer\\$new\(\)](#)
- [DataStorageMSSQLServer\\$clone\(\)](#)

Method `new()`: Initialize the data storage class

Usage:

```

DataStorageMSSQLServer$new(
  username = NULL,
  password = NULL,
  hostname = "127.0.0.1",
  port = 1433,
  dbname = "shiny_telemetry",
  driver = "ODBC Driver 17 for SQL Server",
  trust_server_certificate = "NO"
)

```

Arguments:

username string with a MS SQL Server username.
 password string with the password for the username.
 hostname string with hostname of the MS SQL Server instance.
 port numeric value with the port number of MS SQL Server instance.
 dbname string with the name of the database in the MS SQL Server instance.
 driver string with the name of the ODBC driver class for MS SQL, for example "ODBC Driver 17 for SQL Server".
 trust_server_certificate string with "NO" or "YES", setting whether or not to trust the server's certificate implicitly.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
DataStorageMSSQLServer$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## Not run:
data_storage <- DataStorageMSSQLServer$new(
  user = "sa",
  password = "my-Secr3t_Password",
  hostname = "localhost",
  port = 1433,
  dbname = "shiny_telemetry",
  driver = "ODBC Driver 18 for SQL Server",
  trust_server_certificate = "YES"
)

data_storage$insert("example", "test_event", "session1")
data_storage$insert("example", "input", "s1", list(id = "id1"))
data_storage$insert("example", "input", "s1", list(id = "id2", value = 32))

data_storage$insert(
  "example", "test_event_3_days_ago", "session1",
  time = lubridate::as_datetime(lubridate::today() - 3)
)

data_storage$read_event_data()
data_storage$read_event_data(Sys.Date() - 1, Sys.Date() + 1)
data_storage$close()

## End(Not run)
```

DataStoragePlumber	<i>Data storage class with SQLite provider</i>
--------------------	--

Description

Implementation of the [DataStorage](#) R6 class to SQLite backend using a unified API for read/write operations

Super class

[shiny.telemetry::DataStorage](#) -> DataStoragePlumber

Active bindings

event_read_endpoint string field that returns read action endpoint

event_insert_endpoint string field that returns insert action endpoint

Methods**Public methods:**

- [DataStoragePlumber\\$new\(\)](#)
- [DataStoragePlumber\\$clone\(\)](#)

Method [new\(\)](#): Initialize the data storage class

Usage:

```
DataStoragePlumber$new(  
  hostname = "127.0.0.1",  
  port = 80,  
  protocol = "http",  
  path = NULL,  
  secret = NULL,  
  authorization = NULL  
)
```

Arguments:

hostname string with hostname of plumber instance,

port numeric value with port number of plumber instance.

protocol string with protocol of the connection of the plumber instance.

path string with sub-path of plumber deployment.

secret string with secret to sign communication with plumber (can be NULL for disabling communication signing).

authorization string to use in HTTP headers for authorization (for example: to authenticate to a plumber deployment behind a connect server).

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
DataStoragePlumber$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## Not run:
# Make sure the PLUMBER_SECRET environment variable is valid before
# running these examples (NULL or a valid secret)

data_storage <- DataStoragePlumber$new(
  hostname = "connect.appsiilon.com",
  path = "shiny_telemetry_plumber",
  port = 443,
  protocol = "https",
  authorization = Sys.getenv("CONNECT_AUTHORIZATION_KEY"),
  secret = Sys.getenv("PLUMBER_SECRET")
)

data_storage <- DataStoragePlumber$new(
  hostname = "127.0.0.1",
  path = NULL,
  port = 8087,
  protocol = "http",
  secret = Sys.getenv("PLUMBER_SECRET")
)

data_storage$insert("example", "test_event", "session1")
data_storage$insert("example", "input", "s1", list(id = "id"))
data_storage$insert("example", "input", "s1", list(id = "id2", value = 32))

data_storage$insert(
  "example", "test_event_3_days_ago", "session1",
  time = lubridate::as_datetime(lubridate::today() - 3)
)

data_storage$read_event_data()
data_storage$read_event_data(Sys.Date() - 1, Sys.Date() + 1)

## End(Not run)
```

DataStoragePostgreSQL *Data storage class with PostgreSQL provider*

Description

Implementation of the [DataStorage](#) R6 class to PostgreSQL backend using a unified API for read/write operations

Super classes

`shiny.telemetry::DataStorage -> shiny.telemetry::DataStorageSQLFamily -> DataStoragePostgreSQL`

Methods**Public methods:**

- `DataStoragePostgreSQL$new()`
- `DataStoragePostgreSQL$clone()`

Method `new()`: Initialize the data storage class

Usage:

```
DataStoragePostgreSQL$new(
  username = NULL,
  password = NULL,
  hostname = "127.0.0.1",
  port = 5432,
  dbname = "shiny_telemetry",
  driver = "RPostgreSQL"
)
```

Arguments:

`username` string with a PostgreSQL username.
`password` string with the password for the username.
`hostname` string with hostname of PostgreSQL instance.
`port` numeric value with the port number of PostgreSQL instance.
`dbname` string with the name of the database in the PostgreSQL instance.
`driver` string, to select PostgreSQL driver among `c("RPostgreSQL", "RPostgres")`.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
DataStoragePostgreSQL$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
## Not run:
data_storage <- DataStoragePostgreSQL$new(user = "postgres", password = "mysecretpassword")

data_storage$insert("example", "test_event", "session1")
data_storage$insert("example", "input", "s1", list(id = "id1"))
data_storage$insert("example", "input", "s1", list(id = "id2", value = 32))

data_storage$insert(
  "example", "test_event_3_days_ago", "session1",
  time = lubridate::as_datetime(lubridate::today() - 3)
)
```

```

data_storage$read_event_data()
data_storage$read_event_data(Sys.Date() - 1, Sys.Date() + 1)
data_storage$close()

## End(Not run)

```

DataStorageSQLFamily *Data storage abstract class for SQL providers*

Description

Abstract subclass of the [DataStorage](#) R6 class for the SQL family of providers

Super class

[shiny.telemetry::DataStorage](#) -> DataStorageSQLFamily

Methods

Public methods:

- [DataStorageSQLFamily\\$clone\(\)](#)

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`DataStorageSQLFamily$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

DataStorageSQLite *Data storage class with SQLite provider*

Description

Implementation of the [DataStorage](#) R6 class to SQLite backend using a unified API for read/write operations

Super classes

[shiny.telemetry::DataStorage](#) -> [shiny.telemetry::DataStorageSQLFamily](#) -> DataStorageSQLite

Methods**Public methods:**

- `DataStorageSQLite$new()`
- `DataStorageSQLite$clone()`

Method `new()`: Initialize the data storage class

Usage:

```
DataStorageSQLite$new(db_path = "user_stats.sqlite")
```

Arguments:

`db_path` string with path to SQLite file.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
DataStorageSQLite$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
db_path <- tempfile(fileext = ".sqlite")
data_storage <- DataStorageSQLite$new(db_path = db_path)

data_storage$insert("example", "test_event", "session1")
data_storage$insert("example", "input", "s1", list(id = "id1"))
data_storage$insert("example", "input", "s1", list(id = "id2", value = 32))

data_storage$insert(
  "example", "test_event_3_days_ago", "session1",
  time = lubridate::as_datetime(lubridate::today() - 3)
)

data_storage$read_event_data()
data_storage$read_event_data(Sys.Date() - 1, Sys.Date() + 1)

file.remove(db_path)
```

date_from_null	<i>Common date_from to recognize as NULL</i>
----------------	--

Description

Common `date_from` to recognize as NULL

Usage

```
date_from_null
```

Format

An object of class character of length 1.

date_to_null	<i>Common date_to to recognize as NULL</i>
--------------	--

Description

Common date_to to recognize as NULL

Usage

date_to_null

Format

An object of class character of length 1.

Telemetry	<i>Telemetry class to manage analytics gathering at a global level</i>
-----------	--

Description

An instance of this class will define metadata and data storage provider for gathering telemetry analytics of a Shiny dashboard.

The name and version parameters will describe the dashboard name and version to track using analytics, allowing to store the analytics data from multiple dashboards in the same data storage provider. As well as discriminate different versions of the dashboard.

The default data storage provider uses a local SQLite database, but this can be customizable when instantiating the class, by using another one of the supported providers (see [DataStorage](#)).

Debugging

Events are logged at the DEBUG level using the logger package. To see the logs, you can set:

```
logger::log_threshold("DEBUG", namespace = "shiny.telemetry")
```

Active bindings

data_storage instance of a class that inherits from [DataStorage](#). See the documentation on that class for more information.

app_name string with name of dashboard

Methods

Public methods:

- `Telemetry$new()`
- `Telemetry$start_session()`
- `Telemetry$log_navigation()`
- `Telemetry$log_navigation_manual()`
- `Telemetry$log_login()`
- `Telemetry$log_logout()`
- `Telemetry$log_click()`
- `Telemetry$log_browser_version()`
- `Telemetry$log_button()`
- `Telemetry$log_all_inputs()`
- `Telemetry$log_input()`
- `Telemetry$log_input_manual()`
- `Telemetry$log_custom_event()`
- `Telemetry$log_error()`
- `Telemetry$log_errors()`
- `Telemetry$clone()`

Method `new()`: Constructor that initializes Telemetry instance with parameters.

Usage:

```
Telemetry$new(  
  app_name = "(dashboard)",  
  data_storage = DataStorageSQLite$new(db_path = file.path("telemetry.sqlite"))  
)
```

Arguments:

`app_name` (optional) string that identifies the name of the dashboard. By default it will store data with (dashboard).

`data_storage` (optional) DataStorage instance where telemetry data is being stored. It can take any of data storage providers by this package, By default it will store in a SQLite local database in the current working directory with filename `telemetry.sqlite`

`version` (optional) string that identifies the version of the dashboard. By default it will use `v0.0.0`.

Method `start_session()`: Setup basic telemetry

Usage:

```
Telemetry$start_session(  
  track_inputs = TRUE,  
  track_values = FALSE,  
  login = TRUE,  
  logout = TRUE,  
  browser_version = TRUE,  
  navigation_input_id = NULL,  
  session = shiny::getDefaultReactiveDomain(),
```

```

    username = NULL,
    track_anonymous_user = TRUE,
    track_errors = TRUE
  )

```

Arguments:

`track_inputs` flag that indicates if the basic telemetry should track the inputs that change value. TRUE by default

`track_values` flag that indicates if the basic telemetry should track the values of the inputs that are changing. FALSE by default. This parameter is ignored if `track_inputs` is FALSE

`login` flag that indicates if the basic telemetry should track when a session starts. TRUE by default.

`logout` flag that indicates if the basic telemetry should track when the session ends. TRUE by default.

`browser_version` flag that indicates that the browser version should be tracked. TRUE by default.

`navigation_input_id` string or vector of strings that represent input ids and which value should be tracked as navigation events. i.e. a change in the value represent a navigation to a page or tab. By default, no navigation is tracked.

`session` ShinySession object or NULL to identify the current Shiny session.

`username` Character with username. If set, it will overwrite username from session object.

`track_anonymous_user` flag that indicates to track anonymous user. A cookie is used to track same user without login over multiple sessions, This is only activated if none of the automatic methods produce a username and when a username is not explicitly defined. TRUE by default.

`track_errors` flag that indicates if the basic telemetry should track the errors. TRUE by default. if using shiny version < 1.8.1, it can auto log errors only in UI output functions. By using latest versions of shiny, it can auto log all types of errors.

Returns: Nothing. This method is called for side effects.

Method `log_navigation()`: Log an input change as a navigation event

Usage:

```
Telemetry$log_navigation(input_id, session = shiny::getDefaultReactiveDomain())
```

Arguments:

`input_id` string that identifies the generic input in the Shiny application so that the function can track and log changes to it.

`session` ShinySession object or NULL to identify the current Shiny session.

Returns: Nothing. This method is called for side effects.

Method `log_navigation_manual()`: Log a navigation event manually by indicating the id (as input id)

Usage:

```
Telemetry$log_navigation_manual(
  navigation_id,
  value,
  session = shiny::getDefaultReactiveDomain()
)
```

Arguments:

`navigation_id` string that identifies navigation event.
`value` string that indicates a value for the navigation
`session` `ShinySession` object or `NULL` to identify the current Shiny session.

Returns: Nothing. This method is called for side effects.

Method `log_login()`: Log when session starts

Usage:

```
Telemetry$log_login(  
  username = NULL,  
  session = shiny::getDefaultReactiveDomain()  
)
```

Arguments:

`username` string with username from current session
`session` `ShinySession` object or `NULL` to identify the current Shiny session.

Returns: Nothing. This method is called for side effects.

Method `log_logout()`: Log when session ends

Usage:

```
Telemetry$log_logout(  
  username = NULL,  
  session = shiny::getDefaultReactiveDomain()  
)
```

Arguments:

`username` string with username from current session
`session` `ShinySession` object or `NULL` to identify the current Shiny session.

Returns: Nothing. This method is called for side effects.

Method `log_click()`: Log an action click

Usage:

```
Telemetry$log_click(id, session = shiny::getDefaultReactiveDomain())
```

Arguments:

`id` string that identifies a manual click to the dashboard.
`session` `ShinySession` object or `NULL` to identify the current Shiny session.

Returns: Nothing. This method is called for side effects.

Method `log_browser_version()`: Log the browser version

Usage:

```
Telemetry$log_browser_version(session = shiny::getDefaultReactiveDomain())
```

Arguments:

`session` `ShinySession` object or `NULL` to identify the current Shiny session.

Returns: Nothing. This method is called for side effects.

Method `log_button()`: Track a button and track changes to this input (without storing the values)

Usage:

```
Telemetry$log_button(
  input_id,
  track_value = FALSE,
  session = shiny::getDefaultReactiveDomain()
)
```

Arguments:

`input_id` string that identifies the button in the Shiny application so that the function can track and log changes to it.

`track_value` flag that indicates if the basic telemetry should track the value of the input that are changing. FALSE by default.

`session` ShinySession object or NULL to identify the current Shiny session.

Returns: Nothing. This method is called for side effects.

Method `log_all_inputs()`: Automatic tracking of all input changes in the App. Depending on the parameters, it may only track a subset of inputs by excluding patterns or by including specific vector of `input_ids`.

Usage:

```
Telemetry$log_all_inputs(
  track_values = FALSE,
  excluded_inputs = c("browser_version"),
  excluded_inputs_regex = NULL,
  include_input_ids = NULL,
  session = shiny::getDefaultReactiveDomain()
)
```

Arguments:

`track_values` flag that indicates if the basic telemetry should track the values of the inputs that are changing. FALSE by default. This parameter is ignored if `track_inputs` is FALSE.

`excluded_inputs` vector of `input_ids` that should not be tracked. By default it doesn't track browser version, which is added by this package.

`excluded_inputs_regex` vector of `input_ids` that should not be tracked. All Special characters will be escaped.

`include_input_ids` vector of `input_ids` that will be tracked. This `input_ids` should be an exact match and will be given priority over exclude list.

`session` ShinySession object or NULL to identify the current Shiny session.

Returns: Nothing. This method is called for side effects.

Method `log_input()`: Track changes of a specific input id.

Usage:

```
Telemetry$log_input(
  input_id,
  track_value = FALSE,
  matching_values = NULL,
```

```

    input_type = "text",
    session = shiny::getDefaultReactiveDomain()
  )

```

Arguments:

input_id string (or vector of strings) that identifies the generic input in the Shiny application so that the function can track and log changes to it.

When the **input_id** is a vector of strings, the function will behave just as calling **log_input** one by one with the same arguments.

track_value flag that indicates if the basic telemetry should track the value of the input that are changing. FALSE by default.

matching_values An object specified possible values to register.

input_type "text" to registered bare input value, "json" to parse value from JSON format.

session ShinySession object or NULL to identify the current Shiny session.

Returns: Nothing. This method is called for its side effects.

Method log_input_manual(): Log a manual input value.

This can be called in telemetry and is also used as a layer between **log_input** family of functions and actual log event. It creates the correct payload to log the event internally.

Usage:

```

Telemetry$log_input_manual(
  input_id,
  value = NULL,
  session = shiny::getDefaultReactiveDomain()
)

```

Arguments:

input_id string that identifies the generic input in the Shiny application so that the function can track and log changes to it.

value (optional) scalar value or list with the value to register.

session ShinySession object or NULL to identify the current Shiny session.

Returns: Nothing. This method is called for side effects.

Method log_custom_event(): Log a manual event

Usage:

```

Telemetry$log_custom_event(
  event_type,
  details = NULL,
  session = shiny::getDefaultReactiveDomain()
)

```

Arguments:

event_type string that identifies the event type

details (optional) scalar value or list with the value to register.

session ShinySession object or NULL to identify the current Shiny session.

Returns: Nothing. This method is called for side effects.

Method `log_error()`: Log a manual error event

Usage:

```
Telemetry$log_error(
  output_id,
  message,
  session = shiny::getDefaultReactiveDomain()
)
```

Arguments:

`output_id` string that refers to the output element where the error occurred.

`message` string that describes the error.

`session` ShinySession object or NULL to identify the current Shiny session.

Returns: Nothing. This method is called for side effects.

Method `log_errors()`: Track errors as they occur in observe and reactive

Usage:

```
Telemetry$log_errors(session = shiny::getDefaultReactiveDomain())
```

Arguments:

`session` ShinySession object or NULL to identify the current Shiny session.

Returns: Nothing. This method is called for side effects.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
Telemetry$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

[DataStorage](#) which this function wraps.

Examples

```
log_file_path <- tempfile(fileext = ".txt")
telemetry <- Telemetry$new(
  data_storage = DataStorageLogFile$new(log_file_path = log_file_path)
) # 1. Initialize telemetry with default options

#
# Use in a shiny application

if (interactive()) {
  library(shiny)

  shinyApp(
    ui = fluidPage(
      use_telemetry(), # 2. Add necessary javascript to Shiny
```

```

        numericInput("n", "n", 1),
        plotOutput('plot')
    ),
    server = function(input, output) {
        telemetry$start_session() # 3. Minimal setup to track events
        output$plot <- renderPlot({ hist(runif(input$n)) })
    }
}

#
# Manual logging of Telemetry that can be used inside Shiny Application
# to further customize the events to be tracked.

session <- shiny::MockShinySession$new() # Create dummy session (only for example purposes)
class(session) <- c(class(session), "ShinySession")

telemetry$log_click("a_button", session = session)

telemetry$log_error("global", message = "An error has occurred")

telemetry$log_custom_event("a_button", list(value = 2023), session = session)
telemetry$log_custom_event("a_button", list(custom_field = 23), session = session)

# Manual call login with custom username
telemetry$log_login("ben", session = session)

# Read all data
telemetry$data_storage$read_event_data()

file.remove(log_file_path)

#
# Using SQLite

db_path <- tempfile(fileext = ".sqlite")
telemetry_sqlite <- Telemetry$new(
  data_storage = DataStorageSQLite$new(db_path = db_path)
)

telemetry_sqlite$log_custom_event("a_button", list(value = 2023), session = session)
telemetry_sqlite$log_custom_event("a_button", list(custom_field = 23), session = session)

# Read all data from time range
telemetry_sqlite$data_storage$read_event_data("2020-01-01", "2055-01-01")

file.remove(db_path)

```

Description

Function that adds telemetry HTML elements to UI

Usage

```
use_telemetry(id = "")
```

Arguments

`id` (optional) string with id representing the namespace

Value

A `shiny.tag` object to be included in the UI of a Shiny app.

Index

* datasets

date_from_null, [15](#)

date_to_null, [16](#)

analytics_app, [2](#)

build_id_from_secret, [3](#)

build_token, [3](#)

DataStorage, [4](#), [5–7](#), [9](#), [11](#), [12](#), [14](#), [16](#), [22](#)

DataStorageLogFile, [5](#)

DataStorageMariaDB, [6](#)

DataStorageMongoDB, [7](#)

DataStorageMSSQLServer, [9](#)

DataStoragePlumber, [11](#)

DataStoragePostgreSQL, [12](#)

DataStorageSQLFamily, [14](#)

DataStorageSQLite, [14](#)

date_from_null, [15](#)

date_to_null, [16](#)

mongolite::ssl_options(), [8](#)

shiny.telemetry::DataStorage, [5](#), [6](#), [8](#), [9](#),
[11](#), [13](#), [14](#)

shiny.telemetry::DataStorageSQLFamily,
[6](#), [9](#), [13](#), [14](#)

Telemetry, [16](#)

use_telemetry, [23](#)