

Package ‘simplanonym’

July 23, 2025

Type Package

Title Consistent Anonymisation Across Datasets

Version 0.1.0

Description A simple function that anonymises a list of variables in a consistent way: anonymised factors are not recycled and the same original levels receive the same anonymised factor even if located in different datasets.

License Apache License (>= 2)

Encoding UTF-8

RoxygenNote 7.2.3

URL <https://github.com/dkgaraujo/simplanonym>

BugReports <https://github.com/dkgaraujo/simplanonym/issues>

Imports dplyr (>= 1.0.10), forcats (>= 0.5.1), tidyselect (>= 1.2.0)

Suggests testthat (>= 3.0.0), vroom (>= 1.5.7)

Config/testthat/edition 3

NeedsCompilation no

Author Douglas Kiarely Godoy de Araujo [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-8070-6828>>)

Maintainer Douglas Kiarely Godoy de Araujo <dkg.araujo@gmail.com>

Repository CRAN

Date/Publication 2023-01-30 16:20:05 UTC

Contents

anonymise	2
Index	3

anonymise

Anonymise factor columns across datasets in a consistent way

Description

‘anonymise()’ is a useful function for anonymising factor columns across different datasets using consistent anonymised levels. In other words, if the same factor level appears in more than one dataset, then ‘anonymise()’ will use the same anonymous factor for that level.

Usage

```
anonymise(data_list, prefix = "", return_original_levels = FALSE)
```

Arguments

data_list	A list of data frames or tibbles.
prefix	A character prefix to insert in front of the random labels.
return_original_levels	Whether or not the resulting list should also include the original, non-anonymised levels. Default: FALSE.

Value

A list containing the original data, but with consistently anonymised factors

Examples

```
library(simplanonym)

rand_tbl_1 <- vroom::gen_tbl(10, 4, col_types = "fffd")
rand_tbl_2 <- vroom::gen_tbl(10, 2, col_types = "fd")
rand_tbl_2$X3 <- rand_tbl_1$X3

# note:
# * rand_tbl_1 and rand_tbl_2 share three column names,
#   of which X2 is a factor in one but not the other.
# * X1 factors do not overlap, but their anonymisation
#   should still be consistent (ie, different levels should
#   have their own unique anonymised factors).
# * For X3, the anonymised factors should consider the levels
#   at both `rand_tbl_1$X3` and `rand_tbl_2$X3`.

data_list <- list(rand_tbl_1, rand_tbl_2)
data_list

data_list |> anonymise(return_original_levels = TRUE)
```

Index

anonymise, [2](#)