

Package ‘smoof’

July 23, 2025

Type Package

Title Single and Multi-Objective Optimization Test Functions

Description Provides generators for a high number of both single- and multi-objective test functions which are frequently used for the benchmarking of (numerical) optimization algorithms. Moreover, it offers a set of convenient functions to generate, plot and work with objective functions.

Version 1.6.0.3

Date 2023-03-06

Maintainer Jakob Bossek <j.bossek@gmail.com>

URL <https://jakobbossek.github.io/smoof/>,
<https://github.com/jakobbossek/smoof>

BugReports <https://github.com/jakobbossek/smoof/issues>

License BSD_2_clause + file LICENSE

Depends ParamHelpers (>= 1.8), checkmate (>= 1.1)

Imports BBmisc (>= 1.6), ggplot2 (>= 2.2.1), Rcpp (>= 0.11.0)

Suggests testthat, plot3D, plotly, mco, RColorBrewer, reticulate, covr

ByteCompile yes

LinkingTo Rcpp, RcppArmadillo

RoxygenNote 7.2.3

Encoding UTF-8

NeedsCompilation yes

Author Jakob Bossek [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-4121-4668>>),
Pascal Kerschke [ctb] (ORCID: <<https://orcid.org/0000-0003-2862-1418>>)

Repository CRAN

Date/Publication 2023-03-10 14:20:05 UTC

Contents

smoof-package	6
addCountingWrapper	6
addLoggingWrapper	7
autoplot.smoof_function	8
computeExpectedRunningTime	11
conversion	12
doesCountEvaluations	13
filterFunctionsByTags	13
getAvailableTags	14
getDescription	15
getGlobalOptimum	15
getID	16
getLocalOptimum	16
getLoggedValues	17
getLowerBoxConstraints	17
getMeanFunction	18
getName	18
getNumberOfEvaluations	19
getNumberOfObjectives	19
getNumberOfParameters	20
getParamSet	20
getRefPoint	21
getTags	21
getUpperBoxConstraints	22
getWrappedFunction	22
hasBoxConstraints	23
hasConstraints	23
hasGlobalOptimum	24
hasLocalOptimum	24
hasOtherConstraints	25
hasTags	25
isMultiobjective	26
isNoisy	26
isSingleobjective	27
isSmoofFunction	27
isVectorized	28
isWrappedSmoofFunction	28
makeAckleyFunction	29
makeAdjimanFunction	29
makeAlpine01Function	30
makeAlpine02Function	31
makeAluffiPentiniFunction	31
makeBartelsConnFunction	32
makeBBOBFunction	32
makeBealeFunction	33
makeBentCigarFunction	34

makeBiObjBBOBFunction	34
makeBirdFunction	35
makeBiSphereFunction	36
makeBK1Function	37
makeBohachevskyN1Function	37
makeBoothFunction	38
makeBraninFunction	38
makeBrentFunction	39
makeBrownFunction	39
makeBukinN2Function	40
makeBukinN4Function	41
makeBukinN6Function	41
makeCarromTableFunction	42
makeChichinadzeFunction	42
makeChungReynoldsFunction	43
makeComplexFunction	44
makeCosineMixtureFunction	44
makeCrossInTrayFunction	45
makeCubeFunction	45
makeDeckkersAartsFunction	46
makeDeflectedCorrugatedSpringFunction	47
makeDentFunction	47
makeDixonPriceFunction	48
makeDoubleSumFunction	49
makeDTLZ1Function	49
makeDTLZ2Function	50
makeDTLZ3Function	51
makeDTLZ4Function	52
makeDTLZ5Function	53
makeDTLZ6Function	54
makeDTLZ7Function	55
makeEasomFunction	56
makeED1Function	57
makeED2Function	58
makeEggCrateFunction	59
makeEggholderFunction	59
makeElAttarVidyasagarDuttaFunction	60
makeEngvallFunction	60
makeExponentialFunction	61
makeFreudensteinRothFunction	61
makeFunctionsByName	62
makeGeneralizedDropWaveFunction	63
makeGiuntaFunction	63
makeGoldsteinPriceFunction	64
makeGOMOPFunction	64
makeGriewankFunction	65
makeHansenFunction	66
makeHartmannFunction	66

makeHimmelblauFunction	67
makeHolderTableN1Function	68
makeHolderTableN2Function	68
makeHosakiFunction	69
makeHyperEllipsoidFunction	70
makeInvertedVincentFunction	70
makeJennrichSampsonFunction	71
makeJudgeFunction	72
makeKeaneFunction	72
makeKearfottFunction	73
makeKursaweFunction	73
makeLeonFunction	74
makeMatyasFunction	74
makeMcCormickFunction	75
makeMichalewiczFunction	75
makeMMF10Function	76
makeMMF11Function	77
makeMMF12Function	77
makeMMF13Function	78
makeMMF14aFunction	79
makeMMF14Function	79
makeMMF15aFunction	80
makeMMF15Function	81
makeMMF1eFunction	82
makeMMF1Function	82
makeMMF1zFunction	83
makeMMF2Function	83
makeMMF3Function	84
makeMMF4Function	84
makeMMF5Function	85
makeMMF6Function	85
makeMMF7Function	86
makeMMF8Function	86
makeMMF9Function	87
makeModifiedRastriginFunction	87
makeMOP1Function	88
makeMOP2Function	89
makeMOP3Function	89
makeMOP4Function	90
makeMOP5Function	90
makeMOP6Function	91
makeMOP7Function	91
makeMPM2Function	92
makeMultiObjectiveFunction	93
makeOmniTestFunction	95
makePeriodicFunction	95
makePowellSumFunction	96
makePriceN1Function	97

makePriceN2Function	97
makePriceN4Function	98
makeRastriginFunction	99
makeRosenbrockFunction	99
makeSchafferN2Function	100
makeSchafferN4Function	101
makeSchwefelFunction	101
makeShekelFunction	102
makeShubertFunction	103
makeSingleObjectiveFunction	103
makeSixHumpCamelFunction	106
makeSphereFunction	107
makeStyblinskiTangFunction	107
makeSumOfDifferentSquaresFunction	108
makeSwiler2014Function	108
makeSYMPARTrotatedFunction	109
makeSYMPARTsimpleFunction	110
makeThreeHumpCamelFunction	110
makeTrecanniFunction	111
makeUFFunction	112
makeViennetFunction	112
makeWFG1Function	113
makeWFG2Function	114
makeWFG3Function	115
makeWFG4Function	116
makeWFG5Function	117
makeWFG6Function	118
makeWFG7Function	119
makeWFG8Function	120
makeWFG9Function	121
makeZDT1Function	122
makeZDT2Function	123
makeZDT3Function	124
makeZDT4Function	125
makeZDT6Function	126
makeZettlFunction	127
mnof	127
plot.smoof_function	129
plot1DNumeric	130
plot2DNumeric	130
plot3D	131
resetEvaluationCounter	132
shouldBeMinimized	133
smoof_function	133
snof	134
violatesConstraints	136
visualizeParetoOptimalFront	137

smoof-package

smoof: Single and Multi-Objective Optimization test functions.

Description

The **smoof** R package provides generators for huge set of single- and multi-objective test functions, which are frequently used in the literature to benchmark optimization algorithms. Moreover the package provides methods to create arbitrary objective functions in an object-orientated manner, extract their parameters sets and visualize them graphically.

Some more details

Given a set of criteria $\mathcal{F} = \{f_1, \dots, f_m\}$ with each $f_i : S \subseteq \mathbf{R}^d \rightarrow \mathbf{R}, i = 1, \dots, m$ being an objective-function, the goal in *Global Optimization (GO)* is to find the best solution $\mathbf{x}^* \in S$. The set S is termed the *set of feasible solutions*. In the case of only a single objective function f , - which we want to restrict ourself in this brief description - the goal is to minimize the objective, i. e.,

$$\min_{\mathbf{x}} f(\mathbf{x}).$$

Sometimes we may be interested in maximizing the objective function value, but since $\min(f(\mathbf{x})) = -\min(-f(\mathbf{x}))$, we do not have to tackle this separately. To compare the robustness of optimization algorithms and to investigate their behaviour in different contexts, a common approach in the literature is to use *artificial benchmarking functions*, which are mostly deterministic, easy to evaluate and given by a closed mathematical formula. A recent survey by Jamil and Yang lists 175 single-objective benchmarking functions in total for global optimization [1]. The **smoof** package offers implementations of a subset of these functions beside some other functions as well as generators for large benchmarking sets like the noiseless BBOB2009 function set [2] or functions based on the multiple peaks model 2 [3].

References

[1] Momin Jamil and Xin-She Yang, A literature survey of benchmark functions for global optimization problems, Int. Journal of Mathematical Modelling and Numerical Optimisation, Vol. 4, No. 2, pp. 150-194 (2013). [2] Hansen, N., Finck, S., Ros, R. and Auger, A. Real-Parameter Black-Box Optimization Benchmarking 2009: Noiseless Functions Definitions. Technical report RR-6829. INRIA, 2009. [3] Simon Wessing, The Multiple Peaks Model 2, Algorithm Engineering Report TR15-2-001, TU Dortmund University, 2015.

addCountingWrapper

Return a function which counts its function evaluations.

Description

This is a counting wrapper for a `smoof_function`, i.e., the returned function first checks whether the given argument is a vector or matrix, saves the number of function evaluations of the wrapped function to compute the function values and finally passes down the argument to the wrapped `smoof_function`.

Usage

```
addCountingWrapper(fn)
```

Arguments

```
fn                [smoof_function]  
                  Smoof function which should be wrapped.
```

Value

```
[smoof_counting_function]
```

See Also

```
getNumberOfEvaluations, resetEvaluationCounter
```

Examples

```
fn = makeBBOBFunction(dimensions = 2L, fid = 1L, iid = 1L)  
fn = addCountingWrapper(fn)  
  
# we get a value of 0 since the function has not been called yet  
print(getNumberOfEvaluations(fn))  
  
# now call the function 10 times consecutively  
for (i in seq(10L)) {  
  fn(runif(2))  
}  
print(getNumberOfEvaluations(fn))  
  
# Here we pass a (2x5) matrix to the function with each column representing  
# one input vector  
x = matrix(runif(10), ncol = 5L)  
fn(x)  
print(getNumberOfEvaluations(fn))
```

addLoggingWrapper	<i>Return a function which internally stores x or y values.</i>
-------------------	---

Description

Often it is desired and useful to store the optimization path, i.e., the evaluated function values and/or the parameters. Not all optimization algorithms offer such a trace. This wrapper makes a smoof function handle x/y-values itself.

Usage

```
addLoggingWrapper(fn, logg.x = FALSE, logg.y = TRUE, size = 100L)
```

Arguments

fn	[smoof_function] Smoof function.
logg.x	[logical(1)] Should x-values be logged? Default is FALSE.
logg.y	[logical(1)] Should objective values be logged? Default is TRUE.
size	[integer(1)] Initial size of the internal data structures used for logging. Default is 100. I.e., there is space reserved for 100 function evaluations. In case of an overflow (i.e., more function evaluations than space reserved) the data structures are re-initialized by adding space for another size evaluations. This comes handy if you know the number of function evaluations (or at least an upper bound thereof) a-priori and may serve to reduce the time complexity of logging values.

Value

[smoof_logging_function]

Note

Logging values, in particular logging x-values, will substantially slow down the evaluation of the function.

Examples

```
# We first build the smoof function and apply the logging wrapper to it
fn = makeSphereFunction(dimensions = 2L)
fn = addLoggingWrapper(fn, logg.x = TRUE)

# We now apply an optimization algorithm to it and the logging wrapper keeps
# track of the evaluated points.
res = optim(fn, par = c(1, 1), method = "Nelder-Mead")

# Extract the logged values
log.res = getLoggedValues(fn)
print(log.res$pars)
print(log.res$obj.vals)
log.res = getLoggedValues(fn, compact = TRUE)
print(log.res)
```

autoplot.smoof_function

Generate ggplot2 object.

Description

This function expects a smooof function and returns a ggplot object depicting the function landscape. The output depends highly on the decision space of the smooof function or more technically on the [ParamSet](#) of the function. The following distinctions regarding the parameter types are made. In case of a single numeric parameter a simple line plot is drawn. For two numeric parameters or a single numeric vector parameter of length 2 either a contour plot or a heatmap (or a combination of both depending on the choice of additional parameters) is depicted. If there are both up to two numeric and at least one discrete vector parameter, ggplot faceting is used to generate subplots of the above-mentioned types for all combinations of discrete parameters.

Usage

```
## S3 method for class 'smooof_function'
autoplot(
  object,
  ...,
  show.optimum = FALSE,
  main = getName(x),
  render.levels = FALSE,
  render.contours = TRUE,
  log.scale = FALSE,
  length.out = 50L
)
```

Arguments

object	[smooof_function] Objective function.
...	[any] Not used.
show.optimum	[logical(1)] If the function has a known global optimum, should its location be plotted by a point or multiple points in case of multiple global optima? Default is FALSE.
main	[character(1L)] Plot title. Default is the name of the smooof function.
render.levels	[logical(1)] For 2D numeric functions only: Should an image map be plotted? Default is FALSE.
render.contours	[logical(1)] For 2D numeric functions only: Should contour lines be plotted? Default is TRUE.
log.scale	[logical(1)] Should the z-axis be plotted on log-scale? Default is FALSE.
length.out	[integer(1)] Desired length of the sequence of equidistant values generated for numeric parameters. Higher values lead to more smooth resolution in particular if render.levels

is TRUE. Avoid using a very high value here especially if the function at hand has many parameters. Default is 50.

Value

[ggplot]

Note

Keep in mind, that the plots for mixed parameter spaces may be very large and computationally expensive if the number of possible discrete parameter values is large. I.e., if we have d discrete parameter with each $n_1, n_2, \dots, n_d$ possible values we end up with $n_1 \times n_2 \times \dots \times n_d$ subplots.

Examples

```
library(ggplot2)

# Simple 2D contour plot with activated heatmap for the Himmelblau function
fn = makeHimmelblauFunction()
print(autoplot(fn))
print(autoplot(fn, render.levels = TRUE, render.contours = FALSE))
print(autoplot(fn, show.optimum = TRUE))

# Now we create 4D function with a mixed decision space (two numeric, one discrete,
# and one logical parameter)
fn.mixed = makeSingleObjectiveFunction(
  name = "4d SOO function",
  fn = function(x) {
    if (x$disc1 == "a") {
      (x$x1^2 + x$x2^2) + 10 * as.numeric(x$logic)
    } else {
      x$x1 + x$x2 - 10 * as.numeric(x$logic)
    }
  },
  has.simple.signature = FALSE,
  par.set = makeParamSet(
    makeNumericParam("x1", lower = -5, upper = 5),
    makeNumericParam("x2", lower = -3, upper = 3),
    makeDiscreteParam("disc1", values = c("a", "b")),
    makeLogicalParam("logic")
  )
)
pl = autoplot(fn.mixed)
print(pl)

# Since autoplot returns a ggplot object we can modify it, e.g., add a title
# or hide the legend
pl + ggtitle("My fancy function") + theme(legend.position = "none")
```

computeExpectedRunningTime

Compute the Expected Running Time (ERT) performance measure.

Description

The functions can be called in two different ways

- 1. Pass a vector of function evaluations and a logical vector which indicates which runs were successful (see details).
- 2. Pass a vector of function evaluation, a vector of reached target values and a single target value. In this case the logical vector of option 1. is computed internally.

Usage

```
computeExpectedRunningTime(
  fun.evals,
  fun.success.runs = NULL,
  fun.reached.target.values = NULL,
  fun.target.value = NULL,
  penalty.value = Inf
)
```

Arguments

fun.evals	[numeric] Vector containing the number of function evaluations.
fun.success.runs	[logical] Boolean vector indicating which algorithm runs were successful, i. e., which runs reached the desired target value. Default is NULL.
fun.reached.target.values	[numeric NULL] Numeric vector with the objective values reached in the runs. Default is NULL.
fun.target.value	[numeric(1) NULL] Target value which shall be reached. Default is NULL.
penalty.value	[numeric(1)] Penalty value which should be returned if none of the algorithm runs was successful. Default is Inf.

Details

The Expected Running Time (ERT) is one of the most popular performance measures in optimization. It is defined as the expected number of function evaluations needed to reach a given precision level, i. e., to reach a certain objective value for the first time.

Value

[numeric(1)] Estimated Expected Running Time.

References

A. Auger and N. Hansen. Performance evaluation of an advanced local search evolutionary algorithm. In Proceedings of the IEEE Congress on Evolutionary Computation (CEC 2005), pages 1777-1784, 2005.

conversion

Conversion between minimization and maximization problems.

Description

We can minimize f by maximizing $-f$. The majority of predefined objective functions in **smoof** should be minimized by default. However, there is a handful of functions, e.g., Keane or Alpine02, which shall be maximized by default. For benchmarking studies it might be beneficial to inverse the direction. The functions `convertToMaximization` and `convertToMinimization` do exactly that keeping the attributes.

Usage

```
convertToMaximization(fn)
```

```
convertToMinimization(fn)
```

Arguments

fn	[smoof_function]
	Smoof function.

Value

[smoof_function]

Note

Both functions will quit with an error if multi-objective functions are passed.

Examples

```
# create a function which should be minimized by default
fn = makeSphereFunction(1L)
print(shouldBeMinimized(fn))
# Now invert the objective direction ...
fn2 = convertToMaximization(fn)
# and invert it again
fn3 = convertToMinimization(fn2)
```

```
# Now to convince ourselves we render some plots
opar = par(mfrow = c(1, 3))
plot(fn)
plot(fn2)
plot(fn3)
par(opar)
```

doesCountEvaluations *Check whether the function is counting its function evaluations.*

Description

In this case the function is of type `smoof_counting_function` or it is further wrapped by another wrapper. This function then checks recursively, if there is a counting wrapper.

Usage

```
doesCountEvaluations(object)
```

Arguments

object	[any] Arbitrary R object.
--------	------------------------------

Value

```
logical(1)
```

See Also

[addCountingWrapper](#)

filterFunctionsByTags *Get a list of implemented test functions with specific tags.*

Description

Single objective functions can be tagged, e.g., as unimodal. Searching for all functions with a specific tag by hand is tedious. The `filterFunctionsByTags` function helps to filter all single objective `smoof` function.

Usage

```
filterFunctionsByTags(tags, or = FALSE)
```

Arguments

tags	[character] Character vector of tags. All available tags can be determined with a call to <code>getAvailableTags</code> .
or	[logical(1)] Should all tags be assigned to the function or are single tags allowed as well? Default is FALSE.

Value

[character] Named vector of function names with the given tags.

Examples

```
# list all functions which are unimodal
filterFunctionsByTags("unimodal")
# list all functions which are both unimodal and separable
filterFunctionsByTags(c("unimodal", "separable"))
# list all functions which are unimodal or separable
filterFunctionsByTags(c("multimodal", "separable"), or = TRUE)
```

<code>getAvailableTags</code>	<i>Returns a character vector of possible function tags.</i>
-------------------------------	--

Description

Test function are frequently distinguished by characteristic high-level properties, e.g., unimodal or multimodal, continuous or discontinuous, separable or non-separable. The **smoof** package offers the possibility to associate a set of properties, termed “tags” to a `smoof_function`. This helper function returns a character vector of all possible tags.

Usage

```
getAvailableTags()
```

Value

[character]

getDescription	<i>Return the description of the function.</i>
----------------	--

Description

Return the description of the function.

Usage

```
getDescription(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

[character(1)]

getGlobalOptimum	<i>Returns the global optimum and its value.</i>
------------------	--

Description

Returns the global optimum and its value.

Usage

```
getGlobalOptimum(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

[list] List containing the following entries:

- param [list] Named list of parameter value(s).
- value [numeric(1)] Optimal value.
- is.minimum [logical(1)] Is the global optimum a minimum or maximum?

Note

Keep in mind, that this method makes sense only for single-objective target function.

getID	<i>Return the ID / short name of the function or NA if no ID is set.</i>
-------	--

Description

Return the ID / short name of the function or NA if no ID is set.

Usage

```
getID(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

[character(1)] or NA

getLocalOptimum	<i>Returns the local optima of a single objective smoof function.</i>
-----------------	---

Description

This function returns the parameters and objective values of all local optima (including the global one).

Usage

```
getLocalOptimum(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

[list] List containing the following entries:

- param [list] List of parameter values per local optima.
- value [list] List of objective values per local optima.
- is.minimum [logical(1)] Are the local optima minima or maxima?

Note

Keep in mind, that this method makes sense only for single-objective target functions.

getLoggedValues	<i>Extract logged values of a function wrapped by a logging wrapper.</i>
-----------------	--

Description

Extract logged values of a function wrapped by a logging wrapper.

Usage

```
getLoggedValues(fn, compact = FALSE)
```

Arguments

fn	[wrapped_smoof_function] Wrapped smoof function.
compact	[logical(1)] Wrap all logged values in a single data frame? Default is FALSE.

Value

[list || data.frame] If compact is TRUE, a single data frame. Otherwise the function returns a list containing the following values:

pars Data frame of parameter values, i.e., x-values or the empty data frame if x-values were not logged.

obj.vals Numeric vector of objective vals in the single-objective case respectively a matrix of objective vals for multi-objective functions.

See Also

[addLoggingWrapper](#)

getLowerBoxConstraints	<i>Return lower box constraints.</i>
------------------------	--------------------------------------

Description

Return lower box constraints.

Usage

```
getLowerBoxConstraints(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

[numeric]

getMeanFunction	<i>Return the true mean function in the noisy case.</i>
-----------------	---

Description

Return the true mean function in the noisy case.

Usage

```
getMeanFunction(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

[function]

getName	<i>Return the name of the function.</i>
---------	---

Description

Return the name of the function.

Usage

```
getName(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

[character(1)]

`getNumberOfEvaluations`*Return the number of function evaluations performed by the wrapped smooof_function.*

Description

Return the number of function evaluations performed by the wrapped smooof_function.

Usage

```
getNumberOfEvaluations(fn)
```

Arguments

fn	[smooof_counting_function] Wrapped smooof_function.
----	--

Value

```
[integer(1)]
```

`getNumberOfObjectives` *Determine the number of objectives.*

Description

Determine the number of objectives.

Usage

```
getNumberOfObjectives(fn)
```

Arguments

fn	[smooof_function] Objective function.
----	--

Value

```
[integer(1)]
```

getNumberOfParameters *Determine the number of parameters.*

Description

Determine the number of parameters.

Usage

```
getNumberOfParameters(fn)
```

Arguments

fn	[smoof_function]
	Objective function.

Value

```
[integer(1)]
```

getParamSet *Get parameter set.*

Description

Each smoof function contains a parameter set of type [ParamSet](#) assigned to it, which describes types and bounds of the function parameters. This function returns the parameter set.

Arguments

fn	[smoof_function]
	Objective function.

Value

```
[ParamSet]
```

Examples

```
fn = makeSphereFunction(3L)
ps = getParamSet(fn)
print(ps)
```

getRefPoint	Returns the reference point of a multi-objective function.
-------------	--

Description

Returns the reference point of a multi-objective function.

Usage

```
getRefPoint(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

[numeric]

Note

Keep in mind, that this method makes sense only for multi-objective target functions.

getTags	Returns vector of associated tags.
---------	------------------------------------

Description

Returns vector of associated tags.

Usage

```
getTags(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

[character]

getUpperBoxConstraints

Return upper box constraints.

Description

Return upper box constraints.

Usage

```
getUpperBoxConstraints(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

[numeric]

getWrappedFunction

Extract wrapped function.

Description

The **smoof** package offers means to let a function log its evaluations or even store to points and function values it has been evaluated on. This is done by wrapping the function with other functions. This helper function extract the wrapped function.

Usage

```
getWrappedFunction(fn, deepest = FALSE)
```

Arguments

fn	[smoof_wrapped_function] Wrapping function.
deepest	[logical(1)] Function may be wrapped with multiple wrappers. If deepest is set to TRUE the function unwraps recursively until the “deepest” wrapped smoof_function is reached. Default is FALSE.

Value

[function]

Note

If this function is applied to a simple `smoof_function`, the `smoof_function` itself is returned.

See Also

[addCountingWrapper](#), [addLoggingWrapper](#)

hasBoxConstraints	<i>Checks whether the objective function has box constraints.</i>
-------------------	---

Description

Checks whether the objective function has box constraints.

Usage

```
hasBoxConstraints(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

[logical(1)]

hasConstraints	<i>Checks whether the objective function has constraints.</i>
----------------	---

Description

Checks whether the objective function has constraints.

Usage

```
hasConstraints(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

[logical(1)]

hasGlobalOptimum	<i>Checks whether global optimum is known.</i>
------------------	--

Description

Checks whether global optimum is known.

Usage

```
hasGlobalOptimum(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

[logical(1)]

hasLocalOptimum	<i>Checks whether local optima are known.</i>
-----------------	---

Description

Checks whether local optima are known.

Usage

```
hasLocalOptimum(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

[logical(1)]

hasOtherConstraints	<i>Checks whether the objective function has other constraints.</i>
---------------------	---

Description

Checks whether the objective function has other constraints.

Usage

```
hasOtherConstraints(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

```
[logical(1)]
```

hasTags	<i>Check if function has assigned special tags.</i>
---------	---

Description

Each single-objective smoof function has tags assigned to it (see [getAvailableTags](#)). This little helper returns a vector of assigned tags from a smoof function.

Usage

```
hasTags(fn, tags)
```

Arguments

fn	[smoof_function] Function of smoof_function, a smoof_generator or a string.
tags	[character] Vector of tags/properties to check fn for.

Value

```
[logical(1)]
```

isMultiobjective	<i>Checks whether the given function is multi-objective.</i>
------------------	--

Description

Checks whether the given function is multi-objective.

Usage

```
isMultiobjective(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

[logical(1)] TRUE if function is multi-objective.

isNoisy	<i>Checks whether the given function is noisy.</i>
---------	--

Description

Checks whether the given function is noisy.

Usage

```
isNoisy(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

[logical(1)]

isSingleobjective	<i>Checks whether the given function is single-objective.</i>
-------------------	---

Description

Checks whether the given function is single-objective.

Usage

```
isSingleobjective(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

[logical(1)] TRUE if function is single-objective.

isSmoofFunction	<i>Checks whether the given object is a smoof_function or a smoof_wrapped_function.</i>
-----------------	---

Description

Checks whether the given object is a smoof_function or a smoof_wrapped_function.

Usage

```
isSmoofFunction(object)
```

Arguments

object	[any] Arbitrary R object.
--------	------------------------------

Value

[logical(1)]

See Also

[addCountingWrapper](#), [addLoggingWrapper](#)

isVectorized	<i>Checks whether the given function accept “vectorized” input.</i>
--------------	---

Description

Checks whether the given function accept “vectorized” input.

Usage

```
isVectorized(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

```
[logical(1)]
```

isWrappedSmoofFunction	<i>Checks whether the function is of type smoof_wrapped_function.</i>
------------------------	---

Description

Checks whether the function is of type smoof_wrapped_function.

Usage

```
isWrappedSmoofFunction(object)
```

Arguments

object	[any] Arbitrary R object.
--------	------------------------------

Value

```
[logical(1)]
```

makeAckleyFunction	<i>Ackley Function</i>
--------------------	------------------------

Description

Also known as “Ackley’s Path Function”. Multimodal test function with its global optimum in the center of the definition space. The implementation is based on the formula

$$f(\mathbf{x}) = -a \cdot \exp \left(-b \cdot \sqrt{\left(\frac{1}{n} \sum_{i=1}^n \mathbf{x}_i \right)} \right) - \exp \left(\frac{1}{n} \sum_{i=1}^n \cos(c \cdot \mathbf{x}_i) \right),$$

with $a = 20$, $b = 0.2$ and $c = 2\pi$. The feasible region is given by the box constraints $\mathbf{x}_i \in [-32.768, 32.768]$.

Usage

```
makeAckleyFunction(dimensions)
```

Arguments

dimensions	[integer(1)]
------------	--------------

Size of corresponding parameter space.

Value

```
[smoof_single_objective_function]
```

References

Ackley, D. H.: A connectionist machine for genetic hillclimbing. Boston: Kluwer Academic Publishers, 1987.

makeAdjimanFunction	<i>Adjiman function</i>
---------------------	-------------------------

Description

This two-dimensional multimodal test function follows the formula

$$f(\mathbf{x}) = \cos(\mathbf{x}_1) \sin(\mathbf{x}_2) - \frac{\mathbf{x}_1}{(\mathbf{x}_2^2 + 1)}$$

with $\mathbf{x}_1 \in [-1, 2]$, $\mathbf{x}_2 \in [2, 1]$.

Usage

```
makeAdjimanFunction()
```

Value

[smoof_single_objective_function]

References

C. S. Adjiman, S. Sallwig, C. A. Flouda, A. Neumaier, A Global Optimization Method, aBB for General Twice-Differentiable NLPs-1, Theoretical Advances, Computers Chemical Engineering, vol. 22, no. 9, pp. 1137-1158, 1998.

makeAlpine01Function *Alpine01 function*

Description

Highly multimodal single-objective optimization test function. It is defined as

$$f(\mathbf{x}) = \sum_{i=1}^n |\mathbf{x}_i \sin(\mathbf{x}_i) + 0.1\mathbf{x}_i|$$

with box constraints $\mathbf{x}_i \in [-10, 10]$ for $i = 1, \dots, n$.

Usage

makeAlpine01Function(dimensions)

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

[smoof_single_objective_function]

References

S. Rahnamyan, H. R. Tizhoosh, N. M. M. Salama, A Novel Population Initialization Method for Accelerating Evolutionary Algorithms, Computers and Mathematics with Applications, vol. 53, no. 10, pp. 1605-1614, 2007.

makeAlpine02Function *Alpine02 function*

Description

Another multimodal optimization test function. The implementation is based on the formula

$$f(\mathbf{x}) = \prod_{i=1}^n \sqrt{\mathbf{x}_i} \sin(\mathbf{x}_i)$$

with $\mathbf{x}_i \in [0, 10]$ for $i = 1, \dots, n$.

Usage

makeAlpine02Function(dimensions)

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

[smoof_single_objective_function]

References

M. Clerc, The Swarm and the Queen, Towards a Deterministic and Adaptive Particle Swarm Optimization, IEEE Congress on Evolutionary Computation, Washington DC, USA, pp. 1951-1957, 1999.

makeAluffiPentiniFunction
Aluffi-Pentini function.

Description

Two-dimensional test function based on the formula

$$f(\mathbf{x}) = 0.25x_1^4 - 0.5x_1^2 + 0.1x_1 + 0.5x_2^2$$

with $\mathbf{x}_1, \mathbf{x}_2 \in [-10, 10]$.

Usage

makeAluffiPentiniFunction()

Value

[smoof_single_objective_function]

Note

This functions is also know as the Zirilli function.

References

See <https://al-roomi.org/benchmarks/unconstrained/2-dimensions/26-aluffi-pentini-s-or-zirilli-s-fun>

makeBartelsConnFunction	
	<i>Bartels Conn Function</i>

Description

The Bartels Conn Function is defined as

$$f(\mathbf{x}) = |\mathbf{x}_1^2 + \mathbf{x}_2^2 + \mathbf{x}_1\mathbf{x}_2| + |\sin(\mathbf{x}_1)| + |\cos(\mathbf{x})|$$

subject to $\mathbf{x}_i \in [-500, 500]$ for $i = 1, 2$.

Usage

makeBartelsConnFunction()

Value

[smoof_single_objective_function]

makeBBOBFunction	<i>Generator for the noiseless function set of the real-parameter Black-Box Optimization Benchmarking (BBOB).</i>
------------------	---

Description

Generator for the noiseless function set of the real-parameter Black-Box Optimization Benchmarking (BBOB).

Usage

makeBBOBFunction(dimensions, fid, iid)

Arguments

dimensions	[integer(1)] Problem dimension. Integer value between 2 and 40.
fid	[integer(1)] Function identifier. Integer value between 1 and 24.
iid	[integer(1)] Instance identifier. Integer value greater than or equal 1.

Value

[smoof_single_objective_function]

Note

It is possible to pass a matrix of parameters to the functions, where each column consists of one parameter setting.

References

See the [BBOB website](#) for a detailed description of the BBOB functions.

Examples

```
# get the first instance of the 2D Sphere function
fn = makeBBOBFunction(dimensions = 2L, fid = 1L, iid = 1L)
if (require(plot3D)) {
  plot3D(fn, contour = TRUE)
}
```

makeBealeFunction	<i>Beale Function</i>
-------------------	-----------------------

Description

Multimodal single-objective test function for optimization. It is based on the mathematic formula

$$f(\mathbf{x}) = (1.5 - \mathbf{x}_1 + \mathbf{x}_1\mathbf{x}_2)^2 + (2.25 - \mathbf{x}_1 + \mathbf{x}_1\mathbf{x}_2^2)^2 + (2.625 - \mathbf{x}_1 + \mathbf{x}_1\mathbf{x}_2^3)^2$$

usually evaluated within the bounds $\mathbf{x}_i \in [-4.5, 4.5], i = 1, 2$. The function has a flat but multimodal region around the single global optimum and large peaks in the edges of its definition space.

Usage

```
makeBealeFunction()
```

Value

[smoof_single_objective_function]

makeBentCigarFunction *Bent-Cigar Function*

Description

Scalable test function f with

$$f(\mathbf{x}) = x_1^2 + 10^6 \sum_{i=2}^n x_i^2$$

subject to $-100 \leq x_i \leq 100$ for $i = 1, \dots, n$.

Usage

makeBentCigarFunction(dimensions)

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

[smoof_single_objective_function]

References

See <https://al-roomi.org/benchmarks/unconstrained/n-dimensions/164-bent-cigar-function>.

makeBiObjBBOBFunction *Generator for the function set of the real-parameter Bi-Objective Black-Box Optimization Benchmarking (BBOB).*

Description

Generator for the function set of the real-parameter Bi-Objective Black-Box Optimization Benchmarking (BBOB).

Usage

makeBiObjBBOBFunction(dimensions, fid, iid)

Arguments

dimensions	[integer(1)] Problem dimensions. Integer value between 2 and 40.
fid	[integer(1)] Function identifier. Integer value between 1 and 55.
iid	[integer(1)] Instance identifier. Integer value greater than or equal 1.

Value

[smoof_multi_objective_function]

Note

Concatenation of single-objective BBOB functions into a bi-objective problem.

References

See the [COCO website](#) for a detailed description of the bi-objective BBOB functions. An overview of which pair of single-objective BBOB functions creates which of the 55 bi-objective BBOB functions can be found [here](#).

Examples

```
# get the fifth instance of the concatenation of the
# 3D versions of sphere and Rosenbrock
fn = makeBiObjBBOBFunction(dimensions = 3L, fid = 4L, iid = 5L)
fn(c(3, -1, 0))
# compare to the output of its single-objective pendants
f1 = makeBBOBFunction(dimensions = 3L, fid = 1L, iid = 2L * 5L + 1L)
f2 = makeBBOBFunction(dimensions = 3L, fid = 8L, iid = 2L * 5L + 2L)
identical(fn(c(3, -1, 0)), c(f1(c(3, -1, 0)), f2(c(3, -1, 0))))
```

makeBirdFunction

Bird Function

Description

Multimodal single-objective test function. The implementation is based on the mathematical formulation

$$f(\mathbf{x}) = (\mathbf{x}_1 - \mathbf{x}_2)^2 + \exp((1 - \sin(\mathbf{x}_1))^2) \cos(\mathbf{x}_2) + \exp((1 - \cos(\mathbf{x}_2))^2) \sin(\mathbf{x}_1).$$

The function is restricted to two dimensions with $\mathbf{x}_i \in [-2\pi, 2\pi], i = 1, 2$.

Usage

```
makeBirdFunction()
```

Value

[smoof_single_objective_function]

References

S. K. Mishra, Global Optimization By Differential Evolution and Particle Swarm Methods: Evaluation On Some Benchmark Functions, Munich Research Papers in Economics.

makeBiSphereFunction *Bi-objective Sphere function*

Description

Builds and returns the bi-objective Sphere test problem:

$$f(\mathbf{x}) = \left(\sum_{i=1}^n \mathbf{x}_i^2, \sum_{i=1}^n (\mathbf{x}_i - \mathbf{a})^2 \right)$$

where

$$\mathbf{a} \in R^n$$

.

Usage

```
makeBiSphereFunction(dimensions, a = rep(0, dimensions))
```

Arguments

dimensions	[integer(1)] Number of decision variables.
a	[numeric(1)] Shift parameter for the second objective. Default is (0,...,0).

Value

[smoof_multi_objective_function]

makeBK1Function	<i>BK1 function generator</i>
-----------------	-------------------------------

Description

...

Usage

makeBK1Function()

Value

[smoof_multi_objective_function]

References

...

makeBohachevskyN1Function	<i>Bohachevsky function N. 1</i>
---------------------------	----------------------------------

Description

Highly multimodal single-objective test function. The mathematical formula is given by

$$f(\mathbf{x}) = \sum_{i=1}^{n-1} (\mathbf{x}_i^2 + 2\mathbf{x}_{i+1}^2 - 0.3 \cos(3\pi\mathbf{x}_i) - 0.4 \cos(4\pi\mathbf{x}_{i+1}) + 0.7)$$

with box-constraints $\mathbf{x}_i \in [-100, 100]$ for $i = 1, \dots, n$. The multimodality will be visible by “zooming in” in the plot.

Usage

makeBohachevskyN1Function(dimensions)

Arguments

dimensions	[integer(1)]
------------	--------------

Size of corresponding parameter space.

Value

[smoof_single_objective_function]

References

I. O. Bohachevsky, M. E. Johnson, M. L. Stein, General Simulated Annealing for Function Optimization, Technometrics, vol. 28, no. 3, pp. 209-217, 1986.

makeBoothFunction	<i>Booth Function</i>
-------------------	-----------------------

Description

This function is based on the formula

$$f(\mathbf{x}) = (\mathbf{x}_1 + 2\mathbf{x}_2 - 7)^2 + (2\mathbf{x}_1 + \mathbf{x}_2 - 5)^2$$

subject to $\mathbf{x}_i \in [-10, 10], i = 1, 2$.

Usage

```
makeBoothFunction()
```

Value

[smoof_single_objective_function]

makeBraninFunction	<i>Branin RCOS function</i>
--------------------	-----------------------------

Description

Popular 2-dimensional single-objective test function based on the formula:

$$f(\mathbf{x}) = a (\mathbf{x}_2 - b\mathbf{x}_1^2 + c\mathbf{x}_1 - d)^2 + e (1 - f) \cos(\mathbf{x}_1) + e,$$

where $a = 1, b = \frac{5.1}{4\pi^2}, c = \frac{5}{\pi}, d = 6, e = 10$ and $f = \frac{1}{8\pi}$. The box constraints are given by $\mathbf{x}_1 \in [-5, 10]$ and $\mathbf{x}_2 \in [0, 15]$. The function has three global minima.

Usage

```
makeBraninFunction()
```

Value

[smoof_single_objective_function]

References

F. H. Branin. Widely convergent method for finding multiple solutions of simultaneous nonlinear equations. IBM J. Res. Dev. 16, 504-522, 1972.

Examples

```
library(ggplot2)
fn = makeBraninFunction()
print(fn)
print(autoplot(fn, show.optimum = TRUE))
```

makeBrentFunction	<i>Brent Function</i>
-------------------	-----------------------

Description

Single-objective two-dimensional test function. The formula is given as

$$f(\mathbf{x}) = (\mathbf{x}_1 + 10)^2 + (\mathbf{x}_2 + 10)^2 + \exp(-\mathbf{x}_1^2 - \mathbf{x}_2^2)$$

subject to the constraints $\mathbf{x}_i \in [-10, 10], i = 1, 2$.

Usage

```
makeBrentFunction()
```

Value

```
[smoof_single_objective_function]
```

References

F. H. Branin Jr., Widely Convergent Method of Finding Multiple Solutions of Simultaneous Non-linear Equations, IBM Journal of Research and Development, vol. 16, no. 5, pp. 504-522, 1972.

makeBrownFunction	<i>Brown Function</i>
-------------------	-----------------------

Description

This function belongs to the unimodal single-objective test functions. The function is formulated as

$$f(\mathbf{x}) = \sum_{i=1}^n (\mathbf{x}_i^2)^{(\mathbf{x}_{i+1}+1)} + (\mathbf{x}_{i+1})^{(\mathbf{x}_i+1)}$$

subject to $\mathbf{x}_i \in [-1, 4]$ for $i = 1, \dots, n$.

Usage

```
makeBrownFunction(dimensions)
```

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

[smoof_single_objective_function]

References

O. Begambre, J. E. Laier, A hybrid Particle Swarm Optimization - Simplex Algorithm (PSOS) for Structural Damage Identification, Journal of Advances in Engineering Software, vol. 40, no. 9, pp. 883-891, 2009.

makeBukinN2Function *Bukin function N. 2*

Description

Multimodal, non-scalable, continuous optimization test function given by:

$$f(\mathbf{x}) = 100(\mathbf{x}_2 - 0.01 * \mathbf{x}_1^2 + 1) + 0.01(\mathbf{x}_1 + 10)^2$$

subject to $\mathbf{x}_1 \in [-15, -5]$ and $\mathbf{x}_2 \in [-3, 3]$.

Usage

makeBukinN2Function()

Value

[smoof_single_objective_function]

References

Z. K. Silagadze, Finding Two-Dimensional Peaks, Physics of Particles and Nuclei Letters, vol. 4, no. 1, pp. 73-80, 2007.

See Also

[makeBukinN4Function](#), [makeBukinN6Function](#)

makeBukinN4Function	<i>Bukin function N. 4</i>
---------------------	----------------------------

Description

Second continuous Bukin function test function. The formula is given by

$$f(\mathbf{x}) = 100\mathbf{x}_2^2 + 0.01 * ||\mathbf{x}_1 + 10||$$

and the box constraints $\mathbf{x}_1 \in [-15, 5], \mathbf{x}_2 \in [-3, 3]$.

Usage

```
makeBukinN4Function()
```

Value

```
[smoof_single_objective_function]
```

References

Z. K. Silagadze, Finding Two-Dimensional Peaks, Physics of Particles and Nuclei Letters, vol. 4, no. 1, pp. 73-80, 2007.

See Also

[makeBukinN2Function](#), [makeBukinN6Function](#)

makeBukinN6Function	<i>Bukin function N. 6</i>
---------------------	----------------------------

Description

Beside Bukin N. 2 and N. 4 this is the last “Bukin family” function. It is given by the formula

$$f(\mathbf{x}) = 100\sqrt{||\mathbf{x}_2 - 0.01\mathbf{x}_1^2||} + 0.01||\mathbf{x}_1 + 10||$$

and the box constraints $\mathbf{x}_1 \in [-15, 5], \mathbf{x}_2 \in [-3, 3]$.

Usage

```
makeBukinN6Function()
```

Value

```
[smoof_single_objective_function]
```

References

Z. K. Silagadze, Finding Two-Dimesnional Peaks, Physics of Particles and Nuclei Letters, vol. 4, no. 1, pp. 73-80, 2007.

See Also

[makeBukinN2Function](#), [makeBukinN4Function](#)

makeCarromTableFunction

Carrom Table Function

Description

This function is defined as follows:

$$f(\mathbf{x}) = -\frac{1}{30} \left((\cos(\mathbf{x}_1) \exp(|1 - ((\mathbf{x}_1^2 + \mathbf{x}_2^2)^{0.5}/\pi)^2|)) \right).$$

The box-constraints are given by $\mathbf{x}_i \in [-10, 10], i = 1, 2$.

Usage

makeCarromTableFunction()

Value

[smoof_single_objective_function]

References

S. K. Mishra, Global Optimization By Differential Evolution and Particle Swarm Methods: Evaluation On Some Benchmark Functions, Munich Research Papers in Economics.

makeChichinadzeFunction

Chichinadze Function

Description

Continuous single-objective test function f with

$$f(\mathbf{x}) = \mathbf{x}_1^2 - 12\mathbf{x}_1 + 11 + 10 \cos(0.5\pi\mathbf{x}_1) + 8 \sin(2.5\pi\mathbf{x}_1) - (0.25)^{0.5} \exp(-0.5(\mathbf{x}_2 - 0.5)^2)$$

with $-30 \leq \mathbf{x}_i \leq 30, i = 1, 2$.

Usage

```
makeChichinadzeFunction()
```

Value

```
[smoof_single_objective_function]
```

```
makeChungReynoldsFunction
```

Chung Reynolds Function

Description

The definition is given by

$$f(\mathbf{x}) = \left(\sum_{i=1}^n x_i^2 \right)^2$$

with box-constraints $\mathbf{x}_i \in [-100, 100], i = 1, \dots, n$.

Usage

```
makeChungReynoldsFunction(dimensions)
```

Arguments

dimensions	[integer(1)]
	Size of corresponding parameter space.

Value

```
[smoof_single_objective_function]
```

References

C. J. Chung, R. G. Reynolds, CAEP: An Evolution-Based Tool for Real-Valued Function Optimization Using Cultural Algorithms, International Journal on Artificial Intelligence Tool, vol. 7, no. 3, pp. 239-291, 1998.

Value

[smoof_single_objective_function]

References

M. M. Ali, C. Khompatraporn, Z. B. Zabinsky, A Numerical Evaluation of Several Stochastic Algorithms on Selected Continuous Global Optimization Test Problems, Journal of Global Optimization, vol. 31, pp. 635-672, 2005.

makeCrossInTrayFunction

Cross-In-Tray Function

Description

Non-scalable, two-dimensional test function for numerical optimization with

$$f(\mathbf{x}) = -0.0001 \left(|\sin(\mathbf{x}_1 \mathbf{x}_2 \exp(|100 - [(\mathbf{x}_1^2 + \mathbf{x}_2^2)]^{0.5}/\pi|))| + 1 \right)^{0.1}$$

subject to $\mathbf{x}_i \in [-15, 15]$ for $i = 1, 2$.

Usage

makeCrossInTrayFunction()

Value

[smoof_single_objective_function]

References

S. K. Mishra, Global Optimization By Differential Evolution and Particle Swarm Methods: Evaluation On Some Benchmark Functions, Munich Research Papers in Economics.

makeCubeFunction

Cube Function

Description

The Cube Function is defined as follows:

$$f(\mathbf{x}) = 100(\mathbf{x}_2 - \mathbf{x}_1^3)^2 + (1 - \mathbf{x}_1)^2.$$

The box-constraints are given by $\mathbf{x}_i \in [-10, 10]$, $i = 1, 2$.

Usage

```
makeCubeFunction()
```

Value

```
[smoof_single_objective_function]
```

References

A. Lavi, T. P. Vogel (eds), Recent Advances in Optimization Techniques, John Wiley & Sons, 1966.

```
makeDeckkersAartsFunction
```

Deckkers-Aarts Function

Description

This continuous single-objective test function is defined by the formula

$$f(\mathbf{x}) = 10^5 \mathbf{x}_1^2 + \mathbf{x}_2^2 - (\mathbf{x}_1^2 + \mathbf{x}_2^2)^2 + 10^{-5}(\mathbf{x}_1^2 + \mathbf{x}_2^2)^4$$

with the bounding box $-20 \leq \mathbf{x}_i \leq 20$ for $i = 1, 2$.

Usage

```
makeDeckkersAartsFunction()
```

Value

```
[smoof_single_objective_function]
```

References

M. M. Ali, C. Khompatraporn, Z. B. Zabinsky, A Numerical Evaluation of Several Stochastic Algorithms on Selected Continuous Global Optimization Test Problems, Journal of Global Optimization, vol. 31, pp. 635-672, 2005.

makeDeflectedCorrugatedSpringFunction
Deflected Corrugated Spring function

Description

Scalable single-objective test function based on the formula

$$f(\mathbf{x}) = 0.1 \sum_{i=1}^n (x_i - \alpha)^2 - \cos \left(K \sqrt{\sum_{i=1}^n (x_i - \alpha)^2} \right)$$

with $\mathbf{x}_i \in [0, 2\alpha], i = 1, \dots, n$ and $\alpha = K = 5$ by default.

Usage

```
makeDeflectedCorrugatedSpringFunction(dimensions, K = 5, alpha = 5)
```

Arguments

dimensions	[integer(1)] Size of corresponding parameter space.
K	[numeric(1)] Parameter. Default is 5.
alpha	[numeric(1)] Parameter. Default is 5.

Value

[smoof_single_objective_function]

References

See <https://al-roomi.org/benchmarks/unconstrained/n-dimensions/238-deflected-corrugated-spring-func>

makeDentFunction *Dent Function*

Description

Builds and returns the bi-objective Dent test problem, which is defined as follows:

$$f(\mathbf{x}) = (f_1(\mathbf{x}_1), f_2(\mathbf{x}))$$

with

$$f_1(\mathbf{x}_1) = 0.5 \left(\sqrt{1 + (x_1 + x_2)^2} + \sqrt{1 + (x_1 - x_2)^2} + x_1 - x_2 \right) + d$$

and

$$f_2(\mathbf{x}_1) = 0.5 \left(\sqrt{1 + (x_1 + x_2)^2} + \sqrt{1 + (x_1 - x_2)^2} - x_1 + x_2 \right) + d$$

where $d = \lambda * \exp(-(x_1 - x_2)^2)$ and $\mathbf{x}_i \in [-1.5, 1.5], i = 1, 2$.

Usage

```
makeDentFunction()
```

Value

```
[smoof_multi_objective_function]
```

```
makeDixonPriceFunction
```

Dixon-Price Function

Description

Dixon and Price defined the function

$$f(\mathbf{x}) = (\mathbf{x}_1 - 1)^2 + \sum_{i=1}^n i(2\mathbf{x}_i^2 - \mathbf{x}_{i-1})$$

subject to $\mathbf{x}_i \in [-10, 10]$ for $i = 1, \dots, n$.

Usage

```
makeDixonPriceFunction(dimensions)
```

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

```
[smoof_single_objective_function]
```

References

L. C. W. Dixon, R. C. Price, The Truncated Newton Method for Sparse Unconstrained Optimisation Using Automatic Differentiation, Journal of Optimization Theory and Applications, vol. 60, no. 2, pp. 261-275, 1989.

makeDoubleSumFunction *Double-Sum Function*

Description

Also known as the rotated hyper-ellipsoid function. The formula is given by

$$f(\mathbf{x}) = \sum_{i=1}^n \left(\sum_{j=1}^i \mathbf{x}_j \right)^2$$

with $\mathbf{x}_i \in [-65.536, 65.536], i = 1, \dots, n$.

Usage

```
makeDoubleSumFunction(dimensions)
```

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

```
[smoof_single_objective_function]
```

References

H.-P. Schwefel. Evolution and Optimum Seeking. John Wiley & Sons, New York, 1995.

makeDTLZ1Function *DTLZ1 Function (family)*

Description

Builds and returns the multi-objective DTLZ1 test problem.

The DTLZ1 test problem is defined as follows:

Minimize $f_1(\mathbf{x}) = \frac{1}{2}x_1x_2 \cdots x_{M-1}(1 + g(\mathbf{x}_M))$,

Minimize $f_2(\mathbf{x}) = \frac{1}{2}x_1x_2 \cdots (1 - x_{M-1})(1 + g(\mathbf{x}_M))$,

$\vdots$

Minimize $f_{M-1}(\mathbf{x}) = \frac{1}{2}x_1(1 - x_2)(1 + g(\mathbf{x}_M))$,

Minimize $f_M(\mathbf{x}) = \frac{1}{2}(1 - x_1)(1 + g(\mathbf{x}_M))$,

with $0 \leq x_i \leq 1$, for $i = 1, 2, \dots, n$,

where $g(\mathbf{x}_M) = 100 \left[|\mathbf{x}_M| + \sum_{x_i \in \mathbf{x}_M} (x_i - 0.5)^2 - \cos(20\pi(x_i - 0.5)) \right]$

Usage

```
makeDTLZ1Function(dimensions, n.objectives)
```

Arguments

dimensions [integer(1)]
 Number of decision variables.

n.objectives [integer(1)]
 Number of objectives.

Value

```
[smoof_multi_objective_function]
```

References

K. Deb and L. Thiele and M. Laumanns and E. Zitzler. Scalable Multi-Objective Optimization Test Problems. Computer Engineering and Networks Laboratory (TIK), Swiss Federal Institute of Technology (ETH) Zurich, 112, 2001

makeDTLZ2Function	<i>DTLZ2 Function (family)</i>
-------------------	--------------------------------

Description

Builds and returns the multi-objective DTLZ2 test problem.

The DTLZ2 test problem is defined as follows:

Minimize $f_1(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1\pi/2) \cos(x_2\pi/2) \cdots \cos(x_{M-2}\pi/2) \cos(x_{M-1}\pi/2)$,

Minimize $f_2(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1\pi/2) \cos(x_2\pi/2) \cdots \cos(x_{M-2}\pi/2) \sin(x_{M-1}\pi/2)$,

Minimize $f_3(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1\pi/2) \cos(x_2\pi/2) \cdots \sin(x_{M-2}\pi/2)$,

$\vdots$

Minimize $f_{M-1}(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1\pi/2) \sin(x_2\pi/2)$,

Minimize $f_M(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \sin(x_1\pi/2)$,

with $0 \leq x_i \leq 1$, for $i = 1, 2, \dots, n$,

where $g(\mathbf{x}_M) = \sum_{x_i \in \mathbf{x}_M} (x_i - 0.5)^2$

Usage

```
makeDTLZ2Function(dimensions, n.objectives)
```

Arguments

dimensions [integer(1)]
 Number of decision variables.

n.objectives [integer(1)]
 Number of objectives.

Value

[smoof_multi_objective_function]

Note

Note that in case of a bi-objective scenario (n.objectives = 2L) DTLZ2 and DTLZ5 are identical.

References

K. Deb and L. Thiele and M. Laumanns and E. Zitzler. Scalable Multi-Objective Optimization Test Problems. Computer Engineering and Networks Laboratory (TIK), Swiss Federal Institute of Technology (ETH) Zurich, 112, 2001

makeDTLZ3Function	<i>DTLZ3 Function (family)</i>
-------------------	--------------------------------

Description

Builds and returns the multi-objective DTLZ3 test problem. The formula is very similar to the formula of DTLZ2, but it uses the g function of DTLZ1, which introduces a lot of local Pareto-optimal fronts. Thus, this problems is well suited to check the ability of an optimizer to converge to the global Pareto-optimal front.

The DTLZ3 test problem is defined as follows:

$$\text{Minimize } f_1(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1\pi/2) \cos(x_2\pi/2) \cdots \cos(x_{M-2}\pi/2) \cos(x_{M-1}\pi/2),$$

$$\text{Minimize } f_2(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1\pi/2) \cos(x_2\pi/2) \cdots \cos(x_{M-2}\pi/2) \sin(x_{M-1}\pi/2),$$

$$\text{Minimize } f_3(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1\pi/2) \cos(x_2\pi/2) \cdots \sin(x_{M-2}\pi/2),$$

$\vdots$

$$\text{Minimize } f_{M-1}(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1\pi/2) \sin(x_2\pi/2),$$

$$\text{Minimize } f_M(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \sin(x_1\pi/2),$$

with $0 \leq x_i \leq 1$, for $i = 1, 2, \dots, n$,

$$\text{where } g(\mathbf{x}_M) = 100 \left[|\mathbf{x}_M| + \sum_{x_i \in \mathbf{x}_M} (x_i - 0.5)^2 - \cos(20\pi(x_i - 0.5)) \right]$$

Usage

makeDTLZ3Function(dimensions, n.objectives)

Arguments

dimensions	[integer(1)] Number of decision variables.
n.objectives	[integer(1)] Number of objectives.

Value

[smoof_multi_objective_function]

References

K. Deb and L. Thiele and M. Laumanns and E. Zitzler. Scalable Multi-Objective Optimization Test Problems. Computer Engineering and Networks Laboratory (TIK), Swiss Federal Institute of Technology (ETH) Zurich, 112, 2001

makeDTLZ4Function	<i>DTLZ4 Function (family)</i>
-------------------	--------------------------------

Description

Builds and returns the multi-objective DTLZ4 test problem. It is a slight modification of the DTLZ2 problems by introducing the parameter α . The parameter is used to map $\mathbf{x}_i \rightarrow \mathbf{x}_i^\alpha$.

The DTLZ4 test problem is defined as follows:

$$\text{Minimize } f_1(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1^\alpha \pi/2) \cos(x_2^\alpha \pi/2) \cdots \cos(x_{M-2}^\alpha \pi/2) \cos(x_{M-1}^\alpha \pi/2),$$

$$\text{Minimize } f_2(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1^\alpha \pi/2) \cos(x_2^\alpha \pi/2) \cdots \cos(x_{M-2}^\alpha \pi/2) \sin(x_{M-1}^\alpha \pi/2),$$

$$\text{Minimize } f_3(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1^\alpha \pi/2) \cos(x_2^\alpha \pi/2) \cdots \sin(x_{M-2}^\alpha \pi/2),$$

$$\vdots$$

$$\text{Minimize } f_{M-1}(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1^\alpha \pi/2) \sin(x_2^\alpha \pi/2),$$

$$\text{Minimize } f_M(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \sin(x_1^\alpha \pi/2),$$

with $0 \leq x_i \leq 1$, for $i = 1, 2, \dots, n$,

$$\text{where } g(\mathbf{x}_M) = \sum_{x_i \in \mathbf{x}_M} (x_i - 0.5)^2$$

Usage

```
makeDTLZ4Function(dimensions, n.objectives, alpha = 100)
```

Arguments

dimensions	[integer(1)] Number of decision variables.
n.objectives	[integer(1)] Number of objectives.
alpha	[numeric(1)] Optional parameter. Default is 100, which is recommended by Deb et al.

Value

[smoof_multi_objective_function]

References

K. Deb and L. Thiele and M. Laumanns and E. Zitzler. Scalable Multi-Objective Optimization Test Problems. Computer Engineering and Networks Laboratory (TIK), Swiss Federal Institute of Technology (ETH) Zurich, 112, 2001

makeDTLZ5Function	<i>DTLZ5 Function (family)</i>
-------------------	--------------------------------

Description

Builds and returns the multi-objective DTLZ5 test problem. This problem can be characterized by a disconnected Pareto-optimal front in the search space. This introduces a new challenge to evolutionary multi-objective optimizers, i.e., to maintain different subpopulations within the search space to cover the entire Pareto-optimal front.

The DTLZ5 test problem is defined as follows:

$$\text{Minimize } f_1(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(\theta_1 \pi/2) \cos(\theta_2 \pi/2) \cdots \cos(\theta_{M-2} \pi/2) \cos(\theta_{M-1} \pi/2),$$

$$\text{Minimize } f_2(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(\theta_1 \pi/2) \cos(\theta_2 \pi/2) \cdots \cos(\theta_{M-2} \pi/2) \sin(\theta_{M-1} \pi/2),$$

$$\text{Minimize } f_3(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(\theta_1 \pi/2) \cos(\theta_2 \pi/2) \cdots \sin(\theta_{M-2} \pi/2),$$

$$\vdots$$

$$\text{Minimize } f_{M-1}(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(\theta_1 \pi/2) \sin(\theta_2 \pi/2),$$

$$\text{Minimize } f_M((1 + g(\mathbf{x}_M)) \sin(\theta_1 \pi/2),$$

with $0 \leq x_i \leq 1$, for $i = 1, 2, \dots, n$,

where $\theta_i = \frac{\pi}{4(1+g(\mathbf{x}_M))} (1 + 2g(\mathbf{x}_M)x_i)$, for $i = 2, 3, \dots, (M-1)$

$$\text{and } g(\mathbf{x}_M) = \sum_{x_i \in \mathbf{x}_M} (x_i - 0.5)^2$$

Usage

makeDTLZ5Function(dimensions, n.objectives)

Arguments

dimensions	[integer(1)] Number of decision variables.
n.objectives	[integer(1)] Number of objectives.

Value

[smoof_multi_objective_function]

Note

This problem definition does not exist in the succeeding work of Deb et al. (K. Deb and L. Thiele and M. Laumanns and E. Zitzler (2002). Scalable multi-objective optimization test problems, Proceedings of the IEEE Congress on Evolutionary Computation, pp. 825-830).

Also, note that in case of a bi-objective scenario (n.objectives = 2L) DTLZ2 and DTLZ5 are identical.

References

K. Deb and L. Thiele and M. Laumanns and E. Zitzler. Scalable Multi-Objective Optimization Test Problems. Computer Engineering and Networks Laboratory (TIK), Swiss Federal Institute of Technology (ETH) Zurich, 112, 2001

makeDTLZ6Function	<i>DTLZ6 Function (family)</i>
-------------------	--------------------------------

Description

Builds and returns the multi-objective DTLZ6 test problem. This problem can be characterized by a disconnected Pareto-optimal front in the search space. This introduces a new challenge to evolutionary multi-objective optimizers, i.e., to maintain different subpopulations within the search space to cover the entire Pareto-optimal front.

The DTLZ6 test problem is defined as follows:

$$\text{Minimize } f_1(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(\theta_1 \pi / 2) \cos(\theta_2 \pi / 2) \cdots \cos(\theta_{M-2} \pi / 2) \cos(\theta_{M-1} \pi / 2),$$

$$\text{Minimize } f_2(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(\theta_1 \pi / 2) \cos(\theta_2 \pi / 2) \cdots \cos(\theta_{M-2} \pi / 2) \sin(\theta_{M-1} \pi / 2),$$

$$\text{Minimize } f_3(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(\theta_1 \pi / 2) \cos(\theta_2 \pi / 2) \cdots \sin(\theta_{M-2} \pi / 2),$$

$$\vdots$$

$$\text{Minimize } f_{M-1}(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(\theta_1 \pi / 2) \sin(\theta_2 \pi / 2),$$

$$\text{Minimize } f_M((1 + g(\mathbf{x}_M)) \sin(\theta_1 \pi / 2),$$

with $0 \leq x_i \leq 1$, for $i = 1, 2, \dots, n$,

where $\theta_i = \frac{\pi}{4(1+g(\mathbf{x}_M))} (1 + 2g(\mathbf{x}_M)x_i)$, for $i = 2, 3, \dots, (M-1)$

$$\text{and } g(\mathbf{x}_M) = \sum_{x_i \in \mathbf{x}_M} x_i^{0.1}$$

Usage

```
makeDTLZ6Function(dimensions, n.objectives)
```

Arguments

dimensions [integer(1)]
 Number of decision variables.

n.objectives [integer(1)]
 Number of objectives.

Value

```
[smoof_multi_objective_function]
```

Note

Attention: Within the succeeding work of Deb et al. (K. Deb and L. Thiele and M. Laumanns and E. Zitzler (2002). Scalable multi-objective optimization test problems, Proceedings of the IEEE Congress on Evolutionary Computation, pp. 825-830) this problem was called DTLZ5.

References

K. Deb and L. Thiele and M. Laumanns and E. Zitzler. Scalable Multi-Objective Optimization Test Problems. Computer Engineering and Networks Laboratory (TIK), Swiss Federal Institute of Technology (ETH) Zurich, 112, 2001

makeDTLZ7Function	<i>DTLZ7 Function (family)</i>
-------------------	--------------------------------

Description

Builds and returns the multi-objective DTLZ7 test problem. This problem can be characterized by a disconnected Pareto-optimal front in the search space. This introduces a new challenge to evolutionary multi-objective optimizers, i.e., to maintain different subpopulations within the search space to cover the entire Pareto-optimal front.

The DTLZ7 test problem is defined as follows:

Minimize $f_1(\mathbf{x}) = x_1$,

Minimize $f_2(\mathbf{x}) = x_2$,

$\vdots$

Minimize $f_{M-1}(\mathbf{x}) = x_{M-1}$,

Minimize $f_M(\mathbf{x}) = (1 + g(\mathbf{x}_M))h(f_1, f_2, \dots, f_{M-1}, g)$,

with $0 \leq x_i \leq 1$, for $i = 1, 2, \dots, n$,

where $g(\mathbf{x}_M) = 1 + \frac{9}{|\mathbf{x}_M|} \sum_{x_i \in \mathbf{x}_M} x_i$

and $h(f_1, f_2, \dots, f_{M-1}, g) = M - \sum_{i=1}^{M-1} \left[\frac{f_i}{1+g} (1 + \sin(3\pi f_i)) \right]$

Usage

```
makeDTLZ7Function(dimensions, n.objectives)
```

Arguments

dimensions [integer(1)]
 Number of decision variables.

n.objectives [integer(1)]
 Number of objectives.

Value

```
[smoof_multi_objective_function]
```

Note

Attention: Within the succeeding work of Deb et al. (K. Deb and L. Thiele and M. Laumanns and E. Zitzler (2002). Scalable multi-objective optimization test problems, Proceedings of the IEEE Congress on Evolutionary Computation, pp. 825-830) this problem was called DTLZ6.

References

K. Deb and L. Thiele and M. Laumanns and E. Zitzler. Scalable Multi-Objective Optimization Test Problems. Computer Engineering and Networks Laboratory (TIK), Swiss Federal Institute of Technology (ETH) Zurich, 112, 2001

makeEasomFunction	<i>Easom Function</i>
-------------------	-----------------------

Description

Unimodal function with its global optimum in the center of the search space. The attraction area of the global optimum is very small in relation to the search space:

$$f(\mathbf{x}) = -\cos(\mathbf{x}_1) \cos(\mathbf{x}_2) \exp\left(-\left((\mathbf{x}_1 - \pi)^2 + (\mathbf{x}_2 - \pi)^2\right)\right)$$

with $\mathbf{x}_i \in [-100, 100], i = 1, 2$.

Usage

```
makeEasomFunction()
```

Value

```
[smoof_single_objective_function]
```

References

Easom, E. E.: A survey of global optimization techniques. M. Eng. thesis, University of Louisville, Louisville, KY, 1990.

makeED1Function	<i>ED1 Function</i>
-----------------	---------------------

Description

Builds and returns the multi-objective ED1 test problem.

The ED1 test problem is defined as follows:

Minimize $f_j(\mathbf{x}) = \frac{1}{r(\mathbf{x})+1} \cdot \tilde{p}(\Theta(\mathbf{X}))$, for $j = 1, \dots, m$,

with $\mathbf{x} = (x_1, \dots, x_n)^T$, where $0 \leq x_i \leq 1$, and $\Theta = (\theta_1, \dots, \theta_{m-1})$, where $0 \leq \theta_j \leq \frac{\pi}{2}$, for $i = 1, \dots, n$, and $j = 1, \dots, m-1$.

Moreover $r(\mathbf{X}) = \sqrt{x_m^2 + \dots, x_n^2}$,

$\tilde{p}_1(\Theta) = \cos(\theta_1)^{2/\gamma}$,

$\tilde{p}_j(\Theta) = (\sin(\theta_1) \cdot \dots \cdot \sin(\theta_{j-1}) \cdot \cos(\theta_j))^{2/\gamma}$, for $2 \leq j \leq m-1$,

and $\tilde{p}_m(\Theta) = (\sin(\theta_1) \cdot \dots \cdot \sin(\theta_{m-1}))^{2/\gamma}$.

Usage

```
makeED1Function(dimensions, n.objectives, gamma = 2, theta)
```

Arguments

dimensions	[integer(1)] Number of decision variables.
n.objectives	[integer(1)] Number of objectives.
gamma	[numeric(1)] Optional parameter. Default is 2, which is recommended by Emmerich and Deutz.
theta	[numeric(dimensions)] Parameter vector, whose components have to be between 0 and 0.5*pi. The default is theta = (pi/2) * x (with x being the point from the decision space) as recommended by Emmerich and Deutz.

Value

[smoof_multi_objective_function]

References

M. T. M. Emmerich and A. H. Deutz. Test Problems based on Lamé Superspheres. Proceedings of the International Conference on Evolutionary Multi-Criterion Optimization (EMO 2007), pp. 922-936, Springer, 2007.

makeED2Function	<i>ED2 Function</i>
-----------------	---------------------

Description

Builds and returns the multi-objective ED2 test problem.

The ED2 test problem is defined as follows:

Minimize $f_j(\mathbf{x}) = \frac{1}{F_{natmin}(\mathbf{x})+1} \cdot \tilde{p}(\Theta(\mathbf{X}))$, for $j = 1, \dots, m$,

with $\mathbf{x} = (x_1, \dots, x_n)^T$, where $0 \leq x_i \leq 1$, and $\Theta = (\theta_1, \dots, \theta_{m-1})$, where $0 \leq \theta_j \leq \frac{\pi}{2}$, for $i = 1, \dots, n$, and $j = 1, \dots, m-1$.

Moreover $F_{natmin}(\mathbf{x}) = b + (r(\mathbf{x}) - a) + 0.5 + 0.5 \cdot (2\pi \cdot (r(\mathbf{x}) - a) + \pi)$

with $a \approx 0.051373$, $b \approx 0.0253235$, and $r(\mathbf{X}) = \sqrt{x_m^2 + \dots, x_n^2}$, as well as

$\tilde{p}_1(\Theta) = \cos(\theta_1)^{2/\gamma}$,

$\tilde{p}_j(\Theta) = (\sin(\theta_1) \cdot \dots \cdot \sin(\theta_{j-1}) \cdot \cos(\theta_j))^{2/\gamma}$, for $2 \leq j \leq m-1$,

and $\tilde{p}_m(\Theta) = (\sin(\theta_1) \cdot \dots \cdot \sin(\theta_{m-1}))^{2/\gamma}$.

Usage

```
makeED2Function(dimensions, n.objectives, gamma = 2, theta)
```

Arguments

dimensions	[integer(1)] Number of decision variables.
n.objectives	[integer(1)] Number of objectives.
gamma	[numeric(1)] Optional parameter. Default is 2, which is recommended by Emmerich and Deutz.
theta	[numeric(dimensions)] Parameter vector, whose components have to be between 0 and 0.5*pi. The default is theta = (pi/2) * x (with x being the point from the decision space) as recommended by Emmerich and Deutz.

Value

[smoof_multi_objective_function]

References

M. T. M. Emmerich and A. H. Deutz. Test Problems based on Lamé Superspheres. Proceedings of the International Conference on Evolutionary Multi-Criterion Optimization (EMO 2007), pp. 922-936, Springer, 2007.

makeEggCrateFunction *Egg Crate Function*

Description

This single-objective function follows the definition

$$f(\mathbf{x}) = \mathbf{x}_1^2 + \mathbf{x}_2^2 + 25(\sin^2(\mathbf{x}_1) + \sin^2(\mathbf{x}_2))$$

with $\mathbf{x}_i \in [-5, 5]$ for $i = 1, 2$.

Usage

makeEggCrateFunction()

Value

[smoof_single_objective_function]

makeEggholderFunction *Egg Holder function*

Description

The Egg Holder function is a difficult to optimize function based on the definition

$$f(\mathbf{x}) = \sum_{i=1}^{n-1} \left[-(\mathbf{x}_{i+1} + 47) \sin \sqrt{|\mathbf{x}_{i+1} + 0.5\mathbf{x}_i + 47|} - \mathbf{x}_i \sin(\sqrt{|\mathbf{x}_i - (\mathbf{x}_{i+1} - 47)|}) \right]$$

subject to $-512 \leq \mathbf{x}_i \leq 512$ for $i = 1, \dots, n$.

Usage

makeEggholderFunction()

Value

[smoof_single_objective_function]

makeElAttarVidyasagarDuttaFunction

El-Attar-Vidyasagar-Dutta Function

Description

This function is based on the formula

$$f(\mathbf{x}) = (\mathbf{x}_1^2 + \mathbf{x}_2 - 10)^2 + (\mathbf{x}_1 + \mathbf{x}_2^2 - 7)^2 + (\mathbf{x}_1^2 + \mathbf{x}_2^3 - 1)^2$$

subject to $\mathbf{x}_i \in [-500, 500], i = 1, 2$.

Usage

makeElAttarVidyasagarDuttaFunction()

Value

[smoof_single_objective_function]

References

R. A. El-Attar, M. Vidyasagar, S. R. K. Dutta, An Algorithm for II-norm Minimization With Application to Nonlinear II-approximation, SIAM Journal on Numerical Analysis, vol. 16, no. 1, pp. 70-86, 1979.

makeEngvallFunction *Complex function.*

Description

Two-dimensional test function based on the formula

$$f(\mathbf{x}) = (x_1^4 + x_2^4 + 2x_1^2x_2^2 - 4x_1 + 3$$

with $\mathbf{x}_1, \mathbf{x}_2 \in [-2000, 2000]$.

Usage

makeEngvallFunction()

Value

[smoof_single_objective_function]

References

See <https://al-roomi.org/benchmarks/unconstrained/2-dimensions/116-engvall-s-function>.

makeExponentialFunction

Exponential Function

Description

This scalable test function is based on the definition

$$f(\mathbf{x}) = -\exp\left(-0.5 \sum_{i=1}^n \mathbf{x}_i^2\right)$$

with the box-constraints $\mathbf{x}_i \in [-1, 1], i = 1, \dots, n$.

Usage

```
makeExponentialFunction(dimensions)
```

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

[smoof_single_objective_function]

References

S. Rahnamyan, H. R. Tizhoosh, N. M. M. Salama, Opposition-Based Differential Evolution (ODE) with Variable Jumping Rate, IEEE Symposium Foundations Com- putation Intelligence, Honolulu, HI, pp. 81-88, 2007.

makeFreudensteinRothFunction

Freudenstein Roth Function

Description

This test function is based on the formula

$$f(\mathbf{x}) = (\mathbf{x}_1 - 13 + ((5 - \mathbf{x}_2)\mathbf{x}_2 - 2)\mathbf{x}_2)^2 + (\mathbf{x}_1 - 29 + ((\mathbf{x}_2 + 1)\mathbf{x}_2 - 14)\mathbf{x}_2)^2$$

subject to $\mathbf{x}_i \in [-10, 10], i = 1, 2$.

Usage

```
makeFreudensteinRothFunction()
```

Value

[smoof_single_objective_function]

References

S. S. Rao, Engineering Optimization: Theory and Practice, John Wiley & Sons, 2009.

makeFunctionsByName	<i>Generate smoof function by passing a character vector of generator names.</i>
---------------------	--

Description

This function is especially useful in combination with [filterFunctionsByTags](#) to generate a test set of functions with certain properties, e.g., multimodality.

Usage

```
makeFunctionsByName(fun.names, ...)
```

Arguments

fun.names	[character] Non empty character vector of generator function names.
...	[any] Further arguments passed to generator.

Value

[smoof_function]

See Also

[filterFunctionsByTags](#)

Examples

```
# generate a testset of multimodal 2D functions
## Not run:
test.set = makeFunctionsByName(filterFunctionsByTags("multimodal"), dimensions = 2L, m = 5L)

## End(Not run)
```

makeGeneralizedDropWaveFunction
Generalized Drop-Wave Function

Description

Multimodal single-objective function following the formula:

$$\mathbf{x} = -\frac{1 + \cos(\sqrt{\sum_{i=1}^n \mathbf{x}_i^2})}{2 + 0.5 \sum_{i=1}^n \mathbf{x}_i^2}$$

with $\mathbf{x}_i \in [-5.12, 5.12], i = 1, \dots, n$.

Usage

makeGeneralizedDropWaveFunction(dimensions = 2L)

Arguments

dimensions [integer(1)]
 Size of corresponding parameter space.

Value

[smoof_single_objective_function]

makeGiuntaFunction *Giunta Function*

Description

Multimodal test function based on the definition

$$f(\mathbf{x}) = 0.6 + \sum_{i=1}^n \left[\sin\left(\frac{16}{15}\mathbf{x}_i - 1\right) + \sin^2\left(\frac{16}{15}\mathbf{x}_i - 1\right) + \frac{1}{50} \sin\left(4\left(\frac{16}{15}\mathbf{x}_i - 1\right)\right) \right]$$

with box-constraints $\mathbf{x}_i \in [-1, 1]$ for $i = 1, \dots, n$.

Usage

makeGiuntaFunction()

Value

[smoof_single_objective_function]

References

S. K. Mishra, Global Optimization By Differential Evolution and Particle Swarm Methods: Evaluation On Some Benchmark Functions, Munich Research Papers in Economics.

makeGoldsteinPriceFunction	<i>Goldstein-Price Function</i>
----------------------------	---------------------------------

Description

Two-dimensional test function for global optimization. The implementation follows the formula:

$$f(\mathbf{x}) = (1 + (\mathbf{x}_1 + \mathbf{x}_2 + 1))^2 \cdot (19 - 14\mathbf{x}_1 + 3\mathbf{x}_1^2 - 14\mathbf{x}_2 + 6\mathbf{x}_1\mathbf{x}_2 + 3\mathbf{x}_2^2) \cdot (30 + (2\mathbf{x}_1 - 3\mathbf{x}_2)^2 \cdot (18 - 32\mathbf{x}_1 + 12\mathbf{x}_2))$$

with $\mathbf{x}_i \in [-2, 2], i = 1, 2$.

Usage

```
makeGoldsteinPriceFunction()
```

Value

```
[smoof_single_objective_function]
```

References

Goldstein, A. A. and Price, I. F.: On descent from local minima. Math. Comput., Vol. 25, No. 115, 1971.

makeGOMOPFunction	<i>GOMOP function generator.</i>
-------------------	----------------------------------

Description

Construct a multi-objective function by putting together multiple single-objective smoof functions.

Usage

```
makeGOMOPFunction(dimensions = 2L, funs = list())
```

Arguments

- | | |
|------------|--|
| dimensions | [integer(1)]
Size of corresponding parameter space. |
| funs | [list]
List of single-objective smoof functions. |

Details

The decision space of the resulting function is restricted to $[0, 1]^d$. Each parameter x is stretched for each objective function. I.e., if $f_1, \dots, f_n$ are the single objective smooth functions with box constraints $[l_i, u_i], i = 1, \dots, n$, then

$$f(x) = (f_1(l_1 + x * (u_1 - l_1)), \dots, f_n(l_n + x * (u_n - l_n)))$$

for $x \in [0, 1]^d$ where the additions and multiplication are performed component-wise.

Value

[smoof_multi_objective_function]

makeGriewankFunction	<i>Griewank Function</i>
----------------------	--------------------------

Description

Highly multimodal function with a lot of regularly distributed local minima. The corresponding formula is:

$$f(\mathbf{x}) = \sum_{i=1}^n \frac{\mathbf{x}_i^2}{4000} - \prod_{i=1}^n \cos\left(\frac{\mathbf{x}_i}{\sqrt{i}}\right) + 1$$

subject to $\mathbf{x}_i \in [-100, 100], i = 1, \dots, n$.

Usage

makeGriewankFunction(dimensions)

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

[smoof_single_objective_function]

References

A. O. Griewank, Generalized Descent for Global Optimization, Journal of Optimization Theory and Applications, vol. 34, no. 1, pp. 11-39, 1981.

makeHansenFunction	<i>Hansen Function</i>
--------------------	------------------------

Description

Test function with multiple global optima based on the definition

$$f(\mathbf{x}) = \sum_{i=1}^4 (i+1) \cos(i\mathbf{x}_1 + i - 1) \sum_{j=1}^4 (j+1) \cos((j+2)\mathbf{x}_2 + j + 1)$$

subject to $\mathbf{x}_i \in [-10, 10], i = 1, 2$.

Usage

makeHansenFunction()

Value

[smoof_single_objective_function]

References

C. Fraley, Software Performances on Nonlinear lems, Technical Report no. STAN-CS-89-1244, Computer Science, Stanford University, 1989.

makeHartmannFunction	<i>Hartmann Function</i>
----------------------	--------------------------

Description

Unimodal single-objective test function with six local minima. The implementation is based on the mathematical formulation

$$f(x) = - \sum_{i=1}^4 \alpha_i \exp \left(- \sum_{j=1}^6 A_{ij} (x_j - P_{ij})^2 \right)$$

, where

$$\alpha = (1.0, 1.2, 3.0, 3.2)^T, A = \begin{pmatrix} 10 & 3 & 17 & 3.50 & 1.7 & 8 \\ 0.05 & 10 & 17 & 0.1 & 8 & 14 \\ 3 & 3.5 & 1.7 & 10 & 17 & 8 \\ 17 & 8 & 0.05 & 10 & 0.1 & 14 \end{pmatrix}, P = 10^{-4} \cdot \begin{pmatrix} 1312 & 1696 & 5569 & 124 & 8283 \\ 2329 & 4135 & 8307 & 3736 & 1004 \\ 2348 & 1451 & 3522 & 2883 & 3047 \\ 4047 & 8828 & 8732 & 5743 & 1091 \end{pmatrix}$$

The function is restricted to six dimensions with $\mathbf{x}_i \in [0, 1], i = 1, \dots, 6$. The function is not normalized in contrast to some benchmark applications in the literature.

Usage

```
makeHartmannFunction(dimensions)
```

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

```
[smoof_single_objective_function]
```

References

Picheny, V., Wagner, T., & Ginsbourger, D. (2012). A benchmark of kriging-based infill criteria for noisy optimization.

```
makeHimmelblauFunction
```

Himmelblau Function

Description

Two-dimensional test function based on the function definition

$$f(\mathbf{x}) = (\mathbf{x}_1^2 + \mathbf{x}_2 - 11)^2 + (\mathbf{x}_1 + \mathbf{x}_2^2 - 7)^2$$

with box-constraints $\mathbf{x}_i \in [-5, 5], i = 1, 2$.

Usage

```
makeHimmelblauFunction()
```

Value

```
[smoof_single_objective_function]
```

References

D. M. Himmelblau, Applied Nonlinear Programming, McGraw-Hill, 1972.

makeHolderTableN1Function

Holder Table function N. 1

Description

This multimodal function is defined as

$$f(\mathbf{x}) = - \left| \cos(\mathbf{x}_1) \cos(\mathbf{x}_2) \exp(|1 - \sqrt{\mathbf{x}_1 + \mathbf{x}_2}/\pi|) \right|$$

with box-constraints $\mathbf{x}_i \in [-10, 10], i = 1, 2$.

Usage

```
makeHolderTableN1Function()
```

Value

```
[smoof_single_objective_function]
```

References

S. K. Mishra, Global Optimization By Differential Evolution and Particle Swarm Methods: Evaluation On Some Benchmark Functions, Munich Research Papers in Economics.

See Also

[makeHolderTableN2Function](#)

makeHolderTableN2Function

Holder Table function N. 2

Description

This multimodal function is defined as

$$f(\mathbf{x}) = - \left| \sin(\mathbf{x}_1) \cos(\mathbf{x}_2) \exp(|1 - \sqrt{\mathbf{x}_1 + \mathbf{x}_2}/\pi|) \right|$$

with box-constraints $\mathbf{x}_i \in [-10, 10], i = 1, 2$.

Usage

```
makeHolderTableN2Function()
```

Value

[smoof_single_objective_function]

References

S. K. Mishra, Global Optimization By Differential Evolution and Particle Swarm Methods: Evaluation On Some Benchmark Functions, Munich Research Papers in Economics.

See Also

[makeHolderTableN1Function](#)

makeHosakiFunction	<i>Hosaki Function</i>
--------------------	------------------------

Description

Two-dimensional test function f with

$$f(\mathbf{x}) = (1 - 8\mathbf{x}_1 + 7\mathbf{x}_1^2 - 7/3\mathbf{x}_1^3 + 1/4\mathbf{x}_1^4)\mathbf{x}_2^2 e^{-\mathbf{x}_2}$$

subject to $0 \leq \mathbf{x}_1 \leq 5$ and $0 \leq \mathbf{x}_2 \leq 6$.

Usage

```
makeHosakiFunction()
```

Value

[smoof_single_objective_function]

References

G. A. Bekey, M. T. Ung, A Comparative Evaluation of Two Global Search Algorithms, IEEE Transaction on Systems, Man and Cybernetics, vol. 4, no. 1, pp. 112- 116, 1974.

makeHyperEllipsoidFunction

Hyper-Ellipsoid function

Description

Unimodal, convex test function similar to the Sphere function (see [makeSphereFunction](#)). Calculated via the formula:

$$f(\mathbf{x}) = \sum_{i=1}^n i \cdot \mathbf{x}_i.$$

Usage

```
makeHyperEllipsoidFunction(dimensions)
```

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

[smoof_single_objective_function]

makeInvertedVincentFunction

Inverted Vincent Function

Description

Single-objective test function based on the formula

$$f(\mathbf{x}) = \frac{1}{n} \sum_{i=1}^n \sin(10 \log(\mathbf{x}_i))$$

subject to $\mathbf{x}_i \in [0.25, 10]$ for $i = 1, \dots, n$.

Usage

```
makeInvertedVincentFunction(dimensions)
```

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

[smoof_single_objective_function]

References

Xiadong Li, Andries Engelbrecht, and Michael G. Epitropakis. Benchmark functions for CEC2013 special session and competition on niching methods for multimodal function optimization. Technical report, RMIT University, Evolutionary Computation and Machine Learning Group, Australia, 2013.

makeJennrichSampsonFunction

Jennrich-Sampson function.

Description

Two-dimensional test function based on the formula

$$f(\mathbf{x}) = \sum_{i=1}^{10} [2 + 2i - (e^{ix_1} + e^{ix_2})]^2$$

with $\mathbf{x}_1, \mathbf{x}_2 \in [-1, 1]$.

Usage

makeJennrichSampsonFunction()

Value

[smoof_single_objective_function]

References

See <https://al-roomi.org/benchmarks/unconstrained/2-dimensions/134-jennrich-sampson-s-function>.

makeJudgeFunction	<i>Judge function.</i>
-------------------	------------------------

Description

Two-dimensional test function based on the formula

$$f(\mathbf{x}) = \sum_{i=1}^{20} [(x_1 + B_i x_2 + C_i x_2^2) - A_i]^2$$

with $\mathbf{x}_1, \mathbf{x}_2 \in [-10, 10]$. For details on A, B, C see the referenced website.

Usage

```
makeJudgeFunction()
```

Value

```
[smoof_single_objective_function]
```

References

See <https://al-roomi.org/benchmarks/unconstrained/2-dimensions/133-judge-s-function>.

makeKeaneFunction	<i>Keane Function</i>
-------------------	-----------------------

Description

Two-dimensional test function based on the definition

$$f(\mathbf{x}) = \frac{\sin^2(\mathbf{x}_1 - \mathbf{x}_2) \sin^2(\mathbf{x}_1 + \mathbf{x}_2)}{\sqrt{\mathbf{x}_1^2 + \mathbf{x}_2^2}}.$$

The domain of definition is bounded by the box constraints $\mathbf{x}_i \in [0, 10], i = 1, 2$.

Usage

```
makeKeaneFunction()
```

Value

```
[smoof_single_objective_function]
```

makeKearfottFunction *Kearfott function.*

Description

Two-dimensional test function based on the formula

$$f(\mathbf{x}) = (x_1^2 + x_2^2 - 2)^2 + (x_1^2 - x_2^2 - 1)^2$$

with $\mathbf{x}_1, \mathbf{x}_2 \in [-3, 4]$.

Usage

makeKearfottFunction()

Value

[smoof_single_objective_function]

References

See <https://al-roomi.org/benchmarks/unconstrained/2-dimensions/59-kearfott-s-function>.

makeKursaweFunction *Kursawe Function*

Description

Builds and returns the bi-objective Kursawe test problem.

The Kursawe test problem is defined as follows:

$$\text{Minimize } f_1(\mathbf{x}) = \sum_{i=1}^{n-1} (-10 \cdot \exp(-0.2 \cdot \sqrt{x_i^2 + x_{i+1}^2})),$$

$$\text{Minimize } f_2(\mathbf{x}) = \sum_{i=1}^n (|x_i|^{0.8} + 5 \cdot \sin^3(x_i)),$$

with $-5 \leq x_i \leq 5$, for $i = 1, 2, \dots, n$.

Usage

makeKursaweFunction(dimensions)

Arguments

dimensions [integer(1)]
 Number of decision variables.

Value

[smoof_multi_objective_function]

References

F. Kursawe. A Variant of Evolution Strategies for Vector Optimization. Proceedings of the International Conference on Parallel Problem Solving from Nature, pp. 193-197, Springer, 1990.

makeLeonFunction	<i>Leon Function</i>
------------------	----------------------

Description

The function is based on the definition

$$f(\mathbf{x}) = 100(\mathbf{x}_2 - \mathbf{x}_1^2)^2 + (1 - \mathbf{x}_1)^2$$

. Box-constraints: $\mathbf{x}_i \in [-1.2, 1.2]$ for $i = 1, 2$.

Usage

makeLeonFunction()

Value

[smoof_single_objective_function]

References

A. Lavi, T. P. Vogel (eds), Recent Advances in Optimization Techniques, John Wiley & Sons, 1966.

makeMatyasFunction	<i>Matyas Function</i>
--------------------	------------------------

Description

Two-dimensional, unimodal test function

$$f(\mathbf{x}) = 0.26(\mathbf{x}_1^2 + \mathbf{x}_2^2) - 0.48\mathbf{x}_1\mathbf{x}_2$$

subject to $\mathbf{x}_i \in [-10, 10]$, $i = 1, 2$.

Usage

makeMatyasFunction()

Value

[smoof_single_objective_function]

References

A.-R. Hedar, Global Optimization Test Problems.

makeMcCormickFunction *McCormick Function*

Description

Two-dimensional, multimodal test function. The definition is given by

$$f(\mathbf{x}) = \sin(\mathbf{x}_1 + \mathbf{x}_2) + (\mathbf{x}_1 - \mathbf{x}_2)^2 - 1.5\mathbf{x}_1 + 2.5\mathbf{x}_2 + 1$$

subject to $\mathbf{x}_1 \in [-1.5, 4]$, $\mathbf{x}_2 \in [-3, 3]$.**Usage**

makeMcCormickFunction()

Value

[smoof_single_objective_function]

References

F. A. Lootsma (ed.), Numerical Methods for Non-Linear Optimization, Academic Press, 1972.

makeMichalewiczFunction *Michalewicz Function*

DescriptionHighly multimodal single-objective test function with $n!$ local minima with the formula:

$$f(\mathbf{x}) = - \sum_{i=1}^n \sin(\mathbf{x}_i) \cdot \left(\sin \left(\frac{i \cdot \mathbf{x}_i}{\pi} \right) \right)^{2m}.$$

The recommended value $m = 10$, which is used as a default in the implementation.**Usage**

makeMichalewiczFunction(dimensions, m = 10)

Arguments

dimensions	[integer(1)] Size of corresponding parameter space.
m	[integer(1)] “Steepness” parameter.

Value

[smoof_single_objective_function]

Note

The location of the global optimum s varying based on both the dimension and m parameter and is thus not provided in the implementation.

References

Michalewicz, Z.: Genetic Algorithms + Data Structures = Evolution Programs. Berlin, Heidelberg, New York: Springer-Verlag, 1992.

makeMMF10Function	<i>MMF10 Function</i>
-------------------	-----------------------

Description

Test problem from the set of "multimodal multiobjective functions" as for instance used in the CEC2019 competition.

Usage

makeMMF10Function()

Value

[smoof_multi_objective_function]

References

Caitong Yue, Boyang Qu, Kunjie Yu, Jing Liang, and Xiaodong Li, "A novel scalable test problem suite for multimodal multiobjective optimization," in Swarm and Evolutionary Computation, Volume 48, August 2019, pp. 62–71, Elsevier.

makeMMF11Function	<i>MMF11 Function</i>
-------------------	-----------------------

Description

Test problem from the set of "multimodal multiobjective functions" as for instance used in the CEC2019 competition.

Usage

```
makeMMF11Function(np = 2L)
```

Arguments

np	[integer(1)] Number of global Pareto sets. In the CEC2019 competition, the organizers used np = 2L.
----	--

Value

[smoof_multi_objective_function]

References

Caitong Yue, Boyang Qu, Kunjie Yu, Jing Liang, and Xiaodong Li, "A novel scalable test problem suite for multimodal multiobjective optimization," in Swarm and Evolutionary Computation, Volume 48, August 2019, pp. 62–71, Elsevier.

makeMMF12Function	<i>MMF12 Function</i>
-------------------	-----------------------

Description

Test problem from the set of "multimodal multiobjective functions" as for instance used in the CEC2019 competition.

Usage

```
makeMMF12Function(np = 2L, q = 4L)
```

Arguments

np	[integer(1)] Number of global Pareto sets. In the CEC2019 competition, the organizers used np = 2L.
q	[integer(1)] Number of discontinuous pieces in each Pareto front. In the CEC2019 competition, the organizers used q = 4L.

Value

[smoof_multi_objective_function]

References

Caitong Yue, Boyang Qu, Kunjie Yu, Jing Liang, and Xiaodong Li, "A novel scalable test problem suite for multimodal multiobjective optimization," in Swarm and Evolutionary Computation, Volume 48, August 2019, pp. 62–71, Elsevier.

makeMMF13Function	<i>MMF13 Function</i>
-------------------	-----------------------

Description

Test problem from the set of "multimodal multiobjective functions" as for instance used in the CEC2019 competition.

Usage

makeMMF13Function(np = 2L)

Arguments

np	[integer(1)] Number of global Pareto sets. In the CEC2019 competition, the organizers used np = 2L.
----	--

Value

[smoof_multi_objective_function]

References

Caitong Yue, Boyang Qu, Kunjie Yu, Jing Liang, and Xiaodong Li, "A novel scalable test problem suite for multimodal multiobjective optimization," in Swarm and Evolutionary Computation, Volume 48, August 2019, pp. 62–71, Elsevier.

makeMMF14aFunction	<i>MMF14a Function</i>
--------------------	------------------------

Description

Test problem from the set of "multimodal multiobjective functions" as for instance used in the CEC2019 competition.

Usage

```
makeMMF14aFunction(dimensions, n.objectives, np = 2L)
```

Arguments

- dimensions [integer(1)]
Number of decision variables.
- n.objectives [integer(1)]
Number of objectives.
- np [integer(1)]
Number of global Pareto sets. In the CEC2019 competition, the organizers used np = 2L.

Value

[smoof_multi_objective_function]

References

Caitong Yue, Boyang Qu, Kunjie Yu, Jing Liang, and Xiaodong Li, "A novel scalable test problem suite for multimodal multiobjective optimization," in Swarm and Evolutionary Computation, Volume 48, August 2019, pp. 62–71, Elsevier.

makeMMF14Function	<i>MMF14 Function</i>
-------------------	-----------------------

Description

Test problem from the set of "multimodal multiobjective functions" as for instance used in the CEC2019 competition.

Usage

```
makeMMF14Function(dimensions, n.objectives, np = 2L)
```

Arguments

dimensions	[integer(1)] Number of decision variables.
n.objectives	[integer(1)] Number of objectives.
np	[integer(1)] Number of global Pareto sets. In the CEC2019 competition, the organizers used np = 2L.

Value

[smoof_multi_objective_function]

References

Caitong Yue, Boyang Qu, Kunjie Yu, Jing Liang, and Xiaodong Li, "A novel scalable test problem suite for multimodal multiobjective optimization," in Swarm and Evolutionary Computation, Volume 48, August 2019, pp. 62–71, Elsevier.

makeMMF15aFunction	<i>MMF15a Function</i>
--------------------	------------------------

Description

Test problem from the set of "multimodal multiobjective functions" as for instance used in the CEC2019 competition.

Usage

```
makeMMF15aFunction(dimensions, n.objectives, np = 2L)
```

Arguments

dimensions	[integer(1)] Number of decision variables.
n.objectives	[integer(1)] Number of objectives.
np	[integer(1)] Number of global Pareto sets. In the CEC2019 competition, the organizers used np = 2L.

Value

[smoof_multi_objective_function]

References

Caitong Yue, Boyang Qu, Kunjie Yu, Jing Liang, and Xiaodong Li, "A novel scalable test problem suite for multimodal multiobjective optimization," in Swarm and Evolutionary Computation, Volume 48, August 2019, pp. 62–71, Elsevier.

makeMMF15Function	<i>MMF15 Function</i>
-------------------	-----------------------

Description

Test problem from the set of "multimodal multiobjective functions" as for instance used in the CEC2019 competition.

Usage

```
makeMMF15Function(dimensions, n.objectives, np = 2L)
```

Arguments

dimensions	[integer(1)] Number of decision variables.
n.objectives	[integer(1)] Number of objectives.
np	[integer(1)] Number of global Pareto sets. In the CEC2019 competition, the organizers used np = 2L.

Value

```
[smoof_multi_objective_function]
```

References

Caitong Yue, Boyang Qu, Kunjie Yu, Jing Liang, and Xiaodong Li, "A novel scalable test problem suite for multimodal multiobjective optimization," in Swarm and Evolutionary Computation, Volume 48, August 2019, pp. 62–71, Elsevier.

makeMMF1eFunction	<i>MMF1e Function</i>
-------------------	-----------------------

Description

Test problem from the set of "multimodal multiobjective functions" as for instance used in the CEC2019 competition.

Usage

```
makeMMF1eFunction(a = exp(1L))
```

Arguments

a	[double(1)] Parametrizable factor. In the CEC2019 competition, the organizers used a = exp(1L).
---	--

Value

```
[smoof_multi_objective_function]
```

References

Caitong Yue, Boyang Qu, Kunjie Yu, Jing Liang, and Xiaodong Li, "A novel scalable test problem suite for multimodal multiobjective optimization," in Swarm and Evolutionary Computation, Volume 48, August 2019, pp. 62–71, Elsevier.

makeMMF1Function	<i>MMF1 Function</i>
------------------	----------------------

Description

Test problem from the set of "multimodal multiobjective functions" as for instance used in the CEC2019 competition.

Usage

```
makeMMF1Function()
```

Value

```
[smoof_multi_objective_function]
```

References

Caitong Yue, Boyang Qu, Kunjie Yu, Jing Liang, and Xiaodong Li, "A novel scalable test problem suite for multimodal multiobjective optimization," in Swarm and Evolutionary Computation, Volume 48, August 2019, pp. 62–71, Elsevier.

makeMMF1zFunction	<i>MMF1z Function</i>
-------------------	-----------------------

Description

Test problem from the set of "multimodal multiobjective functions" as for instance used in the CEC2019 competition.

Usage

```
makeMMF1zFunction(k = 3)
```

Arguments

k	[double(1)] Parametrizable factor. In the CEC2019 competition, the organizers used k = 3.
---	--

Value

[smoof_multi_objective_function]

References

Caitong Yue, Boyang Qu, Kunjie Yu, Jing Liang, and Xiaodong Li, "A novel scalable test problem suite for multimodal multiobjective optimization," in Swarm and Evolutionary Computation, Volume 48, August 2019, pp. 62–71, Elsevier.

makeMMF2Function	<i>MMF2 Function</i>
------------------	----------------------

Description

Test problem from the set of "multimodal multiobjective functions" as for instance used in the CEC2019 competition.

Usage

```
makeMMF2Function()
```

Value

[smoof_multi_objective_function]

References

Caitong Yue, Boyang Qu, Kunjie Yu, Jing Liang, and Xiaodong Li, "A novel scalable test problem suite for multimodal multiobjective optimization," in Swarm and Evolutionary Computation, Volume 48, August 2019, pp. 62–71, Elsevier.

makeMMF3Function	<i>MMF3 Function</i>
------------------	----------------------

Description

Test problem from the set of "multimodal multiobjective functions" as for instance used in the CEC2019 competition.

Usage

```
makeMMF3Function()
```

Value

```
[smoof_multi_objective_function]
```

References

Caitong Yue, Boyang Qu, Kunjie Yu, Jing Liang, and Xiaodong Li, "A novel scalable test problem suite for multimodal multiobjective optimization," in Swarm and Evolutionary Computation, Volume 48, August 2019, pp. 62–71, Elsevier.

makeMMF4Function	<i>MMF4 Function</i>
------------------	----------------------

Description

Test problem from the set of "multimodal multiobjective functions" as for instance used in the CEC2019 competition.

Usage

```
makeMMF4Function()
```

Value

```
[smoof_multi_objective_function]
```

References

Caitong Yue, Boyang Qu, Kunjie Yu, Jing Liang, and Xiaodong Li, "A novel scalable test problem suite for multimodal multiobjective optimization," in Swarm and Evolutionary Computation, Volume 48, August 2019, pp. 62–71, Elsevier.

makeMMF5Function	<i>MMF5 Function</i>
------------------	----------------------

Description

Test problem from the set of "multimodal multiobjective functions" as for instance used in the CEC2019 competition.

Usage

```
makeMMF5Function()
```

Value

```
[smoof_multi_objective_function]
```

References

Caitong Yue, Boyang Qu, Kunjie Yu, Jing Liang, and Xiaodong Li, "A novel scalable test problem suite for multimodal multiobjective optimization," in Swarm and Evolutionary Computation, Volume 48, August 2019, pp. 62–71, Elsevier.

makeMMF6Function	<i>MMF6 Function</i>
------------------	----------------------

Description

Test problem from the set of "multimodal multiobjective functions" as for instance used in the CEC2019 competition.

Usage

```
makeMMF6Function()
```

Value

```
[smoof_multi_objective_function]
```

References

Caitong Yue, Boyang Qu, Kunjie Yu, Jing Liang, and Xiaodong Li, "A novel scalable test problem suite for multimodal multiobjective optimization," in Swarm and Evolutionary Computation, Volume 48, August 2019, pp. 62–71, Elsevier.

makeMMF7Function	<i>MMF7 Function</i>
------------------	----------------------

Description

Test problem from the set of "multimodal multiobjective functions" as for instance used in the CEC2019 competition.

Usage

```
makeMMF7Function()
```

Value

```
[smoof_multi_objective_function]
```

References

Caitong Yue, Boyang Qu, Kunjie Yu, Jing Liang, and Xiaodong Li, "A novel scalable test problem suite for multimodal multiobjective optimization," in *Swarm and Evolutionary Computation*, Volume 48, August 2019, pp. 62–71, Elsevier.

makeMMF8Function	<i>MMF8 Function</i>
------------------	----------------------

Description

Test problem from the set of "multimodal multiobjective functions" as for instance used in the CEC2019 competition.

Usage

```
makeMMF8Function()
```

Value

```
[smoof_multi_objective_function]
```

References

Caitong Yue, Boyang Qu, Kunjie Yu, Jing Liang, and Xiaodong Li, "A novel scalable test problem suite for multimodal multiobjective optimization," in *Swarm and Evolutionary Computation*, Volume 48, August 2019, pp. 62–71, Elsevier.

makeMMF9Function	<i>MMF9 Function</i>
------------------	----------------------

Description

Test problem from the set of "multimodal multiobjective functions" as for instance used in the CEC2019 competition.

Usage

```
makeMMF9Function(np = 2L)
```

Arguments

np	[integer(1)] Number of global Pareto sets. In the CEC2019 competition, the organizers used np = 2L.
----	--

Value

[smoof_multi_objective_function]

References

Caitong Yue, Boyang Qu, Kunjie Yu, Jing Liang, and Xiaodong Li, "A novel scalable test problem suite for multimodal multiobjective optimization," in Swarm and Evolutionary Computation, Volume 48, August 2019, pp. 62–71, Elsevier.

makeModifiedRastriginFunction	<i>Rastrigin Function</i>
-------------------------------	---------------------------

Description

A modified version of the Rastrigin function following the formula:

$$f(\mathbf{x}) = \sum_{i=1}^n 10 (1 + \cos(2\pi k_i \mathbf{x}_i)) + 2k_i \mathbf{x}_i^2.$$

The box-constraints are given by $\mathbf{x}_i \in [0, 1]$ for $i = 1, \dots, n$ and k is a numerical vector. Deb et al. (see references) use, e.g., $k = (2, 2, 3, 4)$ for $n = 4$. See the reference for details.

Usage

```
makeModifiedRastriginFunction(dimensions, k = rep(1, dimensions))
```

Arguments

dimensions	[integer(1)] Size of corresponding parameter space.
k	[numeric] Vector of numerical values of length dimensions. Default is rep(1, dimensions)

Value

[smoof_single_objective_function]

References

Kalyanmoy Deb and Amit Saha. Multimodal optimization using a bi- objective evolutionary algorithm. *Evolutionary Computation*, 20(1):27-62, 2012.

makeMOP1Function	<i>MOP1 function generator.</i>
------------------	---------------------------------

Description

MOP1 function from Van Valedhuizen's test suite.

Usage

makeMOP1Function()

Value

[smoof_multi_objective_function]

References

J. D. Schaffer, "Multiple objective optimization with vector evaluated genetic algorithms," in *Proc. 1st Int. Conf. Genetic Algorithms and Their Applications*, J. J. Grenfenstett, Ed., 1985, pp. 93-100.

makeMOP2Function	<i>MOP2 function generator.</i>
------------------	---------------------------------

Description

MOP2 function from Van Valedhuizen's test suite due to Fonseca and Fleming.

Usage

```
makeMOP2Function(dimensions = 2L)
```

Arguments

dimensions	[integer(1)]
------------	--------------

Size of corresponding parameter space.

Value

[smoof_multi_objective_function]

References

C. M. Fonseca and P. J. Fleming, "Multiobjective genetic algorithms made easy: Selection, sharing and mating restriction," Genetic Algorithms in Engineering Systems: Innovations and Applications, pp. 45-52, Sep. 1995. IEE.

makeMOP3Function	<i>MOP3 function generator.</i>
------------------	---------------------------------

Description

MOP3 function from Van Valedhuizen's test suite.

Usage

```
makeMOP3Function(dimensions = 2L)
```

Arguments

dimensions	[integer(1)]
------------	--------------

Size of corresponding parameter space.

Value

[smoof_multi_objective_function]

References

C. Poloni, G. Mosetti, and S. Contessi, "Multi objective optimization by GAs: Application to system and component design," in Proc. Comput. Methods in Applied Sciences'96: Invited Lectures and Special Technological Sessions of the 3rd ECCOMAS Comput. Fluid Dynamics Conf. and the 2nd ECCOMAS Conf. Numerical Methods in Engineering, Sep. 1996, pp. 258-264

makeMOP4Function	<i>MOP4 function generator.</i>
------------------	---------------------------------

Description

MOP4 function from Van Valedhuizen's test suite based on Kursawe.

Usage

```
makeMOP4Function()
```

Value

```
[smoof_multi_objective_function]
```

References

F. Kursawe, "A variant of evolution strategies for vector optimization," in Lecture Notes in Computer Science, H.-P. Schwefel and R. Maenner, Eds. Berlin, Germany: Springer-Verlag, 1991, vol. 496, Proc. Parallel Problem Solving From Nature. 1st Workshop, PPSN I, pp. 193-197.

makeMOP5Function	<i>MOP5 function generator.</i>
------------------	---------------------------------

Description

MOP5 function from Van Valedhuizen's test suite.

Usage

```
makeMOP5Function()
```

Value

```
[smoof_multi_objective_function]
```

Note

Original box constraints where $[-3, 3]$.

References

R. Viennet, C. Fonteix, and I. Marc, "Multicriteria optimization using a genetic algorithm for determining a Pareto set," Int. J. Syst. Sci., vol. 27, no. 2, pp. 255-260, 1996

makeMOP6Function	<i>MOP6 function generator.</i>
------------------	---------------------------------

Description

MOP6 function from Van Valedhuizen's test suite.

Usage

```
makeMOP6Function()
```

Value

```
[smoof_multi_objective_function]
```

makeMOP7Function	<i>MOP7 function generator.</i>
------------------	---------------------------------

Description

MOP7 function from Van Valedhuizen's test suite.

Usage

```
makeMOP7Function()
```

Value

```
[smoof_multi_objective_function]
```

References

R. Viennet, C. Fonteix, and I. Marc, "Multicriteria optimization using a genetic algorithm for determining a Pareto set," Int. J. Syst. Sci., vol. 27, no. 2, pp. 255-260, 1996

makeMPM2Function	<i>Generator for function with multiple peaks following the multiple peaks model 2.</i>
------------------	---

Description

Generator for function with multiple peaks following the multiple peaks model 2.

Usage

```
makeMPM2Function(
  n.peaks,
  dimensions,
  topology,
  seed,
  rotated = TRUE,
  peak.shape = "ellipse"
)
```

Arguments

n.peaks	[integer(1)] Desired number of peaks, i. e., number of (local) optima.
dimensions	[integer(1)] Size of corresponding parameter space.
topology	[character(1)] Type of topology. Possible values are “random” and “funnel”.
seed	[integer(1)] Seed for the random numbers generator.
rotated	[logical(1)] Should the peak shapes be rotated? This parameter is only relevant in case of elliptically shaped peaks.
peak.shape	[character(1)] Shape of peak(s). Possible values are “ellipse” and “sphere”.

Value

[smoof_single_objective_function]

Author(s)

R interface by Jakob Bossek. Original python code provided by the Simon Wessing.

References

See the technical report of multiple peaks model 2 for an in-depth description of the underlying algorithm.

Examples

```
## Not run:
fn = makeMPM2Function(n.peaks = 10L, dimensions = 2L,
  topology = "funnel", seed = 123, rotated = TRUE, peak.shape = "ellipse")
if (require(plot3D)) {
  plot3D(fn)
}

## End(Not run)
## Not run:
fn = makeMPM2Function(n.peaks = 5L, dimensions = 2L,
  topology = "random", seed = 134, rotated = FALSE)
plot(fn, render.levels = TRUE)

## End(Not run)
```

makeMultiObjectiveFunction

Generator for multi-objective target functions.

Description

Generator for multi-objective target functions.

Usage

```
makeMultiObjectiveFunction(
  name = NULL,
  id = NULL,
  description = NULL,
  fn,
  has.simple.signature = TRUE,
  par.set,
  n.objectives = NULL,
  noisy = FALSE,
  fn.mean = NULL,
  minimize = NULL,
  vectorized = FALSE,
  constraint.fn = NULL,
  ref.point = NULL
)
```

Arguments

name	[character(1)] Function name. Used for the title of plots for example.
------	---

id	[character(1) NULL] Optional short function identifier. If provided, this should be a short name without whitespaces and now special characters beside the underscore. Default is NULL, which means no ID at all.
description	[character(1) NULL] Optional function description.
fn	[function] Objective function.
has.simple.signature	[logical(1)] Set this to TRUE if the objective function expects a vector as input and FALSE if it expects a named list of values. The latter is needed if the function depends on mixed parameters. Default is TRUE.
par.set	[ParamSet] Parameter set describing different aspects of the objective function parameters, i.e., names, lower and/or upper bounds, types and so on. See makeParamSet for further information.
n.objectives	[integer(1)] Number of objectives of the multi-objective function.
noisy	[logical(1)] Is the function noisy? Defaults to FALSE.
fn.mean	[function] Optional true mean function in case of a noisy objective function. This functions should have the same mean as fn.
minimize	[logical] Logical vector of length n.objectives indicating if the corresponding objectives shall be minimized or maximized. Default is the vector with all components set to TRUE.
vectorized	[logical(1)] Can the objective function handle “vector” input, i.e., does it accept matrix of parameters? Default is FALSE.
constraint.fn	[function NULL] Function which returns a logical vector indicating whether certain conditions are met or not. Default is NULL, which means, that there are no constraints beside possible box constraints defined via the par.set argument.
ref.point	[numeric] Optional reference point in the objective space, e.g., for hypervolume computation.

Value

[function] Target function with additional stuff attached as attributes.

Examples

```
fn = makeMultiObjectiveFunction(
  name = "My test function",
  fn = function(x) c(sum(x^2), exp(x)),
  n.objectives = 2L,
  par.set = makeNumericParamSet("x", len = 1L, lower = -5L, upper = 5L)
)
print(fn)
```

makeOmniTestFunction *MMF13 Function*

Description

Test problem from the set of "multimodal multiobjective functions" as for instance used in the CEC2019 competition.

Usage

```
makeOmniTestFunction()
```

Value

```
[smoof_multi_objective_function]
```

References

Caitong Yue, Boyang Qu, Kunjie Yu, Jing Liang, and Xiaodong Li, "A novel scalable test problem suite for multimodal multiobjective optimization," in Swarm and Evolutionary Computation, Volume 48, August 2019, pp. 62–71, Elsevier.

makePeriodicFunction *Periodic Function*

Description

Single-objective two-dimensional test function. The formula is given as

$$f(\mathbf{x}) = 1 + \sin^2(\mathbf{x}_1) + \sin^2(\mathbf{x}_2) - 0.1e^{-(\mathbf{x}_1^2 + \mathbf{x}_2^2)}$$

subject to the constraints $\mathbf{x}_i \in [-10, 10], i = 1, 2$.

Usage

```
makePeriodicFunction()
```

Value

[smoof_single_objective_function]

References

M. M. Ali, C. Khompatraporn, Z. B. Zabinsky, A Numerical Evaluation of Several Stochastic Algorithms on Selected Continuous Global Optimization Test Problems, Journal of Global Optimization, vol. 31, pp. 635-672, 2005.

makePowellSumFunction *Powell-Sum Function*

Description

The formula that underlies the implementation is given by

$$f(\mathbf{x}) = \sum_{i=1}^n |\mathbf{x}_i|^{i+1}$$

with $\mathbf{x}_i \in [-1, 1], i = 1, \dots, n$.

Usage

makePowellSumFunction(dimensions)

Arguments

dimensions	[integer(1)]
	Size of corresponding parameter space.

Value

[smoof_single_objective_function]

References

S. Rahnamyan, H. R. Tizhoosh, N. M. M. Salama, A Novel Population Initialization Method for Accelerating Evolutionary Algorithms, Computers and Mathematics with Applications, vol. 53, no. 10, pp. 1605-1614, 2007.

makePriceN1Function *Price Function N. 1*

Description

Second function by Price. The implementation is based on the definition

$$f(\mathbf{x}) = (|\mathbf{x}_1| - 5)^2 + (|\mathbf{x}_2 - 5|)^2$$

subject to $\mathbf{x}_i \in [-500, 500], i = 1, 2$.

Usage

makePriceN1Function()

Value

[smoof_single_objective_function]

References

W. L. Price, A Controlled Random Search Procedure for Global Optimisation, Computer journal, vol. 20, no. 4, pp. 367-370, 1977.

See Also

[makePriceN2Function](#), [makePriceN4Function](#)

makePriceN2Function *Price Function N. 2*

Description

Second function by Price. The implementation is based on the definition

$$f(\mathbf{x}) = 1 + \sin^2(\mathbf{x}_1) + \sin^2(\mathbf{x}_2) - 0.1 \exp(-\mathbf{x}^2 - \mathbf{x}_2^2)$$

subject to $\mathbf{x}_i \in [-10, 10], i = 1, 2$.

Usage

makePriceN2Function()

Value

[smoof_single_objective_function]

References

W. L. Price, A Controlled Random Search Procedure for Global Optimisation, Computer journal, vol. 20, no. 4, pp. 367-370, 1977.

See Also

[makePriceN1Function](#), [makePriceN4Function](#)

makePriceN4Function	<i>Price Function N. 4</i>
---------------------	----------------------------

Description

Fourth function by Price. The implementation is based on the definition

$$f(\mathbf{x}) = (2\mathbf{x}_1^3\mathbf{x}_2 - \mathbf{x}_2^3)^2 + (6\mathbf{x}_1 - \mathbf{x}_2^2 + \mathbf{x}_2)^2$$

subject to $\mathbf{x}_i \in [-500, 500]$.

Usage

`makePriceN4Function()`

Value

`[smoof_single_objective_function]`

References

W. L. Price, A Controlled Random Search Procedure for Global Optimisation, Computer journal, vol. 20, no. 4, pp. 367-370, 1977.

See Also

[makePriceN1Function](#), [makePriceN2Function](#)

makeRastriginFunction *Rastrigin Function*

Description

One of the most popular single-objective test functions consists of many local optima and is thus highly multimodal with a global structure. The implementation follows the formula

$$f(\mathbf{x}) = 10n + \sum_{i=1}^n (\mathbf{x}_i^2 - 10 \cos(2\pi \mathbf{x}_i)) .$$

The box-constraints are given by $\mathbf{x}_i \in [-5.12, 5.12]$ for $i = 1, \dots, n$.

Usage

```
makeRastriginFunction(dimensions)
```

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

[smoof_single_objective_function]

References

L. A. Rastrigin. Extremal control systems. Theoretical Foundations of Engineering Cybernetics Series. Nauka, Moscow, 1974.

makeRosenbrockFunction
Rosenbrock Function

Description

Also known as the “De Jong’s function 2” or the “(Rosenbrock) banana/valley function” due to its shape. The global optimum is located within a large flat valley and thus it is hard for optimization algorithms to find it. The following formula underlies the implementation:

$$f(\mathbf{x}) = \sum_{i=1}^{n-1} 100 \cdot (\mathbf{x}_{i+1} - \mathbf{x}_i^2)^2 + (1 - \mathbf{x}_i)^2 .$$

The domain is given by the constraints $\mathbf{x}_i \in [-30, 30], i = 1, \dots, n$.

Usage

```
makeRosenbrockFunction(dimensions)
```

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

```
[smoof_single_objective_function]
```

References

H. H. Rosenbrock, An Automatic Method for Finding the Greatest or least Value of a Function, Computer Journal, vol. 3, no. 3, pp. 175-184, 1960.

```
makeSchafferN2Function
```

Modified Schaffer Function N. 2

Description

Second function by Schaffer. The definition is given by the formula

$$f(\mathbf{x}) = 0.5 + \frac{\sin^2(\mathbf{x}_1^2 - \mathbf{x}_2^2) - 0.5}{(1 + 0.001(\mathbf{x}_1^2 + \mathbf{x}_2^2))^2}$$

subject to $\mathbf{x}_i \in [-100, 100], i = 1, 2$.

Usage

```
makeSchafferN2Function()
```

Value

```
[smoof_single_objective_function]
```

References

S. K. Mishra, Some New Test Functions For Global Optimization And Performance of Repulsive Particle Swarm Method.

makeSchafferN4Function

Schaffer Function N. 4

Description

Second function by Schaffer. The definition is given by the formula

$$f(\mathbf{x}) = 0.5 + \frac{\cos^2(\sin(|\mathbf{x}_1^2 - \mathbf{x}_2^2|)) - 0.5}{(1 + 0.001(\mathbf{x}_1^2 + \mathbf{x}_2^2))^2}$$

subject to $\mathbf{x}_i \in [-100, 100], i = 1, 2$.

Usage

makeSchafferN4Function()

Value

[smoof_single_objective_function]

References

S. K. Mishra, Some New Test Functions For Global Optimization And Performance of Repulsive Particle Swarm Method.

makeSchwefelFunction *Schwefel function*

Description

Highly multimodal test function. The curious thing about this function is, that the global optimum is far away from the next best local optimum. The function is computed via:

$$f(\mathbf{x}) = \sum_{i=1}^n -\mathbf{x}_i \sin\left(\sqrt{(|\mathbf{x}_i|)}\right)$$

with $\mathbf{x}_i \in [-500, 500], i = 1, \dots, n$.

Usage

makeSchwefelFunction(dimensions)

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

[smoof_single_objective_function]

References

Schwefel, H.-P.: Numerical optimization of computer models. Chichester: Wiley & Sons, 1981.

makeShekelFunction	<i>Shekel functions</i>
--------------------	-------------------------

Description

Single-objective test function based on the formula

$$f(\mathbf{x}) = - \sum_{i=1}^m \left(\sum_{j=1}^4 (x_j - C_{ji})^2 + \beta_i \right)^{-1}$$

. Here, $m \in \{5, 7, 10\}$ defines the number of local optima, C is a 4×10 matrix and $\beta = \frac{1}{10}(1, 1, 2, 2, 4, 4, 6, 3, 7, 5, 5)$ is a vector. See <https://www.sfu.ca/~ssurjano/shekel1.html> for a definition of C .

Usage

makeShekelFunction(m)

Arguments

m	[numeric(1)] Integer parameter (defines the number of local optima). Possible values are 5, 7 or 10.
---	---

Value

[smoof_single_objective_function]

makeShubertFunction	<i>Shubert Function</i>
---------------------	-------------------------

Description

The definition of this two-dimensional function is given by

$$f(\mathbf{x}) = \prod_{i=1}^2 \left(\sum_{j=1}^5 \cos((j+1)\mathbf{x}_i + j) \right)$$

subject to $\mathbf{x}_i \in [-10, 10], i = 1, 2$.

Usage

```
makeShubertFunction()
```

Value

```
[smoof_single_objective_function]
```

References

J. P. Hennart (ed.), Numerical Analysis, Proc. 3rd AS Workshop, Lecture Notes in Mathematics, vol. 90, Springer, 1982.

makeSingleObjectiveFunction	<i>Generator for single-objective target functions.</i>
-----------------------------	---

Description

Generator for single-objective target functions.

Usage

```
makeSingleObjectiveFunction(
  name = NULL,
  id = NULL,
  description = NULL,
  fn,
  has.simple.signature = TRUE,
  vectorized = FALSE,
  par.set,
  noisy = FALSE,
  fn.mean = NULL,
```

```

minimize = TRUE,
constraint.fn = NULL,
tags = character(0),
global.opt.params = NULL,
global.opt.value = NULL,
local.opt.params = NULL,
local.opt.values = NULL
)

```

Arguments

name	[character(1)] Function name. Used for the title of plots for example.
id	[character(1) NULL] Optional short function identifier. If provided, this should be a short name without whitespaces and now special characters beside the underscore. Default is NULL, which means no ID at all.
description	[character(1) NULL] Optional function description.
fn	[function] Objective function.
has.simple.signature	[logical(1)] Set this to TRUE if the objective function expects a vector as input and FALSE if it expects a named list of values. The latter is needed if the function depends on mixed parameters. Default is TRUE.
vectorized	[logical(1)] Can the objective function handle “vector” input, i.e., does it accept matrix of parameters? Default is FALSE.
par.set	[ParamSet] Parameter set describing different aspects of the objective function parameters, i.e., names, lower and/or upper bounds, types and so on. See makeParamSet for further information.
noisy	[logical(1)] Is the function noisy? Defaults to FALSE.
fn.mean	[function] Optional true mean function in case of a noisy objective function. This functions should have the same mean as fn.
minimize	[logical(1)] Set this to TRUE if the function should be minimized and to FALSE otherwise. The default is TRUE.
constraint.fn	[function NULL] Function which returns a logical vector indicating whether certain conditions are met or not. Default is NULL, which means, that there are no constraints beside possible box constraints defined via the par.set argument.

tags [character]
Optional character vector of tags or keywords which characterize the function, e.g. “unimodal”, “separable”. See [getAvailableTags](#) for a character vector of allowed tags.

global.opt.params
[list | numeric | data.frame | matrix | NULL]
Default is NULL which means unknown. Passing a numeric vector will be the most frequent case (numeric only functions). In this case there is only a single global optimum. If there are multiple global optima, passing a numeric matrix is the best choice. Passing a list or a data.frame is necessary if your function is mixed, e.g., it expects both numeric and discrete parameters. Internally, however, each representation is casted to a data.frame for reasons of consistency.

global.opt.value
[numeric(1) | NULL]
Global optimum value if known. Default is NULL, which means unknown. If only the global.opt.params are passed, the value is computed automatically.

local.opt.params
[list | numeric | data.frame | matrix | NULL]
Default is NULL, which means the function has no local optima or they are unknown. For details see the description of global.opt.params.

local.opt.values
[numeric | NULL]
Value(s) of local optima. Default is NULL, which means unknown. If only the local.opt.params are passed, the values are computed automatically.

Value

[function] Objective function with additional stuff attached as attributes.

Examples

```
library(ggplot2)

fn = makeSingleObjectiveFunction(
  name = "Sphere Function",
  fn = function(x) sum(x^2),
  par.set = makeNumericParamSet("x", len = 1L, lower = -5L, upper = 5L),
  global.opt.params = list(x = 0)
)
print(fn)
print(autoplot(fn))

fn.num2 = makeSingleObjectiveFunction(
  name = "Numeric 2D",
  fn = function(x) sum(x^2),
  par.set = makeParamSet(
    makeNumericParam("x1", lower = -5, upper = 5),
    makeNumericParam("x2", lower = -10, upper = 20)
  )
)
```

```

print(fn.num2)
print(autoplot(fn.num2))

fn.mixed = makeSingleObjectiveFunction(
  name = "Mixed 2D",
  fn = function(x) x$num1^2 + as.integer(as.character(x$disc1) == "a"),
  has.simple.signature = FALSE,
  par.set = makeParamSet(
    makeNumericParam("num1", lower = -5, upper = 5),
    makeDiscreteParam("disc1", values = c("a", "b"))
  ),
  global.opt.params = list(num1 = 0, disc1 = "b")
)
print(fn.mixed)
print(autoplot(fn.mixed))

```

makeSixHumpCamelFunction

Three-Hump Camel Function

Description

Two dimensional single-objective test function with six local minima oh which two are global. The surface is similar to the back of a camel. That is why it is called Camel function. The implementation is based on the formula:

$$f(\mathbf{x}) = (4 - 2.1\mathbf{x}_1^2 + \mathbf{x}_1^{0.75}) \mathbf{x}_1^2 + \mathbf{x}_1\mathbf{x}_2 + (-4 + 4\mathbf{x}_2^2) \mathbf{x}_2^2$$

with box constraints $\mathbf{x}_1 \in [-3, 3]$ and $\mathbf{x}_2 \in [-2, 2]$.

Usage

```
makeSixHumpCamelFunction()
```

Value

```
[smoof_single_objective_function]
```

References

Dixon, L. C. W. and Szego, G. P.: The optimization problem: An introduction. In: Towards Global Optimization II, New York: North Holland, 1978.

makeSphereFunction	<i>Sphere Function</i>
--------------------	------------------------

Description

Also known as the the “De Jong function 1”. Convex, continous function calculated via the formula

$$f(\mathbf{x}) = \sum_{i=1}^n \mathbf{x}_i^2$$

with box-constraings $\mathbf{x}_i \in [-5.12, 5.12], i = 1, \dots, n$.

Usage

```
makeSphereFunction(dimensions)
```

Arguments

dimensions	[integer(1)] Size of corresponding parameter space.
------------	--

Value

```
[smoof_single_objective_function]
```

References

M. A. Schumer, K. Steiglitz, Adaptive Step Size Random Search, IEEE Transactions on Automatic Control. vol. 13, no. 3, pp. 270-276, 1968.

makeStyblinskiTangFunction	<i>Styblinski-Tang function</i>
----------------------------	---------------------------------

Description

This function is based on the defintion

$$f(\mathbf{x}) = \frac{1}{2} \sum_{i=1}^2 (\mathbf{x}_i^4 - 16\mathbf{x}_i^2 + 5\mathbf{x}_i)$$

with box-constraints given by $\mathbf{x}_i \in [-5, 5], i = 1, 2$.

Usage

```
makeStyblinskiTangFunction()
```

Value

[smoof_single_objective_function]

References

Z. K. Silagadze, Finding Two-Dimensional Peaks, Physics of Particles and Nuclei Letters, vol. 4, no. 1, pp. 73-80, 2007.

makeSumOfDifferentSquaresFunction

Sum of Different Squares Function

Description

Simple unimodal test function similar to the Sphere and Hyper-Ellipsoidal functions. Formula:

$$f(\mathbf{x}) = \sum_{i=1}^n |\mathbf{x}_i|^{i+1}.$$

Usage

makeSumOfDifferentSquaresFunction(dimensions)

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

[smoof_single_objective_function]

makeSwiler2014Function

Swiler2014 function.

Description

Mixed parameter space with one discrete parameter $x_1 \in \{1, 2, 3, 4, 5\}$ and two numerical parameters $x_1, x_2 \in [0, 1]$. The function is defined as follows:

$$f(\mathbf{x}) = \sin(2\pi x_3 - \pi) + 7 \sin^2(2\pi x_2 - \pi) \text{ if } x_1 = 1 \quad \sin(2\pi x_3 - \pi) + 7 \sin^2(2\pi x_2 - \pi) + 12 \sin(2\pi x_3 - \pi) \text{ if } x_1 = 2 \quad \sin(2\pi x_3 - \pi) + 7 \sin^2(2\pi x_2 - \pi) + 12 \sin(2\pi x_3 - \pi) + 12 \sin(2\pi x_2 - \pi) \text{ if } x_1 = 3$$

Usage

makeSwiler2014Function()

Value

[smoof_single_objective_function]

makeSYMPARTrotatedFunction
MMF13 Function

Description

Test problem from the set of "multimodal multiobjective functions" as for instance used in the CEC2019 competition.

Usage

```
makeSYMPARTrotatedFunction(w = pi/4, a = 1, b = 10, c = 8)
```

Arguments

w	[double(1)] Parametrizable factor. In the CEC2019 competition, the organizers used $w = \pi / 4$.
a	[double(1)] Parametrizable factor. In the CEC2019 competition, the organizers used $a = 1$.
b	[double(1)] Parametrizable factor. In the CEC2019 competition, the organizers used $b = 10$.
c	[double(1)] Parametrizable factor. In the CEC2019 competition, the organizers used $c = 8$.

Value

[smoof_multi_objective_function]

References

Caitong Yue, Boyang Qu, Kunjie Yu, Jing Liang, and Xiaodong Li, "A novel scalable test problem suite for multimodal multiobjective optimization," in Swarm and Evolutionary Computation, Volume 48, August 2019, pp. 62–71, Elsevier.

makeSYMPARTsimpleFunction

MMF13 Function

Description

Test problem from the set of "multimodal multiobjective functions" as for instance used in the CEC2019 competition.

Usage

```
makeSYMPARTsimpleFunction(a = 1, b = 10, c = 8)
```

Arguments

a	[double(1)] Parametrizable factor. In the CEC2019 competition, the organizers used a = 1.
b	[double(1)] Parametrizable factor. In the CEC2019 competition, the organizers used b = 10.
c	[double(1)] Parametrizable factor. In the CEC2019 competition, the organizers used c = 8.

Value

[smoof_multi_objective_function]

References

Caitong Yue, Boyang Qu, Kunjie Yu, Jing Liang, and Xiaodong Li, "A novel scalable test problem suite for multimodal multiobjective optimization," in Swarm and Evolutionary Computation, Volume 48, August 2019, pp. 62–71, Elsevier.

makeThreeHumpCamelFunction

Three-Hump Camel Function

Description

This two-dimensional function is based on the definition

$$f(\mathbf{x}) = 2\mathbf{x}_1^2 - 1.05\mathbf{x}_1^4 + \frac{\mathbf{x}_1^6}{6} + \mathbf{x}_1\mathbf{x}_2 + \mathbf{x}_2^2$$

subject to $-5 \leq \mathbf{x}_i \leq 5$.

Usage

```
makeThreeHumpCamelFunction()
```

Value

```
[smoof_single_objective_function]
```

References

F. H. Branin Jr., Widely Convergent Method of Finding Multiple Solutions of Simultaneous Non-linear Equations, IBM Journal of Research and Development, vol. 16, no. 5, pp. 504-522, 1972.

makeTrecanniFunction	<i>Trecanni Function</i>
----------------------	--------------------------

Description

The Trecanni function belongs to the unimodal test functions. It is based on the formula

$$f((x)) = (x)_1^4 - 4(x)_1^3 + 4(x)_1 + (x)_2^2.$$

The box-constraints $\mathbf{x}_i \in [-5, 5], i = 1, 2$ define the domain of definition.

Usage

```
makeTrecanniFunction()
```

Value

```
[smoof_single_objective_function]
```

References

L. C. W. Dixon, G. P. Szego (eds.), Towards Global Optimization 2, Elsevier, 1978.

makeUFFunction	<i>Generator for the functions UF1, ..., UF10 of the CEC 2009.</i>
----------------	--

Description

Generator for the functions UF1, ..., UF10 of the CEC 2009.

Usage

```
makeUFFunction(dimensions, id)
```

Arguments

dimensions	[integer(1)] Size of corresponding parameter space.
id	[integer(1)] Instance identifier. Integer value between 1 and 10.

Value

[smoof_single_objective_function]

Note

The implementation is based on the original CPP implemenation by Qingfu Zhang, Aimin Zhou, Shizheng Zhaoy, Ponnuthurai Nagaratnam Suganthany, Wudong Liu and Santosh Tiwar.

Author(s)

Jakob Bossek <j.bossek@gmail.com>

makeViennetFunction	<i>Viennet function generator</i>
---------------------	-----------------------------------

Description

The Viennet test problem VNT is designed for three objectives only. It has a discrete set of Pareto fronts. It is defined by the following formulae.

$$f(\mathbf{x}) = (f_1(\mathbf{x}), f_2(\mathbf{x}), f_3(\mathbf{x}))$$

with

$$\begin{aligned} f_1(\mathbf{x}) &= 0.5(\mathbf{x}_1^2 + \mathbf{x}_2^2) + \sin(\mathbf{x}_1^2 + \mathbf{x}_2^2) \\ f_2(\mathbf{x}) &= \frac{(3\mathbf{x}_1 + 2\mathbf{x}_2 + 4)^2}{8} + \frac{(\mathbf{x}_1 - \mathbf{x}_2 + 1)^2}{27} + 15 \\ f_3(\mathbf{x}) &= \frac{1}{\mathbf{x}_1^2 + \mathbf{x}_2^2 + 1} - 1.1 \exp(-(\mathbf{x}_1^1 + \mathbf{x}_2^2)) \end{aligned}$$

with box constraints $-3 \leq \mathbf{x}_1, \mathbf{x}_2 \leq 3$.

Usage

```
makeViennetFunction()
```

Value

```
[smoof_multi_objective_function]
```

References

Viennet, R. (1996). Multicriteria optimization using a genetic algorithm for determining the Pareto set. *International Journal of Systems Science* 27 (2), 255-260.

makeWFG1Function	<i>WFG1 Function</i>
------------------	----------------------

Description

First test problem from the "Walking Fish Group" problem generator toolkit.

Usage

```
makeWFG1Function(n.objectives, k, l)
```

Arguments

n.objectives	[integer(1)] Number of objectives.
k	[integer(1)] Number of position-related parameters. These will automatically be the first k elements from the input vector. This value has to be a multiple of n.objectives - 1.
l	[integer(1)] Number of distance-related parameters. These will automatically be the last l elements from the input vector.

Details

Huband et al. recommend a value of $k = 4L$ position-related parameters for bi-objective problems and $k = 2L * (n.objectives - 1L)$ for many-objective problems. Furthermore the authors recommend a value of $l = 20$ distance-related parameters. Therefore, if k and/or l are not explicitly defined by the user, their values will be set to the recommended values per default.

Value

```
[smoof_multi_objective_function]
```

References

S. Huband, P. Hingston, L. Barone, and L. While, "A Review of Multi-objective Test Problems and a Scalable Test Problem Toolkit," in IEEE Transactions on Evolutionary Computation, Volume 10, No 5, October 2006, pp. 477-506. IEEE.

makeWFG2Function	<i>WFG2 Function</i>
------------------	----------------------

Description

Second test problem from the "Walking Fish Group" problem generator toolkit.

Usage

```
makeWFG2Function(n.objectives, k, l)
```

Arguments

n.objectives	[integer(1)] Number of objectives.
k	[integer(1)] Number of position-related parameters. These will automatically be the first k elements from the input vector. This value has to be a multiple of n.objectives - 1.
l	[integer(1)] Number of distance-related parameters. These will automatically be the last l elements from the input vector. This value has to be a multiple of 2.

Details

Huband et al. recommend a value of $k = 4L$ position-related parameters for bi-objective problems and $k = 2L * (n.objectives - 1L)$ for many-objective problems. Furthermore the authors recommend a value of $l = 20$ distance-related parameters. Therefore, if k and/or l are not explicitly defined by the user, their values will be set to the recommended values per default.

Value

```
[smoof_multi_objective_function]
```

References

S. Huband, P. Hingston, L. Barone, and L. While, "A Review of Multi-objective Test Problems and a Scalable Test Problem Toolkit," in IEEE Transactions on Evolutionary Computation, Volume 10, No 5, October 2006, pp. 477-506. IEEE.

makeWFG3Function	<i>WFG3 Function</i>
------------------	----------------------

Description

Third test problem from the "Walking Fish Group" problem generator toolkit.

Usage

```
makeWFG3Function(n.objectives, k, l)
```

Arguments

n.objectives	[integer(1)] Number of objectives.
k	[integer(1)] Number of position-related parameters. These will automatically be the first k elements from the input vector. This value has to be a multiple of n.objectives - 1.
l	[integer(1)] Number of distance-related parameters. These will automatically be the last l elements from the input vector. This value has to be a multiple of 2.

Details

Huband et al. recommend a value of $k = 4L$ position-related parameters for bi-objective problems and $k = 2L * (n.objectives - 1)$ for many-objective problems. Furthermore the authors recommend a value of $l = 20$ distance-related parameters. Therefore, if k and/or l are not explicitly defined by the user, their values will be set to the recommended values per default.

Value

[smoof_multi_objective_function]

References

S. Huband, P. Hingston, L. Barone, and L. While, "A Review of Multi-objective Test Problems and a Scalable Test Problem Toolkit," in IEEE Transactions on Evolutionary Computation, Volume 10, No 5, October 2006, pp. 477-506. IEEE.

makeWFG4Function	<i>WFG4 Function</i>
------------------	----------------------

Description

Fourth test problem from the "Walking Fish Group" problem generator toolkit.

Usage

```
makeWFG4Function(n.objectives, k, l)
```

Arguments

n.objectives	[integer(1)] Number of objectives.
k	[integer(1)] Number of position-related parameters. These will automatically be the first k elements from the input vector. This value has to be a multiple of n.objectives - 1.
l	[integer(1)] Number of distance-related parameters. These will automatically be the last l elements from the input vector.

Details

Huband et al. recommend a value of $k = 4L$ position-related parameters for bi-objective problems and $k = 2L * (n.objectives - 1)$ for many-objective problems. Furthermore the authors recommend a value of $l = 20$ distance-related parameters. Therefore, if k and/or l are not explicitly defined by the user, their values will be set to the recommended values per default.

Value

[smoof_multi_objective_function]

References

S. Huband, P. Hingston, L. Barone, and L. While, "A Review of Multi-objective Test Problems and a Scalable Test Problem Toolkit," in IEEE Transactions on Evolutionary Computation, Volume 10, No 5, October 2006, pp. 477-506. IEEE.

makeWFG5Function	<i>WFG5 Function</i>
------------------	----------------------

Description

Fifth test problem from the "Walking Fish Group" problem generator toolkit.

Usage

```
makeWFG5Function(n.objectives, k, l)
```

Arguments

n.objectives	[integer(1)] Number of objectives.
k	[integer(1)] Number of position-related parameters. These will automatically be the first k elements from the input vector. This value has to be a multiple of n.objectives - 1.
l	[integer(1)] Number of distance-related parameters. These will automatically be the last l elements from the input vector.

Details

Huband et al. recommend a value of $k = 4L$ position-related parameters for bi-objective problems and $k = 2L * (n.objectives - 1)$ for many-objective problems. Furthermore the authors recommend a value of $l = 20$ distance-related parameters. Therefore, if k and/or l are not explicitly defined by the user, their values will be set to the recommended values per default.

Value

```
[smoof_multi_objective_function]
```

References

S. Huband, P. Hingston, L. Barone, and L. While, "A Review of Multi-objective Test Problems and a Scalable Test Problem Toolkit," in IEEE Transactions on Evolutionary Computation, Volume 10, No 5, October 2006, pp. 477-506. IEEE.

makeWFG6Function	<i>WFG6 Function</i>
------------------	----------------------

Description

Sixth test problem from the "Walking Fish Group" problem generator toolkit.

Usage

```
makeWFG6Function(n.objectives, k, l)
```

Arguments

n.objectives	[integer(1)] Number of objectives.
k	[integer(1)] Number of position-related parameters. These will automatically be the first k elements from the input vector. This value has to be a multiple of n.objectives - 1.
l	[integer(1)] Number of distance-related parameters. These will automatically be the last l elements from the input vector.

Details

Huband et al. recommend a value of $k = 4L$ position-related parameters for bi-objective problems and $k = 2L * (n.objectives - 1)$ for many-objective problems. Furthermore the authors recommend a value of $l = 20$ distance-related parameters. Therefore, if k and/or l are not explicitly defined by the user, their values will be set to the recommended values per default.

Value

[smoof_multi_objective_function]

References

S. Huband, P. Hingston, L. Barone, and L. While, "A Review of Multi-objective Test Problems and a Scalable Test Problem Toolkit," in IEEE Transactions on Evolutionary Computation, Volume 10, No 5, October 2006, pp. 477-506. IEEE.

makeWFG7Function	<i>WFG7 Function</i>
------------------	----------------------

Description

Seventh test problem from the "Walking Fish Group" problem generator toolkit.

Usage

```
makeWFG7Function(n.objectives, k, l)
```

Arguments

n.objectives	[integer(1)] Number of objectives.
k	[integer(1)] Number of position-related parameters. These will automatically be the first k elements from the input vector. This value has to be a multiple of n.objectives - 1.
l	[integer(1)] Number of distance-related parameters. These will automatically be the last l elements from the input vector.

Details

Huband et al. recommend a value of $k = 4L$ position-related parameters for bi-objective problems and $k = 2L * (n.objectives - 1)$ for many-objective problems. Furthermore the authors recommend a value of $l = 20$ distance-related parameters. Therefore, if k and/or l are not explicitly defined by the user, their values will be set to the recommended values per default.

Value

[smoof_multi_objective_function]

References

S. Huband, P. Hingston, L. Barone, and L. While, "A Review of Multi-objective Test Problems and a Scalable Test Problem Toolkit," in IEEE Transactions on Evolutionary Computation, Volume 10, No 5, October 2006, pp. 477-506. IEEE.

makeWFG8Function	<i>WFG8 Function</i>
------------------	----------------------

Description

Eighth test problem from the "Walking Fish Group" problem generator toolkit.

Usage

```
makeWFG8Function(n.objectives, k, l)
```

Arguments

n.objectives	[integer(1)] Number of objectives.
k	[integer(1)] Number of position-related parameters. These will automatically be the first k elements from the input vector. This value has to be a multiple of n.objectives - 1.
l	[integer(1)] Number of distance-related parameters. These will automatically be the last l elements from the input vector.

Details

Huband et al. recommend a value of $k = 4L$ position-related parameters for bi-objective problems and $k = 2L * (n.objectives - 1)$ for many-objective problems. Furthermore the authors recommend a value of $l = 20$ distance-related parameters. Therefore, if k and/or l are not explicitly defined by the user, their values will be set to the recommended values per default.

Value

[smoof_multi_objective_function]

References

S. Huband, P. Hingston, L. Barone, and L. While, "A Review of Multi-objective Test Problems and a Scalable Test Problem Toolkit," in IEEE Transactions on Evolutionary Computation, Volume 10, No 5, October 2006, pp. 477-506. IEEE.

makeWFG9Function	<i>WFG9 Function</i>
------------------	----------------------

Description

Ninth test problem from the "Walking Fish Group" problem generator toolkit.

Usage

```
makeWFG9Function(n.objectives, k, l)
```

Arguments

n.objectives	[integer(1)] Number of objectives.
k	[integer(1)] Number of position-related parameters. These will automatically be the first k elements from the input vector. This value has to be a multiple of n.objectives - 1.
l	[integer(1)] Number of distance-related parameters. These will automatically be the last l elements from the input vector.

Details

Huband et al. recommend a value of $k = 4L$ position-related parameters for bi-objective problems and $k = 2L * (n.objectives - 1)$ for many-objective problems. Furthermore the authors recommend a value of $l = 20$ distance-related parameters. Therefore, if k and/or l are not explicitly defined by the user, their values will be set to the recommended values per default.

Value

[smoof_multi_objective_function]

References

S. Huband, P. Hingston, L. Barone, and L. While, "A Review of Multi-objective Test Problems and a Scalable Test Problem Toolkit," in IEEE Transactions on Evolutionary Computation, Volume 10, No 5, October 2006, pp. 477-506. IEEE.

makeZDT1Function	<i>ZDT1 Function</i>
------------------	----------------------

Description

Builds and returns the two-objective ZDT1 test problem. For m objective it is defined as follows:

$$f(\mathbf{x}) = (f_1(\mathbf{x}_1), f_2(\mathbf{x}))$$

with

$$f_1(\mathbf{x}_1) = \mathbf{x}_1, f_2(\mathbf{x}) = g(\mathbf{x})h(f_1(\mathbf{x}_1), g(\mathbf{x}))$$

where

$$g(\mathbf{x}) = 1 + \frac{9}{m-1} \sum_{i=2}^m \mathbf{x}_i, h(f_1, g) = 1 - \sqrt{\frac{f_1}{g}}$$

and $\mathbf{x}_i \in [0, 1], i = 1, \dots, m$

Usage

```
makeZDT1Function(dimensions)
```

Arguments

dimensions	[integer(1)] Number of decision variables.
------------	---

Value

```
[smoof_multi_objective_function]
```

References

E. Zitzler, K. Deb, and L. Thiele. Comparison of Multiobjective Evolutionary Algorithms: Empirical Results. *Evolutionary Computation*, 8(2):173-195, 2000

makeZDT2Function	<i>ZDT2 Function</i>
------------------	----------------------

Description

Builds and returns the two-objective ZDT2 test problem. The function is nonconvex and resembles the ZDT1 function. For m objective it is defined as follows

$$f(\mathbf{x}) = (f_1(\mathbf{x}_1), f_2(\mathbf{x}))$$

with

$$f_1(\mathbf{x}_1) = \mathbf{x}_1, f_2(\mathbf{x}) = g(\mathbf{x})h(f_1(\mathbf{x}_1), g(\mathbf{x}))$$

where

$$g(\mathbf{x}) = 1 + \frac{9}{m-1} \sum_{i=2}^m \mathbf{x}_i, h(f_1, g) = 1 - \left(\frac{f_1}{g}\right)^2$$

and $\mathbf{x}_i \in [0, 1], i = 1, \dots, m$

Usage

```
makeZDT2Function(dimensions)
```

Arguments

dimensions	[integer(1)] Number of decision variables.
------------	---

Value

```
[smoof_multi_objective_function]
```

References

E. Zitzler, K. Deb, and L. Thiele. Comparison of Multiobjective Evolutionary Algorithms: Empirical Results. *Evolutionary Computation*, 8(2):173-195, 2000

makeZDT3Function	<i>ZDT3 Function</i>
------------------	----------------------

Description

Builds and returns the two-objective ZDT3 test problem. For m objective it is defined as follows

$$f(\mathbf{x}) = (f_1(\mathbf{x}_1), f_2(\mathbf{x}))$$

with

$$f_1(\mathbf{x}_1) = \mathbf{x}_1, f_2(\mathbf{x}) = g(\mathbf{x})h(f_1(\mathbf{x}_1), g(\mathbf{x}))$$

where

$$g(\mathbf{x}) = 1 + \frac{9}{m-1} \sum_{i=2}^m \mathbf{x}_i, h(f_1, g) = 1 - \sqrt{\frac{f_1(\mathbf{x})}{g(\mathbf{x})}} - \left(\frac{f_1(\mathbf{x})}{g(\mathbf{x})} \right) \sin(10\pi f_1(\mathbf{x}))$$

and $\mathbf{x}_i \in [0, 1], i = 1, \dots, m$. This function has some discontinuities in the Pareto-optimal front introduced by the sine term in the h function (see above). The front consists of multiple convex parts.

Usage

```
makeZDT3Function(dimensions)
```

Arguments

dimensions	[integer(1)]
	Number of decision variables.

Value

```
[smoof_multi_objective_function]
```

References

E. Zitzler, K. Deb, and L. Thiele. Comparison of Multiobjective Evolutionary Algorithms: Empirical Results. *Evolutionary Computation*, 8(2):173-195, 2000

makeZDT4Function	<i>ZDT4 Function</i>
------------------	----------------------

Description

Builds and returns the two-objective ZDT4 test problem. For m objective it is defined as follows

$$f(\mathbf{x}) = (f_1(\mathbf{x}_1), f_2(\mathbf{x}))$$

with

$$f_1(\mathbf{x}_1) = \mathbf{x}_1, f_2(\mathbf{x}) = g(\mathbf{x})h(f_1(\mathbf{x}_1), g(\mathbf{x}))$$

where

$$g(\mathbf{x}) = 1 + 10(m - 1) + \sum_{i=2}^m (\mathbf{x}_i^2 - 10 \cos(4\pi \mathbf{x}_i)), h(f_1, g) = 1 - \sqrt{\frac{f_1(\mathbf{x})}{g(\mathbf{x})}}$$

and $\mathbf{x}_i \in [0, 1], i = 1, \dots, m$. This function has many Pareto-optimal fronts and is thus suited to test the algorithms ability to tackle multimodal problems.

Usage

```
makeZDT4Function(dimensions)
```

Arguments

dimensions	[integer(1)]
	Number of decision variables.

Value

```
[smoof_multi_objective_function]
```

References

E. Zitzler, K. Deb, and L. Thiele. Comparison of Multiobjective Evolutionary Algorithms: Empirical Results. *Evolutionary Computation*, 8(2):173-195, 2000

makeZDT6Function	<i>ZDT6 Function</i>
------------------	----------------------

Description

Builds and returns the two-objective ZDT6 test problem. For m objective it is defined as follows

$$f(\mathbf{x}) = (f_1(\mathbf{x}), f_2(\mathbf{x}))$$

with

$$f_1(\mathbf{x}) = 1 - \exp(-4\mathbf{x}_1) \sin^6(6\pi\mathbf{x}_1), f_2(\mathbf{x}) = g(\mathbf{x})h(f_1(\mathbf{x}_1), g(\mathbf{x}))$$

where

$$g(\mathbf{x}) = 1 + 9 \left(\frac{\sum_{i=2}^m \mathbf{x}_i}{m-1} \right)^{0.25}, h(f_1, g) = 1 - \left(\frac{f_1(\mathbf{x})}{g(\mathbf{x})} \right)^2$$

and $\mathbf{x}_i \in [0, 1], i = 1, \dots, m$. This function introduced two difficulties (see reference): 1. the density of solutions decreases with the closeness to the Pareto-optimal front and 2. the Pareto-optimal solutions are nonuniformly distributed along the front.

Usage

```
makeZDT6Function(dimensions)
```

Arguments

dimensions [integer(1)]
Number of decision variables.

Value

```
[smoof_multi_objective_function]
```

References

E. Zitzler, K. Deb, and L. Thiele. Comparison of Multiobjective Evolutionary Algorithms: Empirical Results. *Evolutionary Computation*, 8(2):173-195, 2000

makeZettlFunction	<i>Zettl Function</i>
-------------------	-----------------------

Description

The unimodal Zettl Function is based on the definition

$$f(\mathbf{x}) = (\mathbf{x}_1^2 + \mathbf{x}_2^2 - 2\mathbf{x}_1)^2 + 0.25\mathbf{x}_1$$

with box-constraints $\mathbf{x}_i \in [-5, 10], i = 1, 2$.

Usage

```
makeZettlFunction()
```

Value

```
[smoof_single_objective_function]
```

References

H. P. Schwefel, Evolution and Optimum Seeking, John Wiley Sons, 1995.

mnoF	<i>Helper function to create numeric multi-objective optimization test function.</i>
------	--

Description

This is a simplifying wrapper around [makeMultiObjectiveFunction](#). It can be used if the function to generate is purely numeric to save some lines of code.

Usage

```
mnoF(
  name = NULL,
  id = NULL,
  par.len = NULL,
  par.id = "x",
  par.lower = NULL,
  par.upper = NULL,
  n.objectives,
  description = NULL,
  fn,
  vectorized = FALSE,
  noisy = FALSE,
```

```

    fn.mean = NULL,
    minimize = rep(TRUE, n.objectives),
    constraint.fn = NULL,
    ref.point = NULL
)

```

Arguments

name	[character(1)] Function name. Used for the title of plots for example.
id	[character(1) NULL] Optional short function identifier. If provided, this should be a short name without whitespaces and now special characters beside the underscore. Default is NULL, which means no ID at all.
par.len	[integer(1)] Length of parameter vector.
par.id	[character(1)] Optional name of parameter vector. Default is “x”.
par.lower	[numeric] Vector of lower bounds. A single value of length 1 is automatically replicated to n.pars. Default is -Inf.
par.upper	[numeric] Vector of upper bounds. A single value of length 1 is automatically replicated to n.pars. Default is Inf.
n.objectives	[integer(1)] Number of objectives of the multi-objective function.
description	[character(1) NULL] Optional function description.
fn	[function] Objective function.
vectorized	[logical(1)] Can the objective function handle “vector” input, i.e., does it accept matrix of parameters? Default is FALSE.
noisy	[logical(1)] Is the function noisy? Defaults to FALSE.
fn.mean	[function] Optional true mean function in case of a noisy objective function. This functions should have the same mean as fn.
minimize	[logical] Logical vector of length n.objectives indicating if the corresponding objectives shall be minimized or maximized. Default is the vector with all components set to TRUE.
constraint.fn	[function NULL] Function which returns a logical vector indicating whether certain conditions are met or not. Default is NULL, which means, that there are no constraints beside possible box constraints defined via the par.set argument.

ref.point [numeric]
 Optional reference point in the objective space, e.g., for hypervolume computation.

Examples

```
# first we generate the 10d sphere function the long way
fn = makeMultiObjectiveFunction(
  name = "Testfun",
  fn = function(x) c(sum(x^2), exp(sum(x^2))),
  par.set = makeNumericParamSet(
    len = 10L, id = "a",
    lower = rep(-1.5, 10L), upper = rep(1.5, 10L)
  ),
  n.objectives = 2L
)

# ... and now the short way
fn = mnof(
  name = "Testfun",
  fn = function(x) c(sum(x^2), exp(sum(x^2))),
  par.len = 10L, par.id = "a", par.lower = -1.5, par.upper = 1.5,
  n.objectives = 2L
)
```

plot.smoof_function *Generate ggplot2 object.*

Description

Generate ggplot2 object.

Usage

```
## S3 method for class 'smoof_function'
plot(x, ...)
```

Arguments

x [smoof_function]
 Function.

... [any]
 Further parameters passed to the corresponding plot functions.

Value

Nothing

plot1DNumeric	<i>Plot an one-dimensional function.</i>
---------------	--

Description

Plot an one-dimensional function.

Usage

```
plot1DNumeric(
  x,
  show.optimum = FALSE,
  main = getName(x),
  n.samples = 500L,
  ...
)
```

Arguments

x	[smoof_function] Function.
show.optimum	[logical(1)] If the function has a known global optimum, should its location be plotted by a point or multiple points in case of multiple global optima? Default is FALSE.
main	[character(1L)] Plot title. Default is the name of the smoof function.
n.samples	[integer(1)] Number of locations to be sampled. Default is 500.
...	[any] Further paramerters passed to plot function.

Value

Nothing

plot2DNumeric	<i>Plot a two-dimensional numeric function.</i>
---------------	---

Description

Either a contour-plot or a level-plot.

Usage

```
plot2DNumeric(
  x,
  show.optimum = FALSE,
  main = getName(x),
  render.levels = FALSE,
  render.contours = TRUE,
  n.samples = 100L,
  ...
)
```

Arguments

x	[smoof_function] Function.
show.optimum	[logical(1)] If the function has a known global optimum, should its location be plotted by a point or multiple points in case of multiple global optima? Default is FALSE.
main	[character(1L)] Plot title. Default is the name of the smoof function.
render.levels	[logical(1)] Show a level-plot? Default is FALSE.
render.contours	[logical(1)] Render contours? Default is TRUE.
n.samples	[integer(1)] Number of locations per dimension to be sampled. Default is 100.
...	[any] Further paramerters passed to image respectively contour function.

Value

Nothing

plot3D	<i>Surface plot of two-dimensional test function.</i>
--------	---

Description

Surface plot of two-dimensional test function.

Usage

```
plot3D(x, length.out = 100L, package = "plot3D", ...)
```

Arguments

x	[smoof_function] Two-dimensional smoof function.
length.out	[integer(1)] Determines the “smoothness” of the grid. The higher the value, the smoother the function landscape looks like. However, you should avoid setting this parameter to high, since with the contour option set to TRUE the drawing can take quite a lot of time. Default is 100.
package	[character(1)] String describing the package to use for 3D visualization. At the moment “plot3D” (package plot3D) and “plotly” (package plotly) are supported. The latter opens a highly interactive plot in a web browser and is thus suited well to explore a function by hand. Default is “plot3D”.
...	[any] Further parameters passed to method used for visualization (which is determined by the package argument).

Examples

```
library(plot3D)
fn = makeRastriginFunction(dimensions = 2L)
## Not run:
# use the plot3D::persp3D method (default behaviour)
plot3D(fn)
plot3D(fn, contour = TRUE)
plot3D(fn, image = TRUE, phi = 30)

# use plotly::plot_ly for interactive plot
plot3D(fn, package = "plotly")

## End(Not run)
```

resetEvaluationCounter

Reset evaluation counter.

Description

Reset evaluation counter.

Usage

```
resetEvaluationCounter(fn)
```

Arguments

fn	[smoof_counting_function] Wrapped smoof_function.
----	--

shouldBeMinimized	<i>Check if function should be minimized.</i>
-------------------	---

Description

Functions can have an associated global optimum. In this case one needs to know whether the optimum is a minimum or a maximum.

Usage

shouldBeMinimized(fn)

Arguments

fn [smoof_function]
Objective function.

Value

[logical] Each component indicates whether the corresponding objective should be minimized.

smoof_function	<i>Smoof function</i>
----------------	-----------------------

Description

Regular R function with additional classes `smoof_function` and one of `smoof_single_objective_function` or `codesmoof_multi_objective_function`. Both single- and multi-objective functions share the following attributes.

- name** [character(1)] Optional function name.
- id** [character(1)] Short identifier.
- description** [character(1)] Optional function description.
- has.simple.signature** TRUE if the target function expects a vector as input and FALSE if it expects a named list of values.
- par.set** [[ParamSet](#)] Parameter set describing different aspects of the target function parameters, i. e., names, lower and/or upper bounds, types and so on.
- n.objectives** [integer(1)] Number of objectives.
- noisy** [logical(1)] Boolean indicating whether the function is noisy or not.
- fn.mean** [function] Optional true mean function in case of a noisy objective function.
- minimize** [logical(1)] Logical vector of length `n.objectives` indicating which objectives shall be minimized/maximized.
- vectorized** [logical(1)] Can the handle “vector” input, i. e., does it accept matrix of parameters?

constraint.fn [function] Optional function which returns a logical vector with each component indicating whether the corresponding constraint is violated.

Futhermore, single-objective function may contain additional parameters with information on local and/or global optima as well as characterizing tags.

tags [character] Optional character vector of tags or keywords.

global.opt.params [data.frame] Data frame of parameter values of global optima.

global.opt.value [numeric(1)] Function value of global optima.

local.opt.params [data.frame] Data frame of parameter values of local optima.

global.opt.value [numeric] Function values of local optima.

Currently tagging is not possible for multi-objective functions. The only additional attribute may be a reference point:

ref.point [numeric] Optional reference point of length n.objectives.

snof	<i>Helper function to create numeric single-objective optimization test function.</i>
------	---

Description

This is a simplifying wrapper around [makeSingleObjectiveFunction](#). It can be used if the function to generate is purely numeric to save some lines of code.

Usage

```
snof(
  name = NULL,
  id = NULL,
  par.len = NULL,
  par.id = "x",
  par.lower = NULL,
  par.upper = NULL,
  description = NULL,
  fn,
  vectorized = FALSE,
  noisy = FALSE,
  fn.mean = NULL,
  minimize = TRUE,
  constraint.fn = NULL,
  tags = character(0),
  global.opt.params = NULL,
  global.opt.value = NULL,
  local.opt.params = NULL,
  local.opt.values = NULL
)
```

Arguments

name	[character(1)] Function name. Used for the title of plots for example.
id	[character(1) NULL] Optional short function identifier. If provided, this should be a short name without whitespaces and now special characters beside the underscore. Default is NULL, which means no ID at all.
par.len	[integer(1)] Length of parameter vector.
par.id	[character(1)] Optional name of parameter vector. Default is “x”.
par.lower	[numeric] Vector of lower bounds. A single value of length 1 is automatically replicated to n.pars. Default is -Inf.
par.upper	[numeric] Vector of upper bounds. A single value of length 1 is automatically replicated to n.pars. Default is Inf.
description	[character(1) NULL] Optional function description.
fn	[function] Objective function.
vectorized	[logical(1)] Can the objective function handle “vector” input, i.e., does it accept matrix of parameters? Default is FALSE.
noisy	[logical(1)] Is the function noisy? Defaults to FALSE.
fn.mean	[function] Optional true mean function in case of a noisy objective function. This functions should have the same mean as fn.
minimize	[logical(1)] Set this to TRUE if the function should be minimized and to FALSE otherwise. The default is TRUE.
constraint.fn	[function NULL] Function which returns a logical vector indicating whether certain conditions are met or not. Default is NULL, which means, that there are no constraints beside possible box constraints defined via the par.set argument.
tags	[character] Optional character vector of tags or keywords which characterize the function, e.g. “unimodal”, “separable”. See getAvailableTags for a character vector of allowed tags.
global.opt.params	[list numeric data.frame matrix NULL] Default is NULL which means unknown. Passing a numeric vector will be the most frequent case (numeric only functions). In this case there is only a single

global optimum. If there are multiple global optima, passing a numeric matrix is the best choice. Passing a list or a data.frame is necessary if your function is mixed, e.g., it expects both numeric and discrete parameters. Internally, however, each representation is casted to a data.frame for reasons of consistency.

`global.opt.value`
 [numeric(1) | NULL]
 Global optimum value if known. Default is NULL, which means unknown. If only the `global.opt.params` are passed, the value is computed automatically.

`local.opt.params`
 [list | numeric | data.frame | matrix | NULL]
 Default is NULL, which means the function has no local optima or they are unknown. For details see the description of `global.opt.params`.

`local.opt.values`
 [numeric | NULL]
 Value(s) of local optima. Default is NULL, which means unknown. If only the `local.opt.params` are passed, the values are computed automatically.

Examples

```
# first we generate the 10d sphere function the long way
fn = makeSingleObjectiveFunction(
  name = "Testfun",
  fn = function(x) sum(x^2),
  par.set = makeNumericParamSet(
    len = 10L, id = "a",
    lower = rep(-1.5, 10L), upper = rep(1.5, 10L)
  )
)

# ... and now the short way
fn = snof(
  name = "Testfun",
  fn = function(x) sum(x^2),
  par.len = 10L, par.id = "a", par.lower = -1.5, par.upper = 1.5
)
```

<code>violatesConstraints</code>	<i>Checks whether constraints are violated.</i>
----------------------------------	---

Description

Checks whether constraints are violated.

Usage

```
violatesConstraints(fn, values)
```

Arguments

fn	[smoof_function] Objective function.
values	[numeric] List of values.

Value

[logical(1)]

visualizeParetoOptimalFront

Pareto-optimal front visualization.

Description

Quickly visualize the Pareto-optimal front of a bi-criteria objective function by calling the EMOA [nsga2](#) and extracting the approximated Pareto-optimal front.

Usage

```
visualizeParetoOptimalFront(fn, ...)
```

Arguments

fn	[smoof_multi_objective_function] Multi-objective smoof function.
...	[any] Arguments passed to nsga2 .

Value

[[ggplot](#)]

Examples

```
# Here we visualize the Pareto-optimal front of the bi-objective ZDT3 function
fn = makeZDT3Function(dimensions = 3L)
vis = visualizeParetoOptimalFront(fn)

# Alternatively we can pass some more algorithm parameters to the NSGA2 algorithm
vis = visualizeParetoOptimalFront(fn, popsize = 1000L)
```

Index

addCountingWrapper, [6](#), [13](#), [23](#), [27](#)
addLoggingWrapper, [7](#), [17](#), [23](#), [27](#)
autoplot.smoof_function, [8](#)

computeExpectedRunningTime, [11](#)
conversion, [12](#)
convertToMaximization (conversion), [12](#)
convertToMinimization (conversion), [12](#)

doesCountEvaluations, [13](#)

filterFunctionsByTags, [13](#), [62](#)

getAvailableTags, [14](#), [14](#), [25](#), [105](#), [135](#)
getDescription, [15](#)
getGlobalOptimum, [15](#)
getID, [16](#)
getLocalOptimum, [16](#)
getLoggedValues, [17](#)
getLowerBoxConstraints, [17](#)
getMeanFunction, [18](#)
getName, [18](#)
getNumberOfEvaluations, [7](#), [19](#)
getNumberOfObjectives, [19](#)
getNumberOfParameters, [20](#)
getParamSet, [20](#)
getRefPoint, [21](#)
getTags, [21](#)
getUpperBoxConstraints, [22](#)
getWrappedFunction, [22](#)
ggplot, [10](#), [137](#)

hasBoxConstraints, [23](#)
hasConstraints, [23](#)
hasGlobalOptimum, [24](#)
hasLocalOptimum, [24](#)
hasOtherConstraints, [25](#)
hasTags, [25](#)

isMultiobjective, [26](#)
isNoisy, [26](#)

isSingleobjective, [27](#)
isSmoofFunction, [27](#)
isVectorized, [28](#)
isWrappedSmoofFunction, [28](#)

makeAckleyFunction, [29](#)
makeAdjimanFunction, [29](#)
makeAlpine01Function, [30](#)
makeAlpine02Function, [31](#)
makeAluffiPentiniFunction, [31](#)
makeBartelsConnFunction, [32](#)
makeBBOBFunction, [32](#)
makeBealeFunction, [33](#)
makeBentCigarFunction, [34](#)
makeBiObjBBOBFunction, [34](#)
makeBirdFunction, [35](#)
makeBiSphereFunction, [36](#)
makeBK1Function, [37](#)
makeBohachevskyN1Function, [37](#)
makeBoothFunction, [38](#)
makeBraninFunction, [38](#)
makeBrentFunction, [39](#)
makeBrownFunction, [39](#)
makeBukinN2Function, [40](#), [41](#), [42](#)
makeBukinN4Function, [40](#), [41](#), [42](#)
makeBukinN6Function, [40](#), [41](#), [41](#)
makeCarromTableFunction, [42](#)
makeChichinadzeFunction, [42](#)
makeChungReynoldsFunction, [43](#)
makeComplexFunction, [44](#)
makeCosineMixtureFunction, [44](#)
makeCrossInTrayFunction, [45](#)
makeCubeFunction, [45](#)
makeDeckkersAartsFunction, [46](#)
makeDeflectedCorrugatedSpringFunction, [47](#)
makeDentFunction, [47](#)
makeDixonPriceFunction, [48](#)
makeDoubleSumFunction, [49](#)
makeDTLZ1Function, [49](#)

makeDTLZ2Function, 50
makeDTLZ3Function, 51
makeDTLZ4Function, 52
makeDTLZ5Function, 53
makeDTLZ6Function, 54
makeDTLZ7Function, 55
makeEasomFunction, 56
makeED1Function, 57
makeED2Function, 58
makeEggCrateFunction, 59
makeEggholderFunction, 59
makeElAttarVidyasagarDuttaFunction, 60
makeEngvallFunction, 60
makeExponentialFunction, 61
makeFreudensteinRothFunction, 61
makeFunctionsByName, 62
makeGeneralizedDropWaveFunction, 63
makeGiuntaFunction, 63
makeGoldsteinPriceFunction, 64
makeGOMOPFunction, 64
makeGriewankFunction, 65
makeHansenFunction, 66
makeHartmannFunction, 66
makeHimmelblauFunction, 67
makeHolderTableN1Function, 68, 69
makeHolderTableN2Function, 68, 68
makeHosakiFunction, 69
makeHyperEllipsoidFunction, 70
makeInvertedVincentFunction, 70
makeJennrichSampsonFunction, 71
makeJudgeFunction, 72
makeKeaneFunction, 72
makeKearfottFunction, 73
makeKursaweFunction, 73
makeLeonFunction, 74
makeMatyasFunction, 74
makeMcCormickFunction, 75
makeMichalewiczFunction, 75
makeMMF10Function, 76
makeMMF11Function, 77
makeMMF12Function, 77
makeMMF13Function, 78
makeMMF14aFunction, 79
makeMMF14Function, 79
makeMMF15aFunction, 80
makeMMF15Function, 81
makeMMF1eFunction, 82
makeMMF1Function, 82
makeMMF1zFunction, 83
makeMMF2Function, 83
makeMMF3Function, 84
makeMMF4Function, 84
makeMMF5Function, 85
makeMMF6Function, 85
makeMMF7Function, 86
makeMMF8Function, 86
makeMMF9Function, 87
makeModifiedRastriginFunction, 87
makeMOP1Function, 88
makeMOP2Function, 89
makeMOP3Function, 89
makeMOP4Function, 90
makeMOP5Function, 90
makeMOP6Function, 91
makeMOP7Function, 91
makeMPM2Function, 92
makeMultiObjectiveFunction, 93, 127
makeOmniTestFunction, 95
makeParamSet, 94, 104
makePeriodicFunction, 95
makePowellSumFunction, 96
makePriceN1Function, 97, 98
makePriceN2Function, 97, 97, 98
makePriceN4Function, 97, 98, 98
makeRastriginFunction, 99
makeRosenbrockFunction, 99
makeSchafferN2Function, 100
makeSchafferN4Function, 101
makeSchwefelFunction, 101
makeShekelFunction, 102
makeShubertFunction, 103
makeSingleObjectiveFunction, 103, 134
makeSixHumpCamelFunction, 106
makeSphereFunction, 70, 107
makeStyblinskiTangFunction, 107
makeSumOfDifferentSquaresFunction, 108
makeSwiler2014Function, 108
makeSYMPARTrotatedFunction, 109
makeSYMPARTsimpleFunction, 110
makeThreeHumpCamelFunction, 110
makeTrecanniFunction, 111
makeUFFunction, 112
makeViennetFunction, 112
makeWFG1Function, 113
makeWFG2Function, 114
makeWFG3Function, 115

makeWFG4Function, 116
makeWFG5Function, 117
makeWFG6Function, 118
makeWFG7Function, 119
makeWFG8Function, 120
makeWFG9Function, 121
makeZDT1Function, 122
makeZDT2Function, 123
makeZDT3Function, 124
makeZDT4Function, 125
makeZDT6Function, 126
makeZettlFunction, 127
mnof, 127

nsga2, 137

ParamSet, 9, 20, 94, 104, 133
plot.smoof_function, 129
plot1DNumeric, 130
plot2DNumeric, 130
plot3D, 131

resetEvaluationCounter, 7, 132

shouldBeMinimized, 133
smoof-package, 6
smoof_function, 133
smoof_multi_objective_function
 (smoof_function), 133
smoof_single_objective_function
 (smoof_function), 133
snof, 134

violatesConstraints, 136
visualizeParetoOptimalFront, 137