

# Package ‘tabxplor’

July 22, 2025

**Title** User-Friendly Tables with Color Helpers for Data Exploration

**Version** 1.3.0

**Description** Make it easy to deal with multiple cross-tables in data exploration, by creating them, manipulating them, and adding color helpers to highlight important informations (differences from totals, comparisons between lines or columns, contributions to variance, confidence intervals, odds ratios, etc.). All functions are pipe-friendly and render data frames which can be easily manipulated. In the same time, time-taking operations are done with 'data.table' to go faster with big dataframes. Tables can be exported with formats and colors to 'Excel', plot and html.

**URL** <https://github.com/BriceNocenti/tabxplor>

**BugReports** <https://github.com/BriceNocenti/tabxplor/issues>

**License** GPL (>= 3)

**Encoding** UTF-8

**RoxygenNote** 7.3.2

**Suggests** fansi (>= 0.5.0), htmltools (>= 0.5.0), jmvcore (>= 2.4.0), knitr, openxlsx (>= 4.0.0), R6, ggpubr (>= 0.6.0), ggplot2 (>= 3.4.0), cowplot (>= 1.1.1), gtable, grDevices, grid, rmarkdown, rstudioapi (>= 0.1), testthat (>= 3.0.0), labelled (>= 2.0.0)

**Config/testthat/edition** 3

**Imports** dplyr (>= 1.0.3), stringr (>= 1.4.0), crayon (>= 1.3.0), forcats (>= 0.5.0), magrittr (>= 1.5.0), purrr (>= 0.3.0), rlang (>= 0.4.0), tibble (>= 3.1.0), tidyr (>= 1.1.0), vctrs (>= 0.3.0), cli (>= 2.0.0), tidyselect (>= 1.0.0), stringi (>= 1.4.6), pillar (>= 1.6.0), stats (>= 4.0.0), kableExtra (>= 1.3.0), DescTools (>= 0.99.0), data.table

**Depends** R (>= 4.1.0)

**VignetteBuilder** knitr

**Config/potools/style** explicit

**NeedsCompilation** no

**Author** Brice Nocenti [aut, cre]

**Maintainer** Brice Nocenti <brice.nocenti@gmail.com>

**Repository** CRAN

**Date/Publication** 2025-03-09 17:30:02 UTC

## Contents

|                                                  |    |
|--------------------------------------------------|----|
| arrange.tabxplor_tab . . . . .                   | 4  |
| complete_partial_totals . . . . .                | 5  |
| dplyr_col_modify.tabxplor_grouped_tab . . . . .  | 5  |
| dplyr_reconstruct.tabxplor_grouped_tab . . . . . | 6  |
| dplyr_row_slice.tabxplor_grouped_tab . . . . .   | 6  |
| fct_recode_helper . . . . .                      | 7  |
| fmt . . . . .                                    | 8  |
| fmt_get_color_code . . . . .                     | 15 |
| format.tabxplor_fmt . . . . .                    | 16 |
| get_ci_type.data.frame . . . . .                 | 16 |
| get_ci_type.default . . . . .                    | 17 |
| get_ci_type.tabxplor_fmt . . . . .               | 17 |
| get_color.data.frame . . . . .                   | 18 |
| get_color.default . . . . .                      | 18 |
| get_color.tabxplor_fmt . . . . .                 | 19 |
| get_col_var.data.frame . . . . .                 | 19 |
| get_col_var.default . . . . .                    | 20 |
| get_col_var.tabxplor_fmt . . . . .               | 20 |
| get_ref_type.data.frame . . . . .                | 21 |
| get_ref_type.default . . . . .                   | 21 |
| get_ref_type.tabxplor_fmt . . . . .              | 22 |
| get_type.data.frame . . . . .                    | 22 |
| get_type.default . . . . .                       | 23 |
| get_type.tabxplor_fmt . . . . .                  | 23 |
| group_by.tabxplor_tab . . . . .                  | 24 |
| is_refcol.data.frame . . . . .                   | 24 |
| is_refcol.default . . . . .                      | 25 |
| is_refcol.tabxplor_fmt . . . . .                 | 25 |
| is_refrow.data.frame . . . . .                   | 26 |
| is_refrow.default . . . . .                      | 26 |
| is_refrow.tabxplor_fmt . . . . .                 | 27 |
| is_totcol.data.frame . . . . .                   | 27 |
| is_totcol.default . . . . .                      | 28 |
| is_totcol.tabxplor_fmt . . . . .                 | 28 |
| is_totrow.data.frame . . . . .                   | 29 |
| is_totrow.default . . . . .                      | 29 |
| is_totrow.tabxplor_fmt . . . . .                 | 30 |
| is_tottab.data.frame . . . . .                   | 30 |
| is_tottab.default . . . . .                      | 31 |
| is_tottab.tabxplor_fmt . . . . .                 | 31 |
| jmvtab . . . . .                                 | 32 |

|                                              |    |
|----------------------------------------------|----|
| kable.tabxplor_style . . . . .               | 35 |
| mutate.tabxplor_fmt . . . . .                | 36 |
| new_tab . . . . .                            | 37 |
| pillar_shaft.tabxplor_fmt . . . . .          | 38 |
| pillar_shaft.tab_chi2_fmt . . . . .          | 39 |
| print.tabxplor_grouped_tab . . . . .         | 39 |
| print.tabxplor_tab . . . . .                 | 40 |
| relocate.tabxplor_grouped_tab . . . . .      | 41 |
| rename.tabxplor_grouped_tab . . . . .        | 42 |
| rename_with.tabxplor_grouped_tab . . . . .   | 42 |
| rowwise.tabxplor_grouped_tab . . . . .       | 43 |
| rowwise.tabxplor_tab . . . . .               | 43 |
| score_from_lv1 . . . . .                     | 44 |
| select.tabxplor_grouped_tab . . . . .        | 44 |
| set_display.data.frame . . . . .             | 45 |
| set_display.default . . . . .                | 45 |
| set_display.tabxplor_fmt . . . . .           | 46 |
| summarise.tabxplor_grouped_tab . . . . .     | 46 |
| tab . . . . .                                | 47 |
| tab_chi2 . . . . .                           | 52 |
| tab_ci . . . . .                             | 53 |
| tab_compact . . . . .                        | 54 |
| tab_get_wrapped_dimensions . . . . .         | 55 |
| tab_kable . . . . .                          | 55 |
| tab_many . . . . .                           | 57 |
| tab_num . . . . .                            | 64 |
| tab_pct . . . . .                            | 67 |
| tab_plain . . . . .                          | 68 |
| tab_plot . . . . .                           | 71 |
| tab_prepare . . . . .                        | 72 |
| tab_pvalue_lines . . . . .                   | 73 |
| tab_spread . . . . .                         | 73 |
| tab_tot . . . . .                            | 74 |
| tab_totaltab . . . . .                       | 75 |
| tab_wrap_text . . . . .                      | 76 |
| tab_xl . . . . .                             | 77 |
| tbl_format_body.tabxplor_tab . . . . .       | 78 |
| tbl_format_footer.tabxplor_tab . . . . .     | 79 |
| tbl_sum.tabxplor_grouped_tab . . . . .       | 80 |
| tbl_sum.tabxplor_tab . . . . .               | 80 |
| ungroup.tabxplor_grouped_tab . . . . .       | 81 |
| vec_arith.tabxplor_fmt . . . . .             | 81 |
| vec_cast.character.tabxplor_fmt . . . . .    | 82 |
| vec_cast.double.tabxplor_fmt . . . . .       | 83 |
| vec_cast.integer.tabxplor_fmt . . . . .      | 83 |
| vec_cast.tabxplor_fmt.double . . . . .       | 84 |
| vec_cast.tabxplor_fmt.integer . . . . .      | 84 |
| vec_cast.tabxplor_fmt.tabxplor_fmt . . . . . | 85 |

|                                                |           |
|------------------------------------------------|-----------|
| vec_math.tabxplor_fmt . . . . .                | 85        |
| vec_proxy_compare.tabxplor_fmt . . . . .       | 86        |
| vec_proxy_equal.tabxplor_fmt . . . . .         | 86        |
| vec_ptype2.double.tabxplor_fmt . . . . .       | 87        |
| vec_ptype2.integer.tabxplor_fmt . . . . .      | 87        |
| vec_ptype2.tabxplor_fmt.double . . . . .       | 88        |
| vec_ptype2.tabxplor_fmt.integer . . . . .      | 88        |
| vec_ptype2.tabxplor_fmt.tabxplor_fmt . . . . . | 89        |
| vec_ptype_abbrev.tabxplor_fmt . . . . .        | 89        |
| vec_ptype_full.tabxplor_fmt . . . . .          | 90        |
| [.tabxplor_grouped_tab . . . . .               | 90        |
| [<-.tabxplor_grouped_tab . . . . .             | 91        |
| [[<-.tabxplor_grouped_tab . . . . .            | 92        |
| \$.tabxplor_fmt . . . . .                      | 92        |
| <b>Index</b>                                   | <b>93</b> |

---

|                      |                                              |
|----------------------|----------------------------------------------|
| arrange.tabxplor_tab | <i>arrange method for class tabxplor_tab</i> |
|----------------------|----------------------------------------------|

---

**Description**

arrange method for class tabxplor\_tab

**Usage**

```
## S3 method for class 'tabxplor_tab'
arrange(
  .data,
  ...,
  .by_group = TRUE,
  .by_totals = TRUE,
  .only_main_display = TRUE,
  .locale = NULL
)
```

**Arguments**

- .data            A tibble of class tabxplor\_tab.
- ...            [<data-masking>](#) Variables, or functions of variables. Use desc() to sort a variable in descending order.
- .by\_group       By default, will sort first by grouping variable. Set to FALSE to avoid this behaviour.
- .by\_totals      By default, will put totals at the end of their group. Set to FALSE to avoid this behaviour.

|                                 |                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>.only_main_display</code> | By default, only the rows with the same display than the first row are arranged : if the first row of the group displays percentages, rows with n or pvalues are kept at the same place (typically, at the end of the group). Rows with the text "row_pct", "n" or "pvalue" in the row_var name are also kept at the same place. Set to FALSE to avoid this behaviour. |
| <code>.locale</code>            | The locale to sort character vectors in.                                                                                                                                                                                                                                                                                                                               |

**Value**

A tibble of class `tabxplor__tab` or `tabxplor_grouped_tab`.

---

|                                      |
|--------------------------------------|
| <code>complete_partial_totals</code> |
| <i>Complete partial total rows</i>   |

---

**Description**

Complete partial total rows

**Usage**

`complete_partial_totals(tabs)`

**Arguments**

`tabs` A table or data.frame containing `tabxplor_fmt` columns.

**Value**

The table with completed total rows, total tables, and reference rows.

---

|                                                               |
|---------------------------------------------------------------|
| <code>dplyr_col_modify.tabxplor_grouped_tab</code>            |
| <i>dplyr_col_modify method for class tabxplor_grouped_tab</i> |

---

**Description**

`dplyr_col_modify` method for class `tabxplor_grouped_tab`

**Usage**

```
## S3 method for class 'tabxplor_grouped_tab'
dplyr_col_modify(data, cols)
```

**Arguments**

|      |                                                                                  |
|------|----------------------------------------------------------------------------------|
| data | A data frame.                                                                    |
| cols | A named list used modify columns. A NULL value should remove an existing column. |

**Value**

An object of class `tabxplor_grouped_tab`.

---

`dplyr_reconstruct.tabxplor_grouped_tab`  
*dplyr\_reconstruct method for class tabxplor\_grouped\_tab*

---

**Description**

`dplyr_reconstruct` method for class `tabxplor_grouped_tab`

**Usage**

```
## S3 method for class 'tabxplor_grouped_tab'
dplyr_reconstruct(data, template)
```

**Arguments**

|          |                                          |
|----------|------------------------------------------|
| data     | A data frame.                            |
| template | Template to use for restoring attributes |

**Value**

An object of class `tabxplor_grouped_tab`.

---

`dplyr_row_slice.tabxplor_grouped_tab`  
*dplyr\_row\_slice method for class tabxplor\_grouped\_tab*

---

**Description**

`dplyr_row_slice` method for class `tabxplor_grouped_tab`

**Usage**

```
## S3 method for class 'tabxplor_grouped_tab'
dplyr_row_slice(data, i, ...)
```

**Arguments**

|      |                                                              |
|------|--------------------------------------------------------------|
| data | A data frame.                                                |
| i    | A numeric or logical vector that indexes the rows of . data. |
| ...  | Future parameters.                                           |

**Value**

An object of class `tabxplor_grouped_tab`.

---

|                   |                                                       |
|-------------------|-------------------------------------------------------|
| fct_recode_helper | <i>fct_recode helper to recode multiple variables</i> |
|-------------------|-------------------------------------------------------|

---

**Description**

fct\_recode helper to recode multiple variables

**Usage**

```
fct_recode_helper(
  data,
  .cols = -where(is.numeric),
  name_in,
  name_out,
  style = c("mutate", "base"),
  reminder = TRUE,
  cat = TRUE
)
```

**Arguments**

|          |                                                                                                                                                                                                                        |
|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| data     | The data frame.                                                                                                                                                                                                        |
| .cols    | <a href="#">&lt;tidy-select&gt;</a> The variables to recode.                                                                                                                                                           |
| name_in  | The name of the input data frame. Default to the expression given in data.                                                                                                                                             |
| name_out | The name of the output data frame, if different from the input data frame.                                                                                                                                             |
| style    | Default is to use <code>dplyr::mutate()</code> . Set to <code>base</code> to use <code>data\$var &lt;- style</code> .                                                                                                  |
| reminder | By default, a reminder of the syntax (" <code>new</code> " = " <code>old</code> ") is printed. Set to <code>FALSE</code> to remove it.                                                                                 |
| cat      | By default the result is written in the console if there are less than 6 variables, written in a temporary file and opened otherwise. Set to <code>false</code> to get a data frame with a character variable instead. |

**Value**

When the number of variables is less than 5, a text in console as a side effect. With more than 5 variables, a temporary R file. A tibble with the recode text as a character variable is returned invisibly (or as main result if `cat = TRUE`). If the labelled package is installed, the variable label is used as title in a comment.

fmt

*Create a vector of class formatted numbers***Description**

fmt vectors, of class `tabxplor_fmt`, powers **tabxplor** and **tab** tibbles. As a **record**, they stores all data necessary to calculate percentages, Chi2 metadata or confidence intervals, but also to format and color the table to help the user read it. You can access this data with `vctrs::field`, or change it with `vctrs::field<-`. A fmt vector have 13 fields : `n`, `digits`, `display`, `wn`, `pct`, `mean`, `diff`, `ctr`, `var`, `ci`, `in_totrow`, `in_tottab`, `in_refrow`. Other arguments are attributes, attached not to each value, but to the whole vector, like `type`, `totcol` or `color`. You can get them with `attr` and modify them with `attr<-`. Special functions listed below are made to facilitate programming with **tabxplor** formatted numbers. `taxplfmt` vectors can use all standard operations, like `+`, `-`, `sum()`, or `c()`, using `vctrs`.

**Usage**

```
fmt(
  n = integer(),
  type = "n",
  digits = rep(0L, length(n)),
  display = dplyr::case_when(type == "mean" ~ "mean", type %in% c("row", "col", "all",
    "all_tabs") ~ "pct", TRUE ~ "n"),
  wn = rep(NA_real_, length(n)),
  pct = rep(NA_real_, length(n)),
  mean = rep(NA_real_, length(n)),
  diff = rep(NA_real_, length(n)),
  ctr = rep(NA_real_, length(n)),
  var = rep(NA_real_, length(n)),
  ci = rep(NA_real_, length(n)),
  rr = rep(NA_real_, length(n)),
  or = rep(NA_real_, length(n)),
  in_totrow = rep(FALSE, length(n)),
  in_tottab = rep(FALSE, length(n)),
  in_refrow = rep(FALSE, length(n)),
  comp_all = NA,
  ref = "",
  ci_type = "",
  col_var = "",
  totcol = FALSE,
  refcol = FALSE,
  color = ""
)

is_fmt(x)

get_num(x)
```

```
set_num(x, value)
get_type(x, ...)
set_type(x, type)
is_totrow(x, ...)
as_totrow(x, in_totrow = TRUE)
is_tottab(x, ...)
as_tottab(x, in_tottab = TRUE)
set_display(x, value)
is_totcol(x, ...)
as_totcol(x, totcol = TRUE)
is_refrow(x, ...)
as_refrow(x, in_refrow = TRUE)
get_comp_all(x, replace_na = TRUE)
set_comp_all(x, comp_all = FALSE)
get_ref_type(x, ...)
set_diff_type(x, ref)
get_ci_type(x, ...)
set_ci_type(x, ci_type)
get_col_var(x, ...)
set_col_var(x, col_var)
is_refcol(x, ...)
as_refcol(x, refcol = TRUE)
get_color(x, ...)
set_color(x, color)
```

```
get_digits(x)
```

```
set_digits(x, value)
```

### Arguments

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>n</code>         | The underlying count, as an integer vector of length <code>n()</code> . It is used to calculate confidence intervals.                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <code>type</code>      | The type of the column, which defines the type of background calculation to be made (as a single string, since it's not a field but an attribute) : <ul style="list-style-type: none"> <li>• <code>"n"</code>: counts</li> <li>• <code>"mean"</code>: mean column (from numeric variables)</li> <li>• <code>"row"</code>: row percentages</li> <li>• <code>"col"</code>: column percentages</li> <li>• <code>"all"</code>: frequencies by subtable/group (i.e. by <code>tab_vars</code>)</li> <li>• <code>"all_tabs"</code>: frequencies for the whole table</li> </ul> |
| <code>digits</code>    | The number of digits, as an integer, or an integer vector the length of <code>n</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <code>display</code>   | The display type : the name of the field you want to show when printing the vector. Among <code>"n"</code> , <code>"wn"</code> , <code>"pct"</code> , <code>"diff"</code> , <code>"ctr"</code> , <code>"mean"</code> , <code>"var"</code> , <code>"ci"</code> , <code>"pct_ci"</code> (percentages with visible confidence interval), <code>"mean_ci"</code> (means with visible confidence interval). As a single string, or a character vector the length of <code>n</code> .                                                                                         |
| <code>wn</code>        | The underlying weighted counts, as a double vector the length of <code>n</code> . It is used in certain operations on <code>fmt</code> , like means.                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>pct</code>       | The percentages, as a double vector the length of <code>n</code> . Calculate with <code>tab_pct</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <code>mean</code>      | The means, as a double vector the length of <code>n</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <code>diff</code>      | The differences (from totals or first cells), as a double vector the length of <code>n</code> . Used to set colors for means and row or col percentages. Calculate with <code>tab_pct</code> .                                                                                                                                                                                                                                                                                                                                                                          |
| <code>ctr</code>       | The contributions of cells to (sub)tables variances, as a double vector the length of <code>n</code> . Used to print colors when <code>color = "contrib"</code> . The mean contribution of each (sub)table is written on total rows (then, colors don't print well without total rows). Calculate with <code>tab_chi2</code> .                                                                                                                                                                                                                                          |
| <code>var</code>       | The cells variances, as a double vector the length of <code>n</code> . Used with <code>type = "mean"</code> to calculate confidence intervals. Calculate with <code>tab_plain</code> .                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>ci</code>        | The confidence intervals, as a double vector the length of <code>n</code> . Used to print colors ( <code>"diff_ci"</code> , <code>"after_ci"</code> ). Calculate with <code>tab_ci</code> .                                                                                                                                                                                                                                                                                                                                                                             |
| <code>rr</code>        | The relative risk, as a double vector the length of <code>n</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <code>or</code>        | The odds ratio or relative risk ratio, as a double vector the length of <code>n</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <code>in_totrow</code> | TRUE when the cell is part of a total row                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <code>in_tottab</code> | TRUE when the cell is part of a total table                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <code>in_refrow</code> | TRUE when the cell is part of a reference row (cf. <code>ref</code> )                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| comp_all   | FALSE when the comparison level is the subtable/group, TRUE when it is the whole table                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| ref        | The type of difference of the vector. Cf. <a href="#">tab</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| ci_type    | The type of confidence intervals of the vector (calculate with <a href="#">tab_ci</a> ) : <ul style="list-style-type: none"> <li>• "" or "no": no ci have been calculated</li> <li>• "cell": absolute confidence intervals of cells percentages.</li> <li>• "diff": confidence intervals of the difference between a cell and the relative total cell (or relative first cell when ref = "first").</li> <li>• "auto": "diff" for means and row/col percentages, "cell" for frequencies ("all", "all_tabs").</li> </ul>                                                                                                                                                      |
| col_var    | The name of the col_var used to calculate the vector                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| totcol     | TRUE when the vector is a total column                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| refcol     | TRUE when the vector is a reference column                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| color      | The type of color to print : <ul style="list-style-type: none"> <li>• "no": no colors are printed.</li> <li>• "diff": color percentages and means based on cells differences from totals (or from first cells when ref = "first").</li> <li>• "diff_ci": color pct and means based on cells differences from totals or first cells, removing coloring when the confidence interval of this difference is higher than the difference itself.</li> <li>• "after_ci": idem, but cut off the confidence interval from the difference first.</li> <li>• "contrib": color cells based on their contribution to variance (except mean columns, from numeric variables).</li> </ul> |
| x          | The object to test, to get a field in, or to modify.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| value      | The value you want to inject in some fmt vector's vctrs::field or attribute using a given "set" function.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| ...        | Used in methods to add arguments in the future.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| replace_na | By default, <a href="#">get_comp_all</a> takes NA in comparison level to be a FALSE (=comparison at subtables/groups level). Set to FALSE to avoid this behavior.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

## Value

A vector of class `tabxplor_fmt`.

A logical vector.

A double vector.

A modified fmt vector.

A character vector with the vectors type.

A modified fmt vector.

A logical vector with the fmt vectors totrow field.

A modified fmt vector with totrow field changed.

A logical vector with the fmt vectors tottab field.

A modified fmt vector with tottab field changed.

The entered objects, with all fmt vectors with the wanted display.

A logical vector with the fmt vectors totcol attribute.

A modified fmt vector with totcol attribute changed.

A logical vector with the fmt vectors in\_refrow field

A modified fmt vector with in\_refrow field changed.

A modified fmt vector with comp attribute changed.

A logical vector with the fmt vectors type attributes

A modified fmt vector.

A logical vector with the fmt vectors ci\_type attributes

A modified fmt vector.

A logical vector with the fmt vectors col\_var attributes

A modified fmt vector.

A logical vector with the fmt vectors is\_refcol attributes

A modified fmt vector.

A logical vector with the fmt vectors color attributes

A modified fmt vector.

## Functions

- `is_fmt()`: a test function for class `fmt`.
- `get_num()`: get the currently displayed field
- `set_num()`: set the currently displayed field (not changing display type)
- `get_type()`: get types of fmt columns (at fmt level or tab level)
- `set_type()`: set the column type attribute of a fmt vector
- `is_totrow()`: test function to detect cells in total rows (at fmt level or tab level)
- `as_totrow()`: set the "in\_totrow" field (belong to total row)
- `is_tottab()`: test function to detect cells in total tables (at fmt level or tab level)
- `as_tottab()`: set the "in\_tottab" field (belong to total table)
- `set_display()`: set the "display" vctrs::field of a fmt vector, or of all of them in the whole tibble.
- `is_totcol()`: test function for total columns (at fmt level or tab level)
- `as_totcol()`: set the "totcol" attribute of a fmt vector
- `is_refrow()`: test function to detect cells in reference rows (at fmt level or tab level)
- `as_refrow()`: set the "in\_refrow" field (belong to reference row)
- `get_comp_all()`: get comparison level of fmt columns
- `set_comp_all()`: set the comparison level attribute of a fmt vector

- `get_ref_type()`: get differences type of fmt columns (at fmt level or tab level)
- `set_diff_type()`: set the differences type attribute of a fmt vector
- `get_ci_type()`: get confidence intervals type of fmt columns (at fmt level or tab level)
- `set_ci_type()`: set the confidence intervals type attribute of a fmt vector
- `get_col_var()`: get names of column variable of fmt columns (at fmt level or tab level)
- `set_col_var()`: set the "col\_var" attribute of a fmt vector
- `is_refcol()`: test function for reference columns (at fmt level or tab level)
- `as_refcol()`: set the "ref\_col" attribute of a fmt vector
- `get_color()`: get color (at fmt level or tab level)
- `set_color()`: set the "color" attribute of a fmt vector
- `get_digits()`: get the "digits" field
- `set_digits()`: set the "digits" field

## Examples

```
library(dplyr)

f <- fmt(n = c(7, 19, 2), type = "row", pct = c(0.25, 0.679, 0.07))
f

# To get the currently displayed field :
get_num(f)

# To modify the currently displayed field :
set_num(f, c(1, 0, 0))

# See all the underlying fields of a fmt vector (a data frame with a number of rows
# equal to the length of the vector) :
vctrs::vec_data(f)

# To get the numbers of digits :
vctrs::field(f, "digits")
f$digits

# To get the count :
vctrs::field(f, "n")
f$n

# To get the display :
vctrs::field(f, "display")
f$display

# To modify a field, you can use `dplyr::mutate` on the fmt vector,
# referring to the names of the columns of the underlying data.frame (`vctrs::vec_data`) :
vctrs::`field<-`(f, "pct", c(1, 0, 0))
mutate(f, pct = c(1, 0, 0))
```

```

# See all the attributes of a fmt vector :
attributes(f)

# To modify the "type" attribute of a fmt vector :
set_type(f, "col")

# To modify the "color" attribute of a fmt vector :
set_color(f, "contrib")


tabs <- tab(starwars, sex, hair_color, gender, na = "drop", pct = "row",
            other_if_less_than = 5)

# To identify the total columns, and work with them :
is_totcol(tabs)
tabs %>% mutate(across(where(is_totcol), ~ "total column"))

# To identify the total rows, and work with them :
is_totrow(tabs)
tabs %>%
  mutate(across(
    where(is_fmt),
    ~ if_else(is_totrow(.), true = "into_total_row", false = "normal_cell")
  ))

# To identify the total tables, and work with them :
tottabs <- is_tottab(tabs)
tabs %>% tibble::add_column(tottabs) %>%
  mutate(total = if_else(tottabs, "part of a total table", "normal cell"))

# To access the displayed numbers, as numeric vectors :
tabs %>% mutate(across(where(is_fmt), get_num))

# To access the displayed numbers, as character vectors (without colors) :
tabs %>% mutate(across(where(is_fmt), format))

# To access the (non-displayed) differences of the cells percentages from totals :
tabs %>% mutate(across(where(is_fmt), ~ vctrs::field(., "diff")))


# To do more complex operations, like creating a new column with standard deviation and
# print it with 2 decimals, use `dplyr::mutate` on all the fmt columns of a table :

tab_num(forcats::gss_cat, race, c(age, tvhours), marital, digits = 1L, comp = "all") |>
  dplyr::mutate(dplyr::across( #Mutate over the whole table.
    c(age, tvhours),
    ~ dplyr::mutate(.,          #Mutate over each fmt vector's underlying data.frame.
      var      = sqrt(var),
      display = "var",
      digits   = 2L) |>
    set_color("no"),

```

```

      .names = "{.col}_sd"
    ))

```

---

|                    |                                            |
|--------------------|--------------------------------------------|
| fmt_get_color_code | <i>Get HTML Color Code of a fmt vector</i> |
|--------------------|--------------------------------------------|

---

## Description

Get HTML Color Code of a fmt vector

## Usage

```
fmt_get_color_code(x, type = "text", theme = "light", html_24_bit = NULL)
```

## Arguments

|             |                                                                                                                                                                                                             |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x           | The fmt vector to get the html color codes from.                                                                                                                                                            |
| type        | The style type in set_color_style and get_color_style, "text" to color the text, "bg" to color the background.                                                                                              |
| theme       | For set_color_style and get_color_style, is your console or html table background "light" or "dark" ? Default to RStudio theme.                                                                             |
| html_24_bit | Use 24bits colors palettes for html tables : set to "green_red" or "blue_red". Only with mode = "color_code" (not mode = "crayon") and theme = "light". Default to getOption("tabxplor.color_html_24_bit"). |

## Value

A character vector with html color codes, of the length of the initial vector.

## Examples

```

tabs <- tab(forcats::gss_cat, race, marital, pct = "row", color = "diff")
dplyr::mutate(tabs, across(where(is_fmt), fmt_get_color_code))

```

---

```
format.tabxplor_fmt
```

*Print method for class tabxplor\_fmt*

---

### Description

Print method for class tabxplor\_fmt

### Usage

```
## S3 method for class 'tabxplor_fmt'
format(x, ..., html = FALSE, na = NA, special_formatting = FALSE)
```

### Arguments

|                    |                                                                                                               |
|--------------------|---------------------------------------------------------------------------------------------------------------|
| x                  | A fmt object.                                                                                                 |
| ...                | Other parameters.                                                                                             |
| html               | Should html tags be added (to print confidence intervals as subscripts) ?                                     |
| na                 | How NAs should be printed. Default to NA.                                                                     |
| special_formatting | Set to TRUE to print more verbose results, like indicating which is the reference row or col for differences. |

### Value

The fmt printed in a character vector.

---

```
get_ci_type.data.frame
```

*Get confidence intervals type of fmt columns*

---

### Description

Get confidence intervals type of fmt columns

### Usage

```
## S3 method for class 'data.frame'
get_ci_type(x, ...)
```

### Arguments

|     |                                                      |
|-----|------------------------------------------------------|
| x   | The object to test, to get a field in, or to modify. |
| ... | Used in methods to add arguments in the future.      |

### Value

A character vector with the ci\_type attributes.

---

|                     |                                                     |
|---------------------|-----------------------------------------------------|
| get_ci_type.default | <i>Get confidence intervals type of fmt columns</i> |
|---------------------|-----------------------------------------------------|

---

**Description**

Get confidence intervals type of fmt columns

**Usage**

```
## Default S3 method:  
get_ci_type(x, ...)
```

**Arguments**

|     |                                                      |
|-----|------------------------------------------------------|
| x   | The object to test, to get a field in, or to modify. |
| ... | Used in methods to add arguments in the future.      |

**Value**

A single character with the ci\_type attribute.

---

|                          |                                                     |
|--------------------------|-----------------------------------------------------|
| get_ci_type.tabxplor_fmt | <i>Get confidence intervals type of fmt columns</i> |
|--------------------------|-----------------------------------------------------|

---

**Description**

Get confidence intervals type of fmt columns

**Usage**

```
## S3 method for class 'tabxplor_fmt'  
get_ci_type(x, ...)
```

**Arguments**

|     |                                                      |
|-----|------------------------------------------------------|
| x   | The object to test, to get a field in, or to modify. |
| ... | Used in methods to add arguments in the future.      |

**Value**

A single character with the ci\_type attribute.

---

|                      |                  |
|----------------------|------------------|
| get_color.data.frame | <i>Get color</i> |
|----------------------|------------------|

---

**Description**

Get color

**Usage**

```
## S3 method for class 'data.frame'  
get_color(x, ...)
```

**Arguments**

|     |                                                      |
|-----|------------------------------------------------------|
| x   | The object to test, to get a field in, or to modify. |
| ... | Used in methods to add arguments in the future.      |

**Value**

A character vector with the color attributes.

---

|                   |                  |
|-------------------|------------------|
| get_color.default | <i>Get color</i> |
|-------------------|------------------|

---

**Description**

Get color

**Usage**

```
## Default S3 method:  
get_color(x, ...)
```

**Arguments**

|     |                                                      |
|-----|------------------------------------------------------|
| x   | The object to test, to get a field in, or to modify. |
| ... | Used in methods to add arguments in the future.      |

**Value**

A single character with the color attribute.

---

```
get_color.tabxplor_fmt
```

*Get color*

---

**Description**

Get color

**Usage**

```
## S3 method for class 'tabxplor_fmt'  
get_color(x, ...)
```

**Arguments**

|     |                                                      |
|-----|------------------------------------------------------|
| x   | The object to test, to get a field in, or to modify. |
| ... | Used in methods to add arguments in the future.      |

**Value**

A single character with the color attribute.

---

```
get_col_var.data.frame
```

*Get names of column variable of fmt columns*

---

**Description**

Get names of column variable of fmt columns

**Usage**

```
## S3 method for class 'data.frame'  
get_col_var(x, ...)
```

**Arguments**

|     |                                                      |
|-----|------------------------------------------------------|
| x   | The object to test, to get a field in, or to modify. |
| ... | Used in methods to add arguments in the future.      |

**Value**

A character vector with the col\_var attributes.

---

|                     |                                                    |
|---------------------|----------------------------------------------------|
| get_col_var.default | <i>Get names of column variable of fmt columns</i> |
|---------------------|----------------------------------------------------|

---

**Description**

Get names of column variable of fmt columns

**Usage**

```
## Default S3 method:
get_col_var(x, ...)
```

**Arguments**

|     |                                                      |
|-----|------------------------------------------------------|
| x   | The object to test, to get a field in, or to modify. |
| ... | Used in methods to add arguments in the future.      |

**Value**

A single character with the col\_var attribute.

---

|                          |                                                    |
|--------------------------|----------------------------------------------------|
| get_col_var.tabxplor_fmt | <i>Get names of column variable of fmt columns</i> |
|--------------------------|----------------------------------------------------|

---

**Description**

Get names of column variable of fmt columns

**Usage**

```
## S3 method for class 'tabxplor_fmt'
get_col_var(x, ...)
```

**Arguments**

|     |                                                      |
|-----|------------------------------------------------------|
| x   | The object to test, to get a field in, or to modify. |
| ... | Used in methods to add arguments in the future.      |

**Value**

A single character with the col\_var attribute.

---

`get_ref_type.data.frame`*Get differences type of fmt columns*

---

**Description**

Get differences type of fmt columns

**Usage**

```
## S3 method for class 'data.frame'  
get_ref_type(x, ...)
```

**Arguments**

|                  |                                                      |
|------------------|------------------------------------------------------|
| <code>x</code>   | The object to test, to get a field in, or to modify. |
| <code>...</code> | Used in methods to add arguments in the future.      |

**Value**

A character vector with the ref attribute.

---

`get_ref_type.default` *Get differences type of fmt columns*

---

**Description**

Get differences type of fmt columns

**Usage**

```
## Default S3 method:  
get_ref_type(x, ...)
```

**Arguments**

|                  |                                                      |
|------------------|------------------------------------------------------|
| <code>x</code>   | The object to test, to get a field in, or to modify. |
| <code>...</code> | Used in methods to add arguments in the future.      |

**Value**

A single character with the ref attribute.

---

```
get_ref_type.tabxplor_fmt
```

*Get differences type of fmt columns*

---

### Description

Get differences type of fmt columns

### Usage

```
## S3 method for class 'tabxplor_fmt'
get_ref_type(x, ...)
```

### Arguments

x                      The object to test, to get a field in, or to modify.  
 ...                    Used in methods to add arguments in the future.

### Value

A single character with the ref attribute.

---

```
get_type.data.frame      Get types of fmt columns
```

---

### Description

Get types of fmt columns

### Usage

```
## S3 method for class 'data.frame'
get_type(x, ...)
```

### Arguments

x                      The object to test, to get a field in, or to modify.  
 ...                    Used in methods to add arguments in the future.

### Value

A character vector with the data.frame column's types.

---

|                  |                                 |
|------------------|---------------------------------|
| get_type.default | <i>Get types of fmt columns</i> |
|------------------|---------------------------------|

---

**Description**

Get types of fmt columns

**Usage**

```
## Default S3 method:  
get_type(x, ...)
```

**Arguments**

|     |                                                      |
|-----|------------------------------------------------------|
| x   | The object to test, to get a field in, or to modify. |
| ... | Used in methods to add arguments in the future.      |

**Value**

An empty character vector.

---

|                       |                                 |
|-----------------------|---------------------------------|
| get_type.tabxplor_fmt | <i>Get types of fmt columns</i> |
|-----------------------|---------------------------------|

---

**Description**

Get types of fmt columns

**Usage**

```
## S3 method for class 'tabxplor_fmt'  
get_type(x, ...)
```

**Arguments**

|     |                                                      |
|-----|------------------------------------------------------|
| x   | The object to test, to get a field in, or to modify. |
| ... | Used in methods to add arguments in the future.      |

**Value**

A single string with the vector's type.

---

group\_by.tabxplor\_tab *group\_by method for class tabxplor\_tab*

---

### Description

group\_by method for class tabxplor\_tab

### Usage

```
## S3 method for class 'tabxplor_tab'
group_by(.data, ..., .add = FALSE, .drop = dplyr::group_by_drop_default(.data))
```

### Arguments

|       |                                                                                                                                                          |
|-------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| .data | A tibble of class tabxplor_tab.                                                                                                                          |
| ...   | Variables or computations to group by.                                                                                                                   |
| .add  | When FALSE, the default, group_by() will override existing groups. To add to the existing groups, use .add = TRUE.                                       |
| .drop | Drop groups formed by factor levels that don't appear in the data? The default is TRUE except when .data has been previously grouped with .drop = FALSE. |

### Value

A tibble of class tabxplor\_grouped\_tab.

---

is\_refcol.data.frame *Test function for reference columns*

---

### Description

Test function for reference columns

### Usage

```
## S3 method for class 'data.frame'
is_refcol(x, ...)
```

### Arguments

|     |                                                      |
|-----|------------------------------------------------------|
| x   | The object to test, to get a field in, or to modify. |
| ... | Used in methods to add arguments in the future.      |

### Value

A character vector with the ref\_col attributes.

---

|                   |                                            |
|-------------------|--------------------------------------------|
| is_refcol.default | <i>Test function for reference columns</i> |
|-------------------|--------------------------------------------|

---

**Description**

Test function for reference columns

**Usage**

```
## Default S3 method:  
is_refcol(x, ...)
```

**Arguments**

|     |                                                      |
|-----|------------------------------------------------------|
| x   | The object to test, to get a field in, or to modify. |
| ... | Used in methods to add arguments in the future.      |

**Value**

A single character with the ref\_col attribute.

---

|                        |                                            |
|------------------------|--------------------------------------------|
| is_refcol.tabxplor_fmt | <i>Test function for reference columns</i> |
|------------------------|--------------------------------------------|

---

**Description**

Test function for reference columns

**Usage**

```
## S3 method for class 'tabxplor_fmt'  
is_refcol(x, ...)
```

**Arguments**

|     |                                                      |
|-----|------------------------------------------------------|
| x   | The object to test, to get a field in, or to modify. |
| ... | Used in methods to add arguments in the future.      |

**Value**

A single character with the ref\_col attribute.

---

`is_refrow.data.frame`     *Test function to detect cells in reference rows*

---

### Description

Test function to detect cells in reference rows

### Usage

```
## S3 method for class 'data.frame'
is_refrow(x, ..., partial = TRUE)
```

### Arguments

|                      |                                                                                |
|----------------------|--------------------------------------------------------------------------------|
| <code>x</code>       | The object to test, to get a field in, or to modify.                           |
| <code>...</code>     | Used in methods to add arguments in the future.                                |
| <code>partial</code> | Should partial reference rows be counted as reference rows ? Default to FALSE. |

### Value

A list of logical vectors with the `in_refrow` fields.

---

`is_refrow.default`     *Test function to detect cells in reference rows*

---

### Description

Test function to detect cells in reference rows

### Usage

```
## Default S3 method:
is_refrow(x, ...)
```

### Arguments

|                  |                                                      |
|------------------|------------------------------------------------------|
| <code>x</code>   | The object to test, to get a field in, or to modify. |
| <code>...</code> | Used in methods to add arguments in the future.      |

### Value

A logical vector with FALSE, the length of `x`.

---

`is_refrow.tabxplor_fmt`*Test function to detect cells in reference rows*

---

**Description**

Test function to detect cells in reference rows

**Usage**

```
## S3 method for class 'tabxplor_fmt'  
is_refrow(x, ...)
```

**Arguments**

|                  |                                                      |
|------------------|------------------------------------------------------|
| <code>x</code>   | The object to test, to get a field in, or to modify. |
| <code>...</code> | Used in methods to add arguments in the future.      |

**Value**

A logical vector with the `in_refrow` field.

---

`is_totcol.data.frame`    *Test function for total columns*

---

**Description**

Test function for total columns

**Usage**

```
## S3 method for class 'data.frame'  
is_totcol(x, ...)
```

**Arguments**

|                  |                                                      |
|------------------|------------------------------------------------------|
| <code>x</code>   | The object to test, to get a field in, or to modify. |
| <code>...</code> | Used in methods to add arguments in the future.      |

**Value**

A logical vector, with the `data.frame` column's `totcol` attributes.

---

|                   |                                        |
|-------------------|----------------------------------------|
| is_totcol.default | <i>Test function for total columns</i> |
|-------------------|----------------------------------------|

---

**Description**

Test function for total columns

**Usage**

```
## Default S3 method:
is_totcol(x, ...)
```

**Arguments**

|     |                                                      |
|-----|------------------------------------------------------|
| x   | The object to test, to get a field in, or to modify. |
| ... | Used in methods to add arguments in the future.      |

**Value**

A single logical vector with the totcol attribute

---

|                        |                                        |
|------------------------|----------------------------------------|
| is_totcol.tabxplor_fmt | <i>Test function for total columns</i> |
|------------------------|----------------------------------------|

---

**Description**

Test function for total columns

**Usage**

```
## S3 method for class 'tabxplor_fmt'
is_totcol(x, ...)
```

**Arguments**

|     |                                                      |
|-----|------------------------------------------------------|
| x   | The object to test, to get a field in, or to modify. |
| ... | Used in methods to add arguments in the future.      |

**Value**

A single logical vector with the totcol attribute

---

is\_totrow.data.frame     *Test function to detect cells in total rows*

---

### Description

Test function to detect cells in total rows

### Usage

```
## S3 method for class 'data.frame'
is_totrow(x, ..., partial = FALSE)
```

### Arguments

|         |                                                                        |
|---------|------------------------------------------------------------------------|
| x       | The object to test, to get a field in, or to modify.                   |
| ...     | Used in methods to add arguments in the future.                        |
| partial | Should partial total rows be counted as total rows ? Default to FALSE. |

### Value

A list of logical vectors, with the data.frame column's totrow fields.

---

is\_totrow.default     *Test function to detect cells in total rows*

---

### Description

Test function to detect cells in total rows

### Usage

```
## Default S3 method:
is_totrow(x, ...)
```

### Arguments

|     |                                                      |
|-----|------------------------------------------------------|
| x   | The object to test, to get a field in, or to modify. |
| ... | Used in methods to add arguments in the future.      |

### Value

A logical vector with FALSE.

---

```
is_totrow.tabxplor_fmt
```

*Test function to detect cells in total rows*

---

### Description

Test function to detect cells in total rows

### Usage

```
## S3 method for class 'tabxplor_fmt'
is_totrow(x, ...)
```

### Arguments

|     |                                                      |
|-----|------------------------------------------------------|
| x   | The object to test, to get a field in, or to modify. |
| ... | Used in methods to add arguments in the future.      |

### Value

A logical vector with the totrow field.

---

```
is_tottab.data.frame
```

*Test function to detect cells in total tables*

---

### Description

Test function to detect cells in total tables

### Usage

```
## S3 method for class 'data.frame'
is_tottab(x, ..., partial = FALSE)
```

### Arguments

|         |                                                                        |
|---------|------------------------------------------------------------------------|
| x       | The object to test, to get a field in, or to modify.                   |
| ...     | Used in methods to add arguments in the future.                        |
| partial | Should partial total tabs be counted as total tabs ? Default to FALSE. |

### Value

A list of logical vectors, with the data.frame column's tottab fields.

---

|                   |                                                      |
|-------------------|------------------------------------------------------|
| is_tottab.default | <i>Test function to detect cells in total tables</i> |
|-------------------|------------------------------------------------------|

---

**Description**

Test function to detect cells in total tables

**Usage**

```
## Default S3 method:  
is_tottab(x, ...)
```

**Arguments**

|     |                                                      |
|-----|------------------------------------------------------|
| x   | The object to test, to get a field in, or to modify. |
| ... | Used in methods to add arguments in the future.      |

**Value**

A logical vector with FALSE.

---

|                        |                                                      |
|------------------------|------------------------------------------------------|
| is_tottab.tabxplor_fmt | <i>Test function to detect cells in total tables</i> |
|------------------------|------------------------------------------------------|

---

**Description**

Test function to detect cells in total tables

**Usage**

```
## S3 method for class 'tabxplor_fmt'  
is_tottab(x, ...)
```

**Arguments**

|     |                                                      |
|-----|------------------------------------------------------|
| x   | The object to test, to get a field in, or to modify. |
| ... | Used in methods to add arguments in the future.      |

**Value**

A logical vector with the tottab field.

jmvtab

*Crosstables***Description**

Crosstables

**Usage**

```
jmvtab(
  data,
  row_vars = NULL,
  col_vars = NULL,
  tab_vars = NULL,
  wt = NULL,
  pct = "no",
  color = "no",
  chi2 = TRUE,
  OR = "no",
  na = "keep",
  lvs = "all",
  other_if_less_than = 0,
  cleannames = TRUE,
  ref = "auto",
  ref2 = "first",
  comp = "tab",
  ci = "auto",
  conf_level = 0.95,
  ci_print = "ci",
  totaltab = "line",
  wrap_rows = 35,
  wrap_cols = 15,
  display = "auto",
  add_n = TRUE,
  add_pct = FALSE,
  subtext = "",
  digits = 0
)
```

**Arguments**

|          |                                                                                                                               |
|----------|-------------------------------------------------------------------------------------------------------------------------------|
| data     | A data.frame.                                                                                                                 |
| row_vars | The row variable, which will be printed with one level per line. If numeric, it will be converted to factor.                  |
| col_vars | One column is printed for each level of each column variable. For numeric variables means are calculated, in a single column. |

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| tab_vars           | One subtable is made for each combination of levels of the tab variables. All tab variables are converted to factor. Leave empty to make a simple table.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| wt                 | A weight variable, of class numeric. Leave empty for unweighted results.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| pct                | The type of percentages to calculate : <ul style="list-style-type: none"> <li>• "row": row percentages.</li> <li>• "col": column percentages.</li> <li>• "all": frequencies for each subtable/group, if there is tab_vars.</li> <li>• "all_tabs": frequencies for the whole (set of) table(s).</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| color              | The type of colors to print, as a single string. Vectorised over row_vars. <ul style="list-style-type: none"> <li>• "no": by default, no colors are printed.</li> <li>• "diff": color percentages and means based on cells differences from totals (or from first cells when ref = "first").</li> <li>• "diff_ci": color pct and means based on cells differences from totals or first cells, removing coloring when the confidence interval of this difference is higher than the difference itself.</li> <li>• "after_ci": idem, but cut off the confidence interval from the difference first.</li> <li>• "contrib": color cells based on their contribution to variance (except mean columns, from numeric variables).</li> <li>• "OR": for pct == "col" or pct == "row", color based on odds ratios (or relative risks ratios)</li> </ul> |
| chi2               | Set to TRUE to make a Chi2 and add summary stats. Also useful to color cells based on their contribution to variance.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| OR                 | With pct = "row" or pct = "col", calculate and print odds ratios (for binary variables) or relative risks ratios (for variables with 3 levels or more). <ul style="list-style-type: none"> <li>• "no": by default, no OR are calculated.</li> <li>• "OR": print OR (instead of percentages).</li> <li>• "OR_pct": print OR, with percentages in bracket.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| na                 | The policy to adopt with missing values. It must be a single string. <ul style="list-style-type: none"> <li>• na = "keep": by default, prints NA's as explicit "NA" level.</li> <li>• na = "drop": removes NA levels before making each table (tabs made with different column variables may have a different number of observations, and won't exactly have the same total columns).</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| lvs                | The levels of col_vars to keep. <ul style="list-style-type: none"> <li>• "all": by default, all levels are kept.</li> <li>• "first": only keep the first level of each col_vars</li> <li>• "auto": keep the first level when col_var is only two levels, keep all levels otherwise.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| other_if_less_than | When set to a positive integer, levels with less count than that will be merged into an "Others" level.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| cleannames         | By default, clean levels names, by removing prefix numbers like "1-", and text in parenthesis. Set to FALSE to avoid this behaviour.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ref        | <p>The reference cell to calculate differences and ratios (used to print colors) :</p> <ul style="list-style-type: none"> <li>• "auto": by default, cell difference from the corresponding total (rows or cols depending on <code>pct = "row"</code> or <code>pct = "col"</code>) is used for diff ; cell ratio from the first line (or col) is use for OR (odds ratio/relative risks ratio).</li> <li>• "tot": totals are always used.</li> <li>• "first": calculate cell difference or ratio from the first cell of the row or column (useful to color temporal developments).</li> <li>• n: when ref is an integer, the nth row (or column) is used for comparison.</li> <li>• "regex": when ref is a string, it it used as a regular expression, to match with the names of the rows (or columns). Be precise enough to match only one column or row, otherwise you get a warning message.</li> <li>• "no": not use ref and not calculate diffs to gain calculation time.</li> </ul> |
| ref2       | <p>A second reference cell is needed to calculate odds ratios (or relative risks ratios). The first cell of the row or column is used by default. See ref for the full list of possible values.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| comp       | <p>The comparison level : by subtables/groups, or for the whole table.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| ci         | <p>The type of confidence intervals to calculate, passed to <code>tab_ci</code>.</p> <ul style="list-style-type: none"> <li>• "cell": absolute confidence intervals of cells percentages.</li> <li>• "diff": confidence intervals of the difference between a cell and the relative total cell (or relative first cell when <code>ref = "first"</code>).</li> <li>• "auto": <code>ci = "diff"</code> for means and row/col percentages, <code>ci = "cell"</code> for frequencies ("all", "all_tabs").</li> </ul> <p>By default, for percentages, with <code>ci = "cell"</code> Wilson's method is used, and with <code>ci = "diff"</code> Wald's method along Agresti and Caffo's adjustment. Means use classic method.</p>                                                                                                                                                                                                                                                              |
| conf_level | <p>The confidence level, as a single numeric between 0 and 1.</p> <p>1. Default to 0.95 (95\</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| ci_print   | <p>By default confidence interval are printed with the interval display. Set to "moe" to use <code>pct +/- moe</code> instead.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| totaltab   | <p>The total table, if there are subtables/groups (i.e. when <code>tab_vars</code> is provided). Vectorised over <code>row_vars</code>.</p> <ul style="list-style-type: none"> <li>• "line": by default, add a general total line (necessary for calculations with <code>comp = "all"</code>)</li> <li>• "table": add a complete total table (i.e. <code>row_var</code> by <code>col_vars</code> without <code>tab_vars</code>).</li> <li>• "no": not to draw any total table.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| wrap_rows  | <p>By default, rownames are wrapped when larger than 30 characters.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| wrap_cols  | <p>By default, colnames are wrapped when larger than 12 characters.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| display    | <p>The information to display in the table.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| add_n      | <p>For <code>pct = "row"</code> or <code>pct = "col"</code>, set to FALSE not to add another column or row with unweighted counts (n).</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| add_pct    | <p>Set to TRUE to add a column with the frequencies of the row variable (for <code>pct = "row"</code>) or a row with the frequencies of the column variable (for <code>pct = "col"</code>)</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

|         |                                                                                                       |
|---------|-------------------------------------------------------------------------------------------------------|
| subtext | A character vector to print rows of legend under the table.                                           |
| digits  | The number of digits to print, as a single integer, or an integer vector the same length as col_vars. |

**Value**

A results object containing:

|                     |          |
|---------------------|----------|
| results\$html_table | a html   |
| results\$chi2_table | a table  |
| results\$plot       | an image |

Tables can be converted to data frames with `asDF` or `as.data.frame`. For example:

```
results$chi2_table$asDF
as.data.frame(results$chi2_table)
```

---

`kable_tabxplor_style`    *Print a tabxplor table in html*

---

**Description**

Print a tabxplor table in html

**Usage**

```
kable_tabxplor_style(
  tabs,
  caption = knitr::opts_current$get("tab.cap"),
  theme = c("light", "dark"),
  total_in_bold = TRUE,
  all_column_borders = FALSE,
  html_font = NULL,
  full_width = FALSE,
  wrap_rows = 35,
  wrap_cols = 15,
  whitespace_only = TRUE,
  subtext = "",
  ...
)
```

**Arguments**

|                                 |                                                                                                                                                                                                                                      |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>tabs</code>               | A data.frame.                                                                                                                                                                                                                        |
| <code>caption</code>            | The table caption. For formatting, you need to use a css with <code>caption{}</code> in markdown.                                                                                                                                    |
| <code>theme</code>              | By default, a white table with black text, Set to "dark" for a black table with white text.                                                                                                                                          |
| <code>total_in_bold</code>      | Should rows and cols with "Total" string be set in bold ?                                                                                                                                                                            |
| <code>all_column_borders</code> | Put a vertical border around each column ?                                                                                                                                                                                           |
| <code>html_font</code>          | A string for HTML css font. By default, it uses '"DejaVu Sans", "Arial", arial, helvetica, sans-serif'. Set another default by setting <code>options("tabxplor.kable_html_font" = )</code> .                                         |
| <code>full_width</code>         | A TRUE or FALSE variable controlling whether the HTML table should have the preferable format for full_width. If not specified, a HTML table will have full width by default but this option will be set to FALSE for a LaTeX table. |
| <code>wrap_rows</code>          | By default, rownames are wrapped when larger than 30 characters.                                                                                                                                                                     |
| <code>wrap_cols</code>          | By default, colnames are wrapped when larger than 12 characters.                                                                                                                                                                     |
| <code>whitespace_only</code>    | Set to FALSE to wrap also on non whitespace characters.                                                                                                                                                                              |
| <code>subtext</code>            | A character vector to print rows of legend under the table.                                                                                                                                                                          |
| <code>...</code>                | Other arguments to pass to <code>kableExtra::kable_styling</code> .                                                                                                                                                                  |

**Value**

A html table (opened in the viewer in RStudio). Differences from totals, confidence intervals, contribution to variance, and unweighted counts, are available in an html tooltip at cells hover.

**Examples**

```
tabs <- tibble::tibble(nm      = c("First", "Second", "Total"),
                      column1 = c(1, 2, 3),
                      column2 = c(4, 5, 6)
)
kable_tabxplor_style(tabs)
```

---

|                                  |                                                                      |
|----------------------------------|----------------------------------------------------------------------|
| <code>mutate.tabxplor_fmt</code> | <i>mutate method to access vctrs::fields of tabxplor_fmt vectors</i> |
|----------------------------------|----------------------------------------------------------------------|

---

**Description**

mutate method to access vctrs::fields of tabxplor\_fmt vectors

**Usage**

```
## S3 method for class 'tabxplor_fmt'
mutate(.data, ...)
```

**Arguments**

`.data` A tabxplor\_fmt column.

`...` Name-value pairs. The name gives the name of the column in the output (do not change it).  
The value can be:

- A vector of length 1, which will be recycled to the correct length.
- A vector the same length as the current group (or the whole data frame if ungrouped).

**Value**

An object of class tabxplor\_fmt.

---

|         |                                             |
|---------|---------------------------------------------|
| new_tab | <i>A constructor for class tabxplor_tab</i> |
|---------|---------------------------------------------|

---

**Description**

A constructor for class tabxplor\_tab

**Usage**

```
new_tab(
  tabs = tibble::tibble(),
  subtext = "",
  chi2 = tibble::tibble(tables = character(), pvalue = double(), df = integer(), cells =
    integer(), variance = double(), count = integer()),
  ...,
  class = character()
)

new_grouped_tab(
  tabs = tibble::tibble(),
  groups,
  subtext = "",
  chi2 = tibble::tibble(tables = character(), pvalue = double(), df = integer(), cells =
    integer(), variance = double(), count = integer()),
  ...,
  class = character()
)
```

**Arguments**

|         |                                                                                                                                                                   |
|---------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| tabs    | A table, stored into a <a href="#">tibble</a> data.frame. It is generally made with <a href="#">tab</a> , <a href="#">tab_many</a> or <a href="#">tab_plain</a> . |
| subtext | A character vector to print legend lines under the table.                                                                                                         |
| chi2    | A tibble storing information about pvalues and variances, to fill with <a href="#">tab_chi2</a> .                                                                 |
| ...     | Needed to implement subclasses.                                                                                                                                   |
| class   | Needed to implement subclasses.                                                                                                                                   |
| groups  | The grouping data.                                                                                                                                                |

**Value**

A tibble of class `tabxplor_tab`.

A tibble of class `tabxplor_grouped_tab`.

---

`pillar_shaft.tabxplor_fmt`

*Pillar\_shaft method to print class fmt in a [tibble](#) column*

---

**Description**

Pillar\_shaft method to print class fmt in a [tibble](#) column

**Usage**

```
## S3 method for class 'tabxplor_fmt'
pillar_shaft(x, ...)
```

**Arguments**

|     |                  |
|-----|------------------|
| x   | A fmt object.    |
| ... | Other parameter. |

**Value**

A fmt printed in a pillar.

---

```
pillar_shaft.tab_chi2_fmt
```

*Print Chi2 tables columns*

---

**Description**

Print Chi2 tables columns

**Usage**

```
## S3 method for class 'tab_chi2_fmt'
pillar_shaft(x, ...)
```

**Arguments**

|     |                  |
|-----|------------------|
| x   | A fmt object.    |
| ... | Other parameter. |

**Value**

A Chi2 table column printed in a pillar.

---

```
print.tabxplor_grouped_tab
```

*Printing method for class tabxplor\_grouped\_tab*

---

**Description**

Printing method for class tabxplor\_grouped\_tab

**Usage**

```
## S3 method for class 'tabxplor_grouped_tab'
print(
  x,
  width = NULL,
  ...,
  n = 100,
  max_extra_cols = NULL,
  max_footer_lines = NULL,
  min_row_var = 30,
  get_text = FALSE
)
```

**Arguments**

|                  |                                                                                                                |
|------------------|----------------------------------------------------------------------------------------------------------------|
| x                | Object to format or print.                                                                                     |
| width            | Width of text output to generate.                                                                              |
| ...              | Passed on to tbl_format_setup().                                                                               |
| n                | Number of rows to show.                                                                                        |
| max_extra_cols   | Number of extra columns to print abbreviated information for, if the width is too small for the entire tibble. |
| max_footer_lines | Maximum number of footer lines.                                                                                |
| min_row_var      | Minimum number of characters for the row variable. Default to 30.                                              |
| get_text         | Set to TRUE to get the text as a character vector instead of a printed output.                                 |

**Value**

A printed grouped table.

---

|                    |                                               |
|--------------------|-----------------------------------------------|
| print.tabxplor_tab | <i>Printing method for class tabxplor_tab</i> |
|--------------------|-----------------------------------------------|

---

**Description**

Printing method for class tabxplor\_tab

**Usage**

```
## S3 method for class 'tabxplor_tab'
print(
  x,
  width = NULL,
  ...,
  n = 100,
  max_extra_cols = NULL,
  max_footer_lines = NULL,
  min_row_var = 30,
  get_text = FALSE
)
```

**Arguments**

|       |                                   |
|-------|-----------------------------------|
| x     | Object to format or print.        |
| width | Width of text output to generate. |
| ...   | Passed on to tbl_format_setup().  |
| n     | Number of rows to show.           |

|                  |                                                                                                                |
|------------------|----------------------------------------------------------------------------------------------------------------|
| max_extra_cols   | Number of extra columns to print abbreviated information for, if the width is too small for the entire tibble. |
| max_footer_lines | Maximum number of footer lines.                                                                                |
| min_row_var      | Minimum number of characters for the row variable. Default to 30.                                              |
| get_text         | Set to TRUE to get the text as a character vector instead of a printed output.                                 |

**Value**

A printed table.

---

|                                                       |
|-------------------------------------------------------|
| relocate.tabxplor_grouped_tab                         |
| <i>relocate method for class tabxplor_grouped_tab</i> |

---

**Description**

relocate method for class tabxplor\_grouped\_tab

**Usage**

```
## S3 method for class 'tabxplor_grouped_tab'  
relocate(.data, ...)
```

**Arguments**

|       |                                                                                        |
|-------|----------------------------------------------------------------------------------------|
| .data | A tibble of class tabxplor_tab.                                                        |
| ...   | Columns to move. will move columns to the left-hand side; specifying both is an error. |

**Value**

An object of class tabxplor\_grouped\_tab.

---

```
rename.tabxplor_grouped_tab
```

*rename method for class tabxplor\_grouped\_tab*

---

**Description**

rename method for class tabxplor\_grouped\_tab

**Usage**

```
## S3 method for class 'tabxplor_grouped_tab'
rename(.data, ...)
```

**Arguments**

|                    |                                                       |
|--------------------|-------------------------------------------------------|
| <code>.data</code> | A tibble of class tabxplor_tab.                       |
| <code>...</code>   | Use new_name = old_name to rename selected variables. |

**Value**

An object of class tabxplor\_grouped\_tab.

---

```
rename_with.tabxplor_grouped_tab
```

*rename\_with method for class tabxplor\_grouped\_tab*

---

**Description**

rename\_with method for class tabxplor\_grouped\_tab

**Usage**

```
## S3 method for class 'tabxplor_grouped_tab'
rename_with(.data, .fn, .cols = dplyr::everything(), ...)
```

**Arguments**

|                    |                                                                                                                               |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------|
| <code>.data</code> | A tibble of class tabxplor_tab.                                                                                               |
| <code>.fn</code>   | A function used to transform the selected <code>.cols</code> . Should return a character vector the same length as the input. |
| <code>.cols</code> | Columns to rename; defaults to all columns.                                                                                   |
| <code>...</code>   | Additional arguments passed onto <code>.fn</code> .                                                                           |

**Value**

An object of class tabxplor\_grouped\_tab.

---

```
rowwise.tabxplor_grouped_tab
```

*rowwise method for class tabxplor\_grouped\_tab*

---

**Description**

rowwise method for class tabxplor\_grouped\_tab

**Usage**

```
## S3 method for class 'tabxplor_grouped_tab'  
rowwise(data, ...)
```

**Arguments**

|      |                                                                                                                                        |
|------|----------------------------------------------------------------------------------------------------------------------------------------|
| data | A tibble of class tabxplor_tab.                                                                                                        |
| ...  | Variables to be preserved when calling summarise(). This is typically a set of variables whose combination uniquely identify each row. |

**Value**

An object of class tabxplor\_grouped\_tab and rowwise\_df.

---

```
rowwise.tabxplor_tab
```

*rowwise method for class tabxplor\_tab*

---

**Description**

rowwise method for class tabxplor\_tab

**Usage**

```
## S3 method for class 'tabxplor_tab'  
rowwise(data, ...)
```

**Arguments**

|      |                                                                                                                                        |
|------|----------------------------------------------------------------------------------------------------------------------------------------|
| data | A tibble of class tabxplor_tab.                                                                                                        |
| ...  | Variables to be preserved when calling summarise(). This is typically a set of variables whose combination uniquely identify each row. |

**Value**

A tibble of class tabxplor\_grouped\_tab and rowwise\_df.

---

|                |                                      |
|----------------|--------------------------------------|
| score_from_lv1 | Create a score variable from factors |
|----------------|--------------------------------------|

---

**Description**

Create a score variable from factors

**Usage**

```
score_from_lv1(data, name, vars_list)
```

**Arguments**

|           |                                                                                                   |
|-----------|---------------------------------------------------------------------------------------------------|
| data      | A data.frame.                                                                                     |
| name      | The name of the variable to create.                                                               |
| vars_list | The list of the factors to count (only the first level is counted, as 1) ; as a character vector. |

**Value**

The data.frame, with a new variable.

**Examples**

```
data <- tibble::tibble(group = factor(c("G1", "G1", "G2", "G2", "G3", "G3")),
  a = factor(c("Oui", "Oui", "Oui", "Oui", "Non", "Oui")),
  b = factor(c("Oui", "Non", "Non", "Oui", "Non", "Oui")),
  c = factor(c("Oui", "Oui", "Non", "Non", "Oui", "Oui")))
data |>
  score_from_lv1("score", vars_list = c("a", "b", "c")) |>
  tab(group, score, digits = 1)
```

---

|                             |                                                     |
|-----------------------------|-----------------------------------------------------|
| select.tabxplor_grouped_tab | <i>select method for class tabxplor_grouped_tab</i> |
|-----------------------------|-----------------------------------------------------|

---

**Description**

select method for class tabxplor\_grouped\_tab

**Usage**

```
## S3 method for class 'tabxplor_grouped_tab'
select(.data, ...)
```

**Arguments**

|       |                                                                                                                                                                                                   |
|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| .data | A tibble of class tabxplore_tab.                                                                                                                                                                  |
| ...   | One or more unquoted expressions separated by commas. Variable names can be used as if they were positions in the data frame, so expressions like x:y can be used to select a range of variables. |

**Value**

An object of class tabxplore\_grouped\_tab.

---

```
set_display.data.frame
```

*Set the "display" vctrs::field of a fmt vector.*

---

**Description**

Set the "display" vctrs::field of a fmt vector.

**Usage**

```
## S3 method for class 'data.frame'
set_display(x, value)
```

**Arguments**

|       |                                                                                                           |
|-------|-----------------------------------------------------------------------------------------------------------|
| x     | The object to test, to get a field in, or to modify.                                                      |
| value | The value you want to inject in some fmt vector's vctrs::field or attribute using a given "set" function. |

**Value**

The entered objects, with all fmt vectors with the wanted display.

---

```
set_display.default
```

*Set the "display" vctrs::field of a fmt vector.*

---

**Description**

Set the "display" vctrs::field of a fmt vector.

**Usage**

```
## Default S3 method:
set_display(x, value)
```

**Arguments**

|       |                                                                                                           |
|-------|-----------------------------------------------------------------------------------------------------------|
| x     | The object to test, to get a field in, or to modify.                                                      |
| value | The value you want to inject in some fmt vector's vctrs::field or attribute using a given "set" function. |

**Value**

The entered vector (nothing happens).

---

```
set_display.tabxplor_fmt
```

*Set the "display" vctrs::field of a fmt vector.*

---

**Description**

Set the "display" vctrs::field of a fmt vector.

**Usage**

```
## S3 method for class 'tabxplor_fmt'
set_display(x, value)
```

**Arguments**

|       |                                                                                                           |
|-------|-----------------------------------------------------------------------------------------------------------|
| x     | The object to test, to get a field in, or to modify.                                                      |
| value | The value you want to inject in some fmt vector's vctrs::field or attribute using a given "set" function. |

**Value**

A fmt vectors with the wanted display.

---

```
summarise.tabxplor_grouped_tab
```

*summarise method for class tabxplor\_grouped\_tab*

---

**Description**

summarise method for class tabxplor\_grouped\_tab

**Usage**

```
## S3 method for class 'tabxplor_grouped_tab'
summarise(.data, ..., .groups = NULL)
```

**Arguments**

|                      |                                                                                                 |
|----------------------|-------------------------------------------------------------------------------------------------|
| <code>.data</code>   | A tibble of class <code>tabxplor_tab</code> .                                                   |
| <code>...</code>     | Name-value pairs of summary functions. The name will be the name of the variable in the result. |
| <code>.groups</code> | Grouping structure of the result.                                                               |

**Value**

An object of class `tabxplor_grouped_tab`.

---

|     |                                               |
|-----|-----------------------------------------------|
| tab | <i>Single cross-table, with color helpers</i> |
|-----|-----------------------------------------------|

---

**Description**

A full-featured function to create, manipulate and format single cross-tables, using colors to make the printed tab more easily readable (in R terminal or exported to Excel with [tab\\_xl](#)). Since objects of class `tabxplor_tab` are also of class `tibble`, you can then use all **dplyr** verbs to modify the result, like [select](#), like [arrange](#), [filter](#) or [mutate](#). Wrapper around the more powerful [tab\\_many](#).

**Usage**

```
tab(
  data,
  row_var,
  col_var,
  tab_vars,
  wt,
  sup_cols,
  pct = "no",
  color = "no",
  OR = "no",
  chi2 = FALSE,
  na = "keep",
  cleannames = NULL,
  other_if_less_than = 0,
  other_level = "Others",
  ref = "auto",
  ref2 = "first",
  comp = "tab",
  ci = "no",
  conf_level = 0.95,
  totaltab = "line",
  totaltab_name = "Ensemble",
  tot = c("row", "col"),
  total_names = "Total",
```

```

    add_n = TRUE,
    add_pct = FALSE,
    subtext = "",
    digits = 0,
    filter
  )

```

## Arguments

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| data             | A data frame.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| row_var, col_var | The row variable, which will be printed with one level per line, and the column variable, which will be printed with one level per column. For numeric variables means are calculated, in a single column.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| tab_vars         | <a href="#">&lt;tidy-select&gt;</a> Tab variables : a subtable is made for each combination of levels of the selected variables. Leave empty to make a simple cross-table. All <code>tab_vars</code> are converted to factor.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| wt               | A weight variable, of class numeric. Leave empty for unweighted results.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| sup_cols         | <a href="#">&lt;tidy-select&gt;</a> Supplementary columns variables, with only the first level printed, and row percentages (for numeric variables, a mean will be calculated for each <code>row_var</code> ). To pass many variables you may use syntax <code>sup_cols = c(sup_col1, sup_col2, ...)</code> . To keep all levels of other <code>col_vars</code> , or other types of percentages, use <a href="#">tab_many</a> instead.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| pct              | The type of percentages to calculate : <ul style="list-style-type: none"> <li>• "row": row percentages.</li> <li>• "col": column percentages.</li> <li>• "all": frequencies for each subtable/group, if there is <code>tab_vars</code>.</li> <li>• "all_tabs": frequencies for the whole (set of) table(s).</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| color            | The type of colors to print, as a single string : <ul style="list-style-type: none"> <li>• "no": by default, no colors are printed.</li> <li>• "diff": color percentages and means based on cells differences from totals (or from first cells when <code>ref = "first"</code>).</li> <li>• "diff_ci": color pct and means based on cells differences from totals or first cells, removing coloring when the confidence interval of this difference is higher than the difference itself.</li> <li>• "after_ci": idem, but cut off the confidence interval from the difference first.</li> <li>• "contrib": color cells based on their contribution to variance (except mean columns, from numeric variables).</li> <li>• "OR": for <code>pct == "col"</code> or <code>pct == "row"</code>, color based on odds ratios (or relative risks ratios)</li> <li>• "auto": frequencies (<code>pct = "all"</code>, <code>pct = "all_tabs"</code>) and counts are colored with "contrib". When <code>ci = "diff"</code>, row and col percentages are colored with "after_ci" ; otherwise they are colored with "diff".</li> </ul> |

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OR                 | <p>With <code>pct = "row"</code> or <code>pct = "col"</code>, calculate and print odds ratios (for binary variables) or relative risks ratios (for variables with 3 levels or more).</p> <ul style="list-style-type: none"> <li>• "no": by default, no OR are calculated.</li> <li>• "OR": print OR (instead of percentages).</li> <li>• "OR_pct": print OR, with percentages in bracket.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| chi2               | <p>Set to TRUE to calculate Chi2 summaries with <a href="#">tab_chi2</a>. Useful to print meta-data, and to color cells based on their contribution to variance (<code>color = "contrib"</code>). Automatically added if needed for color.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| na                 | <p>The policy to adopt for missing values, as a single string :</p> <ul style="list-style-type: none"> <li>• "keep": by default, NA's of row, col and tab variables are printed as an explicit "NA" level.</li> <li>• "drop": remove NA's in row, col and tab variables before calculations are done. Supplementary columns are then calculated for observations with no NA in any of the row, col and tab variables.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| cleannames         | <p>Set to TRUE to clean levels names, by removing prefix numbers like "1-", and text in parenthesis. All data formatting arguments are passed to <a href="#">tab_prepare</a>.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| other_if_less_than | <p>When set to a positive integer, levels with less count than it will be merged into an "Others" level.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| other_level        | <p>The name of the "Other" level, as a single string.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| ref                | <p>The reference cell to calculate differences and ratios (used to print colors) :</p> <ul style="list-style-type: none"> <li>• "auto": by default, cell difference from the corresponding total (rows or cols depending on <code>pct = "row"</code> or <code>pct = "col"</code>) is used for diff ; cell ratio from the first line (or col) is use for OR (odds ratio/relative risks ratio).</li> <li>• "tot": totals are always used.</li> <li>• "first": calculate cell difference or ratio from the first cell of the row or column (useful to color temporal developments).</li> <li>• n: when ref is an integer, the nth row (or column) is used for comparison.</li> <li>• "regex": when ref is a string, it it used as a regular expression, to match with the names of the rows (or columns). Be precise enough to match only one column or row, otherwise you get a warning message.</li> <li>• "no": not use ref and not calculate diffs to gain calculation time.</li> </ul> |
| ref2               | <p>A second reference cell is needed to calculate odds ratios (or relative risks ratios). The first cell of the row or column is used by default. See ref above for the full list of possible values.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| comp               | <p>The comparison level : by subtables/groups, or for the whole table.</p> <ul style="list-style-type: none"> <li>• "tab": by default, contributions to variance, row differences from totals/first cells, and row confidence intervals for these differences, are calculated for each <code>tab_vars</code> group.</li> <li>• "all": compare cells to the general total line (provided there is a total table with a total row), or with the first line of the total table when <code>ref = "first"</code>.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| ci                 | <p>The type of confidence intervals to calculate, passed to <a href="#">tab_ci</a> (automatically added if needed for color).</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                            | <ul style="list-style-type: none"> <li>• "cell": absolute confidence intervals of cells percentages.</li> <li>• "diff": confidence intervals of the difference between a cell and the relative total cell (or relative first cell when <code>ref = "first"</code>).</li> <li>• "auto": <code>ci = "diff"</code> for means and row/col percentages, <code>ci = "cell"</code> for frequencies ("all", "all_tabs").</li> </ul> <p>By default, for percentages, with Wilson's method is used, and with <code>ci = "diff"</code> Wald's method along Agresti and Caffo's adjustment. Means use classic method. This can be changed in <code>tab_many</code>. By default, with <code>ci = "cell"</code>, the result is printed in the <code>[inf; sup]</code> form. Set <code>options("tabxplor.ci_print" = "moe")</code> to print <code>pct +/- moe</code> instead.</p> |
| <code>conf_level</code>    | The confidence level, as a single numeric between 0 and 1. Default to 0.95 (95%).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>totaltab</code>      | <p>The total table, if there are subtables/groups (i.e. when <code>tab_vars</code> is provided) :</p> <ul style="list-style-type: none"> <li>• "line": by default, add a general total line (necessary for calculations with <code>comp = "all"</code>)</li> <li>• "table": add a complete total table (i.e. <code>row_var</code> by <code>col_vars</code> without <code>tab_vars</code>).</li> <li>• "no": not to draw any total table.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                |
| <code>totaltab_name</code> | The name of the total table, as a single string.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <code>tot</code>           | <p>The totals :</p> <ul style="list-style-type: none"> <li>• <code>c("col", "row")</code> or "both" : by default, both total rows and total columns.</li> <li>• "row": only total rows.</li> <li>• "col": only total column.</li> <li>• "no": remove all totals (after calculations if needed).</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>total_names</code>   | The names of the totals, as a character vector of length one or two. Use syntax of type <code>c("Total row", "Total column")</code> to set different names for rows and cols.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <code>add_n</code>         | For <code>pct = "row"</code> or <code>pct = "col"</code> , set to FALSE not to add another column or row with unweighted counts (n).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <code>add_pct</code>       | Set to TRUE to add a column with the frequencies of the row variable (for <code>pct = "row"</code> ) or a row with the frequencies of the column variable (for <code>pct = "col"</code> ).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <code>subtext</code>       | A character vector to print rows of legend under the table.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <code>digits</code>        | The number of digits to print, as a single integer. To print a different number of digits for each <code>sup_cols</code> , an integer vector of length <code>1 + sup_cols</code> (the first being the number of digits for the base table).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <code>filter</code>        | A <code>dplyr::filter</code> to apply to the data frame first, as a single string (which will be converted to code, i.e. to a call). Useful when printing multiples tabs with <code>tibble::tribble</code> , to use different filters for similar tables or simply make the field of observation more visible into the code.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

## Value

A tibble of class `tab`, possibly with colored reading helpers. All non-text columns are of class `fmt`, storing all the data necessary to print formats and colors. Columns with `row_var` and `tab_vars` are of class `factor` : every added factor will be considered as a `tab_vars` and used for grouping. To add text columns without using them in calculations, be sure they are of class `character`.

## Examples

```
# A simple cross-table:
tab(forcats::gss_cat, marital, race)

# With more variables provided, `tab` makes a subtables for each combination of levels:
tab(forcats::gss_cat, marital, tab_vars = c(year, race))

# You can also add supplementary columns, text or numeric:
tab(dplyr::storms, category, status, sup_cols = c("pressure", "wind"))

# Colors to help the user read the table:
data <- forcats::gss_cat %>%
  dplyr::filter(year %in% c(2000, 2006, 2012), !marital %in% c("No answer", "Widowed"))
gss <- "Source: General social survey 2000-2014"
gss2 <- "Source: General social survey 2000, 2006 and 2012"

# Differences between the cell and it's subtable's total cell:
tab(data, race, marital, year, subtext = gss2, pct = "row", color = "diff")

# Differences between the cell and the whole table's general total cell:
tab(data, race, marital, year, subtext = gss2, pct = "row", color = "diff",
     comp = "all")

# Historical differences:
data2 <- data %>% dplyr::mutate(year = as.factor(year))
tab(data2, year, marital, race, subtext = gss2, pct = "row",
     color = "diff", ref = "first", tot = "col")

# Differences with the total, except if their confidences intervals are superior to them:
tab(forcats::gss_cat, race, marital, subtext = gss, pct = "row", color = "diff_ci")

# Same differences, minus their confidence intervals:
tab(forcats::gss_cat, race, marital, subtext = gss, pct = "row", color = "after_ci")

# Contribution of cells to table's variance, like in a correspondence analysis:
tab(forcats::gss_cat, race, marital, subtext = gss, color = "contrib")

# Since the result is a tibble, you can use all dplyr verbs to modify it :

library(dplyr)
```

```

tab(dplyr::storms, category, status, sup_cols = c("pressure", "wind")) %>%
  dplyr::filter(category != "-1") %>%
  dplyr::select(-`tropical depression`) %>%
  dplyr::arrange(is_totrow(.), desc(category))

# With `dplyr::arrange`, don't forget to keep the order of tab variables and total rows:
tab(data, race, marital, year, pct = "row") %>%
  dplyr::arrange(year, is_totrow(.), desc(Married))

```

---

tab\_chi2

Add Chi2 summaries to a [tab](#)


---

## Description

Add Chi2 summaries to a [tab](#)

## Usage

```

tab_chi2(
  tabs,
  calc = c("ctr", "p", "var", "counts"),
  comp = NULL,
  color = c("no", "auto", "all", "all_pct")
)

```

## Arguments

- |       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| tabs  | A tibble of class <code>tab</code> , made with <a href="#">tab_plain</a> or <a href="#">tab_many</a> .                                                                                                                                                                                                                                                                                                                                                                          |
| calc  | By default all elements of the Chi2 summary are calculated : contributions to variance, pvalue, variance and unweighted count. You can choose which are computed by selecting elements in the vector <code>c("ctr", "p", "var", "counts")</code> .                                                                                                                                                                                                                              |
| comp  | Comparison level. When <code>tab_vars</code> are present, should the contributions to variance be calculated for each subtable/group (by default, <code>comp = "tab"</code> ) ? Should they be calculated for the whole table ( <code>comp = "all"</code> ) ? <code>comp</code> must be set once and for all the first time you use <a href="#">tab_plain</a> , <a href="#">tab_num</a> or <a href="#">tab_chi2</a> with rows, or <a href="#">tab_ci</a> .                      |
| color | The type of colors to print, as a single string. <ul style="list-style-type: none"> <li>• "no": by default, no colors are printed</li> <li>• "all": color all cells based on their contribution to variance (except for mean columns, from numeric variables)</li> <li>• "all_pct": color all percentages cells based on their contribution to variance</li> <li>• "auto": only color columns with counts, <code>pct = "all"</code> or <code>pct = "all_tabs"</code></li> </ul> |

**Value**

A tibble of class `tab`, with Chi2 summaries as metadata, possibly colored based on contributions of cells to variance.

---

|        |                                                   |
|--------|---------------------------------------------------|
| tab_ci | Add confidence intervals to a <a href="#">tab</a> |
|--------|---------------------------------------------------|

---

**Description**

Add confidence intervals to a [tab](#)

**Usage**

```
tab_ci(
  tabs,
  ci = "auto",
  comp = NULL,
  conf_level = 0.95,
  color = "no",
  visible = FALSE,
  method_cell = "wilson",
  method_diff = "ac"
)
```

**Arguments**

|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| tabs       | A tibble of class <code>tab</code> made with <a href="#">tab_plain</a> or <a href="#">tab_many</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| ci         | The type of ci to calculate. Set to "cell" to calculate absolute confidence intervals. Set to "diff" to calculate the confidence intervals of the difference between a cell and the relative total cell (or the reference cell, when <code>ref</code> is not "tot" in <a href="#">tab_plain</a> or <a href="#">tab_num</a> ). By default, "diff" ci are calculated for means and row and col percentages, "cell" ci for frequencies ("all", "all_tabs"). By default, with <code>ci = "cell"</code> , the result is printed in the <code>[inf;sup]</code> form. Set <code>options("tabxplor.ci_print" = "moe")</code> to print <code>pct +- moe</code> instead. |
| comp       | Comparison level. When <code>tab_vars</code> are present, should the contributions to variance be calculated for each subtable/group (by default, <code>comp = "tab"</code> ) ? Should they be calculated for the whole table ( <code>comp = "all"</code> ) ? <code>comp</code> must be set once and for all the first time you use <a href="#">tab_plain</a> , <a href="#">tab_num</a> or <a href="#">tab_chi2</a> with rows, or <a href="#">tab_ci</a> .                                                                                                                                                                                                     |
| conf_level | The confidence level, as a single numeric between 0 and 1. Default to 0.95 (95%).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| color      | The type of colors to print, as a single string. <ul style="list-style-type: none"> <li>• "no": by default, no colors are printed</li> <li>• "diff_ci": color <code>pct</code> and means based on cells differences from totals or first cells, removing coloring when the confidence interval of this difference is higher than the difference itself</li> </ul>                                                                                                                                                                                                                                                                                              |

|             |                                                                                                                                                                                                                                                                                                                                                                       |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|             | <ul style="list-style-type: none"><li>• "after_ci": idem, but cut off the confidence interval from the difference</li></ul>                                                                                                                                                                                                                                           |
| visible     | By default confidence intervals are calculated and used to set colors, but not printed. Set to TRUE to print them in the result.                                                                                                                                                                                                                                      |
| method_cell | Character string specifying which method to use with percentages for ci = "cell". This can be one out of: "wald", "wilson", "wilsoncc", "agresti-coull", "jeffreys", "modified wilson", "modified jeffreys", "clopper-pearson", "arcsine", "logit", "witting", "pratt", "midp", "lik" and "blaker". Defaults to "wilson". See <a href="#">BinomCI</a> .               |
| method_diff | Character string specifying which method to use with percentages for ci = "diff". This can be one out of: "wald", "waldcc", "ac", "score", "scorecc", "mn", "mee", "blj", "ha", "hal", "jp". Defaults to "ac", Wald interval with the adjustment according to Agresti, Caffo for difference in proportions and independent samples. See <a href="#">BinomDiffCI</a> . |

**Value**

A tibble of class tab, colored based on differences (from totals/first cells) and confidence intervals.

**Examples**

```
# A typical workflow with tabxplor step-by-step functions :

data <- dplyr::starwars %>%
  tab_prepare(sex, hair_color, gender, other_if_less_than = 5,
             na_drop_all = sex)

data %>%
  tab_plain(sex, hair_color, gender, tot = c("row", "col"),
            pct = "row", comp = "all") %>%
  tab_ci("diff", color = "after_ci")
```

---

|             |                                                                                       |
|-------------|---------------------------------------------------------------------------------------|
| tab_compact | <i>Bind a list of tabs with the same col_vars (and no tab_vars) into a single tab</i> |
|-------------|---------------------------------------------------------------------------------------|

---

**Description**

Bind a list of tabs with the same col\_vars (and no tab\_vars) into a single tab

**Usage**

```
tab_compact(tabs)
```

**Arguments**

|      |                                            |
|------|--------------------------------------------|
| tabs | A list of tabxplor_tab (or a tabxplor_tab) |
|------|--------------------------------------------|

**Value**

A tabxplor\_tab

**Examples**

```
forcats::gss_cat |>
  tab_many(c(race, rincome), marital, pct = "row", color = "diff") |>
  tab_compact()
```

---

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| tab_get_wrapped_dimensions | <i>Get the number of actual rows and the max character length of a table after being wrapped (count \n as a linebreak).</i> |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|

---

**Description**

Get the number of actual rows and the max character length of a table after being wrapped (count \n as a linebreak).

**Usage**

```
tab_get_wrapped_dimensions(tabs, no_tab_vars = FALSE, width_pad = 4L)
```

**Arguments**

- tabs                    A data.frame.
- no\_tab\_vars            For data.frame of class tabxplor\_tab, remove tab\_vars.
- width\_pad              Number of characters lengths between columns.

---

|           |                                       |
|-----------|---------------------------------------|
| tab_kable | <i>Print a tabxplor table in html</i> |
|-----------|---------------------------------------|

---

**Description**

Print a tabxplor table in html

**Usage**

```

tab_kable(
  tabs,
  theme = c("light", "dark"),
  color_type = NULL,
  html_24_bit = NULL,
  tooltips = TRUE,
  popover = NULL,
  color_legend = TRUE,
  caption = knitr::opts_current$get("tab.cap"),
  html_font = NULL,
  get_data = FALSE,
  full_width = FALSE,
  wrap_rows = 35,
  wrap_cols = 15,
  whitespace_only = TRUE,
  ...
)

```

**Arguments**

|              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| tabs         | A table made with <code>tab</code> or <code>tab_many</code> , or a list of tab with the same <code>col_vars</code> and no <code>tab_vars</code> .                                                                                                                                                                                                                                                                                                                                                                            |
| theme        | By default, a white table with black text, Set to "dark" for a black table with white text.                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| color_type   | Set to "text" to color the text, "bg" to color the background. By default it takes <code>getOption("tabxplor.color_style_type")</code> .                                                                                                                                                                                                                                                                                                                                                                                     |
| html_24_bit  | Use 24bits colors palettes for html tables : set to "green_red" or "blue_red". Only with <code>mode = "color_code"</code> (not <code>mode = "crayon"</code> ) and <code>theme = "light"</code> . Default to <code>getOption("tabxplor.color_html_24_bit")</code> .                                                                                                                                                                                                                                                           |
| tooltips     | By default, html tooltips are used to display additional informations at mouse hover. Set to FALSE to discard.                                                                                                                                                                                                                                                                                                                                                                                                               |
| popover      | By default, takes <code>getOption("tabxplor.kable_popover")</code> . When FALSE, html tooltips are of the base kind : they can't be used with floating table of content in <b>rmarkdown</b> documents. Set to TRUE to use <b>kableExtra</b> html popovers instead, which are compatible with floating toc. Remember to enable the popover module by copying the following code into your document : <code>&lt;script&gt; \$(document).ready(function() { \$('[data-toggle="popover"]').popover(); }); &lt;/script&gt;</code> |
| color_legend | Print colors legend below the table ? You can then use a css chunk in rmarkdown to change popovers colors.                                                                                                                                                                                                                                                                                                                                                                                                                   |
| caption      | The table caption. For formatting, you need to use a css with <code>caption{}</code> in rmarkdown.                                                                                                                                                                                                                                                                                                                                                                                                                           |
| html_font    | A string for HTML css font. By default, it uses "'DejaVu Sans", "Arial", arial, helvetica, sans-serif'. Set another default by setting <code>options("tabxplor.kable_html_font" = )</code> .                                                                                                                                                                                                                                                                                                                                 |
| get_data     | Get the transformed data instead of the html table.                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

|                 |                                                                                                                                                                                                                                      |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| full_width      | A TRUE or FALSE variable controlling whether the HTML table should have the preferable format for full_width. If not specified, a HTML table will have full width by default but this option will be set to FALSE for a LaTeX table. |
| wrap_rows       | By default, rownames are wrapped when larger than 30 characters.                                                                                                                                                                     |
| wrap_cols       | By default, colnames are wrapped when larger than 12 characters.                                                                                                                                                                     |
| whitespace_only | Set to FALSE to wrap also on non whitespace characters.                                                                                                                                                                              |
| ...             | Other arguments to pass to <code>kableExtra::kable_styling</code> .                                                                                                                                                                  |

### Value

A html table (opened in the viewer in RStudio). Differences from totals, confidence intervals, contribution to variance, and unweighted counts, are available in an html tooltip at cells hover.

### Examples

```
tabs <- tab(forcats::gss_cat, race, marital, year, pct = "row", color = "diff")
tab_kable(tabs, theme = "light", color_type = "text")
```

---

tab\_many

---

*Many cross-tables as one, with color helpers*


---

### Description

A full-featured function to create, manipulate and format many cross-tables as one, using colors to make the printed tab more easily readable (in R terminal or exported to Excel with `tab_xl`). Since objects of class `tabxplor_tab` are also of class `tibble`, you can then use all **dplyr** verbs to modify the result, like `select`, `arrange`, `filter` or `mutate`.

Only breaks for attractions/over-representations (in green) should be given, as a vector of positive doubles, with length between 1 and 5. Breaks for aversions/under-representations (in orange/red) will simply be the opposite.

### Usage

```
tab_many(
  data,
  row_vars,
  col_vars,
  tab_vars,
  wt,
  pct = "no",
  color = "no",
  OR = "no",
  chi2 = FALSE,
  na = "keep",
```

```

    levels = "all",
    na_drop_all,
    cleannames = NULL,
    compact = NULL,
    other_if_less_than = 0,
    other_level = "Others",
    ref = "auto",
    ref2 = "first",
    comp = "tab",
    ci = "no",
    conf_level = 0.95,
    method_cell = "wilson",
    method_diff = "ac",
    totaltab = "line",
    totaltab_name = "Ensemble",
    totrow = TRUE,
    totcol = "last",
    total_names = "Total",
    add_n = TRUE,
    add_pct = FALSE,
    digits = 0,
    subtext = "",
    filter
)

tab_get_vars(tabs, vars = c("row_var", "col_vars", "tab_vars"))

is_tab(x)

set_color_style(
  type = c("text", "bg"),
  theme = NULL,
  html_24_bit = c("blue_red", "green_red", "no"),
  custom_palette = NULL
)

get_color_style(
  mode = c("crayon", "color_code"),
  type = NULL,
  theme = NULL,
  html_24_bit = NULL
)

set_color_breaks(pct_breaks, mean_breaks, contrib_breaks)

get_color_breaks(brk, type = c("positive", "all"))

```

**Arguments**

|          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| data     | A data frame.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| row_vars | The row variable, which will be printed with one level per line. If numeric, it will be converted to factor. If more than one row_var if provided, a different table is made for each of them.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| col_vars | <code>&lt;tidy-select&gt;</code> One column is printed for each level of each column variable. For numeric variables means are calculated, in a single column. To pass many variables you may use syntax <code>col_vars = c(col_var1, col_var2, ...)</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| tab_vars | <code>&lt;tidy-select&gt;</code> One subtable is made for each combination of levels of the tab variables. To pass many variables you may use syntax <code>tab_vars = c(tab_var1, tab_var2, ...)</code> . All tab variables are converted to factor. Leave empty to make a simple table.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| wt       | A weight variable, of class numeric. Leave empty for unweighted results.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| pct      | <p>The type of percentages to calculate :</p> <ul style="list-style-type: none"> <li>• "row": row percentages.</li> <li>• "col": column percentages.</li> <li>• "all": frequencies for each subtable/group, if there is tab_vars.</li> <li>• "all_tabs": frequencies for the whole (set of) table(s).</li> </ul> <p>The argument is vectorised over both row_vars and col_vars. You can then write as the following: <code>pct = list(row_var1 = list("row", "col", "col"), row_var2 = list("col", "row", "row"))</code></p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| color    | <p>The type of colors to print, as a single string. Vectorised over row_vars.</p> <ul style="list-style-type: none"> <li>• "no": by default, no colors are printed.</li> <li>• "diff": color percentages and means based on cells differences from totals (or from first cells when <code>ref = "first"</code>).</li> <li>• "diff_ci": color pct and means based on cells differences from totals or first cells, removing coloring when the confidence interval of this difference is higher than the difference itself.</li> <li>• "after_ci": idem, but cut off the confidence interval from the difference first.</li> <li>• "contrib": color cells based on their contribution to variance (except mean columns, from numeric variables).</li> <li>• "OR": for <code>pct == "col"</code> or <code>pct == "row"</code>, color based on odds ratios (or relative risks ratios)</li> <li>• "auto": frequencies (<code>pct = "all"</code>, <code>pct = "all_tabs"</code>) and counts are colored with "contrib". When <code>ci = "diff"</code>, row and col percentages are colored with "after_ci" ; otherwise they are colored with "diff".</li> </ul> |
| OR       | <p>With <code>pct = "row"</code> or <code>pct = "col"</code>, calculate and print odds ratios (for binary variables) or relative risks ratios (for variables with 3 levels or more).</p> <ul style="list-style-type: none"> <li>• "no": by default, no OR are calculated.</li> <li>• "OR": print OR (instead of percentages).</li> <li>• "OR_pct": print OR, with percentages in bracket.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| chi2               | Set to TRUE to calculate Chi2 summaries with <a href="#">tab_chi2</a> . Useful to print meta-data, and to color cells based on their contribution to variance (color = "contrib"). Vectorised over row_vars.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| na                 | <p>The policy to adopt with missing values. It must be a single string.</p> <ul style="list-style-type: none"> <li>• na = "keep": by default, prints NA's as explicit "NA" level.</li> <li>• na = "drop": removes NA levels before making each table (tabs made with different column variables may have a different number of observations, and won't exactly have the same total columns).</li> <li>• "drop_all": remove NA's for all variables before making the tables.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| levels             | <p>The levels of col_vars to keep (for more complex selections use <a href="#">dplyr::select</a>). The argument is vectorised over col_vars.</p> <ul style="list-style-type: none"> <li>• "all": by default, all levels are kept.</li> <li>• "first": only keep the first level of each col_vars</li> <li>• "auto": keep the first level when col_var is only two levels, keep all levels otherwise</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| na_drop_all        | <a href="#">&lt;tidy-select&gt;</a> Removes all observations with a NA in any of the chosen variables, for all tables (tabs for each column variable will have the same number of observations).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| cleannames         | Set to TRUE to clean levels names, by removing prefix numbers like "1-", and text in parenthesis. All data formatting arguments are passed to <a href="#">tab_prepare</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| compact            | With several row_vars, set to TRUE to bind all tables in a single tabxplor_tab. If not provided, the value of <code>getOption("tabxplor.compact")</code> is taken (FALSE by default). Set <code>options(tabxplor.compact = TRUE)</code> to make this the default behaviour for all tables (but beware because it can break existing code).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| other_if_less_than | When set to a positive integer, levels with less count than it will be merged into an "Others" level.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| other_level        | The name of the "Other" level, as a single string.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| ref                | <p>The reference cell to calculate differences and ratios (used to print colors) :</p> <ul style="list-style-type: none"> <li>• "auto": by default, cell difference from the corresponding total (rows or cols depending on pct = "row" or pct = "col") is used for diff ; cell ratio from the first line (or col) is use for OR (odds ratio/relative risks ratio).</li> <li>• "tot": totals are always used.</li> <li>• "first": calculate cell difference or ratio from the first cell of the row or column (useful to color temporal developments).</li> <li>• n: when ref is an integer, the nth row (or column) is used for comparison.</li> <li>• "regex": when ref is a string, it it used as a regular expression, to match with the names of the rows (or columns). Be precise enough to match only one column or row, otherwise you get a warning message.</li> <li>• "no": not use ref and not calculate diffs to gain calculation time.</li> </ul> |
| ref2               | A second reference cell is needed to calculate odds ratios (or relative risks ratios). The first cell of the row or column is used by default. See ref above for the full list of possible values.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| comp          | <p>The comparison level : by subtables/groups, or for the whole table. Vectorised over row_vars.</p> <ul style="list-style-type: none"> <li>• "tab": by default, contributions to variance, row differences from totals/first cells, and row confidence intervals for these differences, are calculated for each tab_vars group.</li> <li>• "all": compare cells to the general total line (provided there is a total table with a total row), or with the reference line of the total table when ref = "first", an integer or a regular expression.</li> </ul>                                                                                                                                                                                                                                                                                                                                |
| ci            | <p>The type of confidence intervals to calculate, passed to <a href="#">tab_ci</a>. Vectorised over row_vars.</p> <ul style="list-style-type: none"> <li>• "cell": absolute confidence intervals of cells percentages.</li> <li>• "diff": confidence intervals of the difference between a cell and the relative total cell (or relative first cell when ref = "first").</li> <li>• "auto": ci = "diff" for means and row/col percentages, ci = "cell" for frequencies ("all", "all_tabs").</li> </ul> <p>By default, for percentages, with ci = "cell" Wilson's method is used, and with ci = "diff" Wald's method along Agresti and Caffo's adjustment. Means use classic method. This can be changed with method_cell and method_diff. By default, with ci = "cell", the result is printed in the [inf;sup] form. Set options("tabxplor.ci_print" = "moe") to print pct +- moe instead.</p> |
| conf_level    | <p>The confidence level, as a single numeric between 0 and 1. Default to 0.95 (95%).</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| method_cell   | <p>Character string specifying which method to use with percentages for ci = "cell". This can be one out of: "wald", "wilson", "wilsoncc", "agresti-coull", "jeffreys", "modified wilson", "modified jeffreys", "clopper-pearson", "arcsine", "logit", "witting", "pratt", "midp", "lik" and "blaker". Defaults to "wilson". See <a href="#">BinomCI</a>.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| method_diff   | <p>Character string specifying which method to use with percentages for ci = "diff". This can be one out of: "wald", "waldcc", "ac", "score", "scorecc", "mn", "mee", "blj", "ha", "hal", "jp". Defaults to "ac", Wald interval with the adjustment according to Agresti, Caffo for difference in proportions and independent samples. See <a href="#">BinomDiffCI</a>.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| totaltab      | <p>The total table, if there are subtables/groups (i.e. when tab_vars is provided). Vectorised over row_vars.</p> <ul style="list-style-type: none"> <li>• "line": by default, add a general total line (necessary for calculations with comp = "all")</li> <li>• "table": add a complete total table (i.e. row_var by col_vars without tab_vars).</li> <li>• "no": not to draw any total table.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| totaltab_name | <p>The name of the total table, as a single string.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| totrow        | <p>By default, total rows are printed. Set to FALSE to remove them (after calculations if needed). Vectorised over row_vars.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| totcol        | <p>The policy with total columns. Vectorised over col_vars.</p> <ul style="list-style-type: none"> <li>• "last": by default, only prints a total column for the last column variable (of class factor, not numeric).</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                | <ul style="list-style-type: none"> <li>• "each": print a total column for each column variable.</li> <li>• "no": remove all total columns (after calculations if needed).</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| total_names    | The names of the totals, as a character vector of length one or two. Use syntax of type <code>c("Total row", "Total column")</code> to set different names for rows and cols.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| add_n          | For <code>pct = "row"</code> or <code>pct = "col"</code> , set to <code>FALSE</code> not to add another column or row with unweighted counts ( <code>n</code> ).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| add_pct        | Set to <code>TRUE</code> to add a column with the frequencies of the row variable (for <code>pct = "row"</code> ) or a row with the frequencies of the column variable (for <code>pct = "col"</code> ).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| digits         | The number of digits to print, as a single integer, or an integer vector the same length as <code>col_vars</code> . The argument is vectorized over <code>col_vars</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| subtext        | A character vector to print rows of legend under the table.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| filter         | A <code>dplyr::filter</code> to apply to the data frame first, as a single string (which will be converted to code, i.e. to a call). Useful when printing multiples tabs with <code>tibble::tribble</code> , to use different filters for similar tables or simply make the field of observation more visible into the code.                                                                                                                                                                                                                                                                                                                                                                                  |
| tabs           | A tibble of class <code>tab</code> , made with <code>tab</code> , <code>tab_many</code> or <code>tab_plain</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| vars           | In <code>tab_get_vars</code> , a character vector containing the wanted vars names: <code>"row_var"</code> , <code>"col_vars"</code> or <code>"tab_vars"</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| x              | A object to test with <code>is_tab</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| type           | Default to <code>"positive"</code> , which just print breaks for positive spreads. Set to <code>all</code> to get breaks for negative spreads as well.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| theme          | For <code>set_color_style</code> and <code>get_color_style</code> , is your console or html table background <code>"light"</code> or <code>"dark"</code> ? Default to RStudio theme.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| html_24_bit    | Use 24bits colors palettes for html tables : set to <code>"green_red"</code> or <code>"blue_red"</code> . Only with <code>mode = "color_code"</code> (not <code>mode = "crayon"</code> ) and <code>theme = "light"</code> . Default to <code>getOption("tabxplor.color_html_24_bit")</code> .                                                                                                                                                                                                                                                                                                                                                                                                                 |
| custom_palette | Possibility to provide a custom color styles, as a character vector of 10 html color codes (the five first for over-represented numbers, the five last for under-represented ones). The result is saved to <code>options("tabxplor.color_style")</code> . To discard, relaunch the function with <code>custom_palette = NULL</code> .                                                                                                                                                                                                                                                                                                                                                                         |
| mode           | By default, <code>get_color_style</code> returns a list of <b>crayon</b> coloring functions. Set to <code>"color_code"</code> to return html color codes.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| pct_breaks     | If they are to be changed, the breaks used for percentages. Default to <code>c(0.05, 0.1, 0.2, 2, 0.3)</code> : first color used when the pct of a cell is +5% superior to the pct of the related total ; second color used when it is +10% superior ; third +20% superior ; fourth *2 superior ; fifth +30% superior. When <code>&gt; 1</code> , it does not take differences but ratio. The opposite for cells inferior to the total (without the *2 rule). With <code>color = "after_ci"</code> , the first break is subtracted from all breaks (default becomes <code>c(0, 0.05, 0.15, 2, 0.25)</code> : <code>+0%</code> , <code>+5%</code> , <code>+15%</code> , <code>*2</code> , <code>+25%</code> ). |
| mean_breaks    | If they are to be changed, the breaks used for means. Default to <code>c(1.15, 1.5, 2, 4)</code> : first color used when the mean of a cell is superior to 1.15 times the mean of the related total row ; second color used when it is superior to 1.5 times ; etc. The opposite for cells inferior to the total. With <code>color = "after_ci"</code> , the first break is divided from all breaks (default becomes <code>c(1, 1.3, 1.7, 3.5)</code> ).                                                                                                                                                                                                                                                      |

- contrib\_breaks** If they are to be changed, the breaks used for contributions to variance. Default to `c(1, 2, 5, 10)` : first color used when the contribution of a cell is superior to the mean contribution ; second color used when it is superior to 2 times the mean contribution ; etc. The global color (for example green or red/orange) is given by the sign of the spread.
- brk** When missing, return all color breaks. Specify to return a given color break, among "pct", "mean", "contrib", "pct\_ci" and "mean\_ci".

## Value

A tibble of class `tab`, possibly with colored reading helpers. When there are two `row_vars` or more, a list of tibble of class `tab`. All non-text columns are of class `fmt`, storing all the data necessary to print formats and colors. Columns with `row_var` and `tab_vars` are of class `factor` : every added factor will be considered as a `tab_vars` and used for grouping. To add text columns without using them in calculations, be sure they are of class `character`.

A list with the variables names.

A single logical.

Set global options "`tabxplor.color_style_type`" and "`tabxplor.color_style_theme`", used when printing `tab` objects.

A vector of crayon color functions, or a vector of color html codes.

Set the global option "`tabxplor.color_breaks`" as a list different double vectors, and also returns it invisibly.

The color breaks as a double vector, or list of double vectors.

## Functions

- `tab_get_vars()`: Get the variables names of a **tabxplor** `tab`
- `is_tab()`: a test function for class `tabxplor_tab`
- `set_color_style()`: define the color style used to print `tab`.
- `get_color_style()`: get color styles as **crayon** functions or html codes.
- `set_color_breaks()`: set the breaks used to print colors
- `get_color_breaks()`: get the breaks currently used to print colors

## Examples

```
# Make a summary table with many col_vars, showing only one specific level :

library(dplyr)
first_lvs <- c("Married", "$25000 or more", "Strong republican", "Protestant")
data <- forcats::gss_cat %>% mutate(across(
  where(is.factor),
  ~ forcats::fct_relevel(., first_lvs[first_lvs %in% levels(.)])
))
tab_many(data, race, c(marital, rincome, partyid, relig, age, tvhours),
  levels = "first", pct = "row", chi2 = TRUE, color = "auto")
```

```
# Can be used with map and tribble to program several tables with different parameters
# all at once, in a readable way:

library(purrr)
library(tibble)
pmap(
  tribble(
    ~row_var, ~col_vars, ~pct, ~filter, ~subtext,
    "race", "marital", "row", NULL, "Source: GSS 2000-2014",
    "relig", c("race", "age"), "row", "year %in% 2000:2010", "Source: GSS 2000-2010",
    NA_character_, "race", "no", NULL, "Source: GSS 2000-2014",
  ),
  .f = tab_many,
  data = forcats::gss_cat, color = "auto", chi2 = TRUE)

set_color_style(type = "bg")
set_color_breaks(
  pct_breaks = c(0.05, 0.15, 0.3),
  mean_breaks = c(1.15, 2, 4),
  contrib_breaks = c(1, 2, 5)
)
```

---

|         |                    |
|---------|--------------------|
| tab_num | <i>Means table</i> |
|---------|--------------------|

---

## Description

Cross categorical variables with numeric variables, and get a table of means and standard deviations.

## Usage

```
tab_num(
  data,
  row_var,
  col_vars,
  tab_vars,
  wt,
  color = c("auto", "diff", "diff_ci", "after_ci"),
  na = c("keep", "drop", "drop_fct", "drop_num"),
  ref = "tot",
  comp = c("tab", "all"),
  ci = NULL,
  conf_level = 0.95,
  totaltab = "line",
  totaltab_name = "Ensemble",
  tot = NULL,
  total_names = "Total",
  subtext = "",
```

```

    digits = 0,
    num = FALSE,
    df = FALSE
  )

```

## Arguments

|          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| data     | A data frame.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| row_var  | The row variable, which will be printed with one level per line. If numeric, it will be used as a factor.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| col_vars | The numeric variables, which will appear in columns : means and standard deviation are calculated for each levels of row_var and tab_vars.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| tab_vars | <a href="#">&lt;tidy-select&gt;</a> Tab variables : a subtable is made for each combination of levels of the selected variables. Leave empty to make a simple cross-table. All tab variables are converted to factor.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| wt       | A weight variable, of class numeric. Leave empty for unweighted results.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| color    | TRUE print the color percentages and means based on cells differences from totals or reference cell, as provided by ref. Default to FALSE, no colors.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| na       | The policy to adopt for missing values in row and tab variables (factors), as a single string. <ul style="list-style-type: none"> <li>• "keep": by default, NA's of row and tab variables are printed as an explicit "NA" level.</li> <li>• "drop": remove NA's in row and tab variables.</li> </ul> <p>NAs in numeric variables are always removed when calculating means. For that reason the n field of each resulting <a href="#">fmt</a> column, used to calculate confidence intervals, only takes into account the complete observations (without NA). To drop all rows with NA in any numeric variable first, use <a href="#">tab_prepare</a> or <a href="#">tab_many</a> with the na_drop_all argument.</p>                                                                                                                                                                                                                                    |
| ref      | The reference cell to calculate differences and ratios (used to print colors) : <ul style="list-style-type: none"> <li>• "auto": by default, cell difference from the corresponding total (rows or cols depending on pct = "row" or pct = "col") is used for diff ; cell ratio from the first line (or col) is use for OR (odds ratio/relative risks ratio).</li> <li>• "tot": totals are always used.</li> <li>• "first": calculate cell difference or ratio from the first cell of the row or column (useful to color temporal developments).</li> <li>• n: when ref is an integer, the nth row (or column) is used for comparison.</li> <li>• "regex": when ref is a string, it it used as a regular expression, to match with the names of the rows (or columns). Be precise enough to match only one column or row, otherwise you get a warning message.</li> <li>• "no": not use ref and not calculate diffs to gain calculation time.</li> </ul> |
| comp     | Comparison level. When tab_vars are present, should the contributions to variance be calculated for each subtable/group (by default, comp = "tab") ? Should they be calculated for the whole table (comp = "all") ? comp must be set once and for all the first time you use <a href="#">tab_plain</a> , <a href="#">tab_num</a> or <a href="#">tab_chi2</a> with rows, or <a href="#">tab_ci</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ci            | <p>The type of confidence intervals to calculate, passed to <code>tab_ci</code> (automatically added if needed for color).</p> <ul style="list-style-type: none"> <li>• "cell": absolute confidence intervals of cells percentages.</li> <li>• "diff": confidence intervals of the difference between a cell and the relative total cell (or relative first cell when <code>ref = "first"</code>).</li> <li>• "auto": <code>ci = "diff"</code> for means and row/col percentages, <code>ci = "cell"</code> for frequencies ("all", "all_tabs").</li> </ul> |
| conf_level    | The confidence level for the confidence intervals, as a single numeric between 0 and 1. Default to 0.95 (95%).                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| totaltab      | <p>The total table, if there are subtables/groups (i.e. when <code>tab_vars</code> is provided) :</p> <ul style="list-style-type: none"> <li>• "line": by default, add a general total line (necessary for calculations with <code>comp = "all"</code>)</li> <li>• "table": add a complete total table (i.e. <code>row_var</code> by <code>col_vars</code> without <code>tab_vars</code>).</li> <li>• "no": not to draw any total table.</li> </ul>                                                                                                        |
| totaltab_name | The name of the total table, as a single string.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| tot           | <p>The totals :</p> <ul style="list-style-type: none"> <li>• <code>c("col", "row")</code> or "both" : by default, both total rows and total columns.</li> <li>• "row": only total rows.</li> <li>• "col": only total column.</li> <li>• "no": remove all totals (after calculations if needed).</li> </ul>                                                                                                                                                                                                                                                 |
| total_names   | The names of the totals, as a character vector of length one or two. Use syntax of type <code>c("Total row", "Total column")</code> to set different names for rows and cols.                                                                                                                                                                                                                                                                                                                                                                              |
| subtext       | A character vector to print rows of legend under the table.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| digits        | The number of digits to print, as a single integer.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| num           | Set to TRUE to obtain a table with normal numeric vectors (not <code>fmt</code> ).                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| df            | Set to TRUE to obtain a plain <code>data.frame</code> (not a <code>tibble</code> ), with normal numeric vectors (not <code>fmt</code> ). Useful, for example, to pass the table to correspondence analysis with <b>FactoMineR</b> .                                                                                                                                                                                                                                                                                                                        |

## Value

A `tibble` of class `tabxplor_tab`. If ... (`tab_vars`) are provided, a `tab` of class `tabxplor_grouped_tab`. All non-text columns are `fmt` vectors of class `tabxplor_fmt`, storing all the data necessary to print formats and colors. Columns with `row_var` and `tab_vars` are of class `factor` : every added factor will be considered as a `tab_vars` and used for grouping. To add text columns without using them in calculations, be sure they are of class `character`.

## Examples

```
data <- dplyr::storms %>% tab_prepare(category, wind, na_drop_all = wind)
tab_num(data, category, wind, tot = "row", color = "after_ci")
```

---

|         |                                                    |
|---------|----------------------------------------------------|
| tab_pct | Add percentages and diffs to a <a href="#">tab</a> |
|---------|----------------------------------------------------|

---

## Description

Add percentages and diffs to a [tab](#)

## Usage

```
tab_pct(
  tabs,
  pct = "row",
  digits = NULL,
  ref = c("tot", "first", "no"),
  comp = NULL,
  color = FALSE,
  just_diff = FALSE
)
```

## Arguments

|        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| tabs   | A tibble of class tab made with <a href="#">tab_plain</a> or <a href="#">tab_many</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| pct    | The type of percentages to calculate. "row" draw row percentages. Set to "col" for column percentages. Set to "all" for frequencies (based on each subtable/group if tab_vars is provided). Set to "all_tabs" to calculate frequencies based on the whole (set of) table(s).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| digits | The number of digits to print for percentages. As a single integer, or an integer vector the same length than col_vars.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| ref    | The reference cell to calculate differences and ratios (used to print colors) : <ul style="list-style-type: none"> <li>• "auto": by default, cell difference from the corresponding total (rows or cols depending on pct = "row" or pct = "col") is used for diff ; cell ratio from the first line (or col) is use for OR (odds ratio/relative risks ratio).</li> <li>• "tot": totals are always used.</li> <li>• "first": calculate cell difference or ratio from the first cell of the row or column (useful to color temporal developments).</li> <li>• n: when ref is an integer, the nth row (or column) is used for comparison.</li> <li>• "regex": when ref is a string, it it used as a regular expression, to match with the names of the rows (or columns). Be precise enough to match only one column or row, otherwise you get a warning message.</li> <li>• "no": not use ref and not calculate diffs to gain calculation time.</li> </ul> |
| comp   | Comparison level. When tab_vars are present, should the row differences be calculated for each subtable/group (by default comp = "tab" : comparison of each cell to the relative total row) ? Should they be calculated for the whole table (comp = "all" : comparison of each cell to the total row of the total table) ? When comp = "all" and ref = "first", cells are compared to the first cell of                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

- the total table instead. This parameter doesn't affect column percentages. comp must be set once and for all the first time you use `tab_chi2`, `tab_pct` with rows, or `tab_ci`.
- colorSet to TRUE to color the resulting tab based on differences (from totals or from the first cell).
- just\_diffIf percentages are already calculated and you just want to recalculate differences.

Value

A tibble of class `tab`, with percentages displayed, possibly colored based on differences from totals or first cell.

|           |                                 |
|-----------|---------------------------------|
| tab_plain | <i>Plain single cross-table</i> |
|-----------|---------------------------------|

Description

Plain single cross-table

Usage

```
tab_plain(  
  data,  
  row_var,  
  col_var,  
  tab_vars,  
  wt,  
  pct = "no",  
  color = "no",  
  OR = "no",  
  na = "keep",  
  ref = "auto",  
  ref2 = "first",  
  comp = "tab",  
  totaltab = "line",  
  totaltab_name = "Ensemble",  
  tot = NULL,  
  total_names = "Total",  
  subtext = "",  
  digits = 0,  
  num = FALSE,  
  df = FALSE  
)
```

**Arguments**

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| data             | A data frame.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| row_var, col_var | The row variable, which will be printed with one level per line, and the column variable, which will be printed with one level per column. Numeric variables will be used as factors. To calculate means, use <a href="#">tab_num</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| tab_vars         | <code>&lt;tidy-select&gt;</code> Tab variables : a subtable is made for each combination of levels of the selected variables. Leave empty to make a simple cross-table. All tab variables are converted to factor.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| wt               | A weight variable, of class numeric. Leave empty for unweighted results.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| pct              | The type of percentages to calculate : <ul style="list-style-type: none"> <li>• "row": row percentages.</li> <li>• "col": column percentages.</li> <li>• "all": frequencies for each subtable/group, if there is tab_vars.</li> <li>• "all_tabs": frequencies for the whole (set of) table(s).</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| color            | The type of colors to print, as a single string : <ul style="list-style-type: none"> <li>• "no": by default, no colors are printed.</li> <li>• "diff": color percentages and means based on cells differences from totals (or from first cells when ref = "first").</li> <li>• "OR": for pct == "col" or pct == "row", color based on odds ratios (or relative risks ratios)</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| OR               | With pct = "row" or pct = "col", calculate and print odds ratios (for binary variables) or relative risks ratios (for variables with 3 levels or more). <ul style="list-style-type: none"> <li>• "no": by default, no OR are calculated.</li> <li>• "OR": print OR (instead of percentages).</li> <li>• "OR_pct": print OR, with percentages in bracket.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| na               | The policy to adopt with missing values, as a single string. <ul style="list-style-type: none"> <li>• "keep": by default, NA's of row, col and tab variables are printed as explicit "NA" level.</li> <li>• "drop": removes NA of row, col and tab variables.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| ref              | The reference cell to calculate differences and ratios (used to print colors) : <ul style="list-style-type: none"> <li>• "auto": by default, cell difference from the corresponding total (rows or cols depending on pct = "row" or pct = "col") is used for diff ; cell ratio from the first line (or col) is use for OR (odds ratio/relative risks ratio).</li> <li>• "tot": totals are always used.</li> <li>• "first": calculate cell difference or ratio from the first cell of the row or column (useful to color temporal developments).</li> <li>• n: when ref is an integer, the nth row (or column) is used for comparison.</li> <li>• "regex": when ref is a string, it it used as a regular expression, to match with the names of the rows (or columns). Be precise enough to match only one column or row, otherwise you get a warning message.</li> <li>• "no": not use ref and not calculate diffs to gain calculation time.</li> </ul> |

|               |                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ref2          | A second reference cell is needed to calculate odds ratios (or relative risks ratios). The first cell of the row or column is used by default. See ref above for the full list of possible values.                                                                                                                                                                                      |
| comp          | Comparison level. When tab_vars are present, should the contributions to variance be calculated for each subtable/group (by default, comp = "tab") ? Should they be calculated for the whole table (comp = "all") ? comp must be set once and for all the first time you use <code>tab_plain</code> , <code>tab_num</code> or <code>tab_chi2</code> with rows, or <code>tab_ci</code> . |
| totaltab      | The total table, if there are subtables/groups (i.e. when tab_vars is provided) : <ul style="list-style-type: none"> <li>• "line": by default, add a general total line (necessary for calculations with comp = "all")</li> <li>• "table": add a complete total table (i.e. row_var by col_vars without tab_vars).</li> <li>• "no": not to draw any total table.</li> </ul>             |
| totaltab_name | The name of the total table, as a single string.                                                                                                                                                                                                                                                                                                                                        |
| tot           | The totals : <ul style="list-style-type: none"> <li>• c("col", "row") or "both" : by default, both total rows and total columns.</li> <li>• "row": only total rows.</li> <li>• "col": only total column.</li> <li>• "no": remove all totals (after calculations if needed).</li> </ul>                                                                                                  |
| total_names   | The names of the totals, as a character vector of length one or two. Use syntax of type c("Total row", "Total column") to set different names for rows and cols.                                                                                                                                                                                                                        |
| subtext       | A character vector to print rows of legend under the table.                                                                                                                                                                                                                                                                                                                             |
| digits        | The number of digits to print, as a single integer.                                                                                                                                                                                                                                                                                                                                     |
| num           | Set to TRUE to obtain a table with normal numeric vectors (not fmt).                                                                                                                                                                                                                                                                                                                    |
| df            | Set to TRUE to obtain a plain data.frame (not a tibble), with normal numeric vectors (not fmt). Useful, for example, to pass the table to correspondence analysis with <b>FactoMineR</b> .                                                                                                                                                                                              |

## Value

A tibble of class `tabxplor_tab`. If ... (tab\_vars) are provided, a tab of class `tabxplor_grouped_tab`. All non-text columns are `fmt` vectors of class `tabxplor_fmt`, storing all the data necessary to print formats and colors. Columns with `row_var` and `tab_vars` are of class `factor` : every added factor will be considered as a `tab_vars` and used for grouping. To add text columns without using them in calculations, be sure they are of class `character`.

## Examples

```
# A typical workflow with tabxplor step-by-step functions :

data <- dplyr::starwars %>% tab_prepare(sex, hair_color)

data %>%
```

```

tab_plain(sex, hair_color, tot = c("row", "col"), pct = "row") %>%
tab_chi2() %>%
tab_ci(color = "after_ci")

```

---

tab\_plot

---

*Print a tabxplor table as plot*


---

## Description

Print a tabxplor table as plot

## Usage

```

tab_plot(
  tabs,
  theme = c("light", "dark"),
  color_type = NULL,
  html_24_bit = NULL,
  color_legend = TRUE,
  caption = NULL,
  wrap_rows = 35,
  wrap_cols = 14,
  whitespace_only = TRUE
)

```

## Arguments

|                 |                                                                                                                                                                                                                           |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| tabs            | A table made with <a href="#">tab</a> or <a href="#">tab_many</a> .                                                                                                                                                       |
| theme           | By default, a white table with black text, Set to "dark" for a black table with white text.                                                                                                                               |
| color_type      | Set to "text" to color the text, "bg" to color the background. By default it takes <code>getOption("tabxplor.color_style_type")</code> .                                                                                  |
| html_24_bit     | Use 24bits colors palettes for html tables : set to "green_red" or "blue_red". Only with mode = "color_code" (not mode = "crayon") and theme = "light". Default to <code>getOption("tabxplor.color_html_24_bit")</code> . |
| color_legend    | Print colors legend below the table ?                                                                                                                                                                                     |
| caption         | The table caption.                                                                                                                                                                                                        |
| wrap_rows       | By default, rownames are wrapped when larger than 30 characters.                                                                                                                                                          |
| wrap_cols       | By default, colnames are wrapped when larger than 12 characters.                                                                                                                                                          |
| whitespace_only | Set to FALSE to wrap also on non whitespace characters.                                                                                                                                                                   |

## Value

A [ggplot](#) object to be printed in the RStudio Plots pane or exported as image, using [ggtexttable](#).

**Examples**

```
tab(forcats::gss_cat, race, marital, pct = "row", color = "diff") |>
  tab_plot()
```

---

tab\_prepare

---

*Prepare data for [tab\\_plain](#).*


---

**Description**

Prepare data for [tab\\_plain](#).

**Usage**

```
tab_prepare(
  data,
  ...,
  na_drop_all,
  cleannames = NULL,
  other_if_less_than = 0,
  other_level = "Others"
)
```

**Arguments**

|                    |                                                                                                       |
|--------------------|-------------------------------------------------------------------------------------------------------|
| data               | A dataframe.                                                                                          |
| ...                | Variables then to be passed in <a href="#">tab_plain</a> .                                            |
| na_drop_all        | <a href="#">&lt;tidy-select&gt;</a> Removes all observation with a NA in any of the chosen variables. |
| cleannames         | Set to TRUE to clean levels names, by removing prefix numbers like "1-", and text in parentheses.     |
| other_if_less_than | When set to a positive integer, levels with less count than it will be merged into an "Others" level. |
| other_level        | The name of the "Other" level, as a character vector of length one.                                   |

**Value**

A modified data.frame.

**Examples**

```
data <- dplyr::starwars %>%
  tab_prepare(sex, hair_color, gender, other_if_less_than = 5,
              na_drop_all = sex)
data
```

---

|                  |                                                                                 |
|------------------|---------------------------------------------------------------------------------|
| tab_pvalue_lines | <i>Transform chi2 attribute table of a tabxplor_tab into rows with pvalues.</i> |
|------------------|---------------------------------------------------------------------------------|

---

**Description**

Transform chi2 attribute table of a tabxplor\_tab into rows with pvalues.

**Usage**

```
tab_pvalue_lines(tabs)
```

**Arguments**

|      |                                                |
|------|------------------------------------------------|
| tabs | A tabxplor_tab (with chi2 table as attribute). |
|------|------------------------------------------------|

**Value**

A tabxplor\_tab.

---

|            |                                                       |
|------------|-------------------------------------------------------|
| tab_spread | <i>Spread a tab, passing a tab variable to column</i> |
|------------|-------------------------------------------------------|

---

**Description**

Spread a tab, passing a tab variable to column

**Usage**

```
tab_spread(
  tabs,
  spread_vars,
  names_prefix,
  names_sort = FALSE,
  totname = "Total"
)
```

**Arguments**

|              |                                                                                                                                                                                                             |
|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| tabs         | A tibble of class tab, made with <a href="#">tab</a> , <a href="#">tab_many</a> or <a href="#">tab_plain</a> .                                                                                              |
| spread_vars  | <a href="#">&lt;tidy-select&gt;</a> The tab variables to pass to column, with a syntax of type <code>c(var1, var2, ...)</code> .                                                                            |
| names_prefix | String added to the start of every variable name.                                                                                                                                                           |
| names_sort   | If no names_prefix is given, new names takes the form <code>spread_var_col_var_level</code> . Should then the column names be sorted ? If FALSE, the default, column names are ordered by first appearance. |
| totname      | The new name of the total rows, as a single string.                                                                                                                                                         |

**Value**

A tibble of class `tab`, with less rows and more columns.

**Examples**

```
data <- forcats::gss_cat %>% dplyr::filter(year %in% c(2000, 2014))

tabs <-
  tab(data, relig, marital, c(year, race), pct = "row", totaltab = "no",
       color = "diff", tot = "row", other_if_less_than = 30)

tabs %>%
  dplyr::select(year, race, relig, Married) %>%
  tab_spread(race)
```

---

|         |                                     |
|---------|-------------------------------------|
| tab_tot | Add totals to a <a href="#">tab</a> |
|---------|-------------------------------------|

---

**Description**

Add totals to a [tab](#)

**Usage**

```
tab_tot(
  tabs,
  tot = c("row", "col"),
  name = "Total",
  totcol = "last",
  data = NULL
)
```

**Arguments**

|        |                                                                                                                                                                                                                                                        |
|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| tabs   | A tibble of class <code>tab</code> , made with <a href="#">tab_plain</a> or <a href="#">tab_many</a> .                                                                                                                                                 |
| tot    | <code>c("col", "row")</code> and <code>"both"</code> print total rows and total columns. Set to <code>"row"</code> or <code>"col"</code> to print only one type. Set to <code>"no"</code> to remove all totals.                                        |
| name   | The names of the totals, as a character vector of length one or two. Use <code>c("Total_row", "Total_column")</code> to set different names for rows and cols.                                                                                         |
| totcol | <code>"last"</code> only prints a total column for the last factor column variable. Set to <code>"each"</code> to print a total column for each column variable.                                                                                       |
| data   | The original database used to calculate the <code>tab</code> : it is only useful for mean columns (of numeric variables), in order to calculate the variances of total rows, necessary to calculate confidence intervals with <a href="#">tab_ci</a> . |

Value

A tibble of class tab. Total rows can then be detected using `is_totrow`, and total columns using `is_totcol`.

Examples

```
data <- dplyr::starwars %>% tab_prepare(sex, hair_color)

data %>%
  tab_plain(sex, hair_color) %>%
  tab_tot("col", totcol = "each")
```

---

|              |                                          |
|--------------|------------------------------------------|
| tab_totaltab | Add total table to a <a href="#">tab</a> |
|--------------|------------------------------------------|

---

Description

Add total table to a [tab](#)

Usage

```
tab_totaltab(
  tabs,
  totaltab = c("table", "line", "no"),
  name = "Ensemble",
  data = NULL
)
```

Arguments

|          |                                                                                                                                                                                                                                              |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| tabs     | A tibble of class tab, made with <a href="#">tab_plain</a> or <a href="#">tab_many</a> .                                                                                                                                                     |
| totaltab | If there are subtables, corresponding to the levels of tab_vars, totaltab = "table" add a complete total table. totaltab = "line" add a total table of only one row with the general total. totaltab = "no" remove any existing total table. |
| name     | The name of the total table, as a single string.                                                                                                                                                                                             |
| data     | The original database used to calculate the tab : it is only useful for mean columns (of numeric variables), in order to calculate the variances necessary to calculate confidence intervals with <a href="#">tab_ci</a> .                   |

Value

A tibble of class tab. Rows belonging to the total table can then be detected using `is_tottab`.

**Examples**

```
data <- dplyr::starwars %>%
  tab_prepare(sex, hair_color, gender, other_if_less_than = 5,
              na_drop_all = sex)

data %>%
  tab_plain(sex, hair_color, gender) %>%
  tab_totaltab("line")
```

---

|               |                                                          |
|---------------|----------------------------------------------------------|
| tab_wrap_text | <i>Wrap column names and character/factor variables.</i> |
|---------------|----------------------------------------------------------|

---

**Description**

Wrap column names and character/factor variables.

**Usage**

```
tab_wrap_text(
  tabs,
  wrap_rows = 35L,
  wrap_cols = 15L,
  exdent = 1,
  whitespace_only = TRUE,
  unbreakable_spaces = TRUE,
  brk = "\n"
)
```

**Arguments**

|                    |                                                                                                 |
|--------------------|-------------------------------------------------------------------------------------------------|
| tabs               | A <code>tabxplor_tab</code> or a <code>tibble</code> .                                          |
| wrap_rows          | By default, rownames are wrapped when larger than 30 characters.                                |
| wrap_cols          | By default, colnames are wrapped when larger than 12 characters.                                |
| exdent             | On the second lines or more, the number of characters to use for indentation.                   |
| whitespace_only    | Set to FALSE to wrap also on non whitespace characters.                                         |
| unbreakable_spaces | Set to FALSE to keep normal spaces in text (auto-break).                                        |
| brk                | The string to use for linebreak : <code>\n</code> in text, but <code>&lt;br&gt;</code> in html. |

**Value**

The same `tabxplor_tab` or `tibble`.

## Examples

```
tab(forcats::gss_cat, race, marital, pct = "row", color = "diff") |>
  tab_wrap_text(wrap_rows = 5L, wrap_cols = 8L)
```

---

tab\_xl

*Excel output for tabxplore tables, with formatting and colors*


---

## Description

To modify the colors used into the Excel table, you can change the global options with [set\\_color\\_style](#) and [set\\_color\\_breaks](#).

## Usage

```
tab_xl(
  tabs,
  path = NULL,
  replace = FALSE,
  open = rlang::is_interactive(),
  colnames_rotation = 0,
  remove_tab_vars = TRUE,
  colwidth = 10,
  print_color_legend = TRUE,
  sheets = "auto",
  n_min = 0,
  titles,
  font_text = "DejaVu Sans Condensed",
  font_num = "DejaVu Sans",
  text_size = 10,
  text_size_headers = 9,
  text_size_subtext = 9,
  hide_near_zero = Inf,
  color_type = "text"
)
```

## Arguments

**tabs** A table made with [tab](#), [tab\\_many](#) or [tab\\_plain](#), or a list of such tables.  
**path, replace, open**

The name, and possibly the path, of the Excel file to create (possibly without the .xlsx extension). Default path to temporary directory. Set global option "tabxplore.export\_dir" with `link[base:options]{options}` to change default directory. By default replace is TRUE when path is provided, FALSE when path is not provided. Use replace = TRUE to overwrite existing files. Use open = FALSE if you don't want to automatically open the tables in Excel (or another software associated with .xlsx files).

|                                                 |                                                                                                                                                                                                                                                                                  |
|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| colnames_rotation                               | Rotate the names of columns to an angle (in degrees).                                                                                                                                                                                                                            |
| remove_tab_vars                                 | By default, tab_vars columns are removed to gain space. Set to FALSE to keep them.                                                                                                                                                                                               |
| colwidth                                        | The standard width for numeric columns, as a number. Set to "auto" to let Excel choose.                                                                                                                                                                                          |
| print_color_legend                              | Should the color legends be printed with the subtexts ?                                                                                                                                                                                                                          |
| sheets                                          | The Excel sheets options : <ul style="list-style-type: none"> <li>• "tabs": a new sheet is created for each table</li> <li>• "unique": all tables are on the same sheet</li> <li>• "auto": subsequent tables with the same column vars are printed on the same sheets</li> </ul> |
| n_min                                           | The total count under which a column or row is turned pale grey because there is not enough observation for it to be significant. Default to 0 (not used).                                                                                                                       |
| titles                                          | The titles of the different tables, as a character vector. When missing titles are given based on the names of the variables.                                                                                                                                                    |
| font_text, font_num                             | Font for text and for numbers.                                                                                                                                                                                                                                                   |
| text_size, text_size_headers, text_size_subtext | Font sizes of text elements.                                                                                                                                                                                                                                                     |
| hide_near_zero                                  | By default all cells displayed as 0 (even rounded) turn pale grey, to make the distribution of empty cells (and other cells) more visible. Provide a number to turn grey every cell below it. Set to Inf not to use this feature.                                                |
| color_type                                      | By default, the text is colored. Set to "bg" to color the background instead.                                                                                                                                                                                                    |

**Value**

The table(s) with formatting and colors in an Excel file, as a side effect. Invisibly returns tabs.

**Examples**

```
forcats::gss_cat %>%
  tab(marital, race, pct = "row", color = "diff") %>%
  tab_xl()
```

---

tbl\_format\_body.tabxplor\_tab

*Table body for class tab*

---

**Description**

Table body for class tab

**Usage**

```
## S3 method for class 'tabxplor_tab'
tbl_format_body(x, setup, ...)
```

**Arguments**

|       |                                 |
|-------|---------------------------------|
| x     | An object of class tabxplor_tab |
| setup | A setup object from the table   |
| ...   | Other parameters.               |

**Value**

A character vector.

---

|                                   |
|-----------------------------------|
| tbl_format_footer.tabxplor_tab    |
| <i>Table footer for class tab</i> |

---

**Description**

Table footer for class tab

**Usage**

```
## S3 method for class 'tabxplor_tab'
tbl_format_footer(x, setup, ...)
```

**Arguments**

|       |                                 |
|-------|---------------------------------|
| x     | An object of class tabxplor_tab |
| setup | A setup object from the table   |
| ...   | Other parameters.               |

**Value**

A character vector.

---

|                              |                                            |
|------------------------------|--------------------------------------------|
| tbl_sum.tabxplor_grouped_tab |                                            |
|                              | <i>Table headers for class grouped tab</i> |

---

**Description**

Table headers for class grouped tab

**Usage**

```
## S3 method for class 'tabxplor_grouped_tab'
tbl_sum(x, ...)
```

**Arguments**

- x                   An object of class tabxplor\_tab
- ...                Other parameters.

**Value**

A table header

---

|                      |                                    |
|----------------------|------------------------------------|
| tbl_sum.tabxplor_tab | <i>Table headers for class tab</i> |
|----------------------|------------------------------------|

---

**Description**

Table headers for class tab

**Usage**

```
## S3 method for class 'tabxplor_tab'
tbl_sum(x, ...)
```

**Arguments**

- x                   An object of class tabxplor\_tab
- ...                Other parameters.

**Value**

A table header

---

```
ungroup.tabxplor_grouped_tab
      ungroup method for class tabxplor_grouped_tab
```

---

**Description**

ungroup method for class tabxplor\_grouped\_tab

**Usage**

```
## S3 method for class 'tabxplor_grouped_tab'
ungroup(x, ...)
```

**Arguments**

x                    A tibble of class tabxplor\_grouped\_tab.  
 ...                Variables to remove from the grouping.

**Value**

An object of class tabxplor\_tab or tabxplor\_grouped\_tab.

---

```
vec_arith.tabxplor_fmt
      Vec_arith method for fmt
```

---

**Description**

Vec\_arith method for fmt

**Usage**

```
## S3 method for class 'tabxplor_fmt'
vec_arith(op, x, y, ...)

## Default S3 method:
vec_arith.tabxplor_fmt(op, x, y, ...)

## S3 method for class 'tabxplor_fmt'
vec_arith.tabxplor_fmt(op, x, y, ...)

## S3 method for class 'numeric'
vec_arith.tabxplor_fmt(op, x, y, ...)

## S3 method for class 'tabxplor_fmt'
```

```
vec_arith.numeric(op, x, y, ...)

## S3 method for class 'MISSING'
vec_arith.tabxplor_fmt(op, x, y, ...)
```

### Arguments

|     |                  |
|-----|------------------|
| op  | Operation to do. |
| x   | fmt object.      |
| y   | Second object.   |
| ... | Other parameter. |

### Value

A fmt vector  
 A fmt vector  
 A fmt vector  
 A fmt vector  
 A fmt vector  
 A fmt vector

### Methods (by class)

- `vec_arith.tabxplor_fmt(default)`: default `vec_arith` method for `fmt`
- `vec_arith.tabxplor_fmt(tabxplor_fmt)`: `vec_arith` method for `fmt + fmt`
- `vec_arith.tabxplor_fmt(numeric)`: `vec_arith` method for `fmt + numeric`
- `vec_arith.tabxplor_fmt(MISSING)`: `vec_arith` method for `-fmt`

### Functions

- `vec_arith.numeric(tabxplor_fmt)`: `vec_arith` method for `numeric + fmt`

---

```
vec_cast.character.tabxplor_fmt
      Convert fmt into character
```

---

### Description

Convert `fmt` into character

### Usage

```
## S3 method for class 'tabxplor_fmt'
vec_cast.character(x, to, ...)
```

**Arguments**

|     |                    |
|-----|--------------------|
| x   | A fmt vector       |
| to  | A character vector |
| ... | Other parameter    |

**Value**

A character vector

---

```
vec_cast.double.tabxplor_fmt
```

*Convert fmt into double*

---

**Description**

Convert fmt into double

**Usage**

```
## S3 method for class 'tabxplor_fmt'  
vec_cast.double(x, to, ...)
```

**Arguments**

|     |                  |
|-----|------------------|
| x   | A fmt vector     |
| to  | A double vector  |
| ... | Other parameter. |

**Value**

A double vector

---

```
vec_cast.integer.tabxplor_fmt
```

*Convert fmt into integer*

---

**Description**

Convert fmt into integer

**Usage**

```
## S3 method for class 'tabxplor_fmt'  
vec_cast.integer(x, to, ...)
```

**Arguments**

|     |                  |
|-----|------------------|
| x   | A integer vector |
| to  | A fmt vector     |
| ... | Other parameter. |

**Value**

An integer vector

---

```
vec_cast.tabxplor_fmt.double
```

*Convert double into fmt*

---

**Description**

Convert double into fmt

**Usage**

```
## S3 method for class 'tabxplor_fmt.double'
vec_cast(x, to, ...)
```

**Arguments**

|     |                  |
|-----|------------------|
| x   | A double vector  |
| to  | A fmt vector     |
| ... | Other parameter. |

**Value**

A fmt vector

---

```
vec_cast.tabxplor_fmt.integer
```

*Convert integer into fmt*

---

**Description**

Convert integer into fmt

**Usage**

```
## S3 method for class 'tabxplor_fmt.integer'
vec_cast(x, to, ...)
```

**Arguments**

|     |                  |
|-----|------------------|
| x   | A integer vector |
| to  | A fmt vector     |
| ... | Other parameter. |

**Value**

A fmt vector

---

|                                    |
|------------------------------------|
| vec_cast.tabxplor_fmt.tabxplor_fmt |
| <i>Convert fmt into fmt</i>        |

---

**Description**

Convert fmt into fmt

**Usage**

```
## S3 method for class 'tabxplor_fmt.tabxplor_fmt'  
vec_cast(x, to, ...)
```

**Arguments**

|     |                  |
|-----|------------------|
| x   | A fmt vector     |
| to  | A fmt vector     |
| ... | Other parameter. |

**Value**

A fmt vector

---

|                       |                                      |
|-----------------------|--------------------------------------|
| vec_math.tabxplor_fmt | <i>Vec_math method for class fmt</i> |
|-----------------------|--------------------------------------|

---

**Description**

Vec\_math method for class fmt

**Usage**

```
## S3 method for class 'tabxplor_fmt'  
vec_math(.fn, .x, ...)
```

Arguments

- .fn                   A function
- .x                    A fmt object
- ...                   Other parameter

Value

A fmt vector

---

vec\_proxy\_compare.tabxplor\_fmt

Compare with fmt vector

---

Description

Compare with fmt vector

Usage

```
## S3 method for class 'tabxplor_fmt'  
vec_proxy_compare(x, ...)
```

Arguments

- x                    A fmt vector
- ...                   Other parameter

Value

A double vector

---

vec\_proxy\_equal.tabxplor\_fmt

Test equality with fmt vector

---

Description

Test equality with fmt vector

Usage

```
## S3 method for class 'tabxplor_fmt'  
vec_proxy_equal(x, ...)
```

**Arguments**

|     |                 |
|-----|-----------------|
| x   | A fmt vector    |
| ... | Other parameter |

**Value**

A double vector

---

```
vec_ptype2.double.tabxplor_fmt
```

*Find common ptype between double and fmt*

---

**Description**

Find common ptype between double and fmt

**Usage**

```
## S3 method for class 'double.tabxplor_fmt'
vec_ptype2(x, y, ...)
```

**Arguments**

|     |                  |
|-----|------------------|
| x   | A double vector  |
| y   | A fmt vector     |
| ... | Other parameter. |

**Value**

A fmt vector

---

```
vec_ptype2.integer.tabxplor_fmt
```

*Find common ptype between integer and fmt*

---

**Description**

Find common ptype between integer and fmt

**Usage**

```
## S3 method for class 'integer.tabxplor_fmt'
vec_ptype2(x, y, ...)
```

**Arguments**

|     |                   |
|-----|-------------------|
| x   | An integer vector |
| y   | A fmt vector      |
| ... | Other parameter.  |

**Value**

A fmt vector

---

```
vec_ptype2.tabxplor_fmt.double
```

*Find common ptype between fmt and double*

---

**Description**

Find common ptype between fmt and double

**Usage**

```
## S3 method for class 'tabxplor_fmt.double'
vec_ptype2(x, y, ...)
```

**Arguments**

|     |                  |
|-----|------------------|
| x   | A fmt vector     |
| y   | A double vector  |
| ... | Other parameter. |

**Value**

A fmt vector

---

```
vec_ptype2.tabxplor_fmt.integer
```

*Find common ptype between fmt and integer*

---

**Description**

Find common ptype between fmt and integer

**Usage**

```
## S3 method for class 'tabxplor_fmt.integer'
vec_ptype2(x, y, ...)
```

**Arguments**

|     |                   |
|-----|-------------------|
| x   | A fmt vector      |
| y   | An integer vector |
| ... | Other parameter.  |

**Value**

A fmt vector

---

```
vec_ptype2.tabxplor_fmt.tabxplor_fmt
```

*Find common ptype between fmt and fmt*

---

**Description**

Find common ptype between fmt and fmt

**Usage**

```
## S3 method for class 'tabxplor_fmt.tabxplor_fmt'
vec_ptype2(x, y, ...)
```

**Arguments**

|     |                  |
|-----|------------------|
| x   | A fmt object.    |
| y   | A fmt object.    |
| ... | Other parameter. |

**Value**

A fmt vector

---

```
vec_ptype_abbr.tabxplor_fmt
```

*Abbreviated display name for class fmt in tibbles*

---

**Description**

Abbreviated display name for class fmt in tibbles

**Usage**

```
## S3 method for class 'tabxplor_fmt'
vec_ptype_abbr(x, ...)
```

**Arguments**

x                    A fmt object.  
...                  Other parameter.

**Value**

A single string with abbreviated fmt type.

---

|                                   |
|-----------------------------------|
| vec_ptype_full.tabxplor_fmt       |
| <i>Printed type for class fmt</i> |

---

**Description**

Printed type for class fmt

**Usage**

```
## S3 method for class 'tabxplor_fmt'  
vec_ptype_full(x, ...)
```

**Arguments**

x                    A fmt object.  
...                  Other parameter.

**Value**

A single string with full fmt type.

---

|                                                     |
|-----------------------------------------------------|
| [.tabxplor_grouped_tab                              |
| <i>subset method for class tabxplor_grouped_tab</i> |

---

**Description**

subset method for class tabxplor\_grouped\_tab

**Usage**

```
"x[i]   ;   x[i, j, ... , drop = TRUE]"
```

**Arguments**

|           |                                                                                                                                                                               |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x         | A tabxplor_grouped_tab object.                                                                                                                                                |
| i, j, ... | Indices                                                                                                                                                                       |
| drop      | For matrices and arrays. If TRUE the result is coerced to the lowest possible dimension (see the examples). This only works for extracting elements, not for the replacement. |

**Value**

An object of class tabxplor\_grouped\_tab.

---

[<-.tabxplor\_grouped\_tab

*set subset method for class tabxplor\_grouped\_tab*


---

**Description**

set subset method for class tabxplor\_grouped\_tab

**Usage**

```
"x[i] <- value ; x[i, j, ...] <- value"
```

**Arguments**

|           |                                |
|-----------|--------------------------------|
| x         | A tabxplor_grouped_tab object. |
| i, j, ... | Indices.                       |
| value     | The new value.                 |

**Value**

An object of class tabxplor\_grouped\_tab.

---

|                           |                                                             |
|---------------------------|-------------------------------------------------------------|
| [[<-.tabxplor_grouped_tab |                                                             |
|                           | <i>set sub-subset method for class tabxplor_grouped_tab</i> |

---

**Description**

set sub-subset method for class tabxplor\_grouped\_tab

**Usage**

"x[[...]] <- value"

**Arguments**

|       |                                |
|-------|--------------------------------|
| x     | A tabxplor_grouped_tab object. |
| ...   | Indices                        |
| value | The new value.                 |

**Value**

An object of class tabxplor\_grouped\_tab.

---

|                 |                                         |
|-----------------|-----------------------------------------|
| \$.tabxplor_fmt | <i>\$ method for class tabxplor_fmt</i> |
|-----------------|-----------------------------------------|

---

**Description**

\$ method for class tabxplor\_fmt

**Usage**

```
## S3 method for class 'tabxplor_fmt'
x$name
```

**Arguments**

|      |                                   |
|------|-----------------------------------|
| x    | A tabxplor_fmt object.            |
| name | The name of the field to extract. |

**Value**

The relevant field of the tabxplor\_fmt.

# Index

`[.tabxplor_grouped_tab`, 90  
`[<-.tabxplor_grouped_tab`, 91  
`[[<-.tabxplor_grouped_tab`, 92  
`$.tabxplor_fmt`, 92

`arrange`, 47, 57  
`arrange.tabxplor_tab`, 4  
`as.data.frame`, 35  
`as_refcol (fmt)`, 8  
`as_refrow (fmt)`, 8  
`as_totcol (fmt)`, 8  
`as_totrow (fmt)`, 8  
`as_tottab (fmt)`, 8  
`attr`, 8

`BinomCI`, 54, 61  
`BinomDiffCI`, 54, 61

`complete_partial_totals`, 5

`dplyr::filter`, 50, 62  
`dplyr::select`, 60  
`dplyr_col_modify.tabxplor_grouped_tab`, 5  
`dplyr_reconstruct.tabxplor_grouped_tab`, 6  
`dplyr_row_slice.tabxplor_grouped_tab`, 6

`fct_recode_helper`, 7  
`filter`, 47, 57  
`fmt`, 8, 10, 50, 63, 65, 66, 70  
`fmt_get_color_code`, 15  
`format.tabxplor_fmt`, 16

`get_ci_type (fmt)`, 8  
`get_ci_type.data.frame`, 16  
`get_ci_type.default`, 17  
`get_ci_type.tabxplor_fmt`, 17  
`get_col_var (fmt)`, 8  
`get_col_var.data.frame`, 19  
`get_col_var.default`, 20  
`get_col_var.tabxplor_fmt`, 20  
`get_color (fmt)`, 8  
`get_color.data.frame`, 18  
`get_color.default`, 18  
`get_color.tabxplor_fmt`, 19  
`get_color_breaks (tab_many)`, 57  
`get_color_style (tab_many)`, 57  
`get_comp_all`, 11  
`get_comp_all (fmt)`, 8  
`get_digits (fmt)`, 8  
`get_num (fmt)`, 8  
`get_ref_type (fmt)`, 8  
`get_ref_type.data.frame`, 21  
`get_ref_type.default`, 21  
`get_ref_type.tabxplor_fmt`, 22  
`get_type (fmt)`, 8  
`get_type.data.frame`, 22  
`get_type.default`, 23  
`get_type.tabxplor_fmt`, 23  
`ggplot`, 71  
`ggtexttable`, 71  
`group_by.tabxplor_tab`, 24

`is_fmt (fmt)`, 8  
`is_refcol (fmt)`, 8  
`is_refcol.data.frame`, 24  
`is_refcol.default`, 25  
`is_refcol.tabxplor_fmt`, 25  
`is_refrow (fmt)`, 8  
`is_refrow.data.frame`, 26  
`is_refrow.default`, 26  
`is_refrow.tabxplor_fmt`, 27  
`is_tab`, 62  
`is_tab (tab_many)`, 57  
`is_totcol`, 75  
`is_totcol (fmt)`, 8  
`is_totcol.data.frame`, 27  
`is_totcol.default`, 28  
`is_totcol.tabxplor_fmt`, 28

is\_totrow, 75  
 is\_totrow(fmt), 8  
 is\_totrow.data.frame, 29  
 is\_totrow.default, 29  
 is\_totrow.tabxplor\_fmt, 30  
 is\_tottab, 75  
 is\_tottab(fmt), 8  
 is\_tottab.data.frame, 30  
 is\_tottab.default, 31  
 is\_tottab.tabxplor\_fmt, 31  
  
 jmvtab, 32  
  
 kable\_tabxplor\_style, 35  
 kableExtra::kable\_styling, 36, 57  
  
 mutate, 47, 57  
 mutate.tabxplor\_fmt, 36  
  
 new\_grouped\_tab(new\_tab), 37  
 new\_tab, 37  
  
 pillar\_shaft.tab\_chi2\_fmt, 39  
 pillar\_shaft.tabxplor\_fmt, 38  
 print.tabxplor\_grouped\_tab, 39  
 print.tabxplor\_tab, 40  
  
 record, 8  
 relocate.tabxplor\_grouped\_tab, 41  
 rename.tabxplor\_grouped\_tab, 42  
 rename\_with.tabxplor\_grouped\_tab, 42  
 rowwise.tabxplor\_grouped\_tab, 43  
 rowwise.tabxplor\_tab, 43  
  
 score\_from\_lv1, 44  
 select, 47, 57  
 select.tabxplor\_grouped\_tab, 44  
 set\_ci\_type(fmt), 8  
 set\_col\_var(fmt), 8  
 set\_color(fmt), 8  
 set\_color\_breaks, 77  
 set\_color\_breaks(tab\_many), 57  
 set\_color\_style, 77  
 set\_color\_style(tab\_many), 57  
 set\_comp\_all(fmt), 8  
 set\_diff\_type(fmt), 8  
 set\_digits(fmt), 8  
 set\_display(fmt), 8  
 set\_display.data.frame, 45  
 set\_display.default, 45  
  
 set\_display.tabxplor\_fmt, 46  
 set\_num(fmt), 8  
 set\_type(fmt), 8  
 summarise.tabxplor\_grouped\_tab, 46  
  
 tab, 8, 11, 38, 47, 52, 53, 56, 62, 63, 67, 71, 73–75, 77  
 tab\_chi2, 10, 38, 49, 52, 53, 60, 65, 68, 70  
 tab\_ci, 11, 34, 49, 52, 53, 53, 61, 65, 66, 68, 70, 74, 75  
 tab\_compact, 54  
 tab\_get\_vars(tab\_many), 57  
 tab\_get\_wrapped\_dimensions, 55  
 tab\_kable, 55  
 tab\_many, 38, 47, 48, 50, 52, 53, 56, 57, 62, 65, 67, 71, 73–75, 77  
 tab\_num, 52, 53, 64, 65, 69, 70  
 tab\_pct, 10, 67, 68  
 tab\_plain, 38, 52, 53, 62, 65, 67, 68, 70, 72–75, 77  
 tab\_plot, 71  
 tab\_prepare, 49, 60, 65, 72  
 tab\_pvalue\_lines, 73  
 tab\_spread, 73  
 tab\_tot, 74  
 tab\_totaltab, 75  
 tab\_wrap\_text, 76  
 tab\_xl, 47, 57, 77  
 tbl\_format\_body.tabxplor\_tab, 78  
 tbl\_format\_footer.tabxplor\_tab, 79  
 tbl\_sum.tabxplor\_grouped\_tab, 80  
 tbl\_sum.tabxplor\_tab, 80  
 tibble, 38  
 tibble::tribble, 50, 62  
 tidy-select, 7, 48, 59, 60, 65, 69, 72, 73  
  
 ungroup.tabxplor\_grouped\_tab, 81  
  
 vctrs::field, 8  
 vec\_arith.numeric.tabxplor\_fmt  
     (vec\_arith.tabxplor\_fmt), 81  
 vec\_arith.tabxplor\_fmt, 81  
 vec\_cast.character.tabxplor\_fmt, 82  
 vec\_cast.double.tabxplor\_fmt, 83  
 vec\_cast.integer.tabxplor\_fmt, 83  
 vec\_cast.tabxplor\_fmt.double, 84  
 vec\_cast.tabxplor\_fmt.integer, 84  
 vec\_cast.tabxplor\_fmt.tabxplor\_fmt, 85  
 vec\_math.tabxplor\_fmt, 85

`vec_proxy_compare.tabxplor_fmt`, 86  
`vec_proxy_equal.tabxplor_fmt`, 86  
`vec_ptype2.double.tabxplor_fmt`, 87  
`vec_ptype2.integer.tabxplor_fmt`, 87  
`vec_ptype2.tabxplor_fmt.double`, 88  
`vec_ptype2.tabxplor_fmt.integer`, 88  
`vec_ptype2.tabxplor_fmt.tabxplor_fmt`,  
89  
`vec_ptype_abbr.tabxplor_fmt`, 89  
`vec_ptype_full.tabxplor_fmt`, 90