

Package ‘weyl’

July 22, 2025

Type Package

Title The Weyl Algebra

Version 0.0-7

Depends methods, R (>= 4.1.0)

Maintainer Robin K. S. Hankin <hankin.robin@gmail.com>

Description A suite of routines for Weyl algebras. Notation follows Coutinho (1995, ISBN 0-521-55119-6, ``A Primer of Algebraic D-Modules"). Uses 'disordR' discipline (Hankin 2022 <[doi:10.48550/arXiv.2210.03856](https://doi.org/10.48550/arXiv.2210.03856)>). To cite the package in publications, use Hankin 2022 <[doi:10.48550/arXiv.2212.09230](https://doi.org/10.48550/arXiv.2212.09230)>.

License GPL (>= 2)

LazyData yes

Suggests knitr,rmarkdown,testthat,covr

VignetteBuilder knitr

Imports disordR (>= 0.0-8), freealg (>= 1.0-4), spray (>= 1.0-27)

URL <https://github.com/RobinHankin/weyl>,
<https://robinhankin.github.io/weyl/>

BugReports <https://github.com/RobinHankin/weyl/issues>

NeedsCompilation no

Author Robin K. S. Hankin [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-5982-0415>>)

Repository CRAN

Date/Publication 2025-04-08 10:00:02 UTC

Contents

weyl-package	2
coeffs	3

constant	4
degree	5
derivation	6
dim	7
dot-class	8
drop	8
grade	9
horner	10
identity	11
oom	12
Ops	13
print.weyl	14
rweyl	16
spray	17
weyl	18
weyl-class	19
x_and_d	19
zero	20

Index	21
--------------	-----------

weyl-package	<i>The Weyl Algebra</i>
--------------	-------------------------

Description

A suite of routines for Weyl algebras. Notation follows Coutinho (1995, ISBN 0-521-55119-6, "A Primer of Algebraic D-Modules"). Uses 'disordR' discipline (Hankin 2022 <doi:10.48550/arXiv.2210.03856>). To cite the package in publications, use Hankin 2022 <doi:10.48550/arXiv.2212.09230>.

Details

The DESCRIPTION file:

```

Package:      weyl
Type:         Package
Title:        The Weyl Algebra
Version:      0.0-7
Depends:      methods, R (>= 4.1.0)
Authors@R:    person(given=c("Robin", "K. S."), family="Hankin", role = c("aut","cre"), email="hankin.robin@gmail.co
Maintainer:   Robin K. S. Hankin <hankin.robin@gmail.com>
Description:  A suite of routines for Weyl algebras. Notation follows Coutinho (1995, ISBN 0-521-55119-6, "A Primer o
License:      GPL (>= 2)
LazyData:     yes
Suggests:     knitr,rmarkdown,testthat,covr
VignetteBuilder: knitr
Imports:      disordR (>= 0.0-8), freealg (>= 1.0-4), spray (>= 1.0-27)
URL:          https://github.com/RobinHankin/weyl, https://robinhankin.github.io/weyl/

```

BugReports: <https://github.com/RobinHankin/weyl/issues>
 Author: Robin K. S. Hankin [aut, cre] (<<https://orcid.org/0000-0001-5982-0415>>)

Index of help topics:

Ops	Arithmetic Ops Group Methods for the Weyl algebra
coeffs	Manipulate the coefficients of a weyl object
constant	The constant term
degree	The degree of a 'weyl' object
derivation	Derivations
dim	The dimension of a 'weyl' object
dot-class	Class "dot"
drop	Drop redundant information
grade	The grade of a weyl object
horner	Horner's method
identity	The identity operator
oom	One over one minus
print.weyl	Print methods for weyl objects
rweyl	Random weyl objects
spray	Create spray objects
weyl	The algebra and weyl objects
weyl-class	Class "weyl"
weyl-package	The Weyl Algebra
x_and_d	Generating elements for the first Weyl algebra
zero	The zero operator

Author(s)

Robin K. S. Hankin [aut, cre] (<<https://orcid.org/0000-0001-5982-0415>>)
 Maintainer: Robin K. S. Hankin <hankin.robin@gmail.com>

Examples

```
x <- rweyl(d=1)
y <- rweyl(d=1)
z <- rweyl(d=1)

is.zero(x*(y*z) - (x*y)*z) # should be TRUE
```

coeffs

Manipulate the coefficients of a weyl object

Description

Manipulate the coefficients of a weyl object. The coefficients are disord objects.

Usage

```
coeffs(S) <- value
```

Arguments

S	A weyl object
value	Numeric

Details

To access coefficients of a weyl object S, use `spray::coeffs(S)` [package idiom is `coeffs(S)`]. Similarly to access the index matrix use `index(s)`.
The replacement method is package-specific; use `coeffs(S) <-value`.

Value

Extraction methods return a `disord` object (possibly dropped); replacement methods return a `weyl` object.

Author(s)

Robin K. S. Hankin

Examples

```
(a <- rweyl(9))
coeffs(a)
coeffs(a)[coeffs(a)<3] <- 100
a
```

constant	<i>The constant term</i>
----------	--------------------------

Description

The *constant* of a `weyl` object is the coefficient of the term with all zeros.

Usage

```
constant(x, drop = TRUE)
constant(x) <- value
```

Arguments

x	Object of class <code>weyl</code>
drop	Boolean with default <code>TRUE</code> meaning to return the value of the coefficient, and <code>FALSE</code> meaning to return the corresponding <code>Weyl</code> object
value	Constant value to replace existing one

Value

Returns a numeric or weyl object

Note

The `constant.weyl()` function is somewhat awkward because it has to deal with the difficult case where the constant is zero and `drop=FALSE`.

Author(s)

Robin K. S. Hankin

Examples

```
(a <- rweyl()+700)
constant(a)
constant(a,drop=FALSE)

constant(a) <- 0
constant(a)
constant(a,drop=FALSE)

constant(a+66) == constant(a) + 66
```

degree

The degree of a weyl object

Description

The *degree* of a monomial weyl object $x^a \partial^b$ is defined as $a + b$. The degree of a general weyl object expressed as a linear combination of monomials is the maximum of the degrees of these monomials. Following Coutinho we have:

- $\deg(d_1 + d_2) \leq \max(\deg(d_1) + \deg(d_2))$
- $\deg(d_1 d_2) = \deg(d_1) + \deg(d_2)$
- $\deg(d_1 d_2 - d_2 d_1) \leq \deg(d_1) + \deg(d_2) - 2$

Usage

```
deg(S)
```

Arguments

S Object of class weyl

Value

Nonnegative integer (or $-\infty$ for the zero Weyl object)

Note

The degree of the zero object is conventionally $-\infty$.

Author(s)

Robin K. S. Hankin

Examples

```
(a <- rweyl())
deg(a)

d1 <- rweyl(n=2)
d2 <- rweyl(n=2)

deg(d1+d2) <= deg(d1) + deg(d2)
deg(d1*d2) == deg(d1) + deg(d2)
deg(d1*d2-d2*d1) <= deg(d1) + deg(d2) -2
```

derivation

Derivations

Description

A *derivation* D of an algebra A is a linear operator that satisfies $D(d_1 d_2) = d_1 D(d_2) + D(d_1) d_2$, for every $d_1, d_2 \in A$. If a derivation is of the form $D(d) = [d, f] = df - fd$ for some fixed $f \in A$, we say that D is an *inner* derivation.

Function `as.der()` returns a derivation with `as.der(f)(g)=fg-gf`.

Usage

```
as.der(S)
```

Arguments

S Weyl object

Value

Returns a function, a derivation

Author(s)

Robin K. S. Hankin

Examples

```
(o <- rweyl(n=2,d=2))
(f <- as.der(o))

d1 <-rweyl(n=1,d=2)
d2 <-rweyl(n=2,d=2)

f(d1*d2) == d1*f(d2) + f(d1)*d2 # should be TRUE
```

dim	<i>The dimension of a weyl object</i>
-----	---------------------------------------

Description

The *dimension* of a weyl algebra is the number of variables needed; it is half the `spray::arity()`. The *dimension* of a Weyl algebra generated by $\{x_1, x_2, \dots, x_n, \partial_{x_1}, \partial_{x_2}, \dots, \partial_{x_n}\}$ is n (not $2n$).

Usage

```
## S3 method for class 'weyl'
dim(x)
```

Arguments

x Object of class weyl

Value

Integer

Note

Empty spray objects give zero-dimensional weyl objects.

Author(s)

Robin K. S. Hankin

Examples

```
(a <- rweyl())
dim(a)
```

dot-class	<i>Class “dot”</i>
-----------	--------------------

Description

The dot object is defined so that idiom like `. [x, y]` returns the commutator, that is, $xy - yx$.

The dot object is generated by running script `inst/dot.Rmd`, which includes some further discussion and technical documentation, and creates file `dot.rda` which resides in the `data/` directory.

The `borcherds` vignette discusses this in a more general context.

Arguments

<code>x</code>	Object of any class
<code>i, j</code>	elements to commute
<code>...</code>	Further arguments to <code>dot_error()</code> , currently ignored

Value

Always returns an object of the same class as `xy`.

Author(s)

Robin K. S. Hankin

Examples

```
x <- rweyl(n=1,d=2)
y <- rweyl(n=1,d=2)
z <- rweyl(n=1,d=2)

.[x,.[y,z]] + .[y,.[z,x]] + .[z,.[x,y]] # Jacobi identity
```

drop	<i>Drop redundant information</i>
------	-----------------------------------

Description

Coerce constant weyl objects to numeric

Usage

```
drop(x)
```

Arguments

x Weyl object

Details

If its argument is a constant weyl object, coerce to numeric.

Value

Returns either a length-one numeric vector or its argument, a weyl object

Note

Many functions in the package take drop as an argument which, if TRUE, means that the function returns a dropped value.

Author(s)

Robin K. S. Hankin

Examples

```
a <- rweyl() + 67
drop(a)

drop(idweyl(9))

drop(constant(a, drop=FALSE))
```

grade

The grade of a weyl object

Description

The *grade* of a homogeneous term of a Weyl algebra is the sum of the powers. Thus the grade of $4xy^2\partial_x^3\partial_y^4$ is $1 + 2 + 3 + 4 = 10$.

The functionality documented here closely follows the equivalent in the **clifford** package.

Coutinho calls this the *symbol map*.

Usage

```
grade(C, n, drop=TRUE)
grade(C,n) <- value
grades(x)
```

Arguments

<code>C, x</code>	Weyl object
<code>n</code>	Integer vector specifying grades to extract
<code>value</code>	Replacement value, a numeric vector
<code>drop</code>	Boolean, with default TRUE meaning to coerce a constant operator to numeric, and FALSE meaning not to

Details

Function `grades()` returns an (unordered) vector specifying the grades of the constituent terms. Function `grades<-( )` allows idiom such as `grade(x, 1:2) <- 7` to operate as expected [here to set all coefficients of terms with grades 1 or 2 to value 7].

Function `grade(C, n)` returns a Weyl object with just the elements of grade `g`, where $g \%in\% n$.

The zero grade term, `grade(C, 0)`, is given more naturally by `constant(C)`.

Value

Integer vector or weyl object

Author(s)

Robin K. S. Hankin

Examples

```
a <- rweyl(30)

grades(a)
grade(a, 1:4)
grade(a, 5:9) <- -99
a
```

horner

Horner's method

Description

Horner's method

Usage

```
horner(W, v)
```

Arguments

<code>W</code>	Weyl object
<code>v</code>	Numeric vector of coefficients

Details

Given a formal polynomial

$$p(x) = a_0 + a_1 + a_2x^2 + \cdots + a_nx^n$$

it is possible to express $p(x)$ in the algebraically equivalent form

$$p(x) = a_0 + x(a_1 + x(a_2 + \cdots + x(a_{n-1} + xa_n) \cdots))$$

which is much more efficient for evaluation, as it requires only n multiplications and n additions, and this is optimal.

Author(s)

Robin K. S. Hankin

See Also

[oom](#)

Examples

```
horner(x,1:5)
horner(x+d,1:3)

2+x+d |> horner(1:3) |> horner(1:2)
```

identity	<i>The identity operator</i>
----------	------------------------------

Description

The identity operator maps any function to itself.

Usage

```
idweyl(d)
## S3 method for class 'weyl'
as.id(S)
is.id(S)
```

Arguments

- d Integer specifying dimensionality of the weyl object (twice the spray arity)
- S A weyl object

Value

A weyl object corresponding to the identity operator

Note

The identity function cannot be called “`id()`” because then R would not know whether to create a spray or a weyl object.

Examples

```
idweyl(7)

a <- rweyl(d=5)
a
is.id(a)
is.id(1+a-a)
as.id(a)

a == a*1
a == a*as.id(a)
```

oom

One over one minus

Description

Uses Taylor’s theorem to give one over one minus a Weyl object

Usage

```
oom(W,n)
```

Arguments

W	Weyl object
n	Order of expansion

Author(s)

Robin K. S. Hankin

See Also

[horner](#)

Examples

```
oom(x+d,4)

W <- x+x*d
oom(W,4)*(1-W) == 1-W^5
```

Ops

Arithmetic Ops Group Methods for the Weyl algebra

Description

Allows arithmetic operators such as addition, multiplication, division, integer powers, etc. to be used for weyl objects. Idiom such as $x^2 + yz/5$ should work as expected. Addition and subtraction, and scalar multiplication, are the same as those of the **spray** package; but “ $*$ ” is interpreted as operator composition, and “ $^$ ” is interpreted as repeated composition. A number of helper functions are documented here (which are not designed for the end-user).

Usage

```
## S3 method for class 'weyl'
Ops(e1, e2 = NULL)
weyl_prod_helper1(a,b,c,d)
weyl_prod_helper2(a,b,c,d)
weyl_prod_helper3(a,b,c,d)
weyl_prod_univariate_onerow(S1,S2,func)
weyl_prod_univariate_nrow(S1,S2)
weyl_prod_multivariate_onerow_singlecolumn(S1,S2,column)
weyl_prod_multivariate_onerow_allcolumns(S1,S2)
weyl_prod_multivariate_nrow_allcolumns(S1,S2)
weyl_power_scalar(S,n)
```

Arguments

S, S1, S2, e1, e2	Objects of class weyl, elements of a Weyl algebra
a, b, c, d	Integers, see details
column	column to be multiplied
n	Integer power (non-negative)
func	Function used for products

Details

All arithmetic is as for spray objects, apart from $*$ and $^$. Here, $*$ is interpreted as operator concatenation: Thus, if w_1 and w_2 are Weyl objects, then $w_1 w_2$ is defined as the operator that takes f to $w_1(w_2 f)$.

Functions such as `weyl_prod_multivariate_nrow_allcolumns()` are low-level helper functions with self-explanatory names. In this context, “univariate” means the first Weyl algebra, generated by $\{x, \partial\}$, subject to $x\partial - \partial x = 1$; and “multivariate” means the algebra generated by $\{x_1, x_2, \dots, x_n, \partial_{x_1}, \partial_{x_2}, \dots, \partial_{x_n}\}$ where $n > 1$.

The product is somewhat user-customisable via option `prodfunc`, which affects function `weyl_prod_univariate_onerow()`. Currently the package offers three examples: `weyl_prod_helper1()`, `weyl_prod_helper2()`, and `weyl_prod_helper3()`. These are algebraically identical but occupy different positions on the efficiency-readability scale. The option defaults to `weyl_prod_helper3()`, which is the fastest but most opaque. The vignette provides further details, motivation, and examples.

Powers, as in x^n , are defined in the usual way. Negative powers will always return an error.

Value

Generally, return a weyl object

Note

Function `weyl_prod_univariate_nrow()` is present for completeness, it is not used in the package

Author(s)

Robin K. S. Hankin

Examples

```
x <- rweyl(n=1,d=2)
y <- rweyl(n=1,d=2)
z <- rweyl(n=2,d=2)

x*(y+z) == x*y + x*z
is.zero(x*(y*z) - (x*y)*z)
```

print.weyl

Print methods for weyl objects

Description

Printing methods for weyl objects follow those for the **spray** package, with some additional functionality.

Usage

```
## S3 method for class 'weyl'
print(x, ...)
```

Arguments

x	A weyl object
...	Further arguments, currently ignored

Details

Option `polyform` determines whether the object is to be printed in matrix form or polynomial form: as in the **spray** package, this option governs dispatch to either `print_spray_polyform()` or `print_spray_matrixform()`.

```
> a <- rweyl()
> a      # default print method
A member of the Weyl algebra:
  x  y  z dx dy dz      val
  1  2  2  2  1  0  =    3
  2  2  0  0  1  1  =    2
  0  0  0  1  1  2  =    1
> options(polyform = TRUE)
> a
A member of the Weyl algebra:
+3*x*y^2*z^2*dx^2*dy +2*x^2*y^2*dy*dz +dx*dy*dz^2
> options(polyform = FALSE) # restore default
```

Irrespective of the value of `polyform`, option `weylvars` controls the variable names. If `NULL` (the default), then sensible values are used: either `[xyz]` if the dimension is three or less, or integers. But option `weylvars` is user-settable:

```
> options(weylvars=letters[18:20])
> a
A member of the Weyl algebra:
  r  s  t dr ds dt      val
  1  2  2  2  1  0  =    3
  2  2  0  0  1  1  =    2
  0  0  0  1  1  2  =    1
> options(polyform=TRUE)
> a
A member of the Weyl algebra:
+3*r*s^2*t^2*dr^2*ds +2*r^2*s^2*ds*dt +dr*ds*dt^2
> options(polyform=FALSE) ; options(weylvars=NULL)
```

If the user sets `weylvars`, the print method tries to do the Right Thing (tm). If set to `c("a", "b", "c")`, for example, the generators are named `c(" a", " b", " c", "da", "db", "dc")` [note the spaces]. If the algebra is univariate, the names will be something like `d` and `x`. No checking is performed and if the length is not equal to the dimension, undesirable behaviour may occur. For the love of God, do not use a variable named `d`. Internally, `weylvars` works by changing the `sprayvars` option in the **spray** package.

Note that, as for `spray` objects, this option has no algebraic significance: it only affects the print method.

Value

Returns a weyl object.

Author(s)

Robin K. S. Hankin

Examples

```
a <- rweyl()
print(a)
options(polyform=TRUE)
print(a)
```

rweyl

Random weyl objects

Description

Creates random weyl objects: quick-and-dirty examples of Weyl algebra elements

Usage

```
rweyl(nterms = 3, vals = seq_len(nterms), dim = 3, powers = 0:2)
rweyll(nterms = 15, vals = seq_len(nterms), dim = 4, powers = 0:5)
rweylll(nterms = 50, vals = seq_len(nterms), dim = 8, powers = 0:7)
```

Arguments

nterms	Number of terms in output
vals	Values of coefficients
dim	Dimension of weyl object
powers	Set from which to sample the entries of the index matrix

Details

Function `rweyl()` creates a smallish random Weyl object; `rweyll()` and `rweylll()` create successively more complicated objects.

These functions use `spray::rspray()`, so the note there about repeated rows in the index matrix resulting in fewer than `nterms` terms applies.

Function `rweyll()` returns a one-dimensional Weyl object.

Value

Returns a weyl object

Author(s)

Robin K. S. Hankin

Examples

```

rweyl()
rweyll()
rweyl(d=7)

options(polyform = TRUE)
rweyl()
options(polyform = FALSE) # restore default

```

spray

Create spray objects

Description

Function `spray()` creates a sparse array; function `weyl()` coerces a spray object to a Weyl object.

Usage

```
spray(M, x, addrepeats=FALSE)
```

Arguments

M	An integer-valued matrix, the index of the weyl object
x	Numeric vector of coefficients
addrepeats	Boolean, specifying whether repeated rows are to be added

Details

The function is discussed and motivated in the **spray** package.

Value

Return a weyl or a Boolean

Author(s)

Robin K. S. Hankin

Examples

```

(W <- spray(matrix(1:36,6,6),1:6))
weyl(W)

as.weyl(15,d=3)

```

weyl

*The algebra and weyl objects***Description**

Basic functions for weyl objects

Usage

```
weyl(M)
is.weyl(M)
as.weyl(val,d)
is.ok.weyl(M)
```

Arguments

M	A weyl or spray object
val, d	Value and dimension for weyl object

Details

To create a weyl object, pass a spray to function `weyl()`, as in `weyl(M)`. To create a spray object to pass to `weyl()`, use function `spray()`, which is a synonym for `spray::spray()`.

Function `weyl()` is the formal creator method; `is.weyl()` tests for weyl objects and `is.ok.weyl()` checks for well-formed sprays. Function `as.weyl()` tries (but not very hard) to infer what the user intended and return the right thing.

Value

Return a weyl or a Boolean

Author(s)

Robin K. S. Hankin

Examples

```
(W <- spray(matrix(1:36,6,6),1:6))
weyl(W)

as.weyl(15,d=3)

is.ok.weyl(spray(matrix(1:30,5,6)))
is.ok.weyl(spray(matrix(1:30,6,5)))
```

weyl-class

Class “weyl”

Description

The formal S4 class for weyls.

Objects from the Class

Objects *can* be created by calls of the form `new("weyl", ...)` but this is not encouraged. Use functions `weyl()` or `as.weyl()` instead.

Author(s)

Robin K. S. Hankin

x_and_d

*Generating elements for the first Weyl algebra***Description**

Variables `x` and `d` correspond to operator x and ∂_x ; they are provided for convenience. These elements generate the one-dimensional Weyl algebra.

Note that a similar system for multivariate Weyl algebras is not desirable. We might want to consider the Weyl algebra generated by $\{x, y, z, \partial_x, \partial_y, \partial_z\}$ and correspondingly define R variables `x, y, z, dx, dy, dz`. But then variable `x` is ambiguous: is it a member of the first Weyl algebra or the third?

Usage

```
data(x_and_d)
```

Author(s)

Robin K. S. Hankin

Examples

```
d
x

.[d,x] # dx-xd==1

d^3 * x^4

(1-d*x*d)*(x^2-d^3)
```

`zero`*The zero operator*

Description

The zero operator maps any function to the zero function (which maps anything to zero). To test for being zero, use `spray::is.zero()`; package idiom would be `is.zero()`.

Usage

```
zero(d)
```

Arguments

`d` Integer specifying dimensionality of the weyl object (twice the spray arity)

Value

A weyl object corresponding to the zero operator (or a Boolean for `is.zero()`)

Examples

```
(a <- rweyl(d=5))
is.zero(a)
is.zero(a-a)
is.zero(a*0)

a == a + zero(dim(a))
```

Index

- * **classes**
 - weyl-class, 19
- * **datasets**
 - x_and_d, 19
- * **package**
 - weyl-package, 2
- * **symbolmath**
 - horner, 10
 - . (dot-class), 8
 - [,dot,ANY,ANY-method (dot-class), 8
 - [,dot,ANY,missing-method (dot-class), 8
 - [,dot,matrix,matrix-method (dot-class), 8
 - [,dot,missing,ANY-method (dot-class), 8
 - [,dot,missing,missing-method (dot-class), 8
 - [,dot-method (dot-class), 8
 - [.dot (dot-class), 8
- as.der (derivation), 6
- as.id (identity), 11
- as.identity (identity), 11
- as.one.weyl (identity), 11
- as.weyl (weyl), 18
- coeff (coeffs), 3
- coeffs, 3
- coeffs,weyl-method (coeffs), 3
- coeffs.weyl (coeffs), 3
- coeffs<- (coeffs), 3
- coeffs<- ,weyl-method (coeffs), 3
- coeffs<- .weyl (coeffs), 3
- commutator (dot-class), 8
- const (constant), 4
- constant, 4
- constant<- (constant), 4
- d (x_and_d), 19
- deg (degree), 5
- degree, 5
- derivation, 6
- derivations (derivation), 6
- dim, 7
- dimension (dim), 7
- dot (dot-class), 8
- dot-class, 8
- dot_error (dot-class), 8
- drop, 8
- drop,weyl-method (drop), 8
- empty (zero), 20
- extract (dot-class), 8
- grade, 9
- grade<- (grade), 9
- grades (grade), 9
- horner, 10, 12
- id (identity), 11
- identity, 11
- idweyl (identity), 11
- index (coeffs), 3
- is.empty (zero), 20
- is.id (identity), 11
- is.identity (identity), 11
- is.ok.weyl (weyl), 18
- is.weyl (weyl), 18
- is.zero (zero), 20
- jacobi (dot-class), 8
- oom, 11, 12
- Ops, 13
- polyform (print.weyl), 14
- print (print.weyl), 14
- print.weyl, 14
- prodfunc (Ops), 13
- rweyl, 16

`rweyl1` (`rweyl`), 16
`rweyl1` (`rweyl`), 16
`rweyl11` (`rweyl`), 16

`spray`, 17
`symbol_map` (`grade`), 9

`value` (`coeffs`), 3
`value,weyl-method` (`coeffs`), 3
`value.weyl` (`coeffs`), 3
`value<-` (`coeffs`), 3
`values` (`coeffs`), 3

`weyl`, 18
`weyl-class`, 19
`weyl-package`, 2
`weyl_power_scalar` (`Ops`), 13
`weyl_prod` (`Ops`), 13
`weyl_prod_helper1` (`Ops`), 13
`weyl_prod_helper2` (`Ops`), 13
`weyl_prod_helper3` (`Ops`), 13
`weyl_prod_multivariate_nrow_allcolumns`
 (`Ops`), 13
`weyl_prod_multivariate_onerow_allcolumns`
 (`Ops`), 13
`weyl_prod_multivariate_onerow_singlecolumn`
 (`Ops`), 13
`weyl_prod_univariate_nrow` (`Ops`), 13
`weyl_prod_univariate_onerow` (`Ops`), 13
`weylvars` (`print.weyl`), 14

`x` (`x_and_d`), 19
`x_and_d`, 19

`zero`, 20